

MONGODB - INSERT DOCUMENT

https://www.tutorialspoint.com/mongodb/mongodb_insert_document.htm

Copyright © tutorialspoint.com

In this chapter, we will learn how to insert document in MongoDB collection.

The insert Method

To insert data into MongoDB collection, you need to use MongoDB's **insert** or **save** method.

Syntax

The basic syntax of **insert** command is as follows –

```
>db.COLLECTION_NAME.insert(document)
```

Example

```
>db.mycol.insert({
  _id: ObjectId(7df78ad8902c),
  title: 'MongoDB Overview',
  description: 'MongoDB is no sql database',
  by: 'tutorials point',
  url: 'http://www.tutorialspoint.com',
  tags: ['mongodb', 'database', 'NoSQL'],
  likes: 100
})
```

Here **mycol** is our collection name, as created in the previous chapter. If the collection doesn't exist in the database, then MongoDB will create this collection and then insert a document into it.

In the inserted document, if we don't specify the `_id` parameter, then MongoDB assigns a unique ObjectId for this document.

`_id` is 12 bytes hexadecimal number unique for every document in a collection. 12 bytes are divided as follows –

```
_id: ObjectId(4 bytes timestamp, 3 bytes machine id, 2 bytes process id,
3 bytes incrementer)
```

To insert multiple documents in a single query, you can pass an array of documents in insert command.

Example

```
>db.post.insert([
  {
    title: 'MongoDB Overview',
    description: 'MongoDB is no sql database',
    by: 'tutorials point',
    url: 'http://www.tutorialspoint.com',
```

```

    tags: ['mongodb', 'database', 'NoSQL'],
    likes: 100
  },
  {
    title: 'NoSQL Database',
    description: "NoSQL database doesn't have tables",
    by: 'tutorials point',
    url: 'http://www.tutorialspoint.com',
    tags: ['mongodb', 'database', 'NoSQL'],
    likes: 20,
    comments: [
      {
        user: 'user1',
        message: 'My first comment',
        dateCreated: new Date(2013,11,10,2,35),
        like: 0
      }
    ]
  }
]
})

```

To insert the document you can use **db.post.save***document* also. If you don't specify **_id** in the document then **save** method will work same as **insert** method. If you specify **_id** then it will replace whole data of document containing **_id** as specified in save method.