MIPS and SPIM tutorial

Part Five

Exception and Interrups ▶ Polled and Interrupt driven I/O ▶ DMA ▶ Introduction to Operating Systems

**November 2008**

karl.marklund@it.uu.se

Get ready for part five of your MIPS assembly programming training.

PC   = 00400028   EPC   = 00000000   Cause   = 00000000   BadVAddr= 00000000
Status   = 3000ff10   HI   = 00000000   LO   = 00000000

General Registers

R0   (r0) = 00000000   R8 (t0) = ffffffff   R16 (s0) = 00000000   R24 (t8) = 00000000
R1   (at) = 00000000   R9 (t1) = 00000000   R17 (s1) = 00000000   R25 (t9) = 00000000
R2   (v0) = 00000000   R10 (t2) = 00000000   R18 (s2) = 00000000   R26 (k0) = 00000000
R3   (v1)

Mashine instruction `0x2008ffff`, i.e., op 2, register 0, register 8 and the 16 bit immediate constant `0xffff` (-1 in two's complement)

[0x00400018]   nop   ; 181: nop
[0x0040001c]   0x3402000a   ori $2, $0, 10   ; 183: li $v0 10
[0x00400020]   0x0000000c   syscall   ; 184: syscall
[0x00400024]   0x2008ffff   addi $8, $0, -1   ; 7: addi $t0, $zero, 0xffffffff
[0x00400028]   0x21080001   addi $8, $8, 1   ; 8: addi $t0, $t0, 1

DATA
[0x10000000]...[0x10040000]

The assembler is clever enough to interpret th 32 bit number 0xffffffff as the 16 bit number 0xffff (both means -1)

BUT: addi can only handle a 16 bit immediate constant and we try to use the 32 bit number `0xffffffff`

[0x0040000c]   0x00041080   sll $2, $4, 2   ; 178: sll $v0 $a0 2
[0x00400010]   0x00c23021   addu $6, $6, $2   ; 179: addu $a2 $a2 $v0
[0x00400014]   0x0c100009   jal 0x00400024 [main]   ; 180: jal main

PCSpim

File Simulator Window Help

```
R0   (r0) = 00000000   R8   (t0) = 00000000   R16 (s0) = 00000000   R24 (t8) = 00000000
R1   (at) = 00000000   R9   (t1) = 00000000   R17 (s1) = 00000000   R25 (t9) = 00000000
R2   (v0) = 00000000   R10  (t2) = 00000000   R18 (s2) = 00000000   R26 (k0) = 00000000
R3   (v1) = 00000000   R11  (t3) = 00000000   R19 (s3) = 00000000   R27 (k1) = 00000000
R4   (a0) = 00000000   R12  (t4) = 00000000   R20 (s4) = 00000000   R28 (gp) = 10008000
R5   (a1) = 00000000   R13  (t5) = 00000000   R21 (s5) = 00000000   R29 (sp) = 7fffeffc
R6   (a2) = 00000000   R14  (t6) = 00000000   R22 (s6) = 00000000   R30 (s8) = 00000000
R7   (a3) = 00000000   R15  (t7) = 00000000   R23 (s7) = 00000000   R31 (ra) = 00000000
```

```
[0x00400010]          0x00c23021  addu $6, $6, $2                        ; 179: addu $a2 $a2 $v0
[0x00400014]
[0x00400018]
[0x0040001c]
[0x00400020]
            KERNEL
[0x80000180]

            DATA
[0x10000000].

            STACK
[0x7fffeffc]

      KERNEL DATA
[0x90000000]                          0x78452020  0x74706563  0x206e6f69  0x636f2000
```

PCSpim

Loading the file produced warnings.
The messages are:

spim: (parser) immediate value (65535) out of range (-32768 .. 32767) on line 11 of file C:\Documents and Settings\Karl Marklund\My Documents\Teaching\Digitalteknik och Datorarkitektur vt 2008 (1DT033)\Lectures By Karl Marklund\MIPS\overflow.s
   addi $t2, $zero, 0xffff
                 ^

Would you like to open the Settings dialog box to verify simulator settings?

[Yes]   [No]

SPIM Version Version 7.3 of August 26, 2006

R0 (r0) = 00000000   R8 (t0) = 000
R1 (at) = 00000000   R9 (t1) = 000
R2 (v0) = 00000000   R10 (t2) = 000
R3 (v1) = 00000000   R11 (t3) = 000
R4 (a0) = 00000000   R12 (t4) = 000
R5 (a1) = 00000000   R13 (t5) = 00000000
R6 (a2) = 00000000   R14 (t6) = 00000000   R22 (s6) = 00000000   R30 (s8) = 00000000
R7   (ra) = 00000000

The smallest 16 bit negative constant:

1000 0000 0000 0000$_2$ = 0x8000.

Immediate value (65535) out of range (-32768..32767)

[0x00400010]   ddu $6, $6, $2   70: addu $a2 $a2 $v0
[0x00400014]
[0x00400018]   PCSpim
[0x0040001c]
[0x00400020]   ⚠   Loading the ...
                             The messages are:

        KERNE   spim: (parser) immediate
[0x80000180]   Settings\Karl Marklund\M...
                            Marklund\MIPS\overflow.s
                                    addi $t2, $zero, 0xffff
        DATA   ^
[0x10000000].
                            Would you li...   ...gs dialog box to verify simulator settings?

[0x7fff

[0x9000

The largets 16 bit possitive constant:

0111 1111 1111 1111$_2$ = 0x7fff.

We try to add the 16 bit constant 1111 1111 1111 1111$_2$.

But, all numbers are signed. The sign bit requires an extra bit (17 bits in total).

SPIM Version Version 7.3 of August 26, 2006

Load Upper Immediate: *lui*

```
lui    $t2, 0x7fff

addi   $t3, $t2, 0x7fff
```

"upper" half

$t2 ← 0x7fff0000

"lower" half

$t3 ← 0x7fff7fff

```
   0111 1111 1111 1111 0111 1111 1111 1111₂ (0x7fff7fff)

OR 0000 0000 0000 0000 1000 0000 0000 0000₂ (0x00008000)
-------------------------------------------------------
   0111 1111 1111 1111 1111 1111 1111 1111  (0x7fffffff)
```

The largets possitive 32 bit number

```
ori    $t4, $t3, 0x8000
```

$t4 ← 0x7fffffff = 2.147.483.647₁₀

(r0) = 00000000   R8   (t0) = 00000000   R16 (s0) = 00000000   R24 (t8) = 00000000
(at) = 00000000   R9   (t1) = 00000000   R17 (s1) = 00000000   R25 (t9) = 00000000
(v0) = 00000000   R10 (t2) = 7fff0000   R18 (s2) = 00000000   R26 (k0) = 00000000
(v1) = 00000000   R11 (t3) = 7fff7fff   R19 (s3) = 00000000   R27 (k1) = 00000000
(a0) = 00000000   R12 (t4) = 7fffffff   R20 (s4) = 00000000   R28 (gp) = 10008000
(a1) = 7ffff000   R1   (t5) = 00000000   R21 (s5) = 00000000   R29 (sp) = 7fffeffc
(a2) = 7ffff004   R14 (t6) = 00000000   R22 (s6) = 00000000   R30 (s8) = 00000000
(a3) = 00000000   R15 (t7) = 00000000   R23 (s7) = 00000000   R31 (ra) = 00400018

0040001c]   0x3402000a   ori $2, $0, 10   ; 183: li $v0 10
00400020]   0x0000000c   syscall   ; 184: syscall   # syscall 10 (
00400024]   0x2008ffff   addi $8, $0, -1   ; 7: addi $t0, $zero, 0xffffffff
00400028]   0x21080001   addi $8, $8, 1   ; 8: addi $t0, $t0, 1
0040002c]   0x3c0a7fff   lui $10, 32767   ; 11: lui $t2, 0x7fff # den största 16-bitars-ko
00400030]   0x214b7fff   addi $11, $10, 32767   ; 13: addi $t3, $t2, 0x7fff # den största 16-bita
00400034]   0x356c8000   ori $12, $11, -32768   ; 14: ori $t4, $t3, 0x8000 # binärt 1000 0000
00400038]   0x218d0001   addi $13, $12, 1   ; 20: addi $t5, $t4 ,1

        DATA
10000000]...[0x10040000]   0x00000000

        STACK
7fffeffc]

        KERNEL DATA
90000000]   0x636f2000

What happens if we execute this instruction?

00400010]   0x00c23021   addu $6, $6, $2   ; 179: addu $a2 $a2 $v0
00400014]   0x0c100009   jal 0x00400024 [main]   ; 180: jal main
00400024]   0x2008ffff   addi $8, $0, -1   ; 7: addi $t0, $zero, 0xffffffff
00400028]   0x21080001   addi $8, $8, 1   ; 8: addi $t0, $t0, 1
0040002c]   0x3c0a7fff   lui $10, 32767   ; 11: lui $t2, 0x7fff # den största 16-bitars-ko
00400030]   0x214b7fff   addi $11, $10, 32767   ; 13: addi $t3, $t2, 0x7fff # den största 16-bita
00400034]   0x356c8000   ori $12, $11, -32768   ; 14: ori $t4, $t3, 0x8000 # binärt 1000 0000

Coprocessor 1 – floating point unit.

coprocessor 0 – system monitoring. Used to manage *exceptions* and *interrupts*.

Cause register

Branch delay · Pending interrupts · Exception code

31 · 15 · 8 · 6 · 2

BadVAddr= 00000000

R0 (r0) = 00000000   R8 (t0) = 00000006   R16 (s0) = 00000000   R24 (t8) = 00000000
R1 (at) = 90000000   R9 (t1) = 00000003   R17 (s1) = 00000000   R25 (t9) = 00000000
R2 (v0) = 00000000   R10 (t2) = 00000002   R18 (s2) = 00000000   R26 (k0) = 0000001c
R3 (v1) = 00000000   R11 (t3) = 00000000   R19 (s3) = 00000000   R27 (k1) = 00000000
R4 (a0) = 00000000   R12 (t4) = 00000002   R20 (s4) = 00000000   R28 (gp) = 10008000

```
        KERNEL
[0x80000180]    0x0001d821  addu $27, $0, $1              ; 82: move $k1 $at      # Save $at
[0x80000184]    0x3c019000  lui $1, -28672                ; 84: sw $v0 s1         # Not re-entrant an
[0x80000188]    0xac220200  sw $2, 512($1)
[0x8000018c]    0x3c019000  lui $1, -28672                ; 8?: sw $a0 s2         # But we need to us
[0x80000190]    0xac240204  sw $4, 516($1)
[0x80000194]    0x401a6800  mfc0 $26, $13                 ; 87: mfc0 $k0 $13      # Cause register
[0x80000198]    0x001a2082  srl $4, $26, 2                ; 88: srl $a0 $k0 2     # Extract ExcCode
```

```
        DATA
[0x1000000]     0000 0000 0000 0000 0000 0000 0001 1100
        STACK
[0x7fffeffc]                            0x00000000
        KERNEL DATA
[0x90000000]                      0x78452020  0x747065    0x636f2000
```

Move From Coprocessor 0 (*mfc0*) used to get contents of Cause Register into ordinary register.

```
 Bad address
[0x80000180]                                              # Save $at
[0x80000184]                                              # Not re-entrant an
[0x80000188]
[0x8000018c]                                              # But we need to us
[0x80000190]
[0x80000194]    0x401a6800  mfc0 $26, $13                 ; 87: mfc0 $k0 $13    # Cause register
```

Cause register

BadVAddr= 00000000

```
R0   (r0) = 00000000   R8  (t0) = 00000006   R16 (s0) = 00000000   R24 (t8) = 00000000
R1   (at) = 90000000   R9  (t1) = 00000003   R17 (s1) = 00000000   R25 (t9) = 00000000
R2   (v0) = 00000000   R10 (t2) = 00000002   R18 (s2) = 00000000   R26 (k0) = 0000001c
R3   (v1) = 00000000   R11 (t3) = 00000000   R19 (s3) = 00000000   R27 (k1) = 00000000
R4   (a0) = 00000007   R12 (t4) = 00000002   R20 (s4) = 00000000   R28 (gp) = 10008000
```

```
[0x80000180]   0x0001d821   addu $27, $0, $1         ; 82: move $k1 $at        # Save $at
[0x80000184]   0x3c019000   lui $1, -28672           ; 84: sw $v0 s1           # Not re-entrant an
[0x80000188]   0xac220200   sw $2, 512($1)
[0x8000018c]   0x3c019000   lui $1, -28672           ; 85: sw $a0 s2           # But we need to us
[0x80000190]   0xac240204   sw $4, 516($1)
[0x80000194]   0x401a6800   mfc0 $26, $13            ; 87: mfc0 $k0 $13        # Cause register
[0x80000198]   0x001a2082   srl $4, $26, 2           ; 88: srl $a0 $k0 2       # Extract ExcCode b
[0x8000019c]   0x3084001f   andi $4, $4, 31          ; 89: andi $a0 $a0 0x1f
```

DATA
[0x100000

```
0000  0000  0000  0000  0000  0000  0001 1100
```

STACK
[0x7fffeffc]   0x00000000

K...
[0x900000

```
0000  0000  0000  0000  0000  0000  0000 0111
```

```
[0x80000180]   0x0001d821   addu $27, $0, $1         ; 82: move $k1 $at        # Save $at
[0x80000184]   0x3c019000   lui $1,       72         ; 84: sw $v0 s1           # Not re-entrant an
[0x80000188]   0xac220200   sw $2,                   
[0x8000018c]   0x3c019000   lui $1,                  ; 85: sw $a0 s2           # But we need to us
[0x80000
[0x80000                                                                       # Cause register
[0x80000198]   0x001a2082   srl $4, $26, 2           ; 88: srl $a0 $k0 2       # Extract ExcCode b
```

Cause Register Shifted right 2 bits

5 Bit Exception Code

```
                                                                BadVAddr= 00000000
 31              15        8        6   2
  Branch                Pending        Exception
  delay                 interrupts     code
```

```
R0  (r0) = 00000000   R8  (t0) = 00000006   R16 (s0) = 00000000   R24 (t8) = 00000000
R1  (at) = 90000000   R9  (t1) = 00000003   R17 (s1) = 00000000   R25 (t9) = 00000000
R2  (v0) = 00000000   R10 (t2) = 00000002   R18 (s2) = 00000000   R26 (k0) = 0000001c
R3  (v1) = 00000000   R11 (t3) = 00000000   R19 (s3) = 00000000   R27 (k1) = 00000000
R4  (a0) = 00000007   R12 (t4) = 00000002   R20 (s4) = 00000000   R28 (gp) = 10008000
```

```
[0x80000184]   0x3c019000  lui $1, 28672          ; 84: sw $v0 s1          # Not re-entrant a
[0x80000188]   0xa4220200  sw $2, 512($1)
[0x80                      672                    ; 85: sw $a0 s2          # But we need to us
[0x8                       1)
[0x8                       3                      ; 87: mfc0 $k0 $13       # Cause register
[0x8                       2                      ; 88: srl $a0 $k0 2      # Extract ExCode
[0x800                     $4, 31                 ; 89: andi $a0 $a0 0x1f
[0x800001a0]   4020004  ori $2, $0, 4             ; 90: li $v0 4           # syscall 4 (print_
```

Bit Mask **used to mask out only the desired bits**

```
       DATA
[0x10000000].
```

0000 0000 0000 0000 0000 0000 0000 0111

```
       STACK
[0x7fffeffc]                0x00000000
```

XXXX XXXX XXXX XXXX XXXX XXXX XXX0 0111

AND   0000 0000 0000 0000 0000 0000 0001 1111

Exception Code == 7_{10}

0000 0000 0000 0000 0000 0000 0000 0111

```
        .kdata
__m1_:  .asciiz "  Exception "
__m2_:  .asciiz " occurred and ignored\n"

__e0_:  .asciiz "  [Interrupt] "
__e1_:  .asciiz      "  [TLB]"
__e2_:  .asciiz      "  [TLB]"
__e3_:  .asciiz      "  [TLB]"
__e4_:  .asciiz      "  [Address error in inst/data fetch] "
__e5_:  .asciiz      "  [Address error in store] "
__e6_:  .asciiz      "  [Bad instruction address] "
__e7_:  .asciiz      "  [Bad data address] "
__e8_:  .asciiz      "  [Error in syscall] "
__e9_:  .asciiz      "  [Breakpoint] "
__e10_: .asciiz      "  [Reserved instruction] "
__e11_: .asciiz      ""
__e12_: .asciiz      "  [Arithmetic overflow] "
.
.
.
__e30_: .asciiz     "  [Cache]"
__e31_: .asciiz     ""

__excp:  .word __e0_, __e1_, __e2_, __e3_, __e4_, __e5_, __e6_, __e7_, __e8_, __e9_
         .word __e10_, __e11_, __e12_, __e13_, __e14_, __e15_, __e16_, __e17_, __e18_,
         .word __e19_, __e20_, __e21_, __e22_, __e23_, __e24_, __e25_, __e26_, __e27_,
         .word __e28_, __e29_, __e30_, __e31_
```

A number of strings

An array of strings

Error message for exception nr 7

```
        .kdata
__m1_:   .asciiz "  Exception "
__m2_:   .asciiz " occurred and ignored\n"

__e0_:   .asciiz "  [Interrupt] "
__e1_:   .asciiz    "  [TLB]"
__e2_:   .asciiz    "  [TLB]"
__e3_:   .asciiz    "  [TLB]"
__e4_:   .asciiz    "  [Address error in inst/data fetch] "
__e5_:   .asciiz    "  [Address error in store] "
__e6_:   .asciiz    "  [Bad instruction address] "
__e7_:   .asciiz    "  [Bad data address] "
__e8_:   .asciiz    "  [Error in syscall] "
__e9_:   .asciiz    "  [Breakpoint] "
__e10_:  .asciiz    "  [Reserved instruction] "
__e11_:  .asciiz    ""
__e12_:  .asciiz    "  [Arithmetic overflow] "
.
.
.
.
__e30_:  .asciiz    "  [Cache]"
__e31_:  .asciiz    ""
__excp:  .word __e0_, __e1_, __e2_, __e3_, __e4_, __e5_, __e6_, __e7_, __e8_, __e9_
         .word __e10_, __e11_, __e12_, __e13_, __e14_, __e15_, __e16_, __e17_, __e18_,
         .word __e19_, __e20_, __e21_, __e22_, __e23_, __e24_, __e25_, __e26_, __e27_,
         .word __e28_, __e29_, __e30_, __e31_
```

PCSpim

File Simulator Window Help

```
PC        = 00000000
Status    = 3000ff11

R0   (r0)  = 00000000
R1   (at)  = 00000000
R2   (v0)  = 0000000a
R3   (v1)  = 00000000
R4   (a0)  = 00000001
```

Console

Exception 7   [Bad data address]   occurred and ignored

```
[0x00400000]    0x8fa4                      # argc
[0x00400004]    0x27a5                      # argv
[0x00400008]    0x24a6                      # envp
[0x0040000c]    0x0004
[0x00400010]    0x00c2
[0x00400014]    0x0c10
[0x00400018]    0x0000
[0x0040001c]    0x3402
```

```
        DATA
[0x10000000]...[0x1004

        STACK
[0x7fffef78]
[0x7fffef80]
[0x7fffef90]
[0x7fffefa0]
```

DOS and Windows ports
Copyright 1997 by Morgan Kaufmann Publishers, Inc.
See the file README for a full copyright notice.
Loaded: C:\Program Files\PCSpim\exceptions.s
C:\Documents and Settings\Karl Marklund\My Documents\Teaching\Digitalteknik och Datorarkitektur vt 2008 (1D
Exception occurred at PC=0x0040004c
  Bad address in data/stack read: 0x00000000

I/O enhet

Processor

Communication?

Programs we write...

Input devices

Output devices

CPU

Control unit ↔ Arithmetic logic unit

Memory

External storage

Memoy Mapped registers for output of a charactes

7fff fffc$_{hex}$ — Stack segment

Dynamic data / Static data — Data segment

10000000$_{hex}$

Text segment

400000$_{hex}$ — Reserved

Output – *Transmitting* characters

Ready-Bit: automatically set to 1 if the device is ready to transmit a new character, that is, if the character stored in transmitter data has been consued.

Address in memory for the memory mapped register Transmitter control.

Transmitter control (0xffff0008)

Unused   1   1

Interrupt enable   Ready

Transmitter data (0xffff000c)

Unused   8

Transmitted byte

Address in memory for the memory mapped register Transmitter data.

ASCII value of character to output.

Minnes-mappade register för inmatning av tecken.

Input – *Receiving* characters

7fff fffc$_{hex}$

Stack segment

Dynamic data

Static data

Data segment

10000000$_{hex}$

Text segment

400000$_{hex}$

Reserved

Ready-Bit: automatically set to 1 when a new character arrives. Automatically set to 0 when the charecters is consumed (loaded) from Receiver data.

Address in memory for the memory mapped register Receiver control.

Receiver control (0xffff0000)

Unused

1   1

Interrupt enable   Ready

Address in memory for the memory mapped register Receiver data.

Receiver data (0xffff0004)

Unused

8

Received byte

ASCII value of the received character.

Direct Memory Access (DMA)

DMA Issues

- *Handshaking* between DMA controller and the device controller
- *Cycle stealing*
  - DMA controller takes away CPU cycles when it uses CPU memory bus, hence blocks the CPU from accessing the memory
- In general DMA controller improves the total system performance

Direct Memory Access

- For high-bandwidth devices (like disks) interrupt-driven I/O would consume a *lot* of processor cycles

- DMA – the I/O controller has the ability to transfer data directly to/from the memory without involving the processor
  - The processor initiates the DMA transfer by supplying the I/O device address, the operation to be performed, the memory address destination/source, the number of bytes to transfer
  - The I/O DMA controller manages the entire transfer (possibly thousand of bytes in length), arbitrating for the bus
  - When the DMA transfer is complete, the I/O controller interrupts the processor to let it know that the transfer is complete

Want to put less load on the CPU

Interrupt only when the transfer is done

There may be multiple DMA devices in one system

Processor and I/O controllers contend for bus cycles and for memory

MS-DOS 7.10 Setup

MS-DOS 7.10 is now being

Please wait..

MS-DOS 7.10 Setup is unpacking necessary files...

Some operating systems, such as MS-DOS (the predecessor to the Microsoft Windows operating systems) **do not have a distinct kernel mode**; rather, they allow user programs to interact directly with the hardware components.

However, **Unix-like operating systems** use the dual mode mechanism (**user mode/kernel mode**) to **hide** all of the low level **details regarding the physical organization** of the system from application programs launched by the user as a means of assuring system stability and security.

S   DOS Setup

When the CPU is in *kernel mode*, it is assumed to be executing *trusted* software, and thus *it can execute any instructions and reference any memory addresses*.

of the UNIX System

Kernel

Shell

Tools & Apps

A *system call* is a request to the kernel in a Unix-like operating system by an active process for *a service performed by the kernel*.

User mode software must request use of the kernel by means of a *system call* in order to perform privileged instructions, such as process creation or input/output operations.

"Next time a UNIX addict tries to intimidate you, reach for this book."
— Clifford Stoll, Author of the Bestselling *The Cuckoo's Egg*

THE UNIX-HATERS Handbook

The Best of the UNIX-HATERS On-li...

Dennis Ritchie, AT&T Bell Labs

(Special) instructions that can cause harm are called *privileged instructions* e.g. open, create, delete, share files, using input/output devices.

Should be executed only by the OS in supervisor mode

***System call* is a special instruction that *transfers control from user mode to supervisor mode* to a system-call service routine that is part of the OS.**

The OS verifies if the call is correct, legal only then executes the call and *returns control back to the instruction following the system call*.

***Protects the system* – protects the OS from errant/malicious users and errant users from one another!**