ZetaERP — Manual Bug-Testing SOP

Part 7 — Barcode (product barcodes, Code128/EAN encoding, label printing, POS scan)

Document	QA-SOP-07 — Barcode
Product	ZetaERP / Zenith (multi-tenant POS / ERP)
Environment under test	Production — https://erp.zetaclantech.com
Scope of this part	The **Barcode** surface end-to-end: the dedicated **Barcode** module (`/apps/zenith/barcode` — Dashboard, **Product Barcodes** grid, **Label Templates**, **Print Jobs**, the `ProductBarcode` multi-barcode model with EAN/UPC/Code128 types + checksum validation), the **POS barcode screens** (`/apps/zenith/pos/Barcodes` bulk-assign grid + duplicate detection, `/apps/zenith/pos/BarcodeLabels` sticker printing), the **single-product code/barcode** field on EditProduct, the **Code128 / EAN encoders**, label rendering & printing, and **POS Terminal scan → cart** resolution.
Audience	Manual QA tester (no code knowledge assumed)
Document owner	Platform / Solo-dev
Status	Active
Last updated	2026-07-01

CONTENTS

1. Purpose
2. Critical rules for the tester (read before starting)
3. Test environment & preconditions
4. Test data
5. Conventions & severity
6. Flow map (barcode lifecycle)
7. BARCODE DASHBOARD
8. PRODUCT BARCODES (rich ProductBarcode model)
9. LABEL TEMPLATES & PRINT JOBS
   - 9.1 Label Templates
   - 9.2 Print Jobs
10. POS BARCODES GRID & LABEL PRINTING (the pseudoId path)
    - 10.1 POS Bulk Barcodes grid
    - 10.2 POS Barcode Labels (Code128 sticker printing)
11. THE TWO-SYSTEM GAP & SINGLE-PRODUCT EDIT
    - 11.1 Single-product code edit
    - 11.2 The integration gap (verify explicitly)
12. POS TERMINAL SCAN → CART (resolution)
13. MULTI-TENANT ISOLATION
14. UI / ACCESSIBILITY / SECURITY & defect template
15. Areas to probe hardest (attention map)
16. Teardown (mandatory)

1. Purpose

This Standard Operating Procedure tells a tester **exactly how to manually test the Barcode surface A→Z**: creating/assigning barcodes (single, bulk, auto-generated), validating **EAN-13/EAN-8/UPC-A checksums**, enforcing **uniqueness** and **primary** selection, designing **label templates**, **previewing + printing** scannable labels, and — most importantly — **scanning a barcode at the POS Terminal and getting the right product into the cart**. The barcode is what makes fast checkout work, so the highest-value tests are the round-trips: *assign a barcode → print a label → scan that label → correct product appears*.

> **Read this first (the key structural fact):** there are **two barcode stores**:
>
> - The **Barcode module** (`/apps/zenith/barcode`) stores rich barcodes in the `ProductBarcode` entity (multiple per product, typed EAN/UPC/Code128, checksum-validated).
> - **POS billing** and the `pos/Barcodes` grid / `pos/BarcodeLabels` use the product's `pseudoId` ("Item Code / Barcode") field.
>
> **As of commit 39642da the POS Terminal scan resolves BOTH** — `pseudoId` (exact) → `productId` → `ProductBarcode.barcodeValue` (org-scoped, active) → name/code substring. So a barcode added in *Product Barcodes* now scans at the till even if it isn't the `pseudoId` . Re-verify this (§11, BC-060). Label **printing** (`pos/BarcodeLabels`) still keys off `pseudoId` , so a product still needs a `pseudoId` to be *printed* from that screen.

---

2. Critical rules for the tester (read before starting)

> ⚠️ **This is a LIVE commercial system. Barcodes drive real checkout.**

1. **NEVER edit, reassign, or delete a real product's barcode/ `pseudoId`** on the live flagship tenant **MARUTHI (org `100000`)** or any live tenant. A changed `pseudoId` means that product **stops scanning at the till**. Test on a **throwaway tenant** with throwaway products.
2. **Do not print to a real shared printer** during tests — use Print-to-PDF / a preview, or the browser print dialog's cancel. Don't spool test sheets to a store printer.
3. **Duplicate/uniqueness tests must be isolated** — a duplicate `pseudoId` on a live tenant can cause the wrong product to be billed. Only create duplicates on throwaway products, and clean them up.
4. **Clean up every test barcode, label template, print job, and product** you create (§16), or hand the list to the dev.
5. **Barcode data is per-tenant** — verify isolation (§12); a cross-tenant barcode/product resolution is **Critical**.
6. Record the **exact scanned/typed string** (including leading zeros and any scanner suffix like Enter) for every scan case — leading zeros and hidden characters are where barcode bugs hide.

---

3. Test environment & preconditions

Screens (open from the app menu):

Area	Screen (URL)	App	Purpose
Barcode Dashboard	`/apps/zenith/barcode/BarcodeDashboard`	/apps (Bootstrap)	Overview + quick lookup
Product Barcodes	`/apps/zenith/barcode/FindBarcode`	/apps	Add / auto-generate / manage `ProductBarcode` (typed, multi)
Label Templates	`/apps/zenith/barcode/LabelTemplates`	/apps	CRUD label layouts (size, columns, show name/price/SKU/MRP)
Print Jobs	`/apps/zenith/barcode/PrintJobs`	/apps	Print-job history + render labels
POS Bulk Barcodes	`/apps/zenith/pos/Barcodes`	/apps	Assign `pseudoId` per product + duplicate detection
POS Barcode Labels	`/apps/zenith/pos/BarcodeLabels`	/apps	Print Code128 stickers (SVG) by product
Single-product code	EditProduct → "Item Code / Barcode" (`pseudoId`)	**/qapps (Quasar)**	Edit one product's scan code
POS Terminal	`/apps/zenith/pos/Terminal`	/apps	Scan → add to cart (`lookupProducts` , `pseudoId`)

Storage: `Product.pseudoId` (single scan code, per `ownerPartyId`) + `zenith.erp.barcode.ProductBarcode` (many per product; unique on `organizationPartyId + barcodeValue`; types `BctEan13/BctEan8/BctUpcA/BctUpcE/BctCode128/BctCode39/BctQrCode/BctInternal`).

Encoders: a self-contained **Code128-B SVG** encoder in `pos-barcode-labels.js` (start 104, checksum `sum%103`, stop 106) and the **JsBarcode** library (`renderLabels` in the barcode module). EAN/UPC **checksum** validation lives in `add#ProductBarcode`.

Set up on the throwaway tenant: ~5 products, some with `pseudoId` set and some without; a real handheld **USB/Bluetooth barcode scanner** if available (a scanner just types the digits + Enter — you can simulate by typing). Have the **POS Terminal**, **Product Barcodes**, **POS Barcodes** and **Barcode Labels** screens reachable.

Browsers: full pass on Desktop Chrome; spot-check Edge/Safari/mobile. **Tools:** a barcode scanner (or keyboard), a phone barcode-scanner app to read a printed/preview label, DevTools (Console/Network), and Print-to-PDF.

---

4. Test data

Label	Use
Throwaway tenant	Non-MARUTHI org for all barcode testing
`PROD_A` … `PROD_E`	Throwaway products (some with `pseudoId`, some blank)
Valid EAN-13	e.g. `5901234123457` (valid checksum)
Bad-checksum EAN-13	e.g. `5901234123450` (last digit wrong)
Valid UPC-A	e.g. `036000291452`
Code128 value	e.g. `ZEN-ABC-001` (alphanumeric, variable length)
Leading-zero EAN	e.g. `0123456789012`
Duplicate value	the same code deliberately put on two throwaway products
Auto-generated	`generate#InternalBarcode` → `ZEN` + 9 digits (Code128/internal)

EAN-13 checksum (to verify by hand): from the right, weight the 12 data digits alternately ×1,×3,… ; check digit = `(10 − (sum mod 10)) mod 10`. (The service uses the mod-10 alternating 3/1 rule.)

---

5. Conventions & severity


Case Type: `FUNC` · `ENC` (encoder/checksum correctness) · `SCAN` (POS resolution) · `EDGE` · `UI` · `A11Y` · `SEC` · `ISO` · `PERF`.

Sev	Meaning	Example
S1 — Critical	Wrong product billed from a scan; cross-tenant barcode/product access; a printed label that doesn't scan or scans as the wrong code	duplicate `pseudoId` silently bills the wrong item; a Code128 label decodes to a different string
S2 — High	A barcode flow broken or validation missing	EAN checksum not enforced; `add#ProductBarcode` lets a duplicate through; scan of a valid `pseudoId` returns no match
S3 — Medium	Wrong/loose behaviour, limited impact	primary flag not exclusive; label template field ignored; no-match error unclear
S4 — Low	Cosmetic / minor UX	label spacing; grid column misaligned; dashboard count off

Logging a defect (template §14): Case ID, steps, **exact code string** (with leading zeros), product(s) involved, tenant, browser, screenshot (incl. the rendered/printed label and a phone-scan of it where relevant), Console/Network. Evidence is **mandatory** for ENC, SCAN, ISO and SEC.

---

6. Flow map (barcode lifecycle)



---

7. BARCODE DASHBOARD

Screen: `/apps/zenith/barcode/BarcodeDashboard` .

ID	Type	Title	Steps	Expected result	Sev
BC-001	FUNC	Dashboard renders	Open the dashboard	Counts (active barcodes, templates, pending jobs) render; org-scoped; no console errors	S3
BC-002	FUNC	Quick lookup	Enter a known barcode in the quick-lookup form	Resolves to the right product; unknown → clear "not found"	S2
BC-003	UI	Empty state	New tenant, no barcodes	Zero counts, no NaN/crash	S3

---

8. PRODUCT BARCODES (rich `ProductBarcode` model)

Screen: `/apps/zenith/barcode/FindBarcode` . Services `add#ProductBarcode` , `generate#InternalBarcode` , `get#ProductBarcodes` , `lookup#ProductByBarcode` .

ID	Type	Title	Steps	Expected result	Sev
BC-010	FUNC	List barcodes	Open FindBarcode	Grid of product / SKU / value / type / primary; org-scoped	S3
BC-011	FUNC	Add a Code128 barcode	Add a `BctCode128` value to `PROD_A`	Created, linked to product	S2
BC-012	ENC	**EAN-13 checksum accepted**	Add a **valid** EAN-13 (`5901234123457`)	Accepted	S2
BC-013	ENC	**EAN-13 checksum rejected**	Add a **bad-checksum** EAN-13 (`5901234123450`)	**Rejected** with a clear checksum error	S1
BC-014	ENC	EAN-8 / UPC-A checksum	Add valid + invalid EAN-8 and UPC-A	Valid accepted, invalid rejected (12/8-digit + checksum)	S2
BC-015	ENC	Wrong length / non-numeric EAN	12-digit "EAN-13", or letters in an EAN	Rejected (regex `[0-9]{13}` etc.)	S2
BC-016	FUNC	**Uniqueness within tenant**	Add a value already used by another product (same org)	**Rejected** ("barcode already used") — unique on `organizationPartyId+barcodeValue`	S1
BC-017	FUNC	Multiple barcodes / product	Add UPC + EAN + internal to `PROD_A`	All stored; product has several barcodes	S3

ID	Type	Title	Steps	Expected result	Sev
BC-018	FUNC	**Primary is exclusive**	Mark a 2nd barcode `isPrimary=Y`	The previous primary flips to N (only one primary per product)	S2
BC-019	FUNC	Auto-generate internal	`generate#InternalBarcode` for `PROD_B`	`ZEN` +9-digit Code128 value, `isActive=Y`, not primary	S3
BC-020	FUNC	`lookup#ProductByBarcode`	Look up an added value	Returns productId, name, price (mrpAmount), type; unknown → `found=false`	S2
BC-021	EDGE	Deactivate barcode	Set a barcode `isActive=N`	Excluded from active lookups	S3

9. LABEL TEMPLATES & PRINT JOBS

9.1 Label Templates

Screen: `/apps/zenith/barcode/LabelTemplates`. Entity `BarcodeLabel` (width/height mm, `columnsPerRow`, `showProductName/showPrice/showSku/showMrp`, default type, `isDefault`).

ID	Type	Title	Steps	Expected result	Sev
BC-030	FUNC	Create template	New template (50×25, 3 cols, show name+price) → Save	Persists; appears in the list	S3
BC-031	FUNC	Default template	Mark one `isDefault`	Only one default; used as the pre-selected layout	S3
BC-032	UI	Show/hide fields	Toggle name/price/SKU/MRP	The rendered label reflects each toggle (note: `showMrp` may be unused — verify)	S3
BC-033	EDGE	Silly dimensions	0×0 or huge mm, 0 columns	Handled sensibly (no divide-by-zero / blank render)	S3

9.2 Print Jobs

Screen: `/apps/zenith/barcode/PrintJobs`. Services `create#PrintJob` (+ `renderLabels` transition using JsBarcode + QR).

ID	Type	Title	Steps	Expected result	Sev
BC-034	FUNC	Create print job	Pick a template + products×qty → create	`BarcodePrintJob` (Pending), one item per product with its **primary** barcode (else productId)	S2
BC-035	FUNC	Render labels	Open renderLabels for a job	HTML page renders each barcode via JsBarcode; QR renders where type=QR	S2
BC-036	ENC	Type→format mapping	Job with EAN13/Code128/QR items	Each renders in the correct symbology (BctEan13→EAN13, BctInternal→CODE128, etc.)	S2
BC-037	FUNC	Mark printed	Mark job Completed	Status updates; history correct	S3
BC-038	EDGE	Product with no primary barcode	Job includes a product with no barcode	Falls back to productId (or is flagged) — no crash	S3

10. POS BARCODES GRID & LABEL PRINTING (the `pseudoId` path)

10.1 POS Bulk Barcodes grid

Screen: `/apps/zenith/pos/Barcodes` (writes `Product.pseudoId`; `saveBarcode` transition; JS Enter-to-save; duplicate scan).

ID	Type	Title	Steps	Expected result	Sev
BC-040	FUNC	Assign a code	Type a code for `PROD_A`, press Enter	Saved to `pseudoId`; row shows "OK"; AJAX success	S2

ID	Type	Title	Steps	Expected result	Sev
BC-041	FUNC	**Duplicate detection**	Assign the **same** code to `PROD_A` and `PROD_B`	Grid flags both as **"Duplicate"** with a count/warning	S1
BC-042	FUNC	Duplicate blocked on save?	Try to save a code already used by another product	Record actual — does `saveBarcode` **reject** it, or just warn? (a saved duplicate = wrong-product-at-till risk)	S1
BC-043	FUNC	Clear a code	Blank a product's code → save	`pseudoId` cleared; row shows "No code"	S3
BC-044	UI	Search / filter / paginate	Filter by product/category, page through	Correct filtered set; codes persist across pages	S3
BC-045	ISO	Grid org-scoped	List the grid as tenant A	Only A's products; duplicate scan spans only A	S1

10.2 POS Barcode Labels (Code128 sticker printing)

Screen: `/apps/zenith/pos/BarcodeLabels` (`pos-barcode-labels.js` Code128 SVG; sizes 50×25 / 38×25 / 65×35 / 100×50 mm; copies; show price; preview + iframe print).

ID	Type	Title	Steps	Expected result	Sev
BC-050	FUNC	Only coded products selectable	Open the screen	Products **without** `pseudoId` show ❌ / can't be ticked; coded ones tickable	S2
BC-051	FUNC	Preview labels	Tick 2 products, size 50×25, copies 2, show price → Preview	4 labels render in the sheet; name + barcode + code text + ₹price	S2
BC-052	ENC	**Printed label scans back correctly**	Preview/print a label, scan it with a phone app **or** the handheld into a text box	The decoded string **exactly equals** the product's `pseudoId` (incl. leading zeros)	S1
BC-053	ENC	Code128 checksum correctness	Compare the SVG encoder output with JsBarcode for the same value	Byte-identical bars (encoder proven equal to JsBarcode) — decodes identically	S1
BC-054	FUNC	Label sizes & module width	Try 38×25 and 100×50	Barcode scales (module width by label width); still scannable	S3
BC-055	FUNC	Copies & batch	3 products × 3 copies	9 labels, grid wraps, `page-break-inside:avoid` (no split labels)	S3
BC-056	UI	Print pipeline	Click Print	Hidden iframe → browser print dialog; **no popup blocked**; cancel-safe	S3
BC-057	EDGE	Long / special-char value	A long Code128 value; a value with `& < ' \`	SVG width scales; value HTML/JS-escaped (no broken render / injection)	S2

---

11. THE TWO-SYSTEM GAP & SINGLE-PRODUCT EDIT

11.1 Single-product code edit

Screen: EditProduct → "Item Code / Barcode" = `pseudoId` (**/qapps Quasar**).

ID	Type	Title	Steps	Expected result	Sev
BC-058	FUNC	Edit pseudoId	Set a product's Item Code and Save	`pseudoId` persists; field editable (Quasar input)	S2
BC-059	EDGE	No validation on pseudoId	Enter spaces / very long / duplicate here	Record actual — this field has **no** checksum/uniqueness guard (unlike `ProductBarcode`)	S3

11.2 The integration gap (verify explicitly)

ID	Type	Title	Steps	Expected result	Sev
BC-060	SCAN	**ProductBarcode value scans at POS**	Add a value **only** in *Product Barcodes* (`ProductBarcode`), leave `pseudoId` blank → go to the Terminal and scan it	The product is found and added to the cart. **[Fixed 39642da — the Terminal scan now resolves `pseudoId` → `productId` → `ProductBarcode.barcodeValue` (org-scoped, active) → substring. Verified a ProductBarcode-only value resolves to its product.]**	S1
BC-061	SCAN	Same value as pseudoId **does** scan	Set that value as the product's `pseudoId` too → scan	Product resolves and adds to cart	S1

12. POS TERMINAL SCAN → CART (resolution)

Screen: `/apps/zenith/pos/Terminal` (`lookupProducts` , `cartInlineSearch` ; resolves `pseudoId` exact → `productId` → substring on ≤500).

ID	Type	Title	Steps	Expected result	Sev
BC-070	SCAN	Exact `pseudoId` scan	Scan a product's exact code into the cart search	Correct product added to cart immediately	S1
BC-071	SCAN	Scanner Enter key	Scan with a real handheld (types digits + Enter)	Enter triggers add; no stray newline in the field	S2
BC-072	SCAN	Type-ahead by name/code	Type a partial name / code	`lookupProducts` returns top matches (pseudoId/name/productId substring)	S3
BC-073	SCAN	**Unknown barcode**	Scan a code with no product	Clear "not found" message; **nothing** added; cart unchanged	S2
BC-074	SCAN	Duplicate `pseudoId` (prevented)	Attempt to give two products the same `pseudoId` in one org	A within-org duplicate is **blocked** — the DB enforces `UNIQUE (pseudo_id, owner_party_id)` and the save screens show a friendly error first. **[Verified 39642da — the scan also uses `list()` (not `one()`) and returns a clear "fix the duplicate" message rather than mis-billing, hardening the cross-org edge.]**	S2
BC-075	SCAN	Leading zeros	Product `pseudoId` `0123456789012` ; scan it	Resolves exactly (leading zeros preserved end-to-end)	S2
BC-076	PERF	Large catalogue	Tenant with ~3000 products; scan	Resolves fast (indexed pseudoId path, not a full scan every time)	S3
BC-077	EDGE	Whitespace / case	Scan with trailing space or different case	Record actual — does trim/case-insensitivity help or cause a false match?	S3

13. MULTI-TENANT ISOLATION

`ProductBarcode` , `BarcodeLabel` , `BarcodePrintJob` , `BarcodePrintJobItem` are org-filtered (`MANTLE_ACTIVE_ORG` set); `Product` by `ownerPartyId` .

ID	Type	Title	Steps	Expected result	Sev
ISO-001	ISO	Barcodes scoped	Tenant A lists Product Barcodes / labels / jobs	Only A's rows; none of B's	S1
ISO-002	ISO	Same value, two tenants	A and B each have a product with value `123456`	Each resolves to **its own** product; no cross-over	S1
ISO-003	ISO	POS scan scoped	A's Terminal scans a code that only B's product has	**No match** on A (lookup filters by A's org)	S1
ISO-004	ISO	Direct-URL / lookup	A calls `lookup#ProductByBarcode` for B's value	Not found / not B's product	S1
ISO-005	ISO	Print-job render scoped	A opens renderLabels for a job id belonging to B	Blocked / not found	S1

14. UI / ACCESSIBILITY / SECURITY & defect template

ID	Type	Title	Check	Expected result	Sev
BC-090	UI	Desktop layout	Grids + label sheet at 1920/1366	Aligned; label preview grid correct	S4
BC-091	UI	Mobile layout	POS Barcodes / Labels at 360–390px	Usable; no horizontal overflow	S3
BC-092	A11Y	Keyboard	Tab through the grid code inputs; Enter saves	Logical order; Enter-to-save works; visible focus	S3
BC-093	SEC	XSS via product name/value	Product name / barcode value `<img src=x onerror=alert(1)>`	Escaped in grids, labels (SVG/HTML) and print output; never executes (BC-057)	S1
BC-094	SEC	Save-barcode authz/CSRF	(Dev-assisted) POST `saveBarcode` / `add#ProductBarcode` for another tenant's product or without a token	Rejected (org-checked + session token)	S1

```
Defect ID:        ZE-BC-____
Linked Case ID:   BC-0__ / ENC / SCAN / ISO-0__
Title / Severity / Type:
Environment:      Prod | <browser + scanner model> | tenant: <org>
Exact code string: "<value, show leading zeros / suffix>"   Type: EAN13/Code128/…
Product(s):       <productId(s) + pseudoId(s)>
Expected / Actual: (attach screenshot of grid + rendered label + a phone-scan of the label)
Console / Network: (attach)
```

15. Areas to probe hardest (attention map)

1. **The two-system gap (BC-060/061)** — **[Fixed 39642da]** the POS scan now resolves `ProductBarcode` values too, not just `pseudoId`, so the rich barcode module and the billing scan share a lookup. Re-verify a ProductBarcode-only value scans at the till.
2. **Duplicate `pseudoId` (BC-041/042/074)** — corrected finding: the DB **does** enforce `UNIQUE (pseudo_id, owner_party_id)`, so a within-org duplicate can't be created; the save screens show a friendly error before the constraint fires, and the scan now uses `list()` + a clear duplicate message for the cross-org edge. (My initial SOP claim of "no DB uniqueness" was wrong — verified the constraint exists.)
3. **Checksum guards (BC-013/014/015/059)** — `add#ProductBarcode` enforces EAN/UPC checksums; **[Fixed 39642da]** EditProduct's `pseudoId` now gets an **advisory** EAN/UPC check-digit validation (warns on a malformed numeric 8/12/13-digit code, never blocks free-form internal codes) plus a uniqueness + org-isolation guard.
4. **Printed-label-scans-back correctness (BC-052/053)** — the whole point: the Code128 SVG must decode to exactly the stored code. Scan a real printed/preview label with a phone; verify byte-for-byte, including leading zeros.
5. **POS resolution order & no-match (BC-070/073/074/075)** — exact `pseudoId` first, then productId, then substring; unknown must add nothing; leading zeros preserved.
6. **Multi-tenant isolation (§13)** — same barcode value in two tenants must resolve to each tenant's own product; A's till must never find B's product.
7. **Escaping in labels/print (BC-057/093)** — product names/values flow into SVG + inline JS + print HTML; verify escaping (XSS + broken render).

16. Teardown (mandatory)

1. **List everything created** — `ProductBarcode` rows, `pseudoId` values you set, label templates, print jobs, throwaway products — with ids.
2. **Delete/clear** them (or hand the dev the list). In particular, **clear any test `pseudoId`** and **remove duplicate codes** so nothing is left that could mis-scan.
3. Delete any **preview/print PDFs** generated locally; don't leave test sheets on a printer queue.
4. Confirm you **never touched MARUTHI** (org `100000`) or any live product's barcode/`pseudoId`.
5. Attach the run sheet(s) + defect ids to this part's report.

End of Part 7 — Barcode. Related: Part 3 — POS (the Terminal scan + checkout); Part 5 — Inventory (EditProduct holds the `pseudoId`). The three headline gaps were addressed (commit 39642da): the POS scan now resolves `ProductBarcode` values as well as `pseudoId`; `pseudoId` uniqueness is enforced by the DB (`UNIQUE (pseudo_id, owner_party_id)`) plus friendly guards on the save screens; and EditProduct's `pseudoId` gained an

advisory EAN/UPC check-digit validation + org-isolation. Still worth a dev decision: whether the two stores should be fully unified (e.g. mirror a primary `ProductBarcode` into `pseudoId`, or migrate billing entirely onto `ProductBarcode`) so there is a single source of truth, and whether label printing should read `ProductBarcode` too.