

HANDBOOK OF ELECTRIC MOTORS

Second Edition, Revised and Expanded

edited by Hamid A. Toliyat Gerald B. Kliman

Contents

| | | | cond Edition | v | | | 1.5.6 | Parameters from Fields | 19 |
|-----|--------|---------------------|--|-----------|----|------|---------|---|----------|
| • | | o the Fi edgmeni | rst Edition ts | vii ix | | | 1.5.7 | Applications in Two and Three Dimensions | 19 |
| Con | tribui | tors | | xix | | | 1.5.8 | | 19 |
| 1. | PRI | INCIPI | LES OF ENERGY CONVERSION | 1 | | | 1.5.9 | Finite Elements Directly Compute Motor Performance | 20 |
| | 1.1 | GENI | ERAL BACKGROUND | 2 | | 1.6 | | RGY STORED IN | |
| | 1.2 | MAG | NETIC MATERIALS | 4 | | | | NETICALLY COUPLED | |
| | | 1.2.1 | Properties of Ferromagnetic Materials | 5 | | 1.7 | | TIPLE-LOOP SYSTEMS CES AND TORQUES IN THE | 21 |
| | | 1.2.2 | Boundary Conditions for \overline{B} and \overline{H} | 6 | | Refe | erences | EWI | 21 23 |
| | 1.3 | | E BASIC FUNCTIONS RELATED LECTROMAGNETIC FIELDS | 6 | 2. | | | F MOTORS AND THEIR FERISTICS | 25 |
| | | 1.3.1 | Scalar Potential | 7 | | 2.0 | INTR | ODUCTION | 26 |
| | | 1.3.2 | Vector Potential | 7 | | 2.1 | POLY | PHASE SYNCHRONOUS | |
| | | 1.3.3 | Electromagnetic Induction | 8 | | | MOT | ORS | 28 |
| | | 1.3.4 1.3.5 | Energy in an Electromagnetic Field Self-Inductance and Mutual | 8 | | | 2.1.1 | Synchronous Machine Performance Considerations | 32 |
| | | 1.3.6 | Inductance Energy Stored in Current-Carrying | 8 | | 2.2 | | CTION MOTORS—POLYPHASE SINGLE-PHASE | 35 |
| | | 210.0 | Coil | 9 | | | 2.2.1 | General Theory and Definition | |
| | 1.4 | MAG | NETIC CIRCUITS | 9 | | | | of Terms Used | 35 |
| | | 1.4.1 1.4.2 | Concept of a Magnetic Circuit Two-Dimensional Field Problems | 9 12 | | | 2.2.2 | Classification of Motors According to Size | 38 |
| | 1.5 | FINIT | TE ELEMENT ANALYSIS OF NETIC FIELDS | | | | 2.2.3 | Power Requirements, Mechanical, and Thermal Design Considerations | 38 |
| | | 1.5.1 | Motivation | 15 15 | | | 2.2.4 | • | 41 |
| | | 1.5.2 | Energy Functionals | 15 | | | 2.2.5 | Electrical Design Options— | 71 |
| | | 1.5.3 | Finite Element Formulation | 16 | | | | Polyphase | 41 |
| | | 1.5.4 | Boundary Conditions | 17 | | | 2.2.6 | Electrical Design Options— | |
| | | 1.5.5 | Solution Techniques | 17 | | | | Single-Phase | 42 |

xii Contents

| | | 2.2.7 | Performance on Variable-Frequency | | | 3.3 | INITL | AL MOTOR SELECTION | 184 |
|----|------|---------|--|-----|----|------|---------|--|-----|
| | | | Sources | 43 | | | 3.3.1 | Steady-State Solutions | 184 |
| | | 2.2.8 | Linear Induction Motors | 46 | | | 3.3.2 | Dynamic Analysis | 184 |
| | | 2.2.9 | Doubly Fed Induction Motors | 54 | | 3.4 | MOTO | OR EFFICIENCY AND ENERGY | |
| | 2.3 | DIRE | CT-CURRENT MOTORS | 58 | | | CONS | IDERATIONS | 185 |
| | | 2.3.1 | Introduction | 58 | | | 3.4.1 | Efficiency Considerations | 185 |
| | | 2.3.2 | General Description | 58 | | | 3.4.2 | Energy Considerations | 188 |
| | | 2.3.3 | Tests | 62 | | 3.5 | | ACK ANALYSIS AND LIFE- | |
| | | 2.3.4 | Shunt Motors | 64 | | | | E COSTING OF MOTORS | 100 |
| | | 2.3.5 | Series Motors | 66 | | | | CONTROLS | 188 |
| | | 2.3.6 | Compound-Wound DC Motors | 68 | | | 3.5.1 | General-Purpose vs. Special Machines | 189 |
| | | 2.3.7 | Permanent Magnet Motors | 68 | | 3.6 | SAEE | TY CONSIDERATIONS | 190 |
| | | 2.3.8 | Brushless DC Motors | 70 | | 5.0 | | | 190 |
| | | 2.3.9 | Ironless Armature DC Motors | 71 | | | 3.6.1 | Application Information | 190 |
| | 2.4 | ELEC | TRIC TRACTION | 77 | | 27 | 3.6.2 | Installation TO SPECIFY A MOTOR | |
| | | 2.4.1 | Externally Powered Vehicles | 78 | | 3.7 | | TO SPECIFY A MOTOR | 190 |
| | | 2.4.2 | Internal Combustion Powered | | | | 3.7.1 | • | 191 |
| | | | Vehicles | 87 | | | 3.7.2 | | 191 |
| | | 2.4.3 | Battery Powered Vehicles | 94 | | | 3.7.3 | | 191 |
| | | 2.4.4 | Design Considerations | 98 | | | 3.7.4 | 0 , | 191 |
| | 2.5 | | ORS FOR SPECIAL | | ٠ | | 3.7.5 | Rating | 192 |
| | | | ICATIONS | 109 | | | 3.7.6 | | 193 |
| | | 2.5.1 | * * | 109 | | | 3.7.7 | | 197 |
| | | 2.5.2 | | 123 | | | 3.7.8 | | 198 |
| | | 2.5.3 | Deep Well Turbine Pump Motors | 126 | | | 3.7.9 | | 198 |
| | | 2.5.4 | Submersible Motors | 133 | | | 3.7.10 | | 198 |
| | | 2.5.5 | Solid-Rotor Induction Motors | 134 | | • | 3.7.11 | Nameplates | 198 |
| | | 2.5.6 | Synchronous Reluctance Motors | 142 | | | | Performance Tests | 199 |
| | | 2.5.7 | Aerospace Motors | 153 | | | 3.7.13 | | 199 |
| | | 2.5.8 | Superconducting Synchronous | | | | 3.7.14 | Preparation for Shipment and | 100 |
| | | | Motor | 153 | | | | Storage | 199 |
| | | 2.5.9 | | 156 | | • | | Data and Drawings | 200 |
| | | 2.5.10 | • | | | 3.8 | | IAL APPLICATIONS | 200 |
| | | | Reluctance and Permanent Magnet Motors | 159 | | | 3.8.1 | Hermetically Sealed Refrigeration Motors | 200 |
| | | 2.5.11 | Watthour Meters | 160 | | | 3.8.2 | Selection of DC Motors with | |
| | Refe | erences | | 162 | | | | Chopper Drives for Battery | |
| | | | | | | | | Powered Vehicles | 209 |
| 3. | MO | TOR S | ELECTION | 167 | | Refe | erences | | 214 |
| | 3.1 | STAN | DARDS | 168 | 4. | INI | DUCTIO | ON MOTOR ANALYSIS | |
| | | 3.1.1 | Enclosures | 168 | | | D DESI | | 215 |
| | | 3.1.2 | Dimensions | 175 | | 4.0 | INTRO | ODUCTION | 216 |
| | | 3.1.3 | Performance | 176 | | 4.1 | INDU | CTION MOTOR FIELD | |
| | 3.2 | | RACTERISTICS OF DRIVEN | | | | ANAI | | 219 |
| | | EQUI | PMENT | 181 | | | 4.1.1 | Generation of the Rotating Field | 219 |
| | | 3.2.1 | 1 | 182 | | | 4.1.2 | Winding of the Stator | 223 |
| | | 3.2.2 | Viscous Friction Torque | 182 | | | 4.1.3 | Spatial Harmonics in the Field | |
| | | 3.2.3 | Sticking Friction | 182 | | | | Curve | 237 |
| | | 3.2.4 | Coulomb Friction | 183 | | | 4.1.4 | Reactances of the Induction | |
| | | | Fluid Loads | 183 | | | | Motor | 241 |
| | | 3.2.6 | Unusual Load Situations | 183 | | | 4.1.5 | Radial Force Waves | 245 |
| | | | | | | | | | |

| Contents | xiii |
|----------|------|
| | |

| | 4.1.6 | Homopolar Flux and Unbalanced Magnetic Pull in the Two-Pole Induction Motor | 0.45 | | 4.10 | | ITE ELEMENT ANALYSIS NDUCTION MOTORS | 29 |
|-----|---------------|---|------|----|------|--------------------|--|------------|
| | 4.1.7 | Tangential Forces Caused by | 247 | | | 4.10. | 1 Motivation for Induction Motor Finite Element Analysis | 29 |
| | 4.1.8 | | 249 | | | 4.10. | 2 Three-Phase Induction Motor Finite Element Analysis | 29 |
| | 440 | Caused by Inverter Supplies | 251 | | | 4.10. | 8 | |
| | 4.1.9 | S | 252 | | | | Finite Element Analysis | 29 |
| 4.2 | | OR CONSTRUCTION | 256 | | Refe | rences | | 29 |
| | 4.2.1 | Introduction | 256 | 5. | CVA | CHD | MOTIC MOTION AND ENGINE | |
| | 4.2.2 | Squirrel-Cage Design | 257 | 5. | | DESI | ONOUS MOTOR ANALYSIS | 299 |
| | | Wound-Rotor Design | 257 | | 5.0 | | ODUCTION | 300 |
| 4.3 | | ICTION MOTOR EQUIVALENT | | | 5.1 | | AND FLUX DISTRIBUTION | 300 |
| | CIRC | | 258 | | 5.2 | | ATURE WINDINGS | 300 |
| | 4.3.1 | Introduction | 258 | | 5.2 | | Armature Inductance | 30 |
| | 4.3.2 | Steady-State Equivalent Circuit | 258 | | | | Slot Leakage | 30: 30: |
| | 4.3.3 | Transient or Dynamic Equivalent | | | | 5.2.3 | Harmonics in the Flux Distribution | 302 |
| | | Circuit | 260 | | | | Effects of Inverters | |
| 4.4 | | VALENT CIRCUITS FOR | | | 5.3 | |) WINDINGS | 302 |
| | | ABLE FREQUENCY | 261 | | 3.3 | | Leakage Flux | 302 |
| | 4.4.1 | Introduction | 261 | | | | _ | 302 |
| | 4.4.2 | Rotor Deep-Bar Effect | 262 | | 5.4 | | Field Winding Ampere-Turns PER WINDINGS | 302 |
| | 4.4.3 | Solution of Equivalent Circuits | 263 | | | | the state of the s | 303 |
| 4.5 | | PRTANT DESIGN EQUATIONS | 263 | | | | Leakage Flux | 303 |
| | 4.5.1 | Output Equation and Main | | | | | VALENT CIRCUITS | 303 |
| | 450 | Dimensions | 263 | | | 5.5.1 | Steady-State Operation | 303 |
| | 4.5.2 | Design of Stator Winding | 264 | | | 5.5.2 | V-Curves | 304 |
| | 4.5.3 | Fractional Slot Winding | 265 | | | 5.5.3 | Equivalent Circuits During Transients | 304 |
| | 4.5.4 | Squirrel-Cage Rotor Design | 265 | | | 554 | Starting Equivalent Circuits | 305 |
| 4.6 | SPEC DESIG | IAL INDUCTION MOTOR GNS | 271 | | 5.6 | LINEAR SYNCHRONOUS | | |
| | 4.6.1 | Linear Induction Motor Design | 271 | | | MOTO | | 305 |
| | 4.6.2 | Solid-Rotor Induction Motor Design | 273 | | | 5.6.1 | Definitions, Geometries, and Principle of Operation | 305 |
| 4.7 | MECE | HANICAL DESIGN | 277 | | | | Topologies | 306 |
| | 4.7.1 | Crawling and Cogging | 277 | | | 5.6.3 | Performance Calculation | 313 |
| | 4.7.2 | Vibration and Noise | 278 | | | 5.6.4 | Applications | 317 |
| | 4.7.3 | Lamination Fatigue Mechanisms | 279 | | | | GN EQUATIONS FOR A HRONOUS MACHINE | 318 |
| 4.8 | THER | MAL DESIGN | 282 | | | 5.7.1 | Magnetic and Electric Loading | 318 |
| | 4.8.1 | Methods of Cooling | 283 | | | | Main Dimensions and Stator | 010 |
| | 4.8.2 | Design of the Ventilation Circuit | 284 | | | | Windings | 318 |
| 4.9 | | PUTER-AIDED DESIGN OF | | | | 5.7.3 | Cylindrical Rotor Design | 319 |
| | ELEC | TRIC MACHINES | 284 | | | | Salient-Pole Rotors | 320 |
| | 4.9.1 | Why We Need Computers in the | | | | 5.7.5 | Field Winding Design | 320 |
| | | Design of Electric Machines | 284 | | | 5.7.6 | Full-Load Field Ampere-Turns | 320 |
| | 4.9.2 | The Nature of the Design Process | 285 | | | | Machine Oscillations and the | _0 |
| | 4.9.3 | Steps Needed to Design an Electric | | | | | Damper Winding | 321 |
| | 4.9.4 | Machine Examples of Specialized Computer | 286 | | | | E ELEMENT ANALYSIS OF HRONOUS MOTORS | 321 |
| | | Analysis | 290 | | | | Advantages of Finite Element | J21 |
| | 4.9.5 | Automation of the Design Process | 292 | | | | Analysis of Synchronous Motors | 321 |

xiv Contents

| | | 5.8.2 | Motors with Permanent Magnet | 221 | | | 6.9.1 | Advantages of FEA of DC Motors | 354 |
|----|------|------------------|------------------------------------|-------|----|-----|---------|--|-------------|
| | | 5.8.3 | Rotors Variable-Reluctance Stepper | 321 | | | 6.9.2 | Permanent Magnet Brush DC Motors | 35 |
| | | | Motors | 323 | | | 6.9.3 | Magnetization of Permanent | 55. |
| | | 5.8.4 | Axial Flux Machines | 323 | | | 0.7.0 | Magnets | 35: |
| | Refe | erences | | 325 | | | 6.9.4 | Wound-Field Brush DC Motors | 356 |
| _ | | inom c | | | | | 6.9.5 | Universal Motors | 356 |
| 6. | | RECT-C D DESI | CURRENT MOTOR ANALYSIS IGN | 327 | | Ref | erences | | 364 |
| | 6.0 | | ODUCTION | 328 | 7. | TE | STING | FOR PERFORMANCE | 36 |
| | 6.1 | | ATURE WINDINGS | 328 | | 7.0 | | ODUCTION | 360 |
| | | 6.1.1 | Wave Windings | 328 | | 7.1 | | PHASE INDUCTION MOTOR | 50. |
| | | 6.1.2 | Equalizers | 328 | | , | TEST | | 360 |
| | | 6.1.3 | Lap Windings | 329 | | | 7.1.1 | Electrical Test Standards | 360 |
| | | 6.1.4 | Machines with Reduced Numbers | | | | 7.1.2 | Types of Tests | 360 |
| | | | of Slots | 330 | | | 7.1.3 | Sample Calculations | 369 |
| | 6.2 | COM | MUTATORS | 331 | | | 7.1.4 | Variation in Testing | 369 |
| | | 6.2.1 | Commutator Construction | 331 | | | 7.1.5 | Miscellaneous Tests | 37. |
| | | 6.2.2 | Brushes and Holders | 331 | | 7.2 | SING | LE-PHASE INDUCTION MOTORS | 37 |
| | 6.3 | FIELI | POLES AND WINDINGS | 332 | | | 7.2.1 | Electrical Test Standards | 373 |
| | | 6.3.1 | Pole Laminations | 332 | | | 7.2.2 | Types of Tests | 37 1 |
| | | 6.3.2 | Main Field Windings | 332 | | | 7.2.3 | Choices of Tests | 371 |
| | | 6.3.3 | Commutating Poles and Windings | 332 | | | 7.2.4 | Variations Due to Uncontrolled | |
| | | | Pole Face Windings | 333 | | | | Factors | 372 |
| | 6.4 | EQUI | VALENT CIRCUIT | 334 | | | 7.2.5 | Curve Fitting of Performance Data | 373 |
| | | 6.4.1 | Steady-State Analysis | 334 | | | 7.2.6 | Miscellaneous Tests | 373 |
| | | 6.4.2 | Transient Analysis | 334 | | 7.3 | SYNO | CHRONOUS MOTOR TESTS | 374 |
| | 6.5 | DESIG | GN EQUATIONS | 334 | | | 7.3.1 | Electrical Test Standards | 374 |
| | | 6.5.1 | Magnetic Circuit | 335 | | | 7.3.2 | Types of Tests | 374 |
| | | 6.5.2 | Saturation | 335 | | | 7.3.3 | Choices of Tests | 388 |
| | | 6.5.3 | Detailed Magnetic Circuit | | | | 7.3.4 | Variations Due to Uncontrolled | |
| | | | Calculations | 335 | | | | Factors | 388 |
| | 6.6 | DC M | OTORS IN CONTROL SYSTEMS | 338 | | | | Curve Fitting of Performance Data | 388 |
| | | 6.6.1 | Basic Motor Equations | 338 | | | | Miscellaneous Tests | 390 |
| | | 6.6.2 | Basic Mechanical Equation | 339 | | 7.4 | DC M | OTOR TESTS | 391 |
| | | 6.6.3 | Block Diagrams | 340 | | | 7.4.1 | Electrical Test Standards | 391 |
| | | 6.6.4 | Typical Motor Characteristics | | | | 7.4.2 | Preparation for Tests | 391 |
| | | | and Stability Considerations | 341 | | | 7.4.3 | Performance Tests | 392 |
| | | 6.6.5 | Field Control | 341 | | | 7.4.4 | Special Tests | 393 |
| | 6.7 | | OTORS SUPPLIED BY | 2.42 | | 7.5 | | METICALLY SEALED | |
| | | | IFIER OR CHOPPER SOURCES | 343 | | | | IGERATION MOTORS | 394 |
| | | | List of Symbols | 343 | | | 7.5.1 | Electrical Test Standards | 394 |
| | | 6.7.2 | Analysis | 343 | | | 7.5.2 | Types of Tests | 394 |
| | | 6.7.3 | Rectifier Sources | 344 | | | 7.5.3 | Choices of Tests | 394 |
| | | 6.7.4 | Chopper Sources | 347 | | | 7.5.4 | Variations Due to Uncontrolled | |
| | 6.8 | | IANENT MAGNET DC MOTORS | 349 | | | 755 | Factors | 396 |
| | | 6.8.1 | Magnetic Materials | 349 | | | 7.5.5 | Curve Fitting of Performance Data | 397 |
| | | 6.8.2 | Design Features | 351 | | 7. | | Miscellaneous Tests | 397 |
| | c'0 | 6.8.3 | Servo and Control Motors | 354 | | 7.6 | | IALTY TESTING | 397 |
| | 6.9 | | E ELEMENT ANALYSIS OF OTORS | 354 | | | 7.6.1 | Induction Motor Stators Induction Motor Rotors | 397 |
| | | | | .).)4 | | | 7.00.2 | HILLICHON MICHOE KOTOES | 308 |

Contents

| | | 7.6.3 | Permanent Magnet Motors | 400 | | | 9.1.5 | Accelerating Torque and | |
|----|-------|----------|---|--------------------|-----|------|---------|---|------------|
| | 7.7 | SELE | CTION AND APPLICATION | | | | | Multispeed Applications | 456 |
| | | OF TI | EST EQUIPMENT | 400 | | | 9.1.6 | Starting Duty Thermal Limitations | 461 |
| | | 7.7.1 | Reasons for Testing | 400 | | | 9.1.7 | **** | |
| | | 7.7.2 | Functional Specifications of Test | | | | | Starting Topics | 464 |
| | | 7.7.0 | Equipment | 400 | | | 9.1.8 | Bus Transfer and Reclosing of | 467 |
| | | 7.7.3 | Recommended Steps in Purchasing Test Equipment | 401 | | | 010 | Induction Machines | 467 |
| | | 7.7.4 | Types of Tests | 401 401 | | | 9.1.9 | | 473 |
| | | 7.7.5 | • • | 401 401 | | | | Induction Motor Braking | 474 |
| | | 7.7.6 | Types of Data Recording Devices Mechanical and Electrical Loading | 401 | | 9.2 | | CT-CURRENT MOTORS | 475 |
| | | 1.7.0 | Devices | 402 | | | | DC Motor Starting | 475 |
| | | 7.7.7 | Instrumentation | 403 | | | | DC Motor Speed Control | 477 |
| | Refe | erences | | 404 | | | | Braking of Direct-Current Motors | 480 |
| | 11011 | AUNUUS | | 101 | | 9.3 | | ERAL CONSIDERATIONS | |
| 8. | MO | TOR I | NSULATION SYSTEMS | 407 | | | | CERNING SOLID-STATE VERTERS AND CONTROLLERS | 492 |
| | 8.1 | INTR | ODUCTION | 407 | | | 9.3.1 | Converters | 482 482 |
| | | 8.1.1 | Insulation and Ratings | 408 | | | 9.3.1 | Controllers | 482 |
| | | 8.1.2 | Influence of Insulation on Motor | | | 0.4 | | | |
| | | | Efficiency | 408 | | 9.4 | | ER ELECTRONIC DEVICES | 483 |
| | | 8.1.3 | Influence of Insulation on | | | | | Diodes | 484 |
| | | | Motor Life | 408 | | | 9.4.2 | Thyristors | 484 |
| | | 8.1.4 | Random- and Form-Wound | | | | 9.4.3 | Gate Turn-Off Thyristors | 485 |
| | | B 4 3 77 | Motors | 409 | | | 9.4.4 | Bipolar Transistors | 486 |
| | 8.2 | | DOM-WOUND MOTORS | 410 | | | 9.4.5 | Metal Oxide Semiconductor Field-Effect Transistors | 487 |
| | | 8.2.1 | Insulation System of Random- Wound Motors | 410 | | | 0.46 | Insulated-Gate Bipolar Transistors | 488 |
| | | 011 | | 410 | | | 9.4.7 | Integrated Gate-Commutated | 400 |
| | | 8.2.2 | Insulation Testing of Random- Wound Motors | 412 | | | 7.4.7 | Thyristor | 488 |
| | | 8.2.3 | Causes of Insulation Failure | 415 | | 9.5 | CONT | VERTER CIRCUITS | 488 |
| | 8.3 | | M-WOUND MOTORS | 416 | | 7.0 | 9.5.1 | Rectifier Circuits | 489 |
| | | 8.3.1 | Insulation Systems | 416 | | | 9.5.2 | Cycloconverters | 492 |
| | | 8.3.2 | Factors Affecting Insulation | 110 | | | 9.5.3 | Chopper Circuits | 493 |
| | | 0.2.2 | System Design | 419 | | | 9.5.4 | Six-Step Inverters | 493 |
| | | 8.3.3 | Insulation Testing | 422 | | | 9.5.5 | Pulse-Width Modulation Inverters | 495 |
| | 8.4 | EFFE | CT OF INVERTER DRIVES | | | | 9.5.6 | Multilevel Converters | 498 |
| | | ON S | TATOR INSULATION | 427 | | 9.6 | | TROLLERS | |
| | | 8.4.1 | Surge Voltage Environment | 427 | | | | | 498 |
| | | 8.4.2 | Distribution of Voltage Surges | | | 9.7 | | I- AND CLOSED-LOOP I'ROL OF A PERMANENT | |
| | | | within Stator Windings | 428 | | | | NET STEPPER MOTOR | 500 |
| | | 8.4.3 | Mechanisms of Insulation | | | | | Open-Loop Operation of the | 500 |
| | т. с | | Deterioration | 429 | | | ,,,, | Stepper Motor | 501 |
| | | rences | _ | 429 | | | 9.7.2 | | |
| | Gen | eral Rei | ferences | 430 | | | | Stepper Motor | 503 |
| 9. | MΩ | TOR (| CONTROL | 431 | | | 9.7.3 | Experimental Results | 509 |
| • | 9.0 | | ODUCTION | 432 | | Refe | erences | · | 511 |
| | 9.1 | | CTION MOTORS | 432 | 10 | МО | TOD P | DOTECTION | F1 F |
| | | | Electrical Voltage Surges | 432 | 10. | | | ROTECTION | 515 |
| | | 9.1.2 | Voltage Drop During Start-up | 432 | | | A Ov | | E 1 C |
| | | 9.1.3 | Starting Torque Characteristics | 43 <i>1</i> 447 | | 10.1 | | RODUCTION TECTION ACAINST | 516 |
| | | 9.1.4 | Reduced Starting Duty Schemes | 447 | | 10.2 | | TECTION AGAINST RLOADS | 516 |
| | | J. I. T | received prending Duty achemics | 40 I | | | OAE | TO TO | 210 |

| | 10.2.1 | Fuses | 517 | | | 10.9.4 | Selection of Bimetallic Thermal | |
|--------|--------|--|-----|-----|--------|---------|--|-------|
| | 10.2.2 | Thermal Overload Relays | 517 | | | | Protectors for Shaded-Pole, | |
| | 10.2.3 | Switchgear-Type Thermal Relays | 517 | | | | Permanent-Split Capacitor, and Other Slow Heat Rise Single- | |
| | 10.2.4 | | 317 | | | | Phase Motors | 536 |
| | 10.2.4 | Detectors | 517 | | | 10.9.5 | Selection of Bimetallic Thermal | |
| | 10.2.5 | Microprocessor Motor | 317 | | | | Protectors for Single-Voltage | |
| | | Protection Relays | 518 | | | | Split-Phase, Capacitor-Start, | |
| | 10.2.6 | Damper Bar Protection | 520 | | | | Capacitor-Start/Capacitor-Run, | 505 |
| | 10.2.7 | Special Current Detection | 520 | | | 1006 | and Other Single-Phase Motors | 537 |
| | 10.2.8 | Pull-Out Protection | 520 | | | 10.9.6 | Selection of Bimetallic Thermal Protectors for Dual-Voltage | |
| 10.3 | UNBA | LANCED VOLTAGE | | | | | Split-Phase, Capacitor-Start, | |
| | PROT | ECTION | 520 | | | | Capacitor-Start/Capacitor-Run | |
| | 10.3.1 | Phase Loss Relays | 521 | | | | Single-Phase Motors | 540 |
| | 10.3.2 | Negative-Sequence Voltage | | | | 10.9.7 | Selection of Bimetallic | |
| | | Relays | 521 | | | | Thermal Protectors for | |
| | 10.3.3 | Current Unbalance Relays | 521 | | 10.10 | | Three-Phase Motors | 541 |
| | | Microprocessor Devices | 521 | | 10.10 | | NG AGENCY | |
| 10.4 | | ECTION FOR INTERNAL | | | | | REMENTS FOR MOTOR MAL PROTECTORS | 542 |
| | | TRICAL FAILURES | 521 | | | | | 542 |
| | 10.4.1 | Stator Insulation Failure | | | | 10.10.2 | | 542 |
| | 10.10 | Protection | 521 | | | 10.10.2 | ** | 542 |
| | 10.4.2 | Microprocessor Protection for Internal Faults | 500 | | | | Protector Calibration Ranges | 543 |
| 10.5 | CEI E | CTION OF SWITCHING | 522 | | | 10.10.4 | | 543 |
| 10.5 | DEVIC | | 522 | | | | Ambient Temperature | 543 |
| | 10.5.1 | · · | 522 | | | | Multispeed Motors | |
| | | Electrically Operated Circuit | 322 | | | 10.10.7 | - | 543 |
| | 10.5.2 | Breakers | 522 | | 10.11 | | RMANCE REQUIREMENTS | 543 |
| 10.6 | MECH | IANICAL PROTECTION | 523 | | 10.11 | AND T | | 543 |
| | 10,6,1 | Vibration Detectors | 523 | | | 10.11.1 | Running Heating Tests | 543 |
| | 10.6.2 | Bearing Temperature Monitors | 523 | | | | | 543 |
| | 10.6.3 | Microprocessor Protection | 524 | | | | Locked-Rotor Tests | 544 |
| 10.7 | | SSORIES | 524 | | | | - | 544 |
| - *** | 10.7.1 | Filters | 524 | | | | | 544 |
| | | Ventilation Opening Guards | 524 | | | | Limited Short-Circuit Tests | 544 |
| | 10.7.3 | Space Heaters | 524 | | Refere | | Emilied Short-Circuit Tests | 545 |
| Part E | | s and Protection Coordination | 524 | | recien | CHCCS | | 343 |
| 10.8 | | DDUCTION | 524 | 11. | MEC | HANICA | L CONSIDERATIONS | 547 |
| 10.0 | 10.8.1 | Single-Element Fuses | 525 | | 11.1 | NOISE | | 548 |
| | 10.8.2 | Protection Coordination with | 323 | | | 11.1.1 | Noises of Electromagnetic | |
| | 10.0.2 | Single-Element Fuses | 525 | | | | Origin | 551 |
| | 10.8.3 | Dual-Element Fuses | 527 | | | 11.1.2 | Influence of Motor | |
| | 10.8.4 | Protection Coordination with | 32, | | | | Configuration and Design | 554 |
| | | Dual-Element Fuses | 528 | | | 11.1.3 | Regulation of Noise: Typical | |
| | 10.8.5 | Single-Phasing Protection | 529 | | | | Levels | 555 |
| Part C | | etallic Thermal Protectors | | | | 11.1.4 | Reduction of Noise Levels: | E (0 |
| 10.9 | | DUCTION | 532 | | | 1115 | Special Treatment | 560 |
| | 10.9.1 | Definitions | 532 | | | 11.1.5 | Experimental Investigation of Noise | 561 |
| | 10.9.2 | Typical Devices | 533 | | 11.2 | VIBRAT | | 566 |
| | 10.9.3 | Considerations in Device | | | 11.2 | | Vibration Measurement and | 200 |
| | | Selection | 535 | | | | Evaluation | 568 |

| Contents | - | xvii |
|----------|---|------|
|----------|---|------|

| | | 11.2.2 | Housing and Shaft Vibration | 571 | | | 12.7.1 | Ambient Temperature | 640 |
|-----|------|-----------|---|-----|-----|-------|---------------|--|-----|
| | | 11.2.3 | Mounting | 572 | | | 12.7.2 | Altitude | 640 |
| | | | Variable-Speed Motors | 572 | | | 12.7.3 | Moisture | 641 |
| | | 11.2.5 | Standards | 573 | | | 12.7.4 | Solid Contaminants | 641 |
| | 11.3 | BALA | NCING THE ROTOR | 575 | | | 12.7.5 | Chemicals | 642 |
| | | 11.3.1 | Rigid Rotors | 575 | | | 12.7.6 | Hazardous Locations | 642 |
| | | 11.3.2 | Flexible Rotors | 575 | | | 12.7.7 | Seismic Activity | 643 |
| | | 11.3.3 | Unbalance Quality | 576 | | | 12.7.8 | Nuclear Plant Safety | 643 |
| | 11.4 | BEAR | INGS | 576 | | 12.8 | POWE | R SYSTEM QUALITY | 644 |
| | | 11.4.1 | Sleeve Bearings | 576 | | | 12.8.1 | Parameters of Power System | |
| | | 11.4.2 | Antifriction Bearings | 591 | | | | Quality | 644 |
| | 11.5 | BRUS | HES | 596 | | | 12.8.2 | Adjustable Speed Drives | 650 |
| | | 11.5.1 | Introduction | 596 | | Refer | ences | | 653 |
| | | 11.5.2 | Grade Characteristic Definitions | 597 | | | | • | |
| • | | 11.5.3 | Specialty Brushes | 601 | 13. | REL | IABILI | ГҮ | 655 |
| | | 11.5.4 | - | 602 | | 13.1 | RELIA | BILITY OF LARGE MOTORS | 656 |
| | 11.6 | | R HANDLING, MOUNTING, | | | | 13.1.1 | Introduction | 656 |
| | | | MECHANICAL CONNECTION | 602 | | | 13.1.2 | IEEE 1983-1985 Survey | 656 |
| | | 11.6.1 | Motor Handling | 602 | | | 13.1.3 | Failure Rate and Downtime Data | 656 |
| | | 11.6.2 | Motor Mounting Dimensions | 603 | | | 13.1.4 | Data on Failed Components | 657 |
| | | 11.6.3 | Shaft Connections—Belts | 610 | | | 13.1.5 | Causes of Failure | 658 |
| | | 11.6.4 | Shaft Connections—Chain and Sprocket Drives and Flat Belt | | | | 13.1.6 | Comparison: 1973–1974 and 1983–1985 IEEE Surveys | 659 |
| | | | Drives | 613 | | | 13.1.7 | Comparison: AIEE 1962 and | |
| | | 11.6.5 | Shaft Connections—Couplings | 613 | | | | 1983–1985 IEEE Surveys | 659 |
| | | 11.6.6 | Shaft Connections—Splines | 614 | | | 13.1.8 | Comparison: 1983 EPRI and | |
| | | 11.6.7 | Initial Operation | 614 | | | | 1983–1985 IEEE Surveys | 660 |
| | | eferences | | | | 13.2 | RELIA BEAR | BILITY OF ANTIFRICTION INGS | 660 |
| 12. | | | ENTAL CONSIDERATIONS | 617 | | | 13.2.1 | Failure Modes of Rolling | |
| | | | DUCTION | 618 | | | | Bearings | 660 |
| | 12.2 | HEAT | TRANSFER | 619 | | | 13.2.2 | Damage Progression to Failure | 662 |
| | | 12.2.1 | Modes of Heat Transfer | 620 | | | 13.2.3 | Statistical Variation of Bearing | |
| | | | Ventilation | 623 | | | | Life | 663 |
| | 12.3 | COOL | ING OF BASIC MOTOR TYPES | 626 | | 13.3 | | ELINES FOR SUCCESSFUL | |
| | | 12.3.1 | Induction Motors | 626 | | | | IUTATION AND BRUSH | ((2 |
| | | 12.3.2 | Synchronous Motors | 627 | | | OPER/ | | 663 |
| | | 12.3.3 | DC Motors | 627 | | | | Summary | 663 |
| | | 12.3.4 | Special Cooling | 627 | | | 13.3.2 | Introduction | 663 |
| | 12.4 | ENCL | OSURES | 628 | | | 13.3.3 | Acceptable Commutator Conditions | 662 |
| | | 12.4.1 | IEC Enclosures | 628 | | | 13.3.4 | Destructive Commutator | 663 |
| | | 12.4.2 | NEMA Enclosures | 628 | | | 15.5.4 | Conditions | 664 |
| | 12.5 | THER | MAL CIRCUITS | 629 | | | 13.3.5 | Conclusion | 669 |
| | | 12.5.1 | Steady-State Circuits | 630 | | | | Reference Note | 669 |
| | | 12.5.2 | Time-Varying Circuits | 632 | | 13.4 | | FORING FOR SIGNS OF | 009 |
| | | 12.5.3 | Simplified Circuits | 633 | | 15.7 | WEAR | | 669 |
| | 12.6 | DUTY | CYCLES | 636 | | | | Introduction | 669 |
| | | 12.6.1 | RMS Loading Analysis | 636 | | | 13.4.2 | On-Line Tests | 669 |
| | | 12.6.2 | Time-Constant Analysis | 638 | | | 13.4.3 | Off-Line Tests | 670 |
| | 12.7 | AMBII | ENT AND ENVIRONMENTAL | | | | 13.4.4 | | 0.0 |
| | | EFFEC | | 639 | | | | Periodic (Off-Line)? | 672 |
| | | | | | | | | | |

xviii Contents

| | 13.5 | _ | BILITY IMPACT OF | | | 14.6 | CORE | TESTING | 719 |
|-----|-------|---------|---|---------|-----|--------|--------------------|--|------|
| | | | STABLE SPEED DRIVES | (70 | | | 14.6.1 | Loop Test Physical Arrangement | 719 |
| | | ` ′ | ON BEARINGS | 672 | | | 14.6.2 | Thermovision Monitoring During | |
| | | | Introduction | 672 | | | | the Loop Test | 720 |
| | | 13.5.2 | Bearing Current Induced by Supply Voltage | 673 | | | 14.6.3 | Other Core Test Factors | 721 |
| | | 13.5.3 | An Equivalent Circuit for | 075 | | | | Core Hot Spot Repairs | 721 |
| | | 13.3.3 | Bearing Displacement and EDM | | | | 14.6.5 | EL CID Test | 721 |
| | | | Currents | 677 | | Refer | ences | | 727 |
| | | 13.5.4 | Methods to Mitigate Bearing | | | | ~~~ | ra romana | |
| | | | Currents and Their Cost | 688 | 15. | | | IC MOTORS | 731 |
| | 13.6 | | BILITY IMPACT OF | • | | 15.1 | | NATING CURRENT MOTOR CONTROL | 732 |
| | | | STABLE SPEED DRIVES | | | | | Introduction | 732 |
| | | | ON INSULATION | 690 | | | | | 134 |
| | Refer | ences | | 690 | | | 15.1.2 | Thyristor-Based Voltage- Controlled Drives | 733 |
| 14. | MAI | NTENA | NCE | 693 | | | 15.1.3 | Thyristor-Based Load- | |
| | 14.1 | LUBRI | CATION | 694 | | | 22127 | Commutated Inverter | |
| | | 14.1.1 | Lubrication and Maintenance | | | | | Synchronous Motor Drives | 736 |
| | | | of Sleeve Bearings | 694 | | | 15.1.4 | | |
| | | 14.1.2 | Lubrication and Maintenance of | | | | | Frequency Induction Motor | |
| | | | Antifriction Bearings | 694 | | | | Drives | 740 |
| | 14.2 | | EMENTATION OF A | | | | | Field Orientation | 746 |
| | | | BILITY BASED FENANCE PROGRAM | 698 | | | | Induction Motor Observer | 752 |
| | 14.3 | | TENANCE AND REPAIR OF | 090 | | | 15.1.7 | Permanent Magnet Alternating Current Machine Control | 754 |
| | 14.3 | | MUTATORS | 700 | | 15.0 | сматс | HED-RELUCTANCE | 134 |
| | | | Causes of Poor Commutation | 701 | | 15.2 | MACH | | 759 |
| | | | Ordering New Parts | 702 | | | | Definition, History, and | ,,,, |
| | 14.4 | | H REPLACEMENT | 702 | | | 10.2.1 | Properties | 759 |
| | | 14.4.1 | Introduction | 702 | , | | 15.2.2 | Theory of Operation | 760 |
| | | 14.4.2 | When to Replace Brushes | 702 | | | 15.2.3 | Controller Architecture | 763 |
| | | 14.4.3 | Installation of Brushes | 702 | | | 15.2.4 | Applications | 763 |
| | | 14.4.4 | Summary | 704 | | 15.3 | BRUSI | ILESS DC MOTORS | 763 |
| | 14.5 | | TENANCE AND REPAIR OF | | | | 15.3.1 | Introduction | 763 |
| | - • | WIND | | 704 | | | 15.3.2 | Rotor Construction | 764 |
| | | 14.5.1 | Installation of New Equipment | 704 | | | 15.3.3 | Magnets and the Magnetic | |
| | | 14.5.2 | Establishing a Maintenance | | | | | Circuit | 765 |
| | | | Schedule | 705 | | | 15.3.4 | Armature Windings | 768 |
| | | 14.5.3 | Choosing Test Equipment | 705 | | | 15.3.5 | Torque Analysis | 769 |
| | | 14.5.4 | _ | | | | 15.3.6 | Voltage Analysis | 770 |
| | | | Maintenance | 707 | | | 15.3.7 | Equivalent Circuit | 770 |
| | | 14.5.5 | | 711 | | | 15.3.8 | Motor Drive Circuit | 770 |
| | | 14.5.6 | ~ . | 715 | | | 15.3.9 | Performance | 771 |
| | | 14.5.7 | 2 2 | 716 | | Refer | rences | | 772 |
| | | 14.5.8 | - 1 | 718 | | 4 nn - | ndivas | | |
| | | 14.5.9 | | 718 | | | ndixes uivalent | Units | 775 |
| | | 14.5.10 | | | | _ | | onus and Institute Addresses | 777 |
| | | | Maintenance and Repair of | 719 | | Index | | i ana Institute Addresses | 779 |
| | | | Windings | 117 | | тиех | • | | 117 |