Data sheet

PickForm 50 F (3 mm pins)

PickForm 50 F (3 mm pins) is a pin module for automation. The pin field adapts to the workpiece and is locked pneumatically, so one gripper or support can handle many workpiece variants without change-over.

Technical data

Description	**PickForm 50 F (3 mm pins)**
Order no.	**44.0142**
External dimensions W x L x H	**52 x 73 x 140 mm**
Pin field W x L	**32 x 41 mm**
Number of pins	**150**
Pin diameter	**3 mm**
Pin stroke	**16 mm**
Weight	**1,35 kg**
Clamping mechanism	**pneumatic**
Fixing screws	**10 mm**
Pneumatic connection	**M5 / QS-6**
Operating pressure	**6 bar, filtered compressed air**
Mounting position	**any**
CAD data	**STEP**

Issue date: 2024-06

Alvery Spanntechnik GmbH
Gewerbepark Nord 7
71272 Renningen
GERMANY

Phone: +49 7159 555 0120
Fax: +49 7159 555 0129
E-mail: info@alvery-example.com

(fictional company for assessment purposes)

Operating conditions

Ambient temperature	**+5 °C to +50 °C**
Coolant / liquids	**splash water only (IP54)**
Mounting position	**any**
Recommended max. workpiece weight	**1 kg**

Typical applications

- pick-and-place of small, delicate parts

Maintenance

Blow out the pin field with compressed air every 8 hours of operation.

Pneumatic actuators are lubricated for life. Pins: Alvery pin oil (49.9100) every 500 operating hours.

Rated for 2 million clamping cycles; replace the seal kit after 2 million cycles.

Spare parts

Article no.	Description
44.9067	Seal kit for pneumatic actuator
41.9006	Replacement pins Ø 6 mm, pack of 10

Included in the following sets

Available as a single module only.

Alvery Spanntechnik GmbH
Gewerbepark Nord 7
71272 Renningen
GERMANY

Phone: +49 7159 555 0120
Fax: +49 7159 555 0129
E-mail: info@alvery-example.com

(fictional company for assessment purposes)