# Alvery CT systems

## Pin supports for computed tomography

Computed tomography is used more and more in production because it measures contactless and fast. Alvery CT systems hold the most diverse workpieces form-fit within seconds, without retooling.

• Set-up within seconds, perfect fixation • Maximum hold with minimum force • No dedicated fixtures to produce and store • For series and single parts • Maintenance-free

Two systems: FormRest XL 100 CT for small and long parts, FormBed CT for large and heavy parts.

# FormBed CT Set

## Order no. (complete set) 45.8840

| Img. | Article number | Amount | Description |
|---|---|---|---|
| 1 | 45.0835 | 1 | Self-shaping workpiece carrier for CT: carbon fiber pin extension with foam tip. Number of pins: 88, pin tip Ø 8 mm, pin stroke: 32 mm, pin field: 94 x 205 mm, dimension: 125 x 250 x 172 mm (pins extended) |
| 2 | 42.6701 | 2 | Adapter for hold-down clamps |
| 3 | 42.3110 | 4 | Fixing elbow for hold-down clamps |
| 4 | 42.3111 | 2 | Hold-down set (carbon fiber): 3 x 120 mm, 2 x 300 mm |
| | | | Optional complement to the set: |
| | 42.6727 | 2 | FormRest connecting element, base plate 50 x 100 mm |
| | 42.6728 | 2 | FormRest base plate 50 x 100 mm |
| | 49.0200 | 1 | T-slot profile plate 250 x 200 mm |

# FormRest XL 100 CT Set

## Order no. (complete set) 42.6760

| Img. | Article number | Amount | Description |
|---|---|---|---|
| 1 | 42.6757 | 2 | Carbon pin extension with PE foam tip (incl. module 42.0672) |
| 2 | 42.6727 | 2 | FormRest connecting element, base plate |
| 3 | 42.6728 | 2 | FormRest base plate |
| 4 | 42.3110 | 4 | Fixing elbow for hold-down clamps |
| 5 | 42.3112 | 2 | Hold-down set (carbon fiber): 3 x 120 mm, 2 x 250 mm |
| 6 | 49.0200 | 1 | T-slot profile plate |
| 7 | 49.0501 | 1 | Clamping brackets for T-slot plate (1 set = 3 pcs) |
| 8 | 49.2501 | 1 | Fastening set (1 set = 8 pcs) |

## Notes for CT applications

Whether metal parts or technical plastics: thanks to their flexibility, Alvery CT systems suit workpieces of very different composition and shape.

The carbon pins have PE foam tips that are gentle on sensitive surfaces and have a very low attenuation coefficient, so workpiece and support can be separated easily in the reconstruction.

Repeatability: for series measurements every part is fixed in exactly the same position, without readjustment.

Note: foam tips are wear parts. Replacement tips are available in packs of 100 (article 42.6759).