
21CSE221T - Big Data Tools and Techniques

Unit I – Introduction to Big Data and Hadoop

Big Data



Infographic courtesy: DOM Inc, 2020


Sources of Big Data


What's Driving Data Deluge?





Big Data Analytics

- Performing operations like data mining, machine learning or deep learning to large scale datasets.
- Operations can be as simple as counting or as complicated as large scale complex neural network analysis.











Building Blocks of Big Data Analytics



Characteristics of Big Data


- Volume
- Variety
- Velocity
- Veracity

Characteristics of Big Data



Courtesy: IBM

Types of data



Structured data

- Data having defined organizational structure
- Uses a representable schema
- All possible data types
- Store and query

	SUMMER F	OOD SERVICE PRO	GRAM 1]	
(Data as of August 01, 2011)				
Fiscal Year	Number of Sites	Peak (July) Participation	Meals Served	Total Federal Expenditures 2]
Thousands		Mil	Million \$	
1969	1.2	99	2.2	0.3
1970	1.9	227	8.2	1.8
1971	3.2	569	29.0	8.2
1972	6.5	1,080	73.5	21.9
1973	11.2	1,437	65.4	26.6
1974	10.6	1,403	63.6	33.6

Semi-structured data

- Textual data type with a discernible pattern
- XML, JSON
- XML or JSON schema
- MongoDB, Couch DB for storage

Quasi structured data

- Textual data but with inconsistencies
- Effort and time to pre process
- E.g Clickstream data, Web server log, Network packet tracing

```
date time s-ip cs-method cs-uri-stem cs-uri-query s-port cs-username c-ip cs(User-
Agent) sc-status sc-substatus sc-win32-status time-taken
2015-08-03 12:40:57 209.133.7.95 GET /course-eligibility.asp - 80 - 115.118.114.159
Mozilla/5.0+(X11;+Linux+x86_64)+AppleWebKit/537.36+(KHTML,+like+Gecko)+Ubuntu
+Chromium/37.0.2062.120+Chrome/37.0.2062.120+Safari/537.36 200 0 0 1234
2015-08-03 12:40:58 209.133.7.95 GET /css/font-awesome.min.css - 80 -
115.118.114.159 Mozilla/5.0+(X11;+Linux+x86_64)+AppleWebKit/537.36+(KHTML,+like
+Gecko)+Ubuntu+Chromium/37.0.2062.120+Chrome/37.0.2062.120+Safari/537.36 200 0 0
2015-08-03 12:40:58 209.133.7.95 GET /images/ftrlogo.png - 80 - 115.118.114.159
Mozilla/5.0+(X11;+Linux+x86_64)+AppleWebKit/537.36+(KHTML,+like+Gecko)+Ubuntu
+Chromium/37.0.2062.120+Chrome/37.0.2062.120+Safari/537.36 200 0 0 312
2015-08-03 12:40:58 209.133.7.95 GET /css/styles.css - 80 - 115.118.114.159
Mozilla/5.0+(X11;+Linux+x86_64)+AppleWebKit/537.36+(KHTML,+like+Gecko)+Ubuntu
+Chromium/37.0.2062.120+Chrome/37.0.2062.120+Safari/537.36 200 0 0 609
2015-08-03 12:40:58 209.133.7.95 GET /js/modernizr.custom.86080.js - 80 -
115.118.114.159 Mozilla/5.0+(X11;+Linux+x86_64)+AppleWebKit/537.36+(KHTML,+like
+Gecko)+Ubuntu+Chromium/37.0.2062.120+Chrome/37.0.2062.120+Safari/537.36 200 0 0
281
2015-08-03 12:40:58 209.133.7.95 GET /css/bootstrap.min.css - 80 - 115.118.114.159
Mozilla/5.0+(X11;+Linux+x86_64)+AppleWebKit/537.36+(KHTML,+like+Gecko)+Ubuntu
+Chromium/37.0.2062.120+Chrome/37.0.2062.120+Safari/537.36 200 0 0 1171
2015-08-03 12:40:58 209.133.7.95 GET /js/bootstrap.min.js - 80 - 115.118.114.159
Mozilla/5.0+(X11;+Linux+x86_64)+ApplewebKit/537.36+(KHTML,+like+Gecko)+Ubuntu
+Chromium/37.0.2062.120+Chrome/37.0.2062.120+Safari/537.36 200 0 0 593
```


Unstructured data

- Data that has no inherent structure
- Videos, Images, Documents
- Text data
 - ElastiSearch, Solr



Distributed Computing for Big Data

- Usage of more than one connected computer
- Examples: NoW(Network of Workstations)



Distributed Computing for Big Data


- Treated infrastructure as one big pool of computing, storage and networking resources
- Moves to another resource in the pool in case of failure
- Fault Tolerance or High Availability
- Cost of computing and storage resources has decreased considerably
- E.g Distributed File System

Parallel Computing for Big Data

- Serial Sequence of instructions one by one
- Start to Finish on a single processor
- Parallel Programming
 - Processing broken into multiple parts
 - Each part executed concurrently
 - Different CPUs on a single or different machines


Parallel Computing for Big Data

- First step
 - Identify set of tasks that could be run concurrently
 - Data partitioned without dependencies



Distributed, Parallel Computing


Distributed Computing



Cloud Computing for big data

- Set of high powered servers
- Pay as you use
- Memory or Storage intensive
- View and query large data sets quickly
- Infrastructure as a Service
- Platform as a Service
- Software as a Service

Cloud Computing for big data



Drivers of Cloud Computing for big data

On-demand Establish, manage, and terminate services on your own, self-service without involving the service provider Broad network Use a standard Web browser to access the user interface, without any unusual software add-ons or specific operating system requirements access Resource Share resources and costs across a large pool of users, allowing pooling for centralization and increased peak load capacity Rapid Leverage capacity as needed, when needed, and give it back when it is no longer required

Consume resources as a service and pay only for resources used

Measured

service

Cloud Computing for big data

- Need not ship terabytes of data around
- Store in cloud and move analytics close to data
- Store insensitive data in cloud
- Sensitive data Private Cloud/Clusters
- Advantages
 - Scalability
 - Cost reduction
 - Faster time to market

Cloud Computing for big data

- Limitations
 - Latency
 - Multi-tenancy overhead
 - Data privacy
 - Data Security
 - Costs are charged for static storage

In-memory computing for big data

- Computations are latency sensitive
- Have to be done in memory
- Disk reads and writes would cause delays
- For compute-intensive applications
 - Real time stream processing
 - Apache Spark

Big Data Mining

- Two broad categories of BDA
 - Big Data Mining
 - Predictive Analytics
- Big Data Mining
 - Refers to the entire life cycle of processing large data sets
 - From procurement of data to implementation of respective tools to analyze data

- Determine use cases
- Then fix the platforms

Steps

- 1. Who needs big data mining?
 - Which business groups will benefit significantly?
 - Revenue impact
 - E.g Pharmaceutical company Commercial Research, Epidemiology, Health Economics

2. Determining use cases

- Impactful analysis by working closer with practitioner (analyst) and stakeholder (business end user)
- Analyst will work on operational challenges that might be faced in implementing the BD solution
- Business user will highlight the aspects of business that will benefit from the BD solution
- An optimal outcome consolidating both

- 3. Stakeholder's buy in
 - Budget decisions
 - Establish a baseline
 - Can be leveraged on successful BD solution implementation
- 4. Early wins and effort-to-reward ratio
 - Relatively small use case
 - Implemented in short time, smaller budget
 - Optimizes a business critical function
 - Early win

- 5. Leveraging the early wins
 - Ground to develop bigger strategy
 - Establishing value of big data to an audience
 - Single department to broader organizational impact

Big Data Mining - Stakeholders

- Business Sponsor
 - Funding department for the project
 - Benefits from the solution
- Implementation group
 - Analysts, Data Scientist, Field workers
- IT procurement
 - Licensing cost
 - Software, Cloud Renting
- Legal
 - Licensing
 - Open source or in-house

Technical elements of BD platform

- Selection of hardware stack
- Selection of software stack

Selection of hardware stack

- Proper choice depends on key metrics
 - Type of data
 - Size of data
 - Frequency of data updates
- Three broad models of hardware architecture
 - Multi-node architecture
 - Single node architecture
 - Cloud based architecture

Selection of hardware stack

- Multi-node architecture
 - Multiple nodes or servers connected
 - Distributed computing
 - Commodity Servers (low end machines that work in tandem to provide large scale mining and analytics capabilities)
 - Data range TBs and above

Selection of hardware stack

- Single node architecture
 - Single server
 - Structured text data
 - **–** 1-5TB
 - Not commonly used
 - Restricted environments (mobile)

Selection of hardware stack

- Cloud architecture
 - Most efficient
 - Reduced costs in procuring, maintaining physical hardware and hosting software
 - Elastic, provisions on demand
 - Amazon AWS, Microsoft Azure, Google Compute
 - IBM Cloud Brokerage Select and manage multiple cloud based solutions

Selection of software stack

- Popular options
 - Hadoop Ecosystem
 - Multiple projects under the Apache Software Foundation.
 - Core Components:
 - Hadoop Common: Shared utilities and libraries.
 - Hadoop MapReduce: Batch processing engine.
 - Hadoop Distributed File System (HDFS): Reliable distributed storage.
 - Hadoop YARN: Resource management and job scheduling.

Selection of software stack

Popular options

- Apache Spark
 - Developed at UC Berkeley AMPLab.
 - Designed to overcome Hadoop's limitations.
 - Key Features:
 - Support for multiple programming languages, including Python and Scala.
 - Utilizes Resilient Distributed Datasets (RDDs).
 - Compatibility:
 - Integrates seamlessly with existing cluster managers like Mesos and YARN.
 - Provides distributed storage and high-speed processing.

Selection of software stack

- Popular options
 - NoSQL Storage
 - Key Value (Redis, Riak)
 - In-memory (Redis, KDB+)
 - Columnar (Cassandra, Google BigTable)
 - Document-based (MongoDB)
 - Cloud based solutions
 - SaaS, AaaS
 - Data ware houses or storage in Cloud
 - Routine tasks like backup are taken care by the vendor

- 1. Which of the below is an example for quasi structured data?
 - a. Employee information in spreadsheets
 - b. Images
 - c. Audio files
 - d. Clickstream data

- 2. Breaking the process into multiple parts and executing each part concurrently is ------ paradigm
 - a. Distributed Computing
 - b. Parallel Processing
 - c. Cloud Computing
 - d. In-memory computing

- 3. Which of the below statements is related to the attribute "veracity" of big data
 - a. 420 million wearable wireless health monitoring sensors
 - b. 2.5 quintillion bytes of data generated everyday
 - Poor data quality costs aroung \$1 trillion very year to US

- 4. Which of the below is not a Big Data Processing Engine/Framework
 - a. Hadoop
 - b. Spark
 - c. YARN
 - d. Flink

- 5. Which of the below is a NoSQL Storage platform that stores as documents
 - a. Redis
 - b. MongoDB
 - c. Cassandra
 - d. IBM DB2

History of Hadoop

- Inspired by GFS paper in 2003
- Doug Cutting was part of Nutch and Lucene
- NDFS Nutch Distributed File System
- Was moved as a separate project Hadoop

Why Hadoop

- Failure of nodes
- Scalability of nodes
- Petabytes of data to be processed in parallel
- Cost effective
- Efficient
- Data Locality
- Minimal impact to program logic

Apache Hadoop

- Open source framework
- Distributed storage and processing
 - Of large scale data sets
 - On commodity hardware
- Quickly gain insights from structured and unstructured data


Apache Hadoop - Core components

- Hadoop Common
 - Has libraries and utilities required by other modules
- Hadoop Distributed File System (HDFS)
 - Distributed FS
 - Stores data on commodity machines
 - Very high aggregate bandwidth across clusters

Apache Hadoop - Core components

- Hadoop Mapreduce
 - A programming model for large scale data processing
- Hadoop YARN
 - Resource management platform
 - Manages computing resources in clusters
 - Schedules user applications on computing resources

Hadoop Core Components



- Hadoop Ecosystem & System Management
- ZooKeeper: Manages distributed coordination among Hadoop components, ensuring reliability and fault tolerance.
- System Management: Involves tools for monitoring, managing, and optimizing Hadoop clusters.

- Storage Layer
- HDFS (Hadoop Distributed File System):
 - Serves as the foundational storage system in Hadoop.
 - Stores large-scale file data across multiple machines.
 - Provides fault tolerance by replicating data across nodes.

- Data Processing Layer
- MapReduce:
 - A distributed processing model that splits tasks into parallel jobs.
 - Executes computations efficiently on massive datasets.
 - Works with HDFS to process data stored in a distributed manner.

- Data Storage & Querying
- HBase (Row/Column Data Storage):
 - A NoSQL database that provides real-time read/write access.
 - Stores data in a key-value format.
 - Works efficiently with MapReduce and HDFS.
- File Data:
 - Structured and unstructured file data stored in HDFS.

- Query & Processing Languages
- **PIG** (Scripting Language for Big Data Processing):
 - A high-level scripting language designed for data transformation.
 - Converts scripts into MapReduce jobs.
 - Handles semi-structured and structured data efficiently.
- Hive (SQL-on-Hadoop for Querying Large Datasets):
 - Provides an **SQL-like** interface for querying big data.
 - Translates HiveQL (SQL-like queries) into MapReduce jobs.
 - Works well with structured and semi-structured data.


- Search & Indexing
- Lucene:
 - A search engine used for indexing and searching large datasets.
 - Works with Hadoop to enable text-based retrieval.

- Data Extraction & Connectivity
- Large Data Extraction (ETL Extract, Transform, Load):
 - Involves processing large datasets before storing them in Hadoop.
 - Supports integration with external databases.
- Connectivity Options (JS, JDBC, ODBC):
 - JS (JavaScript), JDBC (Java Database Connectivity), and ODBC (Open Database Connectivity) allow users to access Hadoop data from external applications.

Hadoop Core Components Summary

- Four major components
 - Storage --> HDFS
 - Processing --> MR
 - Scheduling --> YARN
 - Common utilities
- Mostly written in Java

Hadoop Core Components



File System

- Methods and data structures that an OS uses to keep track of files on a disk or partition
- Allocates space
- Responsible for organizing files and directories
- Unused space/Slack Space Allocation size

Distributed File System

- File systems that manage storage across a n/w of machines
- Network based so more complex than regular file systems
- Example: Tolerate node failure without data loss.
- Distribution is hidden and is not visible to the user
- High throughput data access


HDFS

- How HDFS is different?
 - Highly fault tolerant
 - Designed for low cost hardware
 - High throughput access to data


Suitable For	Not Suitable For
Very large files	Low-latency data (Hbase is a better choice)
Streaming data access	Lots of small files
Commodity hardware	Multiple writes, arbitrary access

HDFS


- Follows a master slave architecture
- HDFS Cluster (Group of connected machines)
 - Name node
 - Secondary Name node
 - Multiple Data nodes



HDFS



HDFS Architecture



HDFS Concepts

- Blocks
- Namenodes
- DataNodes
- Block Caching
- HDFS Federation
- HDFS High Availability

HDFS Blocks

- Disk Block 512 bytes
- File System Block few kBs
- HDFS Block size 128 MB
- Files in HDFS are broken into block size chunks
- Advantages of block abstraction
 - One file can be larger than a hard disk
 - Blocks from a single file can be stored across multiple disks
 - Simplicity
 - Fit with replication

Name Node

- Master node
- Maps file to blocks and blocks to nodes
- Maintains file system tree and metadata for all files
- Two files
 - FSImage
 - Edit log
- Maintains status of data node
 - Heartbeats
 - Blockreport
- Manages replication
 - Block corruption
 - Data node failure
 - Disk failure

Name Node

- Data Integrity
 - Checksum for each block
- Balancing
 - Addition of new nodes
 - Decommisioning
 - Deletion of failed nodes
 - Maintain metadata

Name Node

- Without name node, HDFS cannot be used
- FS does not know to construct a file
- Should be resilient to failure
 - Metadata is persisted with back up
 - Secondary name node

Secondary Name node

- Present on a separate physical machine
- Does not act as a name node
- Periodically merges edit log with namespace image.
- Keeps a copy of the merged namespace image and edit log
- Data loss is certain


Block Caching

- Data nodes read blocks from disk
- Frequently accessed files blocks are cached in memory
- Off-heap block cache
- Job schedulers run tasks on data node where data is cached for better performance
- Users or application can configure what to cache and how long

HDFS Federation

- Single namenode
 - Keeps track of every file and block
 - Very large clusters with many files?
 - Memory becomes a limiting factor for scaling
- Multiple name nodes
 - Each will manage a portion of file system
 - Each namenode manages a name space volume
 - Namespace (Dedicated for each NN no overlap)
 - Block pool (DNs register with each NN and store blocks from multiple block pools)
 - Name nodes are independent and failure of one does not affect other

HDFS Federation



Courtesy: Cloudera


High Availability

- Secondary NN or Backup
- SPOF
- Recovery from a failure
 - Admin starts a new NN with FS replicas
 - Asks the DNs to use the new NN
- New NN is not ready till
 - loaded its namespace image into memory
 - replayed its edit log, and
 - received enough block reports from the datanodes to leave safe mode.

High Availability

- Takes 30 mins for large clusters
- From Hadoop 2 pair of namenodes in an active-standby configuration
- Architectural changes required:
 - The namenodes must use highly available shared storage to share the edit log.
 - Datanodes must send block reports to both namenodes
 - Clients must be configured to handle namenode failover
 - Includes Secondary NN functionality


Anatomy of a file read



A client reading data from HDFS

Anatomy of a file write

ANATOMY OF A FILE WRITE



4

A client writing data to HDFS

Basic HDFS Shell Commands

https://hadoop.apache.org/docs/r1.2.1/file_s
 ystem_shell.html


Hadoop Ecosystem

- Hadoop Ecosystem is a platform or a suite which provides various services to solve the big data problems.
- It includes Apache projects and various commercial tools and solutions.
- All these tools work collectively to provide services such as absorption, analysis, storage and maintenance of data etc.

Hadoop Ecosystem

- HDFS: Hadoop Distributed File System
- YARN: Yet Another Resource Negotiator
- MapReduce: Programming based Data Processing
- Spark: In-Memory data processing
- PIG, HIVE: Query based processing of data services
- HBase: NoSQL Database
- Mahout, Spark MLLib: Machine Learning algorithm libraries
- Solar, Lucene: Searching and Indexing
- Zookeeper: Managing cluster
- Oozie: Job Scheduling

Hadoop Ecosystem



Courtesy: Cloudera