

1. Putty Commands

```
R4_G8_S1>show ip

Switch IP address: 192.168.100.82

Subnet mask: 255.255.255.0

Default router address: None
TFTP server address: None
Configuration filename: None
Image filename: None
DNS Server: N/A
IP MTU: 1500

R4_G8_S1>show vlan
Total PORT-VLAN entries: 1
Maximum PORT-VLAN entries: 1024

Legend: [Stk=Stack-Id, S=Slot]

PORT-VLAN 1, Name DEFAULT-VLAN, Priority level0, On
Untagged Ports: (U1/M1) 1 2 3 4 5 6 7 8 9 10 11 12

Untagged Ports: (U1/M2) 1 2
Untagged Ports: (U1/M3) 1 2
Tagged Ports: None
Mac-Vlan Ports: None
Monitoring: Disabled

R4_G8_S1>show version
Copyright (c) Ruckus Networks, Inc. All rights reserved.
UNIT 1: compiled on Jun 9 2023 at 06:14:36 labeled as SPS08095k
(31457280 bytes) from Primary SPS08095k.bin (UFI)
SW: Version 08.0.95kT211
Compressed Primary Boot Code size = 786944, Version:10.1.26T225 (mnz10126)
Compiled on Tue Nov 29 12:43:26 2022

HW: Stackable ICX7150-C12-POE
=====
UNIT 1: SL 1: ICX7150-C12-2X1G POE 12-port Management Module
Serial #:FEK3810V04L
Software Package: BASE_SOFT_PACKAGE
Current License: 2X10GR
P-ASIC 0: type B160, rev 11 Chip BCM56160_B0
=====
UNIT 1: SL 2: ICX7150-2X1GC 2-port 2G Module
=====
UNIT 1: SL 3: ICX7150-2X10GF 2-port 20G Module
=====
1000 MHz ARM processor ARMv7 88 MHz bus
8 MB boot flash memory
2 GB code flash memory
```

2. Creating VLANS 10 and 20

```
R4_G8_S1>vlan 10
Invalid input -> vlan 10
Type ? for a list
R4_G8_S1>vlan10
Invalid input -> vlan10
Type ? for a list
R4_G8_S1>en
No password has been assigned yet...
R4_G8_S1#config t
R4_G8_S1(config)#vlan 10
R4_G8_S1(config-vlan-10)#untagged eth 1/1/1 to 1/1/4
Added untagged port(s) ethe 1/1/1 to 1/1/4 to port-vlan 10.
R4_G8_S1(config-vlan-10)#tagged eth 1/2/1 to 1/2/2
Added tagged port(s) ethe 1/2/1 to 1/2/2 to port-vlan 10.
R4_G8_S1(config-vlan-10)#exit
R4_G8_S1(config)#vlan 20
R4_G8_S1(config-vlan-20)#untagged eth 1/1/9 to 1/1/12
Added untagged port(s) ethe 1/1/9 to 1/1/12 to port-vlan 20.
R4_G8_S1(config-vlan-20)#tagged eth 1/2/1 to 1/2/2
Added tagged port(s) ethe 1/2/1 to 1/2/2 to port-vlan 20.
R4_G8_S1(config-vlan-20)#
```

3. Now Pinging from those VLAN to other VLAN

3.1 Same VLAN same switch

```
C:\Users\RVU>ping 192.168.100.87

Pinging 192.168.100.87 with 32 bytes of data:
Reply from 192.168.100.87: bytes=32 time<1ms TTL=128
Reply from 192.168.100.87: bytes=32 time=1ms TTL=128
Reply from 192.168.100.87: bytes=32 time=1ms TTL=128
Reply from 192.168.100.87: bytes=32 time=1ms TTL=128

Ping statistics for 192.168.100.87:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\Users\RVU>
```

3.2 Same VLAN same switch

```
C:\Users\RVU>ping 192.168.100.87

Pinging 192.168.100.87 with 32 bytes of data:
Reply from 192.168.100.87: bytes=32 time<1ms TTL=128
Reply from 192.168.100.87: bytes=32 time=1ms TTL=128
Reply from 192.168.100.87: bytes=32 time<1ms TTL=128
Reply from 192.168.100.87: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.100.87:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms
```

3.3 Different VLAN same switch

```
C:\Users\RVU>ping 192.168.100.87

Pinging 192.168.100.87 with 32 bytes of data:
Reply from 192.168.100.86: Destination host unreachable.
Reply from 192.168.100.86: Destination host unreachable.
Reply from 192.168.100.86: Destination host unreachable.
Reply from 192.168.100.86: Destination host unreachable.

Ping statistics for 192.168.100.87:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
```

3.4 Different VLAN different Switch

```
C:\Users\RVU>ping 192.168.100.87

Pinging 192.168.100.87 with 32 bytes of data:
Reply from 192.168.100.86: Destination host unreachable.
Reply from 192.168.100.86: Destination host unreachable.
Reply from 192.168.100.86: Destination host unreachable.
Reply from 192.168.100.86: Destination host unreachable.

Ping statistics for 192.168.100.87:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

C:\Users\RVU>
```