

1. show version

```

COM16 - PuTTY
R4_G8_S1>show version
Copyright (c) Ruckus Networks, Inc. All rights reserved.
UNIT 1: compiled on Jun  9 2023 at 06:14:36 labeled as SP508095k
(31457280 bytes) from Primary SP508095k.bin (UFI)
SW: Version 06.0.25342211
Compressed Primary Boot Code size = 786944, Version:10.1.26T225 (mmz10126)
Compiled on Tue Nov 29 12:43:26 2022

HW: Stackable ICX7150-Cl2-POE
=====
UNIT 1: SL 1: ICX7150-Cl2-2X1G POE 12-port Management Module
Serial #:FEK3S10V04L
Software Package: BASE_SOFT_PACKAGE
Current License: 2X10GR
P-ASIC 0: type B160, rev 11 Chip BCM56160_B0
=====
UNIT 1: SL 2: ICX7150-2X10G 2-port 2G Module
=====
UNIT 1: SL 3: ICX7150-2X10GF 2-port 20G Module
=====
1000 MHz ARM processor ARMv7 80 MHz bus
8 MB boot flash memory
2 GB code flash memory
1 GB DRAM
STACKID 1 system uptime is 1 hour(s) 43 minute(s) 24 second(s)
The system started at 06:14:36 GMT+00 Fri Jun 09 2023
The system : started=cold start

```

2. show ip

```

R4_G8_S1>
R4_G8_S1>show ip

Switch IP address: 192.168.100.82

Subnet mask: 255.255.255.0

Default router address: None
TFTP server address: None
Configuration filename: None
Image filename: None
DNS Server: N/A
IP MTU: 1500
R4_G8_S1>

```

3. show int brief

```

IP MTU: 1500
R4_G8_S1>show int brief

Port      Link      State    Dupl Speed Trunk Tag Pvid Pri MAC      Name
1/1/1     Up        Forward  Full 1G   None No  1   0  7047.7704.489c
1/1/2     Down     None     None None None No  1   0  7047.7704.489d
1/1/3     Down     None     None None None No  1   0  7047.7704.489e
1/1/4     Down     None     None None None No  1   0  7047.7704.489f
1/1/5     Down     None     None None None No  1   0  7047.7704.48a0
1/1/6     Down     None     None None None No  1   0  7047.7704.48a1
1/1/7     Down     None     None None None No  1   0  7047.7704.48a2
1/1/8     Down     None     None None None No  1   0  7047.7704.48a3
1/1/9     Down     None     None None None No  1   0  7047.7704.48a4
1/1/10    Down     None     None None None No  1   0  7047.7704.48a5
1/1/11    Down     None     None None None No  1   0  7047.7704.48a6
1/1/12    Down     None     None None None No  1   0  7047.7704.48a7
1/2/1     Up        Forward  Full 1G   None No  1   0  7047.7704.48a9
1/2/2     Down     None     None None None No  1   0  7047.7704.48aa
1/3/1     Down     None     None None None No  1   0  7047.7704.48ab
1/3/2     Down     None     None None None No  1   0  7047.7704.48ac
mgmt1     Up        None     Full 1G   None No  None 0  7047.7704.489c
R4_G8_S1>

```

4. show run

```
R4_G8_S1>show run
Current configuration:
!
ver 08.0.95kT211
!
stack unit 1
  module 1 icx7150-cl2-poe-port-management-module
  module 2 icx7150-2-copper-port-2g-module
  module 3 icx7150-2-sfp-plus-port-20g-module
```

5. show user

```
R4_G8_S1>show user
Username                               Password                               Encrypt  Priv Status  Expire Time
=====
super                                   $1$KeS0WGN3$L4tOQag9nLFSiCzB0MVp80  enabled  0           enabled  Never
R4_G8_S1>
```

6. show mac-address

```
R4_G8_S1>show user
Username                               Password                               Encrypt  Priv Status  Expire Time
=====
super                                   $1$KeS0WGN3$L4tOQag9nLFSiCzB0MVp80  enabled  0           enabled  Never
R4_G8_S1>show mac-address
Total active entries from all ports = 4
MAC-Address      Port      Type      VLAN
-----
4cd7.1792.5d32   1/2/1     Dynamic   1
4cd7.1792.6702   1/1/1     Dynamic   1
5c83.6c01.af3a   1/2/1     Dynamic   1
5c83.6c01.af47   1/2/1     Dynamic   1
R4_G8_S1>
```

7. show ip tcp connections

```
R4_G8_S1>show ip tcp connection
Total 3 TCP connections
  LISTEN: 3; SYN-SENT: 0; SYN-RECEIVED: 0; ESTABLISHED: 0; FIN-WAIT-1: 0
  FIN-WAIT-2: 0; CLOSE-WAIT: 0; LAST-ACK: 0; CLOSING: 0; TIME-WAIT: 0
Local IP address:port <-> Remote IP address:port TCP state  RcvQue  RxBufFe  SendQue  TxBufFe
-----
0.0.0.0      22      0.0.0.0      0      LISTEN      0      0      0      0
0.0.0.0      23      0.0.0.0      0      LISTEN      0      0      0      0
0.0.0.0      80      0.0.0.0      0      LISTEN      0      0      0      0

TCP MEMORY USAGE PERCENTAGE
FREE TCB = 97 percent
FREE TCP QUEUE BUFFER = 100 percent
FREE TCP SEND BUFFER = 100 percent
FREE TCP OUT OF SEQUENCE BUFFER = 100 percent
R4_G8_S1>
```

8. show ip tcp traffic

```
R4_G8_S1>show ip tcp traffic
TCP Statistics
  0 current active tcbs, 3 tcbs allocated, 0 tcbs freed 0 tcbs protected
  0 active opens, 0 passive opens, 0 failed attempts
  0 active resets, 0 passive resets, 0 input errors
  0 in segments, 0 out segments, 0 retransmission
  0 in connections requests, 3 out connections requests, 0 connections established,
  0 acks, 0 duplicate acks, 0 duplicate bytes
  0 bad checksum, 0 no checksum, 0 invalid header length
  0 illegal TCP MSS option length, 0 illegal option, 0 minimum TCP header, 0 invalid segment
R4_G8_S1>
```

Rack connections Image

