

Detecting Fake News with Python and Machine Learning

By Vinay Gupta

```
In [2]: import numpy as np
import pandas as pd
import itertools
from sklearn.model_selection import train_test_split
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.linear_model import PassiveAggressiveClassifier
from sklearn.metrics import accuracy_score, confusion_matrix
```

```
In [3]: #Read the data
df=pd.read_csv('C:\\Users\\PRIYTOSH GUPTA\\news.csv')

#Get shape and head
df.shape
df.head()
```

Out[3]:

| Unnamed: 0 | | title | text | label |
|------------|-------|---------------------------------------------------|---------------------------------------------------|-------|
| 0 | 8476 | You Can Smell Hillary's Fear | Daniel Greenfield, a Shillman Journalism Fello... | FAKE |
| 1 | 10294 | Watch The Exact Moment Paul Ryan Committed Pol... | Google Pinterest Digg Linkedin Reddit Stumbleu... | FAKE |
| 2 | 3608 | Kerry to go to Paris in gesture of sympathy | U.S. Secretary of State John F. Kerry said Mon... | REAL |
| 3 | 10142 | Bernie supporters on Twitter erupt in anger ag... | — Kaydee King (@KaydeeKing) November 9, 2016 T... | FAKE |
| 4 | 875 | The Battle of New York: Why This Primary Matters | It's primary day in New York and front-runners... | REAL |

```
In [4]: #DataFlair - Get the labels
labels=df.label
labels.head()
```

Out[4]:

| | |
|---|------|
| 0 | FAKE |
| 1 | FAKE |
| 2 | REAL |
| 3 | FAKE |
| 4 | REAL |

Name: label, dtype: object

```
In [5]: #DataFlair - Split the dataset
x_train,x_test,y_train,y_test=train_test_split(df['text'], labels, test_size=0.2, random_state=7)
```

```
In [6]: #DataFlair - Initialize a TfidfVectorizer
tfidf_vectorizer=TfidfVectorizer(stop_words='english', max_df=0.7)

#DataFlair - Fit and transform train set, transform test set
tfidf_train=tfidf_vectorizer.fit_transform(x_train)
tfidf_test=tfidf_vectorizer.transform(x_test)
```

```
In [8]: #DataFlair - Initialize a PassiveAggressiveClassifier
pac=PassiveAggressiveClassifier(max_iter=50)
pac.fit(tfidf_train,y_train)

#DataFlair - Predict on the test set and calculate accuracy
y_pred=pac.predict(tfidf_test)
score=accuracy_score(y_test,y_pred)
print(f'Accuracy: {round(score*100,2)}%')

Accuracy: 93.21%
```

```
In [9]: #DataFlair - Build confusion matrix
confusion_matrix(y_test,y_pred, labels=['FAKE', 'REAL'])
```

Out[9]:

| |
|---------------------------|
| array([[592, 46], |
| [40, 589]], dtype=int64) |

```
In [ ]:
```