To Create the Calender to read the date from the keyboad and to print Weecks / activity details report on Screen.

```
#include<stdio.h>
#include<stdlib.h>
#include<string.h>

// structure to represent a day
    struct Day
    {
        char *dayName;
        int d, m, y;
        char *activityDiscription;
    };

Function to Create the Calender.
void Create(struct Day *Calender)
{
char dayName[] = {"Monday", "Tuesday",
"Wednesday", "Thrusday", "Friday",
"Saterday", "Sunday"};
```

```
for(int i=0; i<7 ; i++)
// Dynamically allocated memory for day
   name and ActivityDescription.
Calender[i].dayName=strdup(dayName[i]);
        size_t buffersize =256
   Calender[i].ActivityDescription
   = (char*) malloc(buffersize * sizeof
                    (char));
}
```

Function to read data from the keyboard

```
Void read(struct Day **Calender)
{ for(int i=0; i<n; i++)
  { Printf("Enter date for %s in dd/mm/yy",
          Calender[i].dayName);
    Scanf("%d%d%d", &(Calender[i]->d),
          &Calender[i]->m, &Calender[i]
          ->y);
```

```
Printf("Enter the activity for %s",
        Calender[i].dayName);

// Clear the input buffer.
    while(getchar() != '\n');

// Dynamically allocated memory for
   Activity Description
    size_t bufferSize = 256;
    getline(&Calender[i].activityDescription,
            &bufferSize, stdin);

}

}

Function to display
void display(struct day *Calender)
{ printf("%s \t %s %-10s %-10s %-10s\n",
    "Day", "Date", ACTIVITY);
```

```
for (int i=0; i<n; i++)
{ Printf("%-10s %-10d %-10d %-10s",
Calender[i].dayName, Calender[i].d,
Calender[i].M, Calender[i].Y,
Calender[i].ActivityDescription);

}
}

int main()
{
struct Day *Calender =
(struct Day *) malloc 7 * sizeof(struct Day)
);
if (Clander == NULL)
{ Printf("stderr, "Memory allocation
failed");
return 1;
```

```
create(calender);
read(calender);
display(calender);

for(int i=0; i<n; i++)
{
    free(element[i].DayName);
    free(calender);
}
free(calender);
return 0;
}
```