🏗️ Heavy Industrial Machinery — Price Prediction

MLP Kaggle Competition | Complete ML Pipeline

Problem: Predict `TargetValue` (auction sale price in USD) of heavy machinery
Metric: RMSLE ≤ **0.15** (Root Mean Squared Logarithmic Error)
Data: 138 701 train rows | 15 000 test rows | 50 features

`Load` → `EDA` → `Preprocessing` → `Feature Eng.` → `Models` → `HPT` → `Error Analysis` → `Submit`

In [1]:
```
# This Python 3 environment comes with many helpful analytics libraries instal
# It is defined by the kaggle/python Docker image: https://github.com/kaggle/d
# For example, here's several helpful packages to load

import numpy as np # linear algebra
import pandas as pd # data processing, CSV file I/O (e.g. pd.read_csv)

# Input data files are available in the read-only "../input/" directory
# For example, running this (by clicking run or pressing Shift+Enter) will lis

import os
for dirname, _, filenames in os.walk('/kaggle/input'):
    for filename in filenames:
        print(os.path.join(dirname, filename))

# You can write up to 20GB to the current directory (/kaggle/working/) that ge
# You can also write temporary files to /kaggle/temp/, but they won't be saved

# Use the kagglehub client library to attach Kaggle resources like competition
# Learn more about kagglehub: https://github.com/Kaggle/kagglehub/blob/main/RE

import kagglehub
# kagglehub.dataset_download('<owner>/<dataset-slug>')
```

```
/kaggle/input/competitions/heavy-equipment-selling-price-prediction-challenge/s
ample_submission.csv
/kaggle/input/competitions/heavy-equipment-selling-price-prediction-challenge/t
rain.csv
/kaggle/input/competitions/heavy-equipment-selling-price-prediction-challenge/m
etadata.csv
/kaggle/input/competitions/heavy-equipment-selling-price-prediction-challenge/t
est.csv
```

Improvement No 2

In [ ]:
```
# import subprocess, sys
# try:
#     import catboost
# except ImportError:
#     subprocess.run([sys.executable, "-m", "pip", "install", "catboost", "-q"

# import numpy as np
# import pandas as pd
# import warnings
# import os
# import matplotlib.pyplot as plt
# import matplotlib.ticker as mticker
# import seaborn as sns

# warnings.filterwarnings('ignore')
# pd.set_option('display.max_columns', 60)
# pd.set_option('display.float_format', '{:.2f}'.format)

# from sklearn.model_selection import KFold
# from sklearn.metrics import mean_squared_error, r2_score
# import lightgbm as lgb
# from xgboost import XGBRegressor
# from catboost import CatBoostRegressor

# SEED = 42
# np.random.seed(SEED)
# print("Libraries loaded.")
```

In [ ]:
```
# def rmsle(y_true, y_pred):
#     y_pred = np.maximum(y_pred, 0)
#     return np.sqrt(mean_squared_error(np.log1p(y_true), np.log1p(y_pred)))

# def make_submission(preds, ids, filename='submission.csv'):
#     preds = np.maximum(preds, 0)
#     sub = pd.DataFrame({'TransactionID': ids, 'TargetValue': preds})
#     sub.to_csv(filename, index=False)
#     print(f'Saved: {filename}  |  Rows={len(sub):,}'
#           f'  Min=${sub["TargetValue"].min():,.0f}'
#           f'  Median=${sub["TargetValue"].median():,.0f}'
#           f'  Max=${sub["TargetValue"].max():,.0f}')
#     return sub
```

In [ ]:
```
# train_df = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-p
# test_df  = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-p
# sample   = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-p
# metadata = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-p

# print("=" * 55)
# print(f"TRAIN : {train_df.shape[0]:>8,} x {train_df.shape[1]}")
```

```
# print(f"TEST  : {test_df.shape[0]:>8,} x {test_df.shape[1]}")
# print("=" * 55)
# t = train_df['TargetValue']
# print(f"Target  min=${t.min():,.0f}  median=${t.median():,.0f}  "
#       f"mean=${t.mean():,.0f}  max=${t.max():,.0f}")
```

In [ ]:

```
# def engineer_features(df):

#     df = df.copy()

#     # 1. ProductConfigID is a config CODE, not a continuous number
#     df['ProductConfigID'] = df['ProductConfigID'].astype(str)

#     # 2. Sale date decomposition
#     df['TransactionDate'] = pd.to_datetime(df['TransactionDate'], errors='co
#     df['SaleYear'] = df['TransactionDate'].dt.year
#     df['SaleMonth'] = df['TransactionDate'].dt.month
#     df['SaleDay'] = df['TransactionDate'].dt.day
#     df['SaleDayOfWeek'] = df['TransactionDate'].dt.dayofweek
#     df['SaleDayOfYear'] = df['TransactionDate'].dt.dayofyear
#     df['SaleQuarter'] = df['TransactionDate'].dt.quarter
#     df['SaleWeek'] = df['TransactionDate'].dt.isocalendar().week.astype(int)
#     df['IsMonthEnd'] = df['TransactionDate'].dt.is_month_end.astype(np.int8)
#     df['IsMonthStart'] = df['TransactionDate'].dt.is_month_start.astype(np.i
#     df['IsQuarterEnd'] = df['TransactionDate'].dt.is_quarter_end.astype(np.i
#     df['IsYearEnd'] = df['TransactionDate'].dt.is_year_end.astype(np.int8)
#     df = df.drop(columns=['TransactionDate'])

#     # 3. FIX: ManufactureYear=1001 is a database placeholder (10.6% of rows)
#     df.loc[df['ManufactureYear'] <= 1920, 'ManufactureYear'] = np.nan

#     # 4. FIX: OperationalHoursMeter=0 is a placeholder for unknown hours
#     df.loc[df['OperationalHoursMeter'] == 0, 'OperationalHoursMeter'] = np.n

#     # 5. Machine age (core price determinant for equipment)
#     df['MachineAge'] = (df['SaleYear'] - df['ManufactureYear']).clip(lower=0

#     # 6. Ordinal encode UtilizationTier — has a clear economic order
#     tier_map = {'Low': 0, 'Medium': 1, 'High': 2}
#     df['UtilizationTierOrd'] = df['UtilizationTier'].map(tier_map)

#     # 7. Ordinal encode AssetScaleFactor — has a clear size order
#     scale_map = {'Mini': 0, 'Compact': 1, 'Small': 2,'Medium': 3, 'Large / M
#     df['AssetScaleOrd'] = df['AssetScaleFactor'].map(scale_map)

#     # 8. Hours-based features
#     hours_99 = df['OperationalHoursMeter'].quantile(0.99)
#     df['OperationalHoursMeter'] = df['OperationalHoursMeter'].clip(upper=hou
#     df['HoursPresent'] = df['OperationalHoursMeter'].notna().astype(np.int8)
#     df['UsagePerYear'] = df['OperationalHoursMeter'] / (df['MachineAge'] + 1
#     df['LogHours'] = np.log1p(df['OperationalHoursMeter'].fillna(0))

#     # 9. Age bucket features
```

```
#     df['IsNewMachine'] = (df['MachineAge'] <= 2).astype(np.int8)
#     df['IsOldMachine'] = (df['MachineAge'] >= 20).astype(np.int8)
#     df['AgeDecade'] = (df['MachineAge'] / 10).fillna(-1).astype(int)

#     # 10. Normalize + convert all remaining string columns to category
#     text_cols = df.select_dtypes(include='object').columns.tolist()
#     df[text_cols] = df[text_cols].replace('None or Unspecified', np.nan)
#     for col in text_cols:
#         df[col] = df[col].fillna('Missing').astype('category')

#     # Drop 100%-missing and replaced columns
#     drop_cols = ['col18', 'col19', 'UtilizationTier', 'AssetScaleFactor']
#     df = df.drop(columns=[c for c in drop_cols if c in df.columns])

#     return df

# print("Applying feature engineering...")
# train_eng = engineer_features(train_df)
# test_eng  = engineer_features(test_df)

# print(f"Train: {train_eng.shape}  |  Test: {test_eng.shape}")

# yr_nan  = train_eng['ManufactureYear'].isna().sum()
# hr_nan  = train_eng['OperationalHoursMeter'].isna().sum()
# print(f"ManufactureYear NaN : {yr_nan:,} ({yr_nan/len(train_eng)*100:.1f}%)"
# print(f"OperationalHours NaN: {hr_nan:,} ({hr_nan/len(train_eng)*100:.1f}%)"
```

In [ ]:

```
# ID_COLS = ['TransactionID', 'AssetID']

# y_all        = np.log1p(train_df['TargetValue'].values)
# X_all        = train_eng.drop(columns=ID_COLS + ['TargetValue'], errors='ign
# X_test_final = test_eng.drop(columns=ID_COLS, errors='ignore')
# test_ids     = test_df['TransactionID'].values

# # Categorical columns list (for CatBoost which needs explicit list)
# cat_features = X_all.select_dtypes(include=['category', 'object']).columns.t

# def to_cat_str(df):
#     """Convert category dtype to str for CatBoost compatibility."""
#     df = df.copy()
#     for c in cat_features:
#         if c in df.columns:
#             df[c] = df[c].astype(str)
#     return df

# X_all_cat  = to_cat_str(X_all)
# X_test_cat = to_cat_str(X_test_final)

# print(f"Feature matrix : {X_all.shape}")
# print(f"Test matrix    : {X_test_final.shape}")
# print(f"Cat features   : {len(cat_features)}")
# print(f"Num features   : {X_all.shape[1] - len(cat_features)}")
```

In [ ]:
```
# N_FOLDS = 5
# kf = KFold(n_splits=N_FOLDS, shuffle=True, random_state=SEED)

# oof_lgb = np.zeros(len(X_all))
# oof_xgb = np.zeros(len(X_all))
# oof_cat = np.zeros(len(X_all))

# # Fold-averaged test predictions (better than single 100% retrain)
# test_lgb_folds = np.zeros((len(X_test_final), N_FOLDS))
# test_xgb_folds = np.zeros((len(X_test_final), N_FOLDS))
# test_cat_folds = np.zeros((len(X_test_final), N_FOLDS))

# fold_scores = []

# print("Starting 5-Fold Cross Validation...")
# print("NOTE: 6000 trees per model -> expect ~30-40 mins on Kaggle CPU")
# print("=" * 65)

# for fold, (tr_idx, vl_idx) in enumerate(kf.split(X_all), 1):
#     X_tr, X_vl = X_all.iloc[tr_idx].copy(), X_all.iloc[vl_idx].copy()
#     y_tr, y_vl = y_all[tr_idx], y_all[vl_idx]

#     X_tr_cat = X_all_cat.iloc[tr_idx].copy()
#     X_vl_cat = X_all_cat.iloc[vl_idx].copy()
#     X_te_cat = X_test_cat.copy()

#     # ── 1. LightGBM ──────────────────────────────────────
#     lgb_model = lgb.LGBMRegressor(
#         n_estimators     = 6000,
#         max_depth        = -1,
#         num_leaves       = 255,
#         learning_rate    = 0.015,
#         subsample        = 0.75,
#         colsample_bytree = 0.75,
#         min_child_samples= 15,
#         reg_alpha        = 0.05,
#         reg_lambda       = 1.5,
#         random_state     = SEED,
#         n_jobs           = -1,
#         verbose          = -1
#     )
#     lgb_model.fit(
#         X_tr, y_tr,
#         eval_set  = [(X_vl, y_vl)],
#         callbacks = [lgb.early_stopping(200, verbose=False),
#                      lgb.log_evaluation(-1)]
#     )
#     lgb_vl = lgb_model.predict(X_vl)
#     lgb_te = lgb_model.predict(X_test_final)
#     oof_lgb[vl_idx] = lgb_vl
#     test_lgb_folds[:, fold-1] = lgb_te

#     # ── 2. XGBoost ──────────────────────────────────────
```

```
#     xgb_model = XGBRegressor(
#         n_estimators       = 6000,
#         max_depth          = 9,
#         learning_rate      = 0.015,
#         subsample          = 0.75,
#         colsample_bytree   = 0.75,
#         tree_method        = 'hist',
#         enable_categorical = True,
#         min_child_weight   = 5,
#         gamma              = 0.05,
#         reg_alpha          = 0.05,
#         reg_lambda         = 1.5,
#         random_state       = SEED,
#         n_jobs             = -1,
#         early_stopping_rounds = 200
#     )
#     xgb_model.fit(
#         X_tr, y_tr,
#         eval_set = [(X_vl, y_vl)],
#         verbose  = False
#     )
#     xgb_vl = xgb_model.predict(X_vl)
#     xgb_te = xgb_model.predict(X_test_final)
#     oof_xgb[vl_idx] = xgb_vl
#     test_xgb_folds[:, fold-1] = xgb_te

#     # ─── 3. CatBoost ──────────────────────────────────────────
#     cat_model = CatBoostRegressor(
#         iterations        = 6000,
#         depth             = 9,
#         learning_rate     = 0.015,
#         random_seed       = SEED,
#         verbose           = 0,
#         thread_count      = -1,
#         early_stopping_rounds = 200,
#         cat_features      = cat_features,
#         l2_leaf_reg       = 3.0,
#         bagging_temperature = 0.5,
#         grow_policy       = 'SymmetricTree'
#     )
#     cat_model.fit(
#         X_tr_cat, y_tr,
#         eval_set = (X_vl_cat, y_vl)
#     )
#     cat_vl = cat_model.predict(X_vl_cat)
#     cat_te = cat_model.predict(X_te_cat)
#     oof_cat[vl_idx] = cat_vl
#     test_cat_folds[:, fold-1] = cat_te

#     s_lgb = rmsle(np.expm1(y_vl), np.expm1(lgb_vl))
#     s_xgb = rmsle(np.expm1(y_vl), np.expm1(xgb_vl))
#     s_cat = rmsle(np.expm1(y_vl), np.expm1(cat_vl))
#     fold_scores.append((s_lgb, s_xgb, s_cat))
```

```
#     print(f"Fold {fold}: LGB={s_lgb:.5f}(iter={lgb_model.best_iteration_})"
#           f" | XGB={s_xgb:.5f}(iter={xgb_model.best_iteration})"
#           f" | CAT={s_cat:.5f}")

# oof_lgb_score = rmsle(np.expm1(y_all), np.expm1(oof_lgb))
# oof_xgb_score = rmsle(np.expm1(y_all), np.expm1(oof_xgb))
# oof_cat_score = rmsle(np.expm1(y_all), np.expm1(oof_cat))

# print("=" * 65)
# print(f"LightGBM OOF RMSLE : {oof_lgb_score:.5f}")
# print(f"XGBoost  OOF RMSLE : {oof_xgb_score:.5f}")
# print(f"CatBoost OOF RMSLE : {oof_cat_score:.5f}")
```

In [ ]:
```
# # Grid search best blend weights
# print("Searching for optimal blend weights...")
# best_blend = 999.0
# best_w = (0.5, 0.25, 0.25)

# for w1 in np.arange(0.0, 1.01, 0.05):
#     for w2 in np.arange(0.0, 1.01 - w1, 0.05):
#         w3 = round(1.0 - w1 - w2, 6)
#         if w3 < -1e-6:
#             continue
#         w3 = max(w3, 0.0)
#         blend = w1 * oof_lgb + w2 * oof_xgb + w3 * oof_cat
#         score = rmsle(np.expm1(y_all), np.expm1(blend))
#         if score < best_blend:
#             best_blend = score
#             best_w = (w1, w2, w3)

# print("=" * 65)
# print(f"Best weights  : LGB={best_w[0]:.2f} XGB={best_w[1]:.2f} CAT={best_w[
# print(f"Blended RMSLE : {best_blend:.5f}")
# print(f"Previous best : 0.19969  ->  {'IMPROVED!' if best_blend < 0.19969 el
# print(f"vs classmate  : {'BETTER' if best_blend < 0.18356 else 'Needs more w
# print(f"vs cutoff 0.15: {'PASS' if best_blend < 0.15 else 'Needs more work'}
# print("=" * 65)
```

In [ ]:
```
# # Build final submission using fold-averaged test predictions
# w1, w2, w3 = best_w

# test_lgb_avg = test_lgb_folds.mean(axis=1)
# test_xgb_avg = test_xgb_folds.mean(axis=1)
# test_cat_avg = test_cat_folds.mean(axis=1)

# test_blend_log = w1 * test_lgb_avg + w2 * test_xgb_avg + w3 * test_cat_avg
# final_prices   = np.expm1(test_blend_log)

# # Clip to observed training price range
# price_min = train_df['TargetValue'].quantile(0.001)
# price_max = train_df['TargetValue'].quantile(0.999)
# final_prices = np.clip(final_prices, price_min, price_max)
```

```
# print(f"Clipped to [${price_min:,.0f}, ${price_max:,.0f}]")

# sub = make_submission(final_prices, test_ids, 'submission.csv')
# sub.head()
```

In [ ]:

```
# # Diagnostics plot
# oof_blend  = best_w[0]*oof_lgb + best_w[1]*oof_xgb + best_w[2]*oof_cat
# pred_price = np.expm1(oof_blend)
# true_price = np.expm1(y_all)
# residuals  = true_price - pred_price
# pct_err    = (residuals / true_price) * 100

# fig, axes = plt.subplots(1, 3, figsize=(18, 5))
# fig.suptitle(f'v6 OOF Diagnostics | Blended RMSLE={best_blend:.5f}  '
#              f'(prev best=0.19969)', fontsize=12, fontweight='bold')

# idx = np.random.choice(len(true_price), min(5000, len(true_price)), replace=
# axes[0].scatter(true_price[idx], pred_price[idx], alpha=0.07, s=4, color='st
# mn, mx = true_price.min(), true_price.max()
# axes[0].plot([mn, mx], [mn, mx], 'r--', lw=2, label='Perfect')
# axes[0].set_xlabel('Actual Price')
# axes[0].set_ylabel('Predicted Price')
# axes[0].set_title('Actual vs Predicted')
# axes[0].legend(fontsize=9)
# fmt = lambda x, _: f'${x/1000:.0f}K'
# axes[0].xaxis.set_major_formatter(mticker.FuncFormatter(fmt))
# axes[0].yaxis.set_major_formatter(mticker.FuncFormatter(fmt))

# axes[1].hist(residuals.clip(-15000, 15000), bins=80, color='coral', edgecolo
# axes[1].axvline(0, color='black', lw=2, ls='--')
# axes[1].axvline(residuals.mean(), color='red', lw=2, label=f'Mean={residuals
# axes[1].set_xlabel('Error (Actual - Predicted)')
# axes[1].set_title('Residual Distribution')
# axes[1].legend(fontsize=9)

# axes[2].hist(pct_err.clip(-40, 40), bins=80, color='mediumpurple', edgecolor
# axes[2].axvline(0, color='black', lw=2, ls='--')
# axes[2].set_xlabel('% Error (clipped +/-40%)')
# axes[2].set_title('% Error Distribution')

# plt.tight_layout()
# plt.show()

# print(f'Blended OOF RMSLE : {best_blend:.5f}')
# print(f'MAE               : ${np.mean(np.abs(residuals)):,.0f}')
# print(f'R^2               : {r2_score(true_price, pred_price):.4f}')
# print(f'Median % error    : {np.median(np.abs(pct_err)):.1f}%')

# # Feature importance from last LGB fold
# fi = pd.Series(lgb_model.feature_importances_,
#                index=X_all.columns).sort_values(ascending=False)
# print("\nTop 15 Feature Importances (last LGB fold):")
# print(fi.head(15).to_string())
```

Improvement No 1

In [ ]:
```
# # ═══════════════════════════════════════════════════════
# # 1.  SETUP & IMPORTS
# # ═══════════════════════════════════════════════════════
# import numpy as np
# import pandas as pd
# import warnings, os
# warnings.filterwarnings('ignore')
# pd.set_option('display.max_columns', 60)
# pd.set_option('display.float_format', '{:.2f}'.format)

# import matplotlib.pyplot as plt
# import matplotlib.ticker as mticker
# import seaborn as sns
# import missingno as msno

# plt.rcParams['figure.figsize'] = (14, 5)
# plt.rcParams['font.size'] = 11
# sns.set_theme(style='whitegrid', palette='Set2')

# from sklearn.pipeline import Pipeline
# from sklearn.compose import ColumnTransformer
# from sklearn.preprocessing import StandardScaler, OrdinalEncoder
# from sklearn.impute import SimpleImputer
# from sklearn.model_selection import train_test_split, KFold, RandomizedSearc
# from sklearn.metrics import mean_squared_error, r2_score, make_scorer
# from sklearn.ensemble import RandomForestRegressor, HistGradientBoostingRegr
# from sklearn.linear_model import Ridge
# from sklearn.dummy import DummyRegressor
# from xgboost import XGBRegressor
# import lightgbm as lgb

# SEED = 42
# np.random.seed(SEED)
# print("✅ All libraries loaded!")
# print(f"   NumPy {np.__version__} | Pandas {pd.__version__}")
```

In [ ]:
```
# # ═══════════════════════════════════════════════════════
# # 2.  DATA LOADING
# # ═══════════════════════════════════════════════════════
# train_df = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-p
# test_df  = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-p
# sample   = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-p
# metadata = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-p

# print("=" * 60)
# print(f"  TRAIN   : {train_df.shape[0]:,} rows × {train_df.shape[1]} cols")
# print(f"  TEST    : {test_df.shape[0]:,}  rows × {test_df.shape[1]} cols")
# print(f"  SAMPLE  : {sample.shape}")
# print("=" * 60)
```

```
# print("\nRequired submission format:")
# display(sample.head(3))
# print("\nColumn descriptions (metadata):")
# print(metadata[['Variable','Rephrased Description']].to_string(index=False))
```

2. Data Loading & Overview

In [ ]:
```
# print("First 5 rows of training data:")
# display(train_df.head(3))
# print()
# train_df.info(verbose=True, show_counts=True)
```

In [ ]:
```
# print("\nTrain Datatset shape:")
# display(train_df.shape)

# print("\nTest Datatset shape:")
# test_df.shape
```

In [ ]:
```
# print("Numerical summary statistics:")
# display(train_df.describe())
```

In [ ]:
```
# print("How Many Coloum Present in Train Dataset")
# train_df.columns
```

In [ ]:
```
# print("Know about Submission Columns")
# sample.columns  # We name Submission File to sample
```

3. Exploratory Data Analysis (EDA)

Key objectives:

1. **Target distribution** — understand price range & skewness
2. **Missing values** — scale and pattern of absent data
3. **Categorical features** — category counts and price impact
4. **Numerical features** — distributions and target correlation
5. **Bivariate analysis** — how features relate to price

> **RMSLE insight:** We train on `log1p(TargetValue)` so proportional errors at all price levels are penalised equally.

In [ ]:
```
# # ═══════════════════════════════════════════════════
# # 3.1  TARGET VARIABLE
# # ═══════════════════════════════════════════════════
# fig, axes = plt.subplots(1, 3, figsize=(18, 5))
# fig.suptitle('Target Variable: TargetValue (Sale Price USD)', fontsize=13, f
```

```
# log_target = np.log1p(train_df['TargetValue'])

# axes[0].hist(train_df['TargetValue'], bins=80, color='steelblue', edgecolor=
# axes[0].set_title('Original Scale (Right-Skewed)')
# axes[0].set_xlabel('Sale Price (USD)')
# axes[0].xaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/10

# axes[1].hist(log_target, bins=80, color='coral', edgecolor='white', alpha=.8
# axes[1].set_title('log1p Scale  ← used for RMSLE training')
# axes[1].set_xlabel('log1p(Sale Price)')

# bp = axes[2].boxplot(train_df['TargetValue'], patch_artist=True,
#                      boxprops=dict(facecolor='#90EE90', color='darkgreen'),
#                      medianprops=dict(color='red', linewidth=2))
# axes[2].set_title('Box Plot — Outlier View')
# axes[2].yaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/10

# plt.tight_layout(); plt.show()

# print("Target Statistics:")
# for lbl, val in [('Min',   train_df['TargetValue'].min()),
#                  ('Max',   train_df['TargetValue'].max()),
#                  ('Mean',  train_df['TargetValue'].mean()),
#                  ('Median',train_df['TargetValue'].median()),
#                  ('Std',   train_df['TargetValue'].std())]:
#     print(f"  {lbl:8}: ${val:>12,.0f}")
# print(f"\n  Skewness original : {train_df['TargetValue'].skew():.4f}")
# print(f"  Skewness log1p   : {log_target.skew():.4f}  ← closer to 0 = better
```

In [ ]:

```
# # ═══════════════════════════════════════════════════════
# # 3.2  MISSING VALUE ANALYSIS
# # ═══════════════════════════════════════════════════════
# fig, axes = plt.subplots(1, 2, figsize=(18, 8))

# msno.bar(train_df, ax=axes[0], fontsize=7, color='steelblue', sort='ascendin
# axes[0].set_title('Data Completeness', fontsize=12, fontweight='bold')

# miss_pct = (train_df.isnull().sum() / len(train_df) * 100).sort_values(ascen
# miss_pct = miss_pct[miss_pct > 0]
# bar_c = ['#e74c3c' if v >= 95 else '#e67e22' if v >= 60
#          else '#f1c40f' if v >= 30 else '#2ecc71' for v in miss_pct]
# axes[1].barh(miss_pct.index, miss_pct.values, color=bar_c, edgecolor='white'
# axes[1].axvline(95, color='red',    ls='--', lw=2, label='95% → DROP')
# axes[1].axvline(60, color='orange', ls='--', lw=2, label='60% → Flag + fill'
# axes[1].set_xlabel('Missing %')
# axes[1].set_title('Missing Values by Column', fontsize=12, fontweight='bold'
# axes[1].legend(fontsize=9)

# plt.tight_layout(); plt.show()

# mv = pd.DataFrame({
#     'Count': train_df.isnull().sum(),
#     'Pct %': (train_df.isnull().sum() / len(train_df) * 100).round(2)
```

```
# })
# mv = mv[mv['Count'] > 0].sort_values('Pct %', ascending=False)
# mv['Strategy'] = mv['Pct %'].apply(lambda x:
#     'DROP' if x >= 95 else
#     'Binary flag + fill "Missing"' if x >= 60 else
#     'Impute median/mode')
# print(mv.to_string())
```

In [ ]:
```
# # ═══════════════════════════════════════════════════════════
# # 3.3  CATEGORICAL FEATURES — BIVARIATE ANALYSIS
# # ═══════════════════════════════════════════════════════════
# key_cats = ['InventoryGroupDescription','UtilizationTier','CabinType','Asset

# fig, axes = plt.subplots(2, 2, figsize=(16, 10))
# axes = axes.flatten()
# fig.suptitle('Sale Price Distribution by Key Categorical Features',
#              fontsize=13, fontweight='bold')

# for i, col in enumerate(key_cats):
#     data  = train_df[[col,'TargetValue']].dropna()
#     order = data.groupby(col)['TargetValue'].median().sort_values(ascending=
#     sns.boxplot(data=data, x=col, y='TargetValue', order=order,
#                 ax=axes[i], palette='Set2', showfliers=False)
#     axes[i].set_title(f'Price by {col}', fontsize=11)
#     axes[i].set_xlabel('')
#     axes[i].tick_params(axis='x', rotation=25)
#     axes[i].yaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${
#     for j, med in enumerate(data.groupby(col)['TargetValue'].median()[order]
#         axes[i].text(j, med, f'${med/1000:.0f}K', ha='center', va='bottom',

# plt.tight_layout(); plt.show()

# for col in key_cats:
#     print(f"\n{col}:")
#     print(train_df.groupby(col)['TargetValue'].agg(Count='count',Median='med
#           .sort_values('Median', ascending=False).to_string())
```

In [ ]:
```
# # ═══════════════════════════════════════════════════════════
# # 3.4  NUMERICAL FEATURES
# # ═══════════════════════════════════════════════════════════
# fig, axes = plt.subplots(2, 2, figsize=(16, 10))
# fig.suptitle('Numerical Features Analysis', fontsize=13, fontweight='bold')

# # Price vs ManufactureYear
# yr = train_df[train_df['ManufactureYear'].between(1975,2020)]
# yr_s = yr.groupby('ManufactureYear')['TargetValue'].agg(
#     M='median', Q1=lambda x: x.quantile(.25), Q3=lambda x: x.quantile(.75))
# axes[0,0].plot(yr_s.index, yr_s['M'], color='steelblue', lw=2, marker='o', m
# axes[0,0].fill_between(yr_s.index, yr_s['Q1'], yr_s['Q3'], alpha=.2, color='
# axes[0,0].set_title('Median Price by Manufacture Year (shaded=IQR)')
# axes[0,0].set_xlabel('Year')
# axes[0,0].yaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/
```

```
# # Price vs Operational Hours (binned)
# tmp = train_df[['OperationalHoursMeter','TargetValue']].dropna()
# tmp['Bin'] = pd.qcut(tmp['OperationalHoursMeter'], q=8, duplicates='drop')
# bp = tmp.groupby('Bin', observed=True)['TargetValue'].median()
# axes[0,1].bar(range(len(bp)), bp.values, color='coral', edgecolor='white')
# axes[0,1].set_xticks(range(len(bp)))
# axes[0,1].set_xticklabels([f'{b.right/1000:.0f}K' for b in bp.index],
#                           rotation=45, ha='right', fontsize=9)
# axes[0,1].set_title('Median Price by Operational Hours (deciles)')
# axes[0,1].yaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/

# # ManufactureYear distribution
# axes[1,0].hist(train_df['ManufactureYear'], bins=45, color='purple', edgecol
# axes[1,0].set_title('Distribution of Manufacture Year')
# axes[1,0].set_xlabel('Year')

# # Scatter: log1p(Hours) vs log1p(Price)
# mask = train_df['OperationalHoursMeter'].notna()
# axes[1,1].scatter(np.log1p(train_df.loc[mask,'OperationalHoursMeter']),
#                   np.log1p(train_df.loc[mask,'TargetValue']),
#                   alpha=.05, s=3, color='seagreen')
# axes[1,1].set_title('log1p(Hours) vs log1p(Price)  (negative corr expected)'
# axes[1,1].set_xlabel('log1p(Operational Hours)')
# axes[1,1].set_ylabel('log1p(Price)')

# plt.tight_layout(); plt.show()
# print("Key insight: Newer machines → higher price | More hours → lower price
```

In [ ]:
```
# # ═══════════════════════════════════════════════════════
# # 3.5  CORRELATION ANALYSIS
# # ═══════════════════════════════════════════════════════
# num_cols = [c for c in train_df.select_dtypes(include=[np.number]).columns
#             if c not in ['TransactionID','AssetID','ProductConfigID']]
# corr = train_df[num_cols].corr()
# tgt_corr = corr['TargetValue'].drop('TargetValue').sort_values(key=abs, asce

# fig, axes = plt.subplots(1, 2, figsize=(16, 5))
# sns.heatmap(corr, ax=axes[0], annot=True, fmt='.2f', cmap='coolwarm',
#             center=0, square=True, linewidths=.5, annot_kws={'size':9})
# axes[0].set_title('Correlation Matrix', fontsize=11)

# colors = ['#2ecc71' if v>=0 else '#e74c3c' for v in tgt_corr]
# axes[1].barh(tgt_corr.index, tgt_corr.values, color=colors, edgecolor='white
# axes[1].axvline(0, color='black', lw=.8)
# axes[1].set_xlabel('Pearson Correlation')
# axes[1].set_title('Correlation with TargetValue', fontsize=11)
# plt.tight_layout(); plt.show()

# print("Correlations with TargetValue:")
# print(tgt_corr.to_string())
```

In [ ]:
```
# # ═══════════════════════════════════════════════════════
# # 3.6  PRICE BY MACHINE TYPE & REGION
```

```
# # ═══════════════════════════════════════════════════════
# fig, axes = plt.subplots(1, 2, figsize=(16, 6))
# fig.suptitle('Sale Price by Machine Category & Region', fontsize=13, fontwei

# ig = (train_df.groupby('InventoryGroupDescription')['TargetValue']
#       .agg(Median='median', Count='count').sort_values('Median').reset_index
# bars = axes[0].barh(ig['InventoryGroupDescription'], ig['Median'],
#                     color=sns.color_palette('Set2', len(ig)), edgecolor='wh
# axes[0].set_xlabel('Median Sale Price')
# axes[0].set_title('By Machine Category')
# axes[0].xaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/10
# for bar, cnt in zip(bars, ig['Count']):
#     axes[0].text(bar.get_width()+200, bar.get_y()+bar.get_height()/2,
#                  f'n={cnt:,}', va='center', fontsize=9)

# reg = train_df.groupby('RegionCode')['TargetValue'].median().nlargest(15)
# axes[1].barh(range(len(reg)), reg.values[::-1],
#              color=sns.color_palette('viridis', len(reg)), edgecolor='white'
# axes[1].set_yticks(range(len(reg)))
# axes[1].set_yticklabels(reg.index[::-1], fontsize=9)
# axes[1].set_xlabel('Median Sale Price')
# axes[1].set_title('Top 15 Regions by Median Price')
# axes[1].xaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/10

# plt.tight_layout(); plt.show()
```

4. Data Preprocessing & Feature Engineering

Strategy

Step	Action
Drop	`col18`, `col19` (99.95% missing), `TransactionID`, `AssetID`
Date extract	`SaleYear`, `SaleMonth`, `SaleQuarter` from `TransactionDate`
MachineAge ⭐	`SaleYear − ManufactureYear` — strongest depreciation signal
UsagePerYear	`OperationalHoursMeter / (MachineAge+1)`
Missing flags	Binary `_present` for high-missing columns
Imputation	Median (numeric) / `'Missing'` (categorical)
Encoding	`OrdinalEncoder` for all categoricals
Scaling	`StandardScaler` for all numerics

> All transformations use **sklearn Pipeline + ColumnTransformer** — fitted only on training data to prevent leakage.

In [ ]:
```
# # ═══════════════════════════════════════════════════════
```

```
# # 4.1  FEATURE ENGINEERING
# # Applied IDENTICALLY to train and test — no leakage
# # ═══════════════════════════════════════════════════════
# def engineer_features(df):  # Create meaningful new features from raw columr
#     df = df.copy()

#     # Date decomposition
#     df['TransactionDate'] = pd.to_datetime(df['TransactionDate'], errors='co
#     df['SaleYear']    = df['TransactionDate'].dt.year
#     df['SaleMonth']   = df['TransactionDate'].dt.month
#     df['SaleQuarter'] = df['TransactionDate'].dt.quarter
#     df.drop(columns=['TransactionDate'], inplace=True)

#     # MachineAge — KEY feature: older machine = lower price
#     df['MachineAge'] = (df['SaleYear'] - df['ManufactureYear']).clip(lower=0

#     # Usage intensity: high hours/year → faster depreciation
#     df['UsagePerYear'] = df['OperationalHoursMeter'] / (df['MachineAge'] + 1

#     # Binary presence flags for high-missing columns
#     high_miss = ['col6','col7','col8','col9','col11','col12',
#                  'col13','col14','col3','Forks','col4','col5',
#                  'col27','col28','col29','col30']
#     for c in high_miss:
#         if c in df.columns:
#             df[f'{c}_present'] = df[c].notna().astype(np.int8)

#     # Standardise "None or Unspecified" → NaN
#     obj = df.select_dtypes(include='object').columns
#     df[obj] = df[obj].replace('None or Unspecified', np.nan)

#     # Drop near-empty columns
#     df.drop(columns=[c for c in ['col18','col19'] if c in df.columns], inpla

#     return df

# train_eng = engineer_features(train_df)
# test_eng  = engineer_features(test_df)

# print("Feature engineering applied!")
# print(f"  Train: {train_df.shape} → {train_eng.shape}")
# print(f"  Test : {test_df.shape}  → {test_eng.shape}")
# print()
# new = ['SaleYear','SaleMonth','SaleQuarter','MachineAge','UsagePerYear']
# print("New feature statistics:")
# print(train_eng[new].describe().round(2).to_string())
```

In [ ]:

```
# # ═══════════════════════════════════════════════════════
# # 4.2  PREPARE FEATURE MATRICES & TARGET
# # ═══════════════════════════════════════════════════════
# ID_COLS = ['TransactionID', 'AssetID']

# # log1p(price) → symmetric distribution, aligns with RMSLE optimisation
```

```
# y_all  = np.log1p(train_eng['TargetValue'])
# X_all  = train_eng.drop(columns=ID_COLS + ['TargetValue'], errors='ignore')
# X_test_final = test_eng.drop(columns=ID_COLS, errors='ignore')
# test_ids     = test_df['TransactionID'].values

# print(f"X_all   : {X_all.shape}")
# print(f"y_all   : {y_all.shape}  (log1p scale)")
# print(f"X_test  : {X_test_final.shape}")

# # 80 / 20 train-validation split
# X_train, X_val, y_train, y_val = train_test_split(
#     X_all, y_all, test_size=0.2, random_state=SEED)

# print(f"\nSplit 80/20:")
# print(f"  X_train: {X_train.shape}   X_val: {X_val.shape}")
# print(f"\nTarget (log1p) range:")
# print(f"  Min {y_all.min():.3f} → ${np.expm1(y_all.min()):,.0f}")
# print(f"  Max {y_all.max():.3f} → ${np.expm1(y_all.max()):,.0f}")
```

In [ ]:

```
# # ═══════════════════════════════════════════════════════
# # 4.3  SKLEARN PREPROCESSING PIPELINE
# # ═══════════════════════════════════════════════════════
# numeric_cols = X_train.select_dtypes(include=[np.number]).columns.tolist()
# cat_cols     = X_train.select_dtypes(include=['object']).columns.tolist()

# print(f"Numeric  cols ({len(numeric_cols)}): {numeric_cols}")
# print(f"\nCategorical cols ({len(cat_cols)}): {cat_cols}")

# numeric_transformer = Pipeline([
#     ('imputer', SimpleImputer(strategy='median')),
#     ('scaler',  StandardScaler())
# ])

# categorical_transformer = Pipeline([
#     ('imputer', SimpleImputer(strategy='constant', fill_value='Missing')),
#     ('encoder', OrdinalEncoder(handle_unknown='use_encoded_value', unknown_v
# ])

# preprocessor = ColumnTransformer(
#     transformers=[
#         ('num', numeric_transformer, numeric_cols),
#         ('cat', categorical_transformer, cat_cols),
#     ],
#     remainder='drop',
#     verbose_feature_names_out=False
# )

# # fit_transform only on TRAIN — transform val/test without refitting
# X_train_proc = preprocessor.fit_transform(X_train)
# X_val_proc   = preprocessor.transform(X_val)
# X_test_proc  = preprocessor.transform(X_test_final)

# feature_names_out = numeric_cols + cat_cols
```

```
# print(f"\nPreprocessed shapes:")
# print(f"  X_train_proc : {X_train_proc.shape}")
# print(f"  X_val_proc   : {X_val_proc.shape}")
# print(f"  X_test_proc  : {X_test_proc.shape}")
# print("\nPipeline summary:")
# print("  Numeric  → Median Imputation → StandardScaler")
# print("  Categorical → fill 'Missing' → OrdinalEncoder")
```

5. Model Building & Comparison

Five models from **different ML families** are compared on the 20 % validation set:

#	Model	Family	Strength	Weakness
0	DummyRegressor	Baseline	—	Always predicts mean
1	Ridge Regression	Linear	Fast, interpretable	Linear only
2	Random Forest	Bagging Ensemble	Robust, non-linear	Memory-heavy
3	HistGradientBoosting	Boosting Ensemble	Fast, handles NaN	Fewer options
4	XGBoost	Boosting Ensemble	Best accuracy, L1+L2	Many params
5	LightGBM	Boosting Ensemble	Fastest, large-data	Can overfit

In [ ]:
```
# # ── RMSLE — competition metric ──────────────────────────────
# def rmsle(y_true, y_pred):
#     # Root Mean Squared Logarithmic Error. Lower = better. Target <= 0.85.
#     y_pred = np.maximum(y_pred, 0)
#     return np.sqrt(mean_squared_error(np.log1p(y_true), np.log1p(y_pred)))

# def neg_rmsle_log(y_true, y_pred):
#     # Scorer for sklearn when target is already log1p transformed.
#     return -np.sqrt(mean_squared_error(y_true, y_pred))

# rmsle_scorer = make_scorer(neg_rmsle_log)

# # ── Submission generator ────────────────────────────────────
# def make_submission(model, X_proc, test_ids, log_target=True,
#                     filename='submission.csv'):
#     preds = model.predict(X_proc)
#     if log_target:
#         preds = np.expm1(preds)
#     preds = np.maximum(preds, 0)
#     sub = pd.DataFrame({'TransactionID': test_ids, 'TargetValue': preds})
#     sub.to_csv(filename, index=False)
#     print(f"✅ {filename} saved ({len(sub):,} rows)")
```

```
#     return sub

# print("\n✅ Helpers ready.")
```

In [ ]:
```
# # ═══════════════════════════════════════════════════════════
# # 5.  MODEL BUILDING & COMPARISON
# # ═══════════════════════════════════════════════════════════
# model_results  = {}
# trained_models = {}

# print("=" * 60)
# print("  MODEL COMPARISON — RMSLE on 20% Validation Set")
# print("=" * 60)

# # ── Baseline: DummyRegressor ──────────────────────────────
# dummy = DummyRegressor(strategy='mean')
# dummy.fit(X_train_proc, y_train)
# d_r = rmsle(np.expm1(y_val), np.expm1(dummy.predict(X_val_proc)))
# model_results['0. Dummy Baseline']   = d_r
# trained_models['0. Dummy Baseline']  = dummy
# print(f"\n  0. DummyRegressor (mean)         RMSLE: {d_r:.4f}  [must beat th

# # ── Model 1: Ridge Regression (Linear) ────────────────────
# # Pros: Extremely fast, interpretable coefficients
# # Cons: Captures linear relationships only — will underfit this data
# ridge = Ridge(alpha=10.0, random_state=SEED)
# ridge.fit(X_train_proc, y_train)
# r_r = rmsle(np.expm1(y_val), np.expm1(ridge.predict(X_val_proc)))
# model_results['1. Ridge Regression']  = r_r
# trained_models['1. Ridge Regression'] = ridge
# print(f"  1. Ridge Regression              RMSLE: {r_r:.4f}")
# print(f"     Pros: Fast, interpretable | Cons: Linear only")
```

In [ ]:
```
# # ── Model 2: Random Forest (Bagging) ──────────────────────
# # Pros: Handles non-linearity, robust to outliers, good feature importance
# # Cons: Slower than boosting, memory-intensive with many trees
# rf = RandomForestRegressor(n_estimators=200, max_depth=12, min_samples_leaf=
#                            max_features='sqrt', random_state=SEED, n_jobs=-
# rf.fit(X_train_proc, y_train)
# rf_r = rmsle(np.expm1(y_val), np.expm1(rf.predict(X_val_proc)))
# model_results['2. Random Forest']  = rf_r
# trained_models['2. Random Forest'] = rf
# print(f"  2. Random Forest                 RMSLE: {rf_r:.4f}")
# print(f"     Pros: Non-linear, robust | Cons: Slower, memory-heavy")

# # ── Model 3: HistGradientBoosting (Boosting) ──────────────
# # Pros: Fast, handles NaN natively, built-in regularisation
# # Cons: Fewer tuning knobs than XGBoost / LightGBM
# hgb = HistGradientBoostingRegressor(max_iter=500, max_depth=6, learning_rate
#                                     min_samples_leaf=20, l2_regularization=
#                                     random_state=SEED)
# hgb.fit(X_train_proc, y_train)
# hgb_r = rmsle(np.expm1(y_val), np.expm1(hgb.predict(X_val_proc)))
```

```
# model_results['3. HistGradientBoosting']  = hgb_r
# trained_models['3. HistGradientBoosting'] = hgb
# print(f"  3. HistGradientBoosting          RMSLE: {hgb_r:.4f}")
# print(f"     Pros: Fast, handles NaN | Cons: Fewer tuning options")
```

In [ ]:
```
# # ── Model 4: XGBoost (Boosting) ──────────────────────
# # Pros: Outstanding accuracy, L1+L2 regularisation, sparse data friendly
# # Cons: Many hyperparameters, slower than LightGBM
# xgb_m = XGBRegressor(n_estimators=700, max_depth=6, learning_rate=0.05,
#                      subsample=0.8, colsample_bytree=0.8,
#                      reg_alpha=0.1, reg_lambda=1.0, min_child_weight=3,
#                      tree_method='hist', random_state=SEED, n_jobs=-1, verb
# xgb_m.fit(X_train_proc, y_train, eval_set=[(X_val_proc, y_val)], verbose=Fal
# xgb_r = rmsle(np.expm1(y_val), np.expm1(xgb_m.predict(X_val_proc)))
# model_results['4. XGBoost']  = xgb_r
# trained_models['4. XGBoost'] = xgb_m
# print(f"  4. XGBoost                       RMSLE: {xgb_r:.4f}")
# print(f"     Pros: Best accuracy, L1+L2 reg | Cons: Many params, slower")

# # ── Model 5: LightGBM (Boosting) ─────────────────────
# # Pros: Fastest boosting, great with 100K+ rows, leaf-wise growth
# # Cons: Can overfit on small datasets, sensitive to hyperparameters
# lgbm_m = lgb.LGBMRegressor(n_estimators=700, max_depth=6, learning_rate=0.05
#                            subsample=0.8, colsample_bytree=0.8,
#                            reg_alpha=0.1, reg_lambda=1.0,
#                            min_child_samples=20, num_leaves=63,
#                            random_state=SEED, n_jobs=-1, verbose=-1)
# lgbm_m.fit(X_train_proc, y_train, eval_set=[(X_val_proc, y_val)],
#            callbacks=[lgb.early_stopping(50, verbose=False), lgb.log_evaluat
# lgbm_r = rmsle(np.expm1(y_val), np.expm1(lgbm_m.predict(X_val_proc)))
# model_results['5. LightGBM']  = lgbm_r
# trained_models['5. LightGBM'] = lgbm_m
# print(f"  5. LightGBM                      RMSLE: {lgbm_r:.4f}")
# print(f"     Pros: Fastest, great at scale | Cons: Can overfit, sensitive pa
# print(f"\n{'='*60}")
```

In [ ]:
```
# # ── Model Comparison Chart ──────────────────────────
# fig, ax = plt.subplots(figsize=(12, 6))

# names  = list(model_results.keys())
# scores = list(model_results.values())
# colors = ['#27ae60' if s < 0.85 else '#e74c3c' for s in scores]

# bars = ax.barh(names, scores, color=colors, edgecolor='white', height=0.6)
# ax.axvline(0.85, color='crimson', ls='--', lw=2.5, label='Competition Cutoff
# ax.set_xlabel('RMSLE — Validation Set  (lower = better)')
# ax.set_title('Model Performance Comparison\n'
#              'Green ✅ = beats cutoff  |  Red ❌ = above cutoff',
#              fontsize=13, fontweight='bold')
# ax.legend(fontsize=11)
# for bar, sc in zip(bars, scores):
#     ax.text(sc+0.003, bar.get_y()+bar.get_height()/2,
#             f'{sc:.4f}', va='center', fontsize=11, fontweight='bold')
```

```
# plt.tight_layout(); plt.show()

# print("\nFull comparison:")
# print(f"{'Model':<35} {'RMSLE':>10}  {'Gap to 0.85':>12}  Status")
# print("-"*72)
# for name, sc in sorted(model_results.items(), key=lambda x: x[1]):
#     gap = 0.85 - sc
#     st  = '✅ BEATS CUTOFF' if sc < 0.85 else '❌ Above cutoff'
#     print(f"{name:<35} {sc:>10.4f}  {gap:>+12.4f}  {st}")

# best = min(model_results, key=model_results.get)
# print(f"\n Best model: {best}  RMSLE={model_results[best]:.4f}")
```

6. Hyperparameter Tuning

RandomizedSearchCV is used on XGBoost (typically the best performer):

- Samples randomly from a parameter distribution — wider exploration, fewer evaluations
- 3-fold CV for speed (increase `cv=5` for a more reliable estimate)
- Custom `rmsle_scorer` passed directly — sklearn maximises, we negate RMSLE

Increase `n_iter` from **25 → 50+** for a more thorough search at the cost of runtime.

In [ ]:
```
# # ═══════════════════════════════════════════════════════════
# # 6.  HYPERPARAMETER TUNING — RandomizedSearchCV (XGBoost)
# # ═══════════════════════════════════════════════════════════
# print("Running RandomizedSearchCV (25 iterations × 3-fold CV) ...")

# param_dist = {
#     'n_estimators':     [300, 500, 700, 1000],
#     'max_depth':        [4, 5, 6, 7, 8],
#     'learning_rate':    [0.01, 0.03, 0.05, 0.08, 0.1],
#     'subsample':        [0.7, 0.8, 0.9, 1.0],
#     'colsample_bytree': [0.7, 0.8, 0.9, 1.0],
#     'reg_alpha':        [0, 0.05, 0.1, 0.3, 0.5],
#     'reg_lambda':       [0.5, 1.0, 2.0, 5.0],
#     'min_child_weight': [1, 3, 5, 7, 10],
#     'gamma':            [0, 0.1, 0.3, 0.5],
# }

# rs = RandomizedSearchCV(
#     XGBRegressor(tree_method='hist', random_state=SEED, n_jobs=-1, verbosity
#     param_distributions=param_dist,
#     n_iter=25,          # ← increase to 50-100 for better results
#     scoring=rmsle_scorer,
#     cv=3,
```

```
#     random_state=SEED,
#     n_jobs=-1,
#     verbose=1,
#     refit=True
# )
# rs.fit(X_train_proc, y_train)

# print("\nBest Parameters:")
# for p, v in sorted(rs.best_params_.items()):
#     print(f"  {p:<25}: {v}")

# tuned_preds = rs.best_estimator_.predict(X_val_proc)
# tuned_rmsle = rmsle(np.expm1(y_val), np.expm1(tuned_preds))
# print(f"\n  CV RMSLE (log space)  : {-rs.best_score_:.4f}")
# print(f"  Val RMSLE (default)   : {xgb_r:.4f}")
# print(f"  Val RMSLE (tuned)     : {tuned_rmsle:.4f}")
# print(f"  Improvement           : {xgb_r - tuned_rmsle:+.4f}")
```

In [ ]:

```
# # ── Final Model: train on ALL data (train + val) ──────
# print("Training final model on 100% of training data ...")

# preprocessor_final = ColumnTransformer(
#     transformers=[
#         ('num', Pipeline([('i', SimpleImputer(strategy='median')),
#                           ('s', StandardScaler())]), numeric_cols),
#         ('cat', Pipeline([('i', SimpleImputer(strategy='constant', fill_valu
#                           ('e', OrdinalEncoder(handle_unknown='use_encoded_v
#                                                unknown_value=-1))]), cat_col
#     ], remainder='drop', verbose_feature_names_out=False
# )
# X_all_proc        = preprocessor_final.fit_transform(X_all)
# X_test_final_proc = preprocessor_final.transform(X_test_final)

# final_model = XGBRegressor(**rs.best_params_, tree_method='hist',
#                            random_state=SEED, n_jobs=-1, verbosity=0)
# final_model.fit(X_all_proc, y_all)

# print(f"\nFinal model trained on {X_all_proc.shape[0]:,} samples, {X_all_pro
# print(f"\n{'='*55}")
# print(f"  PERFORMANCE SUMMARY")
# print(f"{'='*55}")
# for nm, sc in sorted(model_results.items(), key=lambda x: x[1]):
#     print(f"  {nm:<35} {sc:.4f}")
# print(f"  {'XGBoost (tuned HPT)':<35} {tuned_rmsle:.4f}  ← Final")
# print(f"  {'Competition Cutoff':<35} 0.8500")
# st = 'BEATS CUTOFF ✅' if tuned_rmsle < 0.85 else 'Needs improvement ⚠'
# print(f"  Status: {st}")
```

7. Error & Residual Analysis

Understanding *where* the model is wrong guides further improvement:

- **Actual vs Predicted** — perfect model sits on the diagonal
- **Residuals distribution** — centred at 0 = unbiased
- **Residuals vs Predicted** — horizontal band = homoscedastic (good)
- **Feature importance** — what drives price predictions

In [ ]:
```
# # ═══════════════════════════════════════════════════════════
# # 7.1  RESIDUAL ANALYSIS
# # ═══════════════════════════════════════════════════════════
# pred_log   = rs.best_estimator_.predict(X_val_proc)
# pred_price = np.expm1(pred_log)
# true_price = np.expm1(y_val.values)

# resid    = true_price - pred_price
# pct_err  = (resid / true_price) * 100

# fig, axes = plt.subplots(2, 2, figsize=(16, 10))
# fig.suptitle('Error & Residual Analysis — Validation Set', fontsize=14, font

# # Actual vs Predicted
# axes[0,0].scatter(true_price, pred_price, alpha=.25, s=5, color='steelblue')
# mn, mx = true_price.min(), true_price.max()
# axes[0,0].plot([mn,mx],[mn,mx], 'r--', lw=2, label='Perfect')
# axes[0,0].set_xlabel('Actual Price'); axes[0,0].set_ylabel('Predicted Price'
# axes[0,0].set_title('Actual vs Predicted')
# axes[0,0].legend()
# axes[0,0].xaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/
# axes[0,0].yaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/

# # Residuals distribution
# axes[0,1].hist(resid, bins=80, color='coral', edgecolor='white', alpha=.85)
# axes[0,1].axvline(0, color='black', lw=2, ls='--', label='Zero error')
# axes[0,1].axvline(resid.mean(), color='red', lw=2, label=f'Mean={resid.mean(
# axes[0,1].set_xlabel('Residual (Actual − Predicted)'); axes[0,1].legend(font
# axes[0,1].set_title('Residuals Distribution')
# axes[0,1].xaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/

# # Residuals vs Predicted
# axes[1,0].scatter(pred_price, resid, alpha=.2, s=4, color='seagreen')
# axes[1,0].axhline(0, color='red', lw=2, ls='--')
# axes[1,0].set_xlabel('Predicted Price'); axes[1,0].set_ylabel('Residual')
# axes[1,0].set_title('Residuals vs Predicted  (flat band = good)')
# axes[1,0].xaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/
# axes[1,0].yaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/

# # % error distribution
# axes[1,1].hist(pct_err.clip(-60, 60), bins=80, color='mediumpurple', edgecol
# axes[1,1].axvline(0, color='black', lw=2, ls='--')
# axes[1,1].set_xlabel('% Error — clipped ±60%')
# axes[1,1].set_title('Percentage Error Distribution')

# plt.tight_layout(); plt.show()
```

```
# print("Error Metrics — Validation Set:")
# print(f"  RMSLE  : {tuned_rmsle:.4f}  (competition metric)")
# print(f"  MAE    : ${np.mean(np.abs(resid)):>10,.2f}")
# print(f"  RMSE   : ${np.sqrt(np.mean(resid**2)):>10,.2f}")
# print(f"  R2     :  {r2_score(true_price, pred_price):>10.4f}")
# print(f"  MedAPE :  {np.median(np.abs(pct_err)):>10.2f}%")
```

In [ ]:
```
# # ═══════════════════════════════════════════════════════════
# # 7.2  FEATURE IMPORTANCE
# # ═══════════════════════════════════════════════════════════
# fi = pd.DataFrame({'Feature': feature_names_out,
#                    'Importance': rs.best_estimator_.feature_importances_}
#                   ).sort_values('Importance', ascending=False).head(30)

# fig, ax = plt.subplots(figsize=(13, 11))
# cmap = plt.cm.viridis(np.linspace(0.1, 0.9, len(fi)))
# ax.barh(fi['Feature'][::-1], fi['Importance'][::-1], color=cmap[::-1], edgec
# ax.set_xlabel('Feature Importance (XGBoost Gain)')
# ax.set_title('Top 30 Most Predictive Features', fontsize=13, fontweight='bol
# plt.tight_layout(); plt.show()

# print("Top 20 Features:")
# print(fi.head(20).to_string(index=False))
# print("\nKey findings:")
# print("  MachineAge / ManufactureYear  — depreciation is the strongest signa
# print("  OperationalHoursMeter         — more usage = lower residual value")
# print("  FunctionalClassification      — machine type sets the price bracket
# print("  RegionCode                    — geographic price variation")
```

8. Final Prediction & Submission

- Model: **XGBoost (tuned hyperparameters)** trained on all 138 701 samples
- Convert log1p predictions back to USD with `expm1()`
- Clip any negatives to 0 (physical constraint — no negative prices)
- Save `submission.csv` in the required format

In [ ]:
```
# # ═══════════════════════════════════════════════════════════
# # 8.  FINAL SUBMISSION
# # ═══════════════════════════════════════════════════════════
# sub = make_submission(final_model, X_test_final_proc, test_ids,
#                       log_target=True, filename='submission.csv')

# print("\nSubmission statistics:")
# print(f"  Rows   : {len(sub):,}")
# print(f"  Min    : ${sub['TargetValue'].min():>12,.2f}")
# print(f"  Max    : ${sub['TargetValue'].max():>12,.2f}")
# print(f"  Mean   : ${sub['TargetValue'].mean():>12,.2f}")
# print(f"  Median : ${sub['TargetValue'].median():>12,.2f}")
```

```
# neg = (sub['TargetValue'] < 0).sum()
# print(f"  Negative predictions: {neg}  {'✅ None' if neg==0 else '⚠  clippe

# print(f"\n{'='*55}")
# print(f"  SUBMISSION READY!")
# print(f"  File : submission.csv")
# print(f"  Val RMSLE : {tuned_rmsle:.4f}  (target <= 0.85)")
# print(f"{'='*55}")
```

In [ ]:
```
# # Sanity check: test prediction distribution should mirror training
# fig, axes = plt.subplots(1, 2, figsize=(14, 5))
# fig.suptitle('Submission Sanity Check', fontsize=12, fontweight='bold')

# axes[0].hist(train_df['TargetValue'], bins=60, alpha=.6, color='steelblue',
#              edgecolor='white', label='Train (actual)', density=True)
# axes[0].hist(sub['TargetValue'], bins=60, alpha=.6, color='coral',
#              edgecolor='white', label='Test (predicted)', density=True)
# axes[0].set_title('Price Distribution: Train vs Predicted')
# axes[0].set_xlabel('Price (USD)')
# axes[0].legend()
# axes[0].xaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/10

# axes[1].hist(sub['TargetValue'], bins=40, color='coral', edgecolor='white')
# axes[1].set_title('Predicted Price Histogram (Test Set)')
# axes[1].set_xlabel('Predicted Price (USD)')
# axes[1].set_ylabel('Count')
# axes[1].xaxis.set_major_formatter(mticker.FuncFormatter(lambda x,_: f'${x/10

# plt.tight_layout(); plt.show()

# print("First 10 rows of submission.csv:")
# print(sub.head(10).to_string(index=False))
```

🏗️ Milestone 1 Answers

Milestone Deadline: June 23, 2026

This notebook answers all **14 questions** from **Milestone 1** in order.

Each section contains:

- The **question** restated
- Clean, readable **code**

In [ ]:
```
# print('='*50)
# print('Q1: Dataset Dimensions')
# print(f' Train dataset: {train_df.shape[0]:,} row × {train_df.shape[1]} colu
# print(f' Test  dataset : {test_df.shape[0]:,} rows × {test_df.shape[1]} colu
# print('='*50)
```

In [ ]:
```
# print('=' * 50)
# print('  Q2: Target Variable Identification')
# target_cols = set(train_df.columns) - set(test_df.columns)
# print(f' Target_cols: {target_cols}')
# print('=' * 50)
```

In [ ]:
```
# print('=' * 50)
# print('  Q3: Numerical Feature Count')
# num_cols = train_df.select_dtypes(include=['int64', 'float64']).columns.toli
# print(f'  Total columns in train : {train_df.shape[1]}')
# print(f'  Strictly numerical (int/float): {len(num_cols)}')
# print(f'  Column names: {num_cols}')
# print('=' * 50)
```

In [ ]:
```
# print('=' * 60)
# print('  Q4: Columns with > 90% Missing Values')
# missing_count = train_df.isnull().sum()
# missing_pct= missing_count/len(train_df)*100
# very_sparse = missing_pct[missing_pct > 90].sort_values(ascending=False)
# question_cols = ['col18', 'col19', 'CabinType', 'col5']
# print()
# print(f' Threshold : 90% -> {int(len(train_df)*0.90):,} missing value')
# print()
# print(f'  ALL columns exceeding 90% missing:')
# print(f'  {"Column":<20} {"Missing Rows":>15} {"Missing %":>12}')
# print('  ' + '-' * 50)
# for col in very_sparse.index:
#     flag = ' ← IN QUESTION' if col in question_cols else ''
#     print(f'  {col:<20} {missing_count[col]:>15,} {missing_pct[col]:>11.2f}%
# print()
# print('  Checking the 4 specific options from the question:')
# for c in question_cols:
#     pct = missing_pct[c]
#     status = '✅ YES (> 90%)' if pct > 90 else '❌ NO'
#     print(f'    {c:<15}: {pct:.2f}% missing  → {status}')

# print('=' * 60)
```

In [ ]:
```
# print('=' * 50)
# print('  Q5: Missing Values — OperationalHoursMeter')
# n_missing   = train_df[col].isnull().sum()
# pct_missing = n_missing / len(train_df) * 100
# n_present   = len(train_df) - n_missing
# print()
# print(f'  Total train rows    : {len(train_df):,}')
# print(f'  Non-null rows       : {n_present:,}')
# print(f'  Missing rows        : {n_missing:,}')
# print(f'  Missing percentage  : {pct_missing:.2f}%')
# print()
# print(f'✅ ANSWER: ~{pct_missing:.1f}%')
# print('=' * 50)
```

In [ ]:
```
# print('=' * 50)
# print('  Q6: TargetValue (Sale Price) Distribution')
# print()
# median_price = train_df['TargetValue'].median()
# mean_price   = train_df['TargetValue'].mean()
# print(f'  MEDIAN : ${median_price:>10,.2f}  ← answer')
# print(f'  Mean   : ${mean_price:>10,.2f}')
# print('=' * 50)
```

In [ ]:
```
# print('=' * 60)
# print('  Q7: ManufactureYear — Anomalous Mode Detection')
# mode_year = train_df['ManufactureYear'].mode()[0]
# mode_count = (train_df['ManufactureYear'] ==mode_year).sum()
# mode_pct = mode_count / len(train_df) *100
# print(f'  Mode (most frequent year) : {int(mode_year)}')
# print(f'  Count                     : {mode_count:,}  ({mode_pct:.1f}% of al
# print()
# print('  Top 10 Most Frequent ManufactureYears:')
# print(train_df['ManufactureYear'].value_counts().head(10).to_string())
# print()
# print(f'✅ ANSWER: {int(mode_year)}')
# print('=' * 60)
```

In [ ]:
```
# print('=' * 50)
# print('  Q8: TransactionDate — Time Span')
# train_df['TransactionDate'] = pd.to_datetime(train_df['TransactionDate'], er
# min_date  = train_df['TransactionDate'].min()
# max_date  = train_df['TransactionDate'].max()
# span_days = (max_date - min_date).days
# print(f'  Earliest (Min) date : {min_date.date()}')
# print(f'  Latest   (Max) date : {max_date.date()}')
# print(f'  Total span          : {span_days:,} days  (~{span_days/365.25:.1f}
# print()
# print(f'✅ ANSWER: A) 1989-01-31  (Earliest TransactionDate = {min_date.date
# print('=' * 50)
```

In [ ]:
```
# print('=' * 50)
# print('  Q9: Spec_BaseClass — Unique Classes')
# col = 'Spec_BaseClass'
# n_uniq = train_df[col].nunique()
# print(f'  Unique classes in "{col}" : {n_uniq}')
# print('=' * 50)
```

In [ ]:
```
# print('=' * 60)
# print('  Q10: Geographical Transaction Volume')
# region_counts = train_df['RegionCode'].value_counts()
# top_region    = region_counts.idxmax()
# top_count     = region_counts.max()
# top_pct       = top_count / len(train_df) * 100
# print(f'  Most frequent region : {top_region}')
# print(f'  Transaction count    : {top_count:,}  ({top_pct:.1f}% of all recor
# print('=' * 60)
```

In [ ]:
```
# print('=' * 60)
# print('  Q11: Florida — Average Sale Price')
# florida_df   = train_df[train_df['RegionCode'] == 'Florida']
# fl_mean      = florida_df['TargetValue'].mean()
# fl_median    = florida_df['TargetValue'].median()
# fl_count     = len(florida_df)

# print(f'  Florida transaction count : {fl_count:,}')
# print(f'  Florida Mean  TargetValue : ${fl_mean:,.2f}')
# print(f'  Florida Median TargetValue: ${fl_median:,.2f}')
# print(f'✅ ANSWER: ~${fl_mean:,.0f}')
# print('=' * 60)
```

In [ ]:
```
# print('=' * 50)
# print('  Q12: UtilizationTier Value Counts')
# util_counts = train_df['UtilizationTier'].value_counts()
# most_common = util_counts.idxmax()
# print(util_counts.to_string())
# print(f'\n  Most common tier : {most_common}')
# print('✅ ANSWER: B) Medium')
# print('=' * 50)
```

In [ ]:
```
# print('=' * 60)
# print('  Q13: Pearson Correlation — TargetValue vs OperationalHoursMeter')
# corr_df = train_df[['TargetValue', 'OperationalHoursMeter']].dropna()
# pearson  = corr_df['TargetValue'].corr(corr_df['OperationalHoursMeter'])
# print(f'  Rows used (after dropping NaN) : {len(corr_df):,}')
# print(f'  Pearson Correlation Coefficient: {pearson:.4f}')
# print('✅ ANSWER: C) ~0.002 (Virtually Zero)')
# print('=' * 60)
```

In [ ]:
```
# print('=' * 70)
# print('  Q14: Most Common FunctionalClassification')
# fc_counts = train_df['FunctionalClassification'].value_counts()
# top_fc    = fc_counts.idxmax()
# top_count = fc_counts.max()
# top_pct   = top_count / len(train_df) * 100
# print(f'  #1 Most Common : {top_fc}')
# print(f'  Count : {top_count:,}  ({top_pct:.1f}% of all records)')
# print()

# print('=' * 70)
```

🏗️ Milestone 2 Answers

Milestone Deadline: June 29, 2026

This notebook answers all **11 questions** from **Milestone 2** in order.

Section	Topic	Questions
1	Feature Engineering	Q1 – Q6
2	Encoding (One-Hot)	Q7
3	Correlation Analysis	Q8
4	Feature Scaling + Train/Val Split	Q9 – Q10
5	Linear Regression Model	Q11

In [2]:
```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import warnings

from sklearn.preprocessing import StandardScaler
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
from sklearn.metrics import r2_score

warnings.filterwarnings('ignore')
pd.set_option('display.max_columns', 60)
sns.set_theme(style='whitegrid', palette='Set2')

train_df = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-pri
test_df = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-pric
sample = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-price

print(f'✅ Data loaded!')
print(f'   Train : {train_df.shape[0]:,} rows  ×  {train_df.shape[1]} cols')
```

```
✅ Data loaded!
   Train : 138,701 rows  ×  50 cols
```

📂 Section 1: Feature Engineering

Create the following 6 new features on the Train Dataset:

1. **TransactionYear** — from `TransactionDate`
2. **TransactionQuarter** — from `TransactionDate`
3. **AssetAge** — `TransactionYear - ManufactureYear`
4. **DescriptorLength** — number of characters in `Spec_FullDescriptor`
5. **HasOperationalHours** — binary: 1 if `OperationalHoursMeter` is present, else 0
6. **HasVariantModifier** — binary: 1 if `Spec_VariantModifier` is present, else 0

In [8]:
```
# ── Feature Engineering ──────────────────────────────────────

# Parse TransactionDate
train_df['TransactionDate'] = pd.to_datetime(train_df['TransactionDate'], errc
# 1. TransactionYear
train_df['TransactionYear'] = train_df['TransactionDate'].dt.year
# 2. TransactionQuarter
train_df['TransactionQuarter'] = train_df['TransactionDate'].dt.quarter
# 3. AssetAge = TransactionYear - ManufactureYear
train_df['AssetAge'] = train_df['TransactionYear'] - train_df['ManufactureYear
# 4. DescriptorLength = number of characters in Spec_FullDescriptor
train_df['DescriptorLength'] = train_df['Spec_FullDescriptor'].fillna('').appl
# 5. HasOperationalHours: 1 if OperationalHoursMeter is available, 0 otherwise
train_df['HasOperationalHours'] = train_df['OperationalHoursMeter'].notna().as
# 6. HasVariantModifier: 1 if Spec_VariantModifier is available, 0 otherwise
train_df['HasVariantModifier'] = train_df['Spec_VariantModifier'].notna().asty

print('✅ Feature engineering complete!')
print(f'   Shape after FE : {train_df.shape}')
print()
new_features = ['TransactionYear', 'TransactionQuarter', 'AssetAge','Descriptc
print('New feature sample statistics:')
print(train_df[new_features].describe().round(2))
```

```
Feature engineering complete!
Shape after FE: (138701, 57)

New feature sample statistics:
       TransactionYear  TransactionQuarter   AssetAge  DescriptorLength  \
count        138701.00           138701.00  138701.00         138701.00
mean           2007.49                2.34     115.85              5.44
std               4.79                1.14     307.18              1.77
min            1990.00                1.00      -7.00              2.00
25%            2005.00                1.00       5.00              4.00
50%            2009.00                2.00       9.00              5.00
75%            2011.00                3.00      16.00              7.00
max            2013.00                4.00    1012.00             19.00

       HasOperationalHours  HasVariantModifier
count            138701.00           138701.00
mean                  0.59                0.38
std                   0.49                0.48
min                   0.00                0.00
25%                   0.00                0.00
50%                   1.00                0.00
75%                   1.00                1.00
max                   1.00                1.00
```

In [53]:
```
print('=' * 50)
print('  Q1: Most Frequent AssetAge')
asset_age_counts = train_df['AssetAge'].value_counts()
mode_age = train_df['AssetAge'].mode()[0]
print(f'  Mode (most frequent) AssetAge : {int(mode_age)} ← answer')
print(f'  Count                         : {asset_age_counts[mode_age]:,}')
```

```
print('=' * 50)
```

```
==================================================
  Q1: Most Frequent AssetAge
  Mode (most frequent) AssetAge : 5 ← answer
  Count                         : 12,542
==================================================
```

In [32]:
```
print('=' * 50)
print('  Q2: Average TargetValue by TransactionQuarter')
quarter_avg = train_df.groupby('TransactionQuarter')['TargetValue'].mean().rou
best_quarter = quarter_avg.idxmax()
print(f'  {"Quarter":<12} {"Avg TargetValue":>18}')
print('  ' + '-' * 32)
for q, avg in quarter_avg.items():
    marker = ' ← HIGHEST' if q == best_quarter else ''
    print(f'  Q{q:<11} ${avg:>16,.2f}{marker}')
print()
print(f'✅ ANSWER: Q{best_quarter}')
print('=' * 50)
```

```
==================================================
  Q2: Average TargetValue by TransactionQuarter
  Quarter         Avg TargetValue
  --------------------------------
  Q1           $       42,873.59 ← HIGHEST
  Q2           $       41,408.26
  Q3           $       40,619.20
  Q4           $       40,562.45

  ✅ ANSWER: Q1
==================================================
```

In [41]:
```
print('=' * 50)
print('  Q3: DescriptorLength Statistics')
max_desc_len = train_df['DescriptorLength'].max()
print(f'  Max    : {max_desc_len}  ← answer')
print()
print('  Value counts of DescriptorLength:')
print(train_df['DescriptorLength'].value_counts().sort_index().to_string())
print('=' * 50)
```

```
==================================================
  Q3: DescriptorLength Statistics
  Max    : 19  ← answer

  Value counts of DescriptorLength:
DescriptorLength
2       301
3     12294
4     39056
5     29998
6     21553
7     14850
8     13776
9      3932
10     1870
11      198
12      733
13       49
14       61
15       14
16        7
17        6
19        3
==================================================
```

In [47]:
```
print('=' * 55)
print('  Q4: HasOperationalHours = 1 Count')
has_op_hours_count = (train_df['HasOperationalHours'] == 1).sum()
no_op_hours_count  = (train_df['HasOperationalHours'] == 0).sum()
print(f'  Total training rows           : {len(train_df):,}')
print(f'  HasOperationalHours = 1 (yes) : {has_op_hours_count:,}')
print(f'  HasOperationalHours = 0 (no)  : {no_op_hours_count:,}')
print()
print(f'✅ ANSWER: {has_op_hours_count:,}')
print('=' * 55)
```

```
==================================================
  Q4: HasOperationalHours = 1 Count
  Total training rows           : 138,701
  HasOperationalHours = 1 (yes) : 82,058
  HasOperationalHours = 0 (no)  : 56,643

✅ ANSWER: 82,058
==================================================
```

In [46]:
```
print('=' * 55)
print('  Q5: Percentage with HasVariantModifier = 1')
has_variant_count = (train_df['HasVariantModifier'] == 1).sum()
pct_variant       = has_variant_count / len(train_df) * 100
print(f'  Records with variant info     : {has_variant_count:,}')
print(f'  Percentage                    : {pct_variant:.4f}%')
print()
print(f'✅ ANSWER: {answer}')
print('=' * 55)
```

```
==========================================================
  Q5: Percentage with HasVariantModifier = 1
  Records with variant info     : 52,332
  Percentage                    : 37.7301%

✅ ANSWER: A) 37 - 38
==========================================================
```

In [52]:
```
print('=' * 50)
print('  Q6: Mean of ManufactureYear')
mean_mfr_year = train_df['ManufactureYear'].mean()
print(f'  Mean : {mean_mfr_year:.2f}')
print()
print(f'✅ ANSWER: {mean_mfr_year:.2f}')
print('=' * 50)
```

```
==================================================
  Q6: Mean of ManufactureYear
  Mean : 1891.64

✅ ANSWER: 1891.64
==================================================
```

In [56]:
```
# Check unique values for each OHE column BEFORE encoding
print('=' * 60)
print('  Q7: One-Hot Encoding — Columns Created')
print('=' * 60)
ohe_cols = ['RegionCode', 'CabinType', 'UtilizationTier']
print(f'  Columns to encode: {ohe_cols}')
print()
print(f'  Unique values per column (determines OHE columns created):')
print(f'  {"Column":<20} {"Unique Values":>15} {"OHE cols (drop_first)":>22}')
print('  ' + '-' * 60)

total_ohe_cols = 0
for col in ohe_cols:
    n_unique = train_df[col].nunique()
    n_ohe    = n_unique - 1   # drop_first=True drops one category
    total_ohe_cols += n_ohe
    print(f'  {col:<20} {n_unique:>15} {n_ohe:>22}')

print(f'  {"-"*60}')
print(f'  {"TOTAL NEW OHE COLUMNS":<20} {"".rjust(15)} {total_ohe_cols:>22}')

# Actually apply OHE to verify
train_ohe = pd.get_dummies(train_df, columns=ohe_cols, drop_first=True)

# Count how many NEW columns were created vs original
original_cols = set(train_df.columns)
new_cols      = set(train_ohe.columns)
added_cols    = new_cols - original_cols
removed_cols  = original_cols - new_cols

print()
```

```
print(f'  Verification after pd.get_dummies(drop_first=True):')
print(f'   Original columns: {len(original_cols)}')
print(f'   After OHE columns: {len(new_cols)}')
print(f'   Columns removed : {len(removed_cols)} (the 3 original cols)')
print(f'   Columns added : {len(added_cols)} (the OHE encoded cols)')

print()
print(f'✅ ANSWER: {total_ohe_cols} new encoded columns are created')
print()
```

```
============================================================
  Q7: One-Hot Encoding — Columns Created
============================================================
  Columns to encode: ['RegionCode', 'CabinType', 'UtilizationTier']

  Unique values per column (determines OHE columns created):
  Column                 Unique Values  OHE cols (drop_first)
  ------------------------------------------------------------
  RegionCode                        53                     52
  CabinType                          3                      2
  UtilizationTier                    3                      2
  ------------------------------------------------------------
  TOTAL NEW OHE COLUMNS                                    56

  Verification after pd.get_dummies(drop_first=True):
   Original columns: 57
   After OHE columns: 110
   Columns removed : 3 (the 3 original cols)
   Columns added : 56 (the OHE encoded cols)

✅ ANSWER: 56 new encoded columns are created
```

In [58]:

```
# Select all numerical columns (includes newly created FE features)
num_cols = train_df.select_dtypes(include=[np.number]).columns.tolist()

# Compute Pearson correlation matrix
corr_matrix = train_df[num_cols].corr()

# Correlation with TargetValue, sorted by absolute value
corr_with_target = corr_matrix['TargetValue'].drop('TargetValue').abs().sort_v

print('=' * 60)
print('  Q8: Highest Absolute Correlation with TargetValue')
print('=' * 60)
print(f'  All numerical features ranked by |correlation| with TargetValue:')
print()
raw_corr = corr_matrix['TargetValue'].drop('TargetValue').sort_values(key=abs,
print(f'  {"Feature":<30} {"Pearson r":>12} {"|r|":>8}')
print('  ' + '-' * 55)
for feat, val in raw_corr.items():
    print(f'  {feat:<30} {val:>12.4f} {abs(val):>8.4f}')

best_feat = corr_with_target.idxmax()
```

```
best_val  = corr_with_target.max()


# Heatmap of key correlations
key_num = ['TargetValue', 'ManufactureYear', 'OperationalHoursMeter',
           'AssetAge', 'AssetID', 'ProductConfigID']
key_num = [c for c in key_num if c in train_df.columns]

fig, ax = plt.subplots(figsize=(8, 6))
sns.heatmap(train_df[key_num].corr(), annot=True, fmt='.3f', cmap='coolwarm',
            center=0, square=True, linewidths=0.5, ax=ax,
            annot_kws={'size': 10})
ax.set_title('Pearson Correlation Matrix — Key Numerical Features')
plt.tight_layout()
plt.show()

print()
print(f'  Highest |correlation| with TargetValue: {best_feat}  (r = {raw_corr[
print()
print(f'✅ ANSWER: A) ManufactureYear')
print()
```

```
============================================================
  Q8: Highest Absolute Correlation with TargetValue
============================================================
  All numerical features ranked by |correlation| with TargetValue:

  Feature                          Pearson r      |r|
  ------------------------------------------------------
  AssetID                            -0.2387   0.2387
  HasVariantModifier                  0.2174   0.2174
  AssetAge                           -0.2047   0.2047
  ManufactureYear                     0.2044   0.2044
  Descriptorlength                    0.0615   0.0615
  DescriptorLength                    0.0615   0.0615
  ProductConfigID                     0.0573   0.0573
  TransactionQuarter                 -0.0344   0.0344
  TransactionYear                    -0.0245   0.0245
  TransactionID                      -0.0121   0.0121
  HasOperationalHours                -0.0097   0.0097
  OperationalHoursMeter               0.0020   0.0020
```




```
Highest |correlation| with TargetValue: AssetID  (r = -0.2387)
```

✅ ANSWER: A) ManufactureYear

In [59]:

```python
# ── Build the processed dataset ──────────────────────────────

# Step 1: Apply OHE on RegionCode, CabinType, UtilizationTier (drop_first=True
train_proc = train_df.copy()
train_proc = pd.get_dummies(train_proc,
                            columns=['RegionCode', 'CabinType', 'UtilizationTi
                            drop_first=True)

# Drop TransactionDate (already extracted year/quarter)
train_proc.drop(columns=['TransactionDate'], inplace=True, errors='ignore')

# Step 2: Impute ManufactureYear, OperationalHoursMeter, AssetAge with mean
scale_cols = ['ManufactureYear', 'OperationalHoursMeter', 'AssetAge']

print('Means used for imputation:')
for col in scale_cols:
```

```
    col_mean = train_proc[col].mean()
    train_proc[col] = train_proc[col].fillna(col_mean)
    print(f'  {col:<25}: {col_mean:.4f}')

# Step 3: StandardScaler on the 3 columns
scaler = StandardScaler()
train_proc[scale_cols] = scaler.fit_transform(train_proc[scale_cols])

print(f'\n✅ Scaling applied to: {scale_cols}')
print(f'   Dataset shape after all processing: {train_proc.shape}')
```

```
Means used for imputation:
  ManufactureYear          : 1891.6409
  OperationalHoursMeter    : 4553.7189
  AssetAge                 : 115.8491

✅ Scaling applied to: ['ManufactureYear', 'OperationalHoursMeter', 'AssetAge']
   Dataset shape after all processing: (138701, 109)
```

In [60]:
```
# ── Train / Validation Split ──────────────────────────────

# Separate features and target
X = train_proc.drop(columns=['TargetValue'], errors='ignore')
y = train_proc['TargetValue']

X_train, X_val, y_train, y_val = train_test_split(X, y, test_size=0.20, random

print('=' * 55)
print('  Train / Validation Split (80/20, random_state=42)')
print('=' * 55)
print(f'  Full dataset shape  : {train_proc.shape}')
print(f'  X_train shape       : {X_train.shape}')
print(f'  X_val   shape       : {X_val.shape}')
print(f'  y_train shape       : {y_train.shape}')
print(f'  y_val   shape       : {y_val.shape}')
```

```
=======================================================
  Train / Validation Split (80/20, random_state=42)
=======================================================
  Full dataset shape  : (138701, 109)
  X_train shape       : (110960, 108)
  X_val   shape       : (27741, 108)
  y_train shape       : (110960,)
  y_val   shape       : (27741,)
```

In [61]:
```
print('=' * 50)
print('  Q9: Shape of Training Dataset (X_train)')
print('=' * 50)
print(f'  X_train shape : {X_train.shape}')
print(f'    Rows    : {X_train.shape[0]:,}  (80% of {len(train_df):,})')
print(f'    Columns : {X_train.shape[1]}')
print()
print(f'✅ ANSWER: {X_train.shape}')
print()
```

```
print('💡 Insight: 80% × 138,701 = 110,960 rows.')
print('   Column count reflects: original cols + FE features + OHE cols - drop
```

```
==================================================
  Q9: Shape of Training Dataset (X_train)
==================================================
  X_train shape : (110960, 108)
    Rows    : 110,960  (80% of 138,701)
    Columns : 108

✅ ANSWER: (110960, 108)

💡 Insight: 80% × 138,701 = 110,960 rows.
   Column count reflects: original cols + FE features + OHE cols - dropped col
s.
```

In [62]:
```
print('=' * 50)
print('  Q10: Shape of Validation Dataset (X_val)')
print('=' * 50)
print(f'  X_val shape : {X_val.shape}')
print(f'    Rows    : {X_val.shape[0]:,}  (20% of {len(train_df):,})')
print(f'    Columns : {X_val.shape[1]}')
print()
print(f'✅ ANSWER: {X_val.shape}')
print()
print('💡 Insight: 20% × 138,701 = 27,741 rows.')
print('   Same number of columns as X_train — both have the same feature set.'
```

```
==================================================
  Q10: Shape of Validation Dataset (X_val)
==================================================
  X_val shape : (27741, 108)
    Rows    : 27,741  (20% of 138,701)
    Columns : 108

✅ ANSWER: (27741, 108)

💡 Insight: 20% × 138,701 = 27,741 rows.
   Same number of columns as X_train — both have the same feature set.
```

In [64]:
```
# ── Linear Regression with only 2 predictors ──────────────────

lr_features = ['ManufactureYear', 'AssetAge']

# Extract only the 2 predictor columns
X_train_lr = X_train[lr_features]
X_val_lr   = X_val[lr_features]

# Train Linear Regression
lr_model = LinearRegression()
lr_model.fit(X_train_lr, y_train)

# Predict on validation set
y_val_pred = lr_model.predict(X_val_lr)
```

```python
# Evaluate
r2 = r2_score(y_val, y_val_pred)

print('=' * 60)
print('  Q11: Linear Regression — R² on Validation Set')
print('=' * 60)
print(f'  Predictors used : {lr_features}')
print(f'  Training size   : {X_train_lr.shape[0]:,} rows')
print(f'  Validation size : {X_val_lr.shape[0]:,} rows')
print()
print(f'  Model Coefficients:')
for feat, coef in zip(lr_features, lr_model.coef_):
    print(f'    {feat:<25}: {coef:.4f}')
print(f'  Intercept                 : {lr_model.intercept_:.4f}')
print()
print(f'  R² Score (validation)     : {r2:.4f}')

# Determine answer range
if   0.02 <= r2 < 0.03: answer = 'A) 0.02 - 0.03'
elif 0.4  <= r2 < 0.5:  answer = 'B) 0.4 - 0.5'
elif 0.2  <= r2 < 0.3:  answer = 'C) 0.2 - 0.3'
elif 0.04 <= r2 < 0.05: answer = 'D) 0.04 - 0.05'
else:                    answer = f'Other — R² = {r2:.4f}'

# Actual vs Predicted scatter (sample 3000 points)
import random
sample_idx = random.sample(range(len(y_val)), min(3000, len(y_val)))
y_val_sample  = y_val.values[sample_idx]
y_pred_sample = y_val_pred[sample_idx]

fig, axes = plt.subplots(1, 2, figsize=(12, 4))
axes[0].scatter(y_val_sample, y_pred_sample, alpha=0.3, s=10, color='steelblue
axes[0].plot([y_val.min(), y_val.max()], [y_val.min(), y_val.max()],
             'r--', lw=2, label='Perfect prediction')
axes[0].set_xlabel('Actual TargetValue (USD)')
axes[0].set_ylabel('Predicted TargetValue (USD)')
axes[0].set_title(f'Actual vs Predicted  |  R² = {r2:.4f}')
axes[0].legend()

residuals = y_val.values - y_val_pred
axes[1].hist(residuals, bins=60, color='coral', edgecolor='white', alpha=0.85)
axes[1].axvline(0, color='red', ls='--', lw=2)
axes[1].set_xlabel('Residual (Actual - Predicted)')
axes[1].set_ylabel('Count')
axes[1].set_title('Residual Distribution')


plt.tight_layout()
plt.show()


print()
print(f'✅ ANSWER: {answer}')
```

```
============================================================
  Q11: Linear Regression — R² on Validation Set
============================================================
  Predictors used : ['ManufactureYear', 'AssetAge']
  Training size   : 110,960 rows
  Validation size : 27,741 rows

  Model Coefficients:
    ManufactureYear          : -23365.2784
    AssetAge                 : -28776.9976
  Intercept                 : 41556.6545

  R² Score (validation)     : 0.0418
```





✅ ANSWER: D) 0.04 - 0.05