Heavy Equipment Price Prediction - v15 (Expanded TE + Dual LGB)

IITM BS degree - Machine Learning Practice (MLP) Course Project

Notebook: 22f2001153_Improved_v15.ipynb

REGULATIONS COMPLIANCE:

- Allowed Libraries: Uses ONLY Scikit-learn, LightGBM, CatBoost, Pandas, NumPy, Matplotlib.
- Forbidden Libraries: Does NOT use PyTorch, TensorFlow, NLTK, word2vec, textblob, Pickle, or AutoML.

---

v15 Improvements Over v14 (Score: 0.18964):

1. **Expanded Target Encoding** (4 cols -> 7 cols):
    - Added: `Spec_SubClass` (eta2=0.24 - strongest unused signal!)
    - Added: `Spec_VariantModifier` (eta2=0.22 - strong signal)
    - Added: `RegionCode` (53 regions, each pricing signal)
2. **Interaction Target Encoding**: `InventoryGroupDescription x RegionCode`
    - Captures regional pricing premiums per machine type.
3. **Tuned LightGBM**: lr=0.010, num_leaves=511 (was lr=0.015, num_leaves=255)
    - Deeper trees, more iterations = higher accuracy.
4. **Replaced XGBoost with LGB2** (LightGBM, seed=123):
    - XGBoost got 0% blend weight in v14 (no contribution).
    - LGB2 provides diversity via different random subsampling.
5. **Broader Group Statistics**:
    - Added VendorPartnerID group stats for Hours and Age.

- Added RegionCode group mean Hours and Age.

All features remain leak-free (computed inside CV fold loop).

In [6]:
```
# This Python 3 environment comes with many helpful analytics libraries instal
# It is defined by the kaggle/python Docker image: https://github.com/kaggle/d
# For example, here's several helpful packages to load

import numpy as np # linear algebra
import pandas as pd # data processing, CSV file I/O (e.g. pd.read_csv)

# Input data files are available in the read-only "../input/" directory
# For example, running this (by clicking run or pressing Shift+Enter) will lis

import os
for dirname, _, filenames in os.walk('/kaggle/input'):
    for filename in filenames:
        print(os.path.join(dirname, filename))

# You can write up to 20GB to the current directory (/kaggle/working/) that ge
# You can also write temporary files to /kaggle/temp/, but they won't be saved

# Use the kagglehub client library to attach Kaggle resources like competition
# Learn more about kagglehub: https://github.com/Kaggle/kagglehub/blob/main/RE

import kagglehub
# kagglehub.dataset_download('<owner>/<dataset-slug>')
```

```
/kaggle/input/competitions/heavy-equipment-selling-price-prediction-challenge/s
ample_submission.csv
/kaggle/input/competitions/heavy-equipment-selling-price-prediction-challenge/t
rain.csv
/kaggle/input/competitions/heavy-equipment-selling-price-prediction-challenge/m
etadata.csv
/kaggle/input/competitions/heavy-equipment-selling-price-prediction-challenge/t
est.csv
```

📂 Improvement No 5

In [66]:
```
import subprocess, sys
try:
    import catboost
except ImportError:
    subprocess.run([sys.executable, "-m", "pip", "install", "catboost", "-q"],

import numpy as np
import pandas as pd
import warnings
```

```
import os
import matplotlib.pyplot as plt
import matplotlib.ticker as mticker

warnings.filterwarnings('ignore')
pd.set_option('display.max_columns', 60)
pd.set_option('display.float_format', '{:.2f}'.format)

from sklearn.model_selection import KFold
from sklearn.metrics import mean_squared_error, r2_score
import lightgbm as lgb
from catboost import CatBoostRegressor

SEED = 42
np.random.seed(SEED)
print("ALL LIBRARIES LOADED OK.")
print("NOTE: XGBoost removed in v15 (was getting 0 percent blend weight).")
```

```
ALL LIBRARIES LOADED OK.
NOTE: XGBoost removed in v15 (was getting 0 percent blend weight).
```

In [67]:
```
def rmsle(y_true, y_pred):
    y_pred = np.maximum(y_pred, 0)
    return np.sqrt(mean_squared_error(np.log1p(y_true), np.log1p(y_pred)))

def make_submission(preds, ids, filename='submission.csv'):
    preds = np.maximum(preds, 0)
    sub = pd.DataFrame({'TransactionID': ids, 'TargetValue': preds})
    sub.to_csv(filename, index=False)
    print(f'Saved {filename}: {len(sub):,} rows | '
          f'min=${sub["TargetValue"].min():,.0f} '
          f'median=${sub["TargetValue"].median():,.0f} '
          f'max=${sub["TargetValue"].max():,.0f}')
    return sub

print("Helper functions ready.")
```

```
Helper functions ready.
```

In [68]:
```
train_df = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-pri
test_df  = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-pri
sample   = pd.read_csv('/kaggle/input/competitions/heavy-equipment-selling-pri

print("=" * 55)
print(f"TRAIN : {train_df.shape[0]:>8,} rows x {train_df.shape[1]} cols")
print(f"TEST  : {test_df.shape[0]:>8,} rows x {test_df.shape[1]} cols")
print("=" * 55)
t = train_df['TargetValue']
print(f"Price range: ${t.min():,.0f} - ${t.max():,.0f}")
```

```
=======================================================
TRAIN :  138,701 rows x 50 cols
TEST  :   15,000 rows x 49 cols
=======================================================
Price range: $7,500 - $142,000
```

In [69]:
```
print("Building leak-free asset history features...")
full_df = pd.concat([train_df, test_df], axis=0, ignore_index=True)
# Sort by TransactionID to establish temporal order within each Asset
full_df = full_df.sort_values('TransactionID').reset_index(drop=True)

full_df['log_target'] = np.log1p(full_df['TargetValue'])
grouped = full_df.groupby('AssetID')

# Cumulative count of previous sales
full_df['Asset_Prev_Sales_Count'] = grouped.cumcount().astype(np.int32)

# Cumulative sum / count of target values BEFORE current row (shift ensures no
full_df['cum_sum_log_target']      = grouped['log_target'].cumsum()
full_df['cum_sum_log_target_prev'] = full_df['cum_sum_log_target'] - full_df['

full_df['has_target']           = full_df['TargetValue'].notna().astype(np.int
full_df['cum_count_target']     = grouped['has_target'].cumsum()
full_df['cum_count_target_prev']= full_df['cum_count_target'] - full_df['has_t

# Prev Mean Price (log scale) and Last Price
full_df['Asset_Prev_Mean_Price'] = (
    full_df['cum_sum_log_target_prev'] /
    full_df['cum_count_target_prev'].replace(0, np.nan)
).astype(np.float32)
full_df['Asset_Prev_Last_Price'] = grouped['log_target'].shift(1).astype(np.fl

# Days since last sale for the same asset
full_df['TransactionDate_dt'] = pd.to_datetime(full_df['TransactionDate'], err
full_df['Asset_Days_Since_Last_Sale'] = grouped['TransactionDate_dt'].diff().d

# Drop helper columns
full_df = full_df.drop(columns=[
    'log_target', 'cum_sum_log_target', 'cum_sum_log_target_prev',
    'has_target', 'cum_count_target', 'cum_count_target_prev', 'TransactionDat
])

# Split back and restore original ordering
train_features = full_df[full_df['TargetValue'].notna()].copy()
test_features  = full_df[full_df['TargetValue'].isna()].copy()

train_features = train_features.set_index('TransactionID').loc[train_df['Trans
test_features  = test_features.set_index('TransactionID').loc[test_df['Transac

print(f"Asset history features added. Train: {train_features.shape} | Test: {t
```

```
Building leak-free asset history features...
Asset history features added. Train: (138701, 54) | Test: (15000, 54)
```

In [70]:
```
def preprocess_df(df):
    """
    BASE preprocessing only - no group-mean or frequency features.
    Those are computed fold-by-fold inside the CV loop to prevent leakage.
    """
    df = df.copy()
```

```
# ProductConfigID as string (will become category later)
df['ProductConfigID'] = df['ProductConfigID'].astype(str)

# Date features
df['TransactionDate'] = pd.to_datetime(df['TransactionDate'], errors='coer
df['SaleYear']       = df['TransactionDate'].dt.year
df['SaleMonth']      = df['TransactionDate'].dt.month
df['SaleDay']        = df['TransactionDate'].dt.day
df['SaleDayOfWeek']  = df['TransactionDate'].dt.dayofweek
df['SaleDayOfYear']  = df['TransactionDate'].dt.dayofyear
df['SaleQuarter']    = df['TransactionDate'].dt.quarter
df['SaleWeek']       = df['TransactionDate'].dt.isocalendar().week.astype(

# Time-based flags
df['IsMonthEnd']    = df['TransactionDate'].dt.is_month_end.astype(np.int8
df['IsMonthStart']  = df['TransactionDate'].dt.is_month_start.astype(np.in
df['IsQuarterEnd']  = df['TransactionDate'].dt.is_quarter_end.astype(np.in
df['IsQuarterStart']= df['TransactionDate'].dt.is_quarter_start.astype(np.
df['IsYearEnd']     = df['TransactionDate'].dt.is_year_end.astype(np.int8)
df['IsYearStart']   = df['TransactionDate'].dt.is_year_start.astype(np.int
df = df.drop(columns=['TransactionDate'])

# ManufactureYear cleaning
df.loc[df['ManufactureYear'] <= 1920, 'ManufactureYear'] = np.nan

# OperationalHoursMeter: 0 is placeholder for missing
df.loc[df['OperationalHoursMeter'] == 0, 'OperationalHoursMeter'] = np.nan

# Machine Age
df['MachineAge'] = (df['SaleYear'] - df['ManufactureYear']).clip(lower=0)

# Ordinal encodings (known natural order)
tier_map  = {'Low': 0, 'Medium': 1, 'High': 2}
scale_map = {'Mini': 0, 'Compact': 1, 'Small': 2, 'Medium': 3, 'Large / Me
df['UtilizationTierOrd'] = df['UtilizationTier'].map(tier_map)
df['AssetScaleOrd']      = df['AssetScaleFactor'].map(scale_map)

# Hours engineering
hours_99 = df['OperationalHoursMeter'].quantile(0.99)
df['OperationalHoursMeter'] = df['OperationalHoursMeter'].clip(upper=hours
df['HoursPresent'] = df['OperationalHoursMeter'].notna().astype(np.int8)
df['LogHours']     = np.log1p(df['OperationalHoursMeter'].fillna(0))
df['UsagePerYear'] = df['OperationalHoursMeter'] / (df['MachineAge'] + 1)

# Age buckets
df['IsNewMachine'] = (df['MachineAge'] <= 2).astype(np.int8)
df['IsOldMachine'] = (df['MachineAge'] >= 20).astype(np.int8)
df['AgeDecade']    = (df['MachineAge'] // 10).fillna(-1).astype(int)

# Clean text and convert to category
text_cols = df.select_dtypes(include='object').columns.tolist()
df[text_cols] = df[text_cols].replace('None or Unspecified', np.nan)
```

```
    for col in text_cols:
        df[col] = df[col].fillna('Missing').astype('category')

    # Drop noisy/useless columns
    for c in ['col18', 'col19', 'UtilizationTier', 'AssetScaleFactor']:
        if c in df.columns:
            df = df.drop(columns=[c])

    return df

print("Preprocessing features (no leaky group features)...")
train_proc = preprocess_df(train_features)
test_proc  = preprocess_df(test_features)
print(f"Train preprocessed: {train_proc.shape} | Test preprocessed: {test_proc
```

```
Preprocessing features (no leaky group features)...
Train preprocessed: (138701, 71) | Test preprocessed: (15000, 71)
```

In [71]:
```
ID_COLS = ['TransactionID', 'AssetID']

y_all        = np.log1p(train_proc['TargetValue'].values)
X_all        = train_proc.drop(columns=ID_COLS + ['TargetValue'], errors='ignc
X_test_final = test_proc.drop(columns=ID_COLS + ['TargetValue'], errors='ignor
test_ids     = test_df['TransactionID'].values

cat_cols = X_all.select_dtypes(include=['category', 'object']).columns.tolist(

print(f"Feature matrix : {X_all.shape}")
print(f"Test matrix    : {X_test_final.shape}")
print(f"Cat features   : {len(cat_cols)}")
print(f"Num features   : {X_all.shape[1] - len(cat_cols)}")
```

```
Feature matrix : (138701, 68)
Test matrix    : (15000, 68)
Cat features   : 40
Num features   : 28
```

In [72]:
```
# ── OOF Target Encoding ──────────────────────────────────────────────
def add_oof_target_encoding(X_tr, y_tr, X_vl, X_te, cols, n_splits=5, alpha=15
    """
    Proper leak-free Out-Of-Fold target encoding.
    Training rows: encoded from the OTHER inner folds (never their own target)
    Validation / Test rows: encoded from the full training fold.
    """
    X_tr, X_vl, X_te = X_tr.copy(), X_vl.copy(), X_te.copy()
    global_mean = float(y_tr.mean())
    kf_inner = KFold(n_splits=n_splits, shuffle=True, random_state=seed)

    for col in cols:
        col_te = col + '_TE'
        X_tr[col_te] = global_mean
        X_vl[col_te] = global_mean
        X_te[col_te] = global_mean
```

```
        tr_val = X_tr[col].astype(str)
        vl_val = X_vl[col].astype(str)
        te_val = X_te[col].astype(str)

        # Map validation & test from full training fold stats
        stats = pd.DataFrame({'cat': tr_val, 'y': y_tr})
        agg   = stats.groupby('cat')['y'].agg(['mean', 'count'])
        agg['sm'] = (agg['count'] * agg['mean'] + alpha * global_mean) / (agg[
        m = agg['sm'].to_dict()
        X_vl[col_te] = vl_val.map(m).fillna(global_mean).values
        X_te[col_te] = te_val.map(m).fillna(global_mean).values

        # Map training rows from inner-fold stats (no leakage)
        col_idx = X_tr.columns.get_loc(col_te)
        for tr_in_idx, vl_in_idx in kf_inner.split(X_tr):
            in_stats = pd.DataFrame({'cat': tr_val.iloc[tr_in_idx], 'y': y_tr[
            in_agg   = in_stats.groupby('cat')['y'].agg(['mean', 'count'])
            in_agg['sm'] = (in_agg['count'] * in_agg['mean'] + alpha * global_
            m_in = in_agg['sm'].to_dict()
            X_tr.iloc[vl_in_idx, col_idx] = tr_val.iloc[vl_in_idx].map(m_in).f

    return X_tr, X_vl, X_te


# ── Interaction Target Encoding ──────────────────────────────────────
def add_interaction_target_encoding(X_tr, y_tr, X_vl, X_te,
                                    col_a, col_b, alpha=20.0, seed=42):
    """
    Creates an interaction feature (col_a + '__' + col_b) and
    applies OOF target encoding on it.
    Higher alpha (20 vs 15) since interaction cells have fewer observations.
    """
    X_tr, X_vl, X_te = X_tr.copy(), X_vl.copy(), X_te.copy()
    global_mean = float(y_tr.mean())
    kf_inner    = KFold(n_splits=5, shuffle=True, random_state=seed)
    feat_name   = col_a + '__x__' + col_b + '_TE'

    # Build interaction key (string concat) - safe for categorical dtype
    tr_int = X_tr[col_a].astype(str) + '__' + X_tr[col_b].astype(str)
    vl_int = X_vl[col_a].astype(str) + '__' + X_vl[col_b].astype(str)
    te_int = X_te[col_a].astype(str) + '__' + X_te[col_b].astype(str)

    # Initialise to global mean
    X_tr[feat_name] = global_mean
    X_vl[feat_name] = global_mean
    X_te[feat_name] = global_mean

    # Map val & test from full training fold
    stats = pd.DataFrame({'cat': tr_int, 'y': y_tr})
    agg   = stats.groupby('cat')['y'].agg(['mean', 'count'])
    agg['sm'] = (agg['count'] * agg['mean'] + alpha * global_mean) / (agg['cou
    m = agg['sm'].to_dict()
    X_vl[feat_name] = vl_int.map(m).fillna(global_mean).values
```

```
    X_te[feat_name] = te_int.map(m).fillna(global_mean).values

    # Map train rows from inner-fold stats
    col_idx = X_tr.columns.get_loc(feat_name)
    for tr_in_idx, vl_in_idx in kf_inner.split(X_tr):
        in_stats = pd.DataFrame({'cat': tr_int.iloc[tr_in_idx], 'y': y_tr[tr_i
        in_agg   = in_stats.groupby('cat')['y'].agg(['mean', 'count'])
        in_agg['sm'] = (in_agg['count'] * in_agg['mean'] + alpha * global_mean
        m_in = in_agg['sm'].to_dict()
        X_tr.iloc[vl_in_idx, col_idx] = tr_int.iloc[vl_in_idx].map(m_in).fillna

    return X_tr, X_vl, X_te


# ── Fold-Level Group Statistics ──────────────────────────────────────
def add_fold_group_features(X_tr, X_vl, X_te):
    """
    Compute group-level statistics using ONLY the training fold, then map
    to validation and test. Prevents distribution-mismatch leakage.
    .astype(str) is used before every groupby/map to avoid pandas categorical
    """
    X_tr, X_vl, X_te = X_tr.copy(), X_vl.copy(), X_te.copy()

    # 1. Frequency encoding for high-cardinality columns
    freq_cols = ['ProductConfigID', 'Spec_FullDescriptor', 'Spec_BaseClass', '
    for col in freq_cols:
        freq_map    = X_tr[col].astype(str).value_counts().to_dict()
        global_freq = 1.0  # fallback for unseen categories
        for df_part in [X_tr, X_vl, X_te]:
            df_part[col + '_Freq'] = df_part[col].astype(str).map(freq_map).fi

    # 2. Group means for OperationalHoursMeter and MachineAge per group columns
    group_cols   = ['InventoryGroupCategory', 'Spec_BaseClass', 'ProductConfig
                    'VendorPartnerID', 'RegionCode']
    target_feats = ['OperationalHoursMeter', 'MachineAge']

    for grp_col in group_cols:
        for target_col in target_feats:
            global_mean = float(X_tr[target_col].mean())
            group_means = X_tr.groupby(X_tr[grp_col].astype(str))[target_col].
            feat_name   = f'{grp_col}_{target_col}_mean'
            for df_part in [X_tr, X_vl, X_te]:
                df_part[feat_name] = (
                    df_part[grp_col].astype(str).map(group_means)
                    .fillna(global_mean).astype(np.float32)
                )
            # Relative feature: how does this machine compare to its group ave
            for df_part in [X_tr, X_vl, X_te]:
                df_part[f'{target_col}_rel_{grp_col}'] = (
                    df_part[target_col] / (df_part[feat_name] + 1)
                ).astype(np.float32)

    return X_tr, X_vl, X_te
```

```
# v15 TE columns: 7 columns (was 4 in v14)
TE_COLS = [
    'Spec_FullDescriptor',     # 3505 unique - very high cardinality
    'Spec_BaseClass',          # 1249 unique
    'ProductConfigID',         # 3594 unique - very high cardinality
    'FunctionalClassification',# 65 unique
    'Spec_SubClass',           # 147 unique, eta2=0.24 (STRONGEST new signal!)
    'Spec_VariantModifier',    # 132 unique, eta2=0.22
    'RegionCode',              # 53 unique
]

print("All fold-level feature engineering functions compiled. Ready for CV.")
print(f"Target encoding columns: {len(TE_COLS)} (v14 had 4)")
```

```
All fold-level feature engineering functions compiled. Ready for CV.
Target encoding columns: 7 (v14 had 4)
```

In [73]:

```
N_FOLDS = 5
kf = KFold(n_splits=N_FOLDS, shuffle=True, random_state=SEED)

oof_lgb1 = np.zeros(len(X_all))
oof_lgb2 = np.zeros(len(X_all))
oof_cat  = np.zeros(len(X_all))

test_lgb1_folds = np.zeros((len(X_test_final), N_FOLDS))
test_lgb2_folds = np.zeros((len(X_test_final), N_FOLDS))
test_cat_folds  = np.zeros((len(X_test_final), N_FOLDS))

fold_scores = []

print("Starting 5-Fold CV - v15 (Expanded TE + Dual LGB)")
print("=" * 70)

for fold, (tr_idx, vl_idx) in enumerate(kf.split(X_all), 1):
    X_tr_raw = X_all.iloc[tr_idx].copy()
    X_vl_raw = X_all.iloc[vl_idx].copy()
    y_tr     = y_all[tr_idx]
    y_vl     = y_all[vl_idx]

    # Step 1: OOF Target Encoding (leak-free, 7 columns)
    X_tr, X_vl, X_te = add_oof_target_encoding(
        X_tr_raw, y_tr, X_vl_raw, X_test_final.copy(), TE_COLS, alpha=15.0
    )

    # Step 2: Interaction Target Encoding (InventoryGroupDescription x RegionC
    X_tr, X_vl, X_te = add_interaction_target_encoding(
        X_tr, y_tr, X_vl, X_te,
        col_a='InventoryGroupDescription', col_b='RegionCode', alpha=20.0
    )

    # Step 3: All group/frequency features (computed from training fold only)
    X_tr, X_vl, X_te = add_fold_group_features(X_tr, X_vl, X_te)
```

```
    # For CatBoost: convert category columns to string
    cat_fold = [c for c in cat_cols if c in X_tr.columns]

    def to_str(df, cols):
        df = df.copy()
        for c in cols:
            if c in df.columns:
                df[c] = df[c].astype(str)
        return df

    X_tr_c = to_str(X_tr, cat_fold)
    X_vl_c = to_str(X_vl, cat_fold)
    X_te_c = to_str(X_te, cat_fold)

    # ── LightGBM 1 (primary, seed=42) ──────────────────────────────────
    lgb_params_1 = dict(
        n_estimators      = 15000,
        max_depth         = -1,
        num_leaves        = 511,
        learning_rate     = 0.010,
        subsample         = 0.75,
        colsample_bytree  = 0.70,
        min_child_samples = 30,
        reg_alpha         = 0.1,
        reg_lambda        = 3.0,
        random_state      = 42,
        n_jobs            = -1,
        verbose           = -1
    )
    lgb1_m = lgb.LGBMRegressor(**lgb_params_1)
    lgb1_m.fit(
        X_tr, y_tr,
        eval_set=[(X_vl, y_vl)],
        callbacks=[lgb.early_stopping(300, verbose=False), lgb.log_evaluation(
    )
    oof_lgb1[vl_idx]          = lgb1_m.predict(X_vl)
    test_lgb1_folds[:, fold-1] = lgb1_m.predict(X_te)

    # ── LightGBM 2 (diversity, seed=123) ───────────────────────────────
    lgb_params_2 = dict(
        n_estimators      = 15000,
        max_depth         = -1,
        num_leaves        = 511,
        learning_rate     = 0.010,
        subsample         = 0.80,
        colsample_bytree  = 0.65,
        min_child_samples = 30,
        reg_alpha         = 0.2,
        reg_lambda        = 2.0,
        random_state      = 123,
        n_jobs            = -1,
        verbose           = -1
```

```
    )
    lgb2_m = lgb.LGBMRegressor(**lgb_params_2)
    lgb2_m.fit(
        X_tr, y_tr,
        eval_set=[(X_vl, y_vl)],
        callbacks=[lgb.early_stopping(300, verbose=False), lgb.log_evaluation(
    )
    oof_lgb2[vl_idx]          = lgb2_m.predict(X_vl)
    test_lgb2_folds[:, fold-1] = lgb2_m.predict(X_te)

    # ── CatBoost ──────────────────────────────────────────────────────────
    cat_m = CatBoostRegressor(
        iterations            = 15000,
        learning_rate         = 0.010,
        random_seed           = SEED,
        verbose               = 0,
        thread_count          = -1,
        early_stopping_rounds = 300,
        cat_features          = cat_fold,
        l2_leaf_reg           = 3.0,
        bagging_temperature   = 0.5,
        grow_policy           = 'Lossguide',
        max_leaves            = 255,
        min_data_in_leaf      = 30
    )
    cat_m.fit(X_tr_c, y_tr, eval_set=(X_vl_c, y_vl))
    oof_cat[vl_idx]          = cat_m.predict(X_vl_c)
    test_cat_folds[:, fold-1] = cat_m.predict(X_te_c)

    s_1 = rmsle(np.expm1(y_vl), np.expm1(oof_lgb1[vl_idx]))
    s_2 = rmsle(np.expm1(y_vl), np.expm1(oof_lgb2[vl_idx]))
    s_c = rmsle(np.expm1(y_vl), np.expm1(oof_cat[vl_idx]))
    fold_scores.append((s_1, s_2, s_c))

    print(f"Fold {fold}: LGB1={s_1:.5f}(iter={lgb1_m.best_iteration_:4d}) | "
          f"LGB2={s_2:.5f}(iter={lgb2_m.best_iteration_:4d}) | "
          f"CAT={s_c:.5f}")

oof_1 = rmsle(np.expm1(y_all), np.expm1(oof_lgb1))
oof_2 = rmsle(np.expm1(y_all), np.expm1(oof_lgb2))
oof_c = rmsle(np.expm1(y_all), np.expm1(oof_cat))
print("=" * 70)
print(f"LGB1 OOF RMSLE : {oof_1:.5f}  (v14 LGB was 0.19733, target < 0.19733)"
print(f"LGB2 OOF RMSLE : {oof_2:.5f}")
print(f"CAT  OOF RMSLE : {oof_c:.5f}")
```

```
Starting 5-Fold CV - v15 (Expanded TE + Dual LGB)
======================================================================
Fold 1: LGB1=0.19421(iter=4474) | LGB2=0.19399(iter=4391) | CAT=0.20306
Fold 2: LGB1=0.19660(iter=5257) | LGB2=0.19627(iter=5234) | CAT=0.20537
Fold 3: LGB1=0.19706(iter=4420) | LGB2=0.19687(iter=3925) | CAT=0.20555
Fold 4: LGB1=0.19686(iter=4657) | LGB2=0.19659(iter=4410) | CAT=0.20670
Fold 5: LGB1=0.19570(iter=4123) | LGB2=0.19553(iter=4240) | CAT=0.20335
======================================================================
LGB1 OOF RMSLE : 0.19609  (v14 LGB was 0.19733, target < 0.19733)
LGB2 OOF RMSLE : 0.19585
CAT  OOF RMSLE : 0.20481
```

In [74]:
```
print("Searching optimal blend weights (LGB1, LGB2, CAT)...")
best_blend, best_w = 999.0, (0.50, 0.20, 0.30)

for w1 in np.arange(0.0, 1.01, 0.05):
    for w2 in np.arange(0.0, 1.01 - w1, 0.05):
        w3    = max(round(1.0 - w1 - w2, 6), 0.0)
        score = rmsle(np.expm1(y_all),
                      np.expm1(w1*oof_lgb1 + w2*oof_lgb2 + w3*oof_cat))
        if score < best_blend:
            best_blend, best_w = score, (w1, w2, w3)

print("=" * 70)
print(f"Best blend    : LGB1={best_w[0]:.2f}  LGB2={best_w[1]:.2f}  CAT={best_
print(f"Blended RMSLE : {best_blend:.5f}  (v14 blended was 0.19542)")
target = 0.18964
status = "[ON TRACK] Beat 0.18964!" if best_blend < target else "[KEEP GOING]
print(f"Kaggle v14 score : {target}  ->  {status}")
```

```
Searching optimal blend weights (LGB1, LGB2, CAT)...
======================================================================
Best blend    : LGB1=0.30  LGB2=0.40  CAT=0.30
Blended RMSLE : 0.19415  (v14 blended was 0.19542)
Kaggle v14 score : 0.18964  ->  [KEEP GOING] Still above 0.18964...
```

In [75]:
```
w1, w2, w3 = best_w

test_blend   = w1*test_lgb1_folds.mean(1) + w2*test_lgb2_folds.mean(1) + w3*te
final_prices = np.expm1(test_blend)

# Clip to training price range (0.1th-99.9th percentile)
plo = train_df['TargetValue'].quantile(0.001)
phi = train_df['TargetValue'].quantile(0.999)
final_prices = np.clip(final_prices, plo, phi)
print(f"Price clipped to [${plo:,.0f}, ${phi:,.0f}]")

sub = make_submission(final_prices, test_ids, 'submission.csv')
print()
print(sub.head())
```

```
Price clipped to [$7,500, $137,500]
Saved submission.csv: 15,000 rows | min=$7,532 median=$34,638 max=$137,500
```

	TransactionID	TargetValue
0	1139307	69355.55
1	1139419	80544.98
2	1139482	32087.68
3	1139522	20193.94
4	1139684	12721.44

In [76]:

```
oof_blend  = best_w[0]*oof_lgb1 + best_w[1]*oof_lgb2 + best_w[2]*oof_cat
pred_price = np.expm1(oof_blend)
true_price = np.expm1(y_all)
residuals  = true_price - pred_price
pct_err    = (residuals / true_price) * 100

fig, axes = plt.subplots(1, 3, figsize=(18, 5))
fig.suptitle(f'v15 OOF Diagnostics | Blended RMSLE={best_blend:.5f}',
             fontsize=12, fontweight='bold')

idx = np.random.choice(len(true_price), min(5000, len(true_price)), replace=Fa
axes[0].scatter(true_price[idx], pred_price[idx], alpha=0.07, s=4, color='stee
mn, mx = true_price.min(), true_price.max()
axes[0].plot([mn, mx], [mn, mx], 'r--', lw=2, label='Perfect')
axes[0].set_xlabel('Actual Price');  axes[0].set_ylabel('Predicted')
axes[0].set_title('Actual vs Predicted'); axes[0].legend(fontsize=9)
fmt = lambda x, _: f'${x/1000:.0f}K'
axes[0].xaxis.set_major_formatter(mticker.FuncFormatter(fmt))
axes[0].yaxis.set_major_formatter(mticker.FuncFormatter(fmt))


axes[1].hist(residuals.clip(-15000, 15000), bins=80, color='coral', edgecolor=
axes[1].axvline(0, color='black', lw=2, ls='--')
axes[1].axvline(residuals.mean(), color='red', lw=2, label=f'Mean={residuals.m
axes[1].set_xlabel('Residual'); axes[1].set_title('Residuals'); axes[1].legend

axes[2].hist(pct_err.clip(-40, 40), bins=80, color='mediumpurple', edgecolor='
axes[2].axvline(0, color='black', lw=2, ls='--')
axes[2].set_xlabel('% Error (+-40% clip)'); axes[2].set_title('% Error Distrib

plt.tight_layout(); plt.show()

print(f"Blended OOF RMSLE : {best_blend:.5f}")
print(f"R2                : {r2_score(true_price, pred_price):.4f}")
print(f"MAE               : ${np.mean(np.abs(residuals)):,.0f}")
print(f"Median % error    : {np.median(np.abs(pct_err)):.1f}%")

# Feature importances from last LGB1 fold
fi = pd.Series(lgb1_m.feature_importances_, index=X_tr.columns).sort_values(as
print("\nTop 30 features (LGB1 last fold):")
print(fi.head(30).to_string())
```




```
Blended OOF RMSLE : 0.19415
R2                : 0.9153
MAE               : $5,088
Median % error    : 9.9%

Top 30 features (LGB1 last fold):
SaleDayOfYear                                129616
MachineAge_rel_ProductConfigID               104706
RegionCode                                   102389
SaleDay                                      100747
ProductConfigID                               83304
MachineAge_rel_Spec_BaseClass                 82669
MachineAge_rel_RegionCode                     78848
InventoryGroupDescription__x__RegionCode_TE   71422
RegionCode_TE                                 69934
SaleYear                                      68504
MachineAge_rel_VendorPartnerID                65347
ManufactureYear                               54214
Spec_BaseClass                                51116
FunctionalClassification_TE                   46904
MachineAge_rel_InventoryGroupCategory         44771
Spec_FullDescriptor_TE                        44393
Spec_SubClass_TE                              43212
Spec_FullDescriptor                           41862
Spec_BaseClass_TE                             41182
Spec_VariantModifier_TE                       41084
SaleWeek                                      35314
FunctionalClassification                      34590
SaleDayOfWeek                                 34553
OperationalHoursMeter_rel_ProductConfigID     33475
ProductConfigID_Freq                          33355
OperationalHoursMeter_rel_Spec_BaseClass      28995
UsagePerYear                                  27885
RegionCode_OperationalHoursMeter_mean         26359
RegionCode_MachineAge_mean                    25780
VendorPartnerID                               24032
```