

Conversation 56

Commits 1

Checks 0

Files changed 23



VinayTanniru

 commented

2 weeks ago

Owner

- Developed a console to handle the students/courses/enrollments
- wrote all the crud operations using the Array-list
- the data will be stored in-memory



🔗

 Implemeted management console as per the requirement

0822783

👁

airtribe-bot

 reviewed

2 weeks ago

View reviewed changes

src/com/airtribe/learntrack/entity/Course.java

```
4 | + * Course entity class representing a course in the system.
5 | + */
6 | + public class Course {
7 | +     private int id;
```



airtribe-bot

2 weeks ago

Consider changing the data type of `id` from `int` to `long` to better accommodate a larger range of values and prevent potential overflow issues in the future.





VinayTanniru

20 hours ago

Owner

Author

changed the data type from `int` to `long`.





Reply...

Resolve conversation

src/com/airtribe/learntrack/entity/Course.java

```
46 +  
47 +     public String getCourseName() {  
48 +         return courseName;  
49 +     }
```



airtribe-bot [2 weeks ago](#)

To enhance the robustness of the setter method, consider adding validation logic to check for null or empty values when setting `courseName` .



VinayTanniru [20 hours ago](#)

Owner

Author

added a helper method and used for checking strings for the null and empty values.



Reply...

Resolve conversation

src/com/airtribe/learntrack/entity/Course.java

```
57 +     }  
58 +  
59 +     public void setDescription(String description) {  
60 +         this.description = description;
```



airtribe-bot [2 weeks ago](#)

To enhance the robustness of the setter method, consider adding validation logic to check for null or empty values when setting `description` .



VinayTanniru [20 hours ago](#)

Owner

Author

added a helper method and used for checking strings for the null and empty values.



Reply...

Resolve conversation

src/com/airtribe/learntrack/entity/Course.java

```
65 +     }  
66 +  
67 +     public void setDurationInWeeks(int durationInWeeks) {  
68 +         this.durationInWeeks = durationInWeeks;
```



airtribe-bot [2 weeks ago](#)

It's a good practice to enforce a positive value for `durationInWeeks` in the `setDurationInWeeks` method to avoid invalid data.



VinayTanniru [20 hours ago](#)

Owner

Author

added a check if the value is greater than zero.



Reply...

Resolve conversation

airtribe-bot reviewed [2 weeks ago](#)

[View reviewed changes](#)

src/com/airtribe/learntrack/entity/Enrollment.java

```
8 | +   private int id;
9 | +   private int studentId;
10| +   private int courseId;
11| +   private String enrollmentDate;
```



airtribe-bot [2 weeks ago](#)

Consider using `java.time.LocalDate` or `java.time.LocalDateTime` for `enrollmentDate` instead of `String` for better date management and validation.



VinayTanniru [20 hours ago](#)

Owner

Author

Changed the data type from `String` to `LocalDate`



Reply...

Resolve conversation

src/com/airtribe/learntrack/entity/Enrollment.java

```
22 | +   * Parameterized constructor with all fields
23 | +   */
24 | +   public Enrollment(int id, int studentId, int courseId, String enrollmentDate, EnrollmentStatus status)
25 | +   {
    | +       this.id = id;
```



airtribe-bot [2 weeks ago](#)

When assigning `enrollmentDate`, consider converting it to a `LocalDate` or `LocalDateTime` object if you switch to those types, for consistency in date handling.



VinayTanniru [20 hours ago](#)

Owner

Author

Changed the data type from `String` to `LocalDate` and rest of connected constructors and methods are update accordingly.



Reply...

Resolve conversation

src/com/airtribe/learntrack/entity/Enrollment.java

```
65 +         return enrollmentDate;
66 +     }
67 +
68 +     public void setEnrollmentDate(String enrollmentDate) {
```



airtribe-bot [2 weeks ago](#)

If you change `enrollmentDate` to `LocalDate` or `LocalDateTime`, remember to modify the parameter and processing here to handle the date object instead of `String`.



VinayTanniru [20 hours ago](#)

Owner

Author

Changed the data type from `String` to `LocalDate` and rest of connected constructors and methods are update accordingly.



Reply...

Resolve conversation

airtribe-bot reviewed [2 weeks ago](#)

[View reviewed changes](#)

src/com/airtribe/learntrack/entity/Person.java

```
33 +         this.id = id;
34 +         this.firstName = firstName;
35 +         this.lastName = lastName;
36 +         this.email = "";
```



airtribe-bot [2 weeks ago](#)

Consider assigning `null` to `email` instead of an empty string. This can make the intention clear when no email is provided, indicating the absence of a value.



VinayTanniru [20 hours ago](#)

Owner

Author

added the null value



Reply...

Resolve conversation

src/com/airtribe/learntrack/entity/Person.java

```
66 +     }
67 +
68 +     /**
69 +      * Returns a display-friendly name.
```

airtribe-bot [2 weeks ago](#)

If the `getDisplayName()` method is meant for subclass customization, consider making the method `protected` or adding an `abstract` class indicating that subclasses should override it. Use of `@Override` annotation can help ensure that the method is overridden correctly in subclasses.



Reply...

Resolve conversation

airtribe-bot reviewed [2 weeks ago](#)

[View reviewed changes](#)

src/com/airtribe/learntrack/entity/Student.java

```
19 +     /**
20 +      * Parameterized constructor with all fields including email
21 +      */
22 +     public Student(int id, String firstName, String lastName, String email, String batch, boolean active)
```

airtribe-bot [2 weeks ago](#)

Consider checking if the parameters have valid values to ensure the stability of the `student` object creation. For example, parameters like `id`, `firstName`, `lastName`, and `email` should be checked if they are non-negative, non-null, or non-empty as applicable.



VinayTanniru [20 hours ago](#)

Owner

Author

Added small helper methods and updated the constructors to have proper validation.



[Resolve conversation](#)

src/com/airtribe/learntrack/entity/Student.java

```
28 + /**
29 +    * Constructor without email (demonstrates constructor overloading)
30 +    */
31 +    public Student(int id, String firstName, String lastName, String batch) {
```



airtribe-bot [2 weeks ago](#)

Ensure that the `id`, `firstName`, `lastName`, and `batch` parameters are validated here for nullability and proper values to maintain consistency across constructors.



VinayTanniru [20 hours ago](#)

Owner

Author

Added small helper methods and updated the constructors to have proper validation.

[Resolve conversation](#)

src/com/airtribe/learntrack/entity/Student.java

```
37 + /**
38 +    * Constructor with basic info only
39 +    */
40 +    public Student(int id, String firstName, String lastName) {
```



airtribe-bot [2 weeks ago](#)

Ensure nullability and validity checks are performed on parameters like `id`, `firstName`, and `lastName` to avoid creating incomplete `Student` objects.



VinayTanniru [20 hours ago](#)

Owner

Author

Added small helper methods and updated the constructors to have proper validation.

[Resolve conversation](#)

src/com/airtribe/learntrack/entity/Student.java

```
48 +    return batch;
```

```
49 | +      }
50 | +
51 | +      public void setBatch(String batch) {
```



airtribe-bot [2 weeks ago](#)

You might want to add validation here to check if the `batch` is not null or empty when setting it.



VinayTanniru [20 hours ago](#)

Owner

Author

Added a small check while setting up the batch



Reply...

Resolve conversation

src/com/airtribe/learntrack/entity/Student.java

```
56 | +      return active;
57 | +      }
58 | +
59 | +      public void setActive(boolean active) {
```



airtribe-bot [2 weeks ago](#)

Adding a validation step to ensure `active` has a sensible value could help maintain the object's integrity.



Reply...

Resolve conversation

src/com/airtribe/learntrack/entity/Student.java

```
73 | +      }
74 | +
75 | +      @Override
76 | +      public String toString() {
```



airtribe-bot [2 weeks ago](#)

In the `toString` method, ensure that `email` can handle cases where it may be null or empty to avoid any null pointer exceptions.



Reply...

Resolve conversation

 **airtribe-bot** reviewed [2 weeks ago](#)

[View reviewed changes](#)

```
src/com/airtribe/learntrack/service/CourseService.java  
  
15 + public class CourseService {  
16 +  
17 +     // In-memory storage using ArrayList  
18 +     private ArrayList<Course> courses;
```

 **airtribe-bot** [2 weeks ago](#)

Consider using a more generic collection type, such as `List<Course>`, for the `courses` field. This will allow you to change the underlying implementation without changing the rest of the code.



 **VinayTanniru** [20 hours ago](#)

[Owner](#) [Author](#)

Updated the return type to List



 [Reply...](#)

[Resolve conversation](#)

```
src/com/airtribe/learntrack/service/CourseService.java  
  
76 +     * @return ArrayList of all courses  
77 +     */  
78 +     public ArrayList<Course> getAllCourses() {  
79 +         return new ArrayList<>(courses);
```

 **airtribe-bot** [2 weeks ago](#)

Use the `List<Course>` interface as the return type rather than `ArrayList<Course>`. This promotes coding to the interface rather than the implementation and makes it easier to change the list implementation in the future.



 **VinayTanniru** [20 hours ago](#)

[Owner](#) [Author](#)

Done updated as told



 [Reply...](#)

[Resolve conversation](#)


```
src/com/airtribe/learntrack/service/CourseService.java
```

```
84 | +      *  
85 | +      * @return ArrayList of active courses  
86 | +      */  
87 | +      public ArrayList<Course> getActiveCourses() {
```



airtribe-bot [2 weeks ago](#)

Change the return type of this method to `List<Course>` instead of `ArrayList<Course>`. This enables more flexibility in the list's implementation.



VinayTanniru [20 hours ago](#)

Owner

Author

Done updated as told



Reply...

Resolve conversation

```
src/com/airtribe/learntrack/service/CourseService.java
```

```
108 | +      throws EntityNotFoundException {  
109 | +      Course course = getCourseById(id);  
110 | +  
111 | +      if (InputValidator.isEmpty(courseName)) {
```



airtribe-bot [2 weeks ago](#)

Consider validating if `courseName` is not null before checking if it's non-empty, to avoid potential `NullPointerExceptions`. Same for `description` on line 114.



VinayTanniru [20 hours ago](#)

Owner

Author

added the null check while setting the course name



Reply...

Resolve conversation

airtribe-bot reviewed [2 weeks ago](#)

[View reviewed changes](#)

```
src/com/airtribe/learntrack/service/EnrollmentService.java
```

```
42 | +      */
```

```
43 + public Enrollment enrollStudent(int studentId, int courseId)
44 +     throws EntityNotFoundException, InvalidInputException {
45 +     // Validate that student exists
```



airtribe-bot [2 weeks ago](#)

The method `enrollStudent` should first check if the student and course IDs provided are valid before attempting to retrieve their respective data. Consider reordering the code to verify the existence of student and course before getting them.



Reply...

Resolve conversation

src/com/airtribe/learntrack/service/EnrollmentService.java

```
86 + * @return ArrayList of all enrollments
87 + */
88 + public ArrayList<Enrollment> getAllEnrollments() {
89 +     return new ArrayList<>(enrollments);
```



airtribe-bot [2 weeks ago](#)

Returning a new `ArrayList` in `getAllEnrollments` creates a separate copy of the enrollments list. While this is good for encapsulation, it could lead to performance issues if the number of enrollments is large. Consider returning a read-only view or using a different collection type to prevent unintended modifications while improving performance.



VinayTanniru [20 hours ago](#)

Owner

Author

updated used collections to return the data



Reply...

Resolve conversation

airtribe-bot reviewed [2 weeks ago](#)

[View reviewed changes](#)

src/com/airtribe/learntrack/service/StudentService.java

```
15 + public class StudentService {
16 +
17 +     // In-memory storage using ArrayList
18 +     private ArrayList<Student> students;
```



airtribe-bot [2 weeks ago](#)

Consider using an interface for the students list, such as `List<Student>` , instead of `ArrayList<Student>` directly to make it easier to change the implementation later if needed.



VinayTanniru [20 hours ago](#)

Owner

Author

done updated the ArrayList with the List at all locations



Reply...

Resolve conversation

src/com/airtribe/learntrack/service/StudentService.java

```
16 +  
17 + // In-memory storage using ArrayList  
18 + private ArrayList<Student> students;  
19 +
```



airtribe-bot [2 weeks ago](#)

Avoid accessing class variables directly when they can be encapsulated - consider using a `getStudents()` method to access the student list. This ensures encapsulation and facilitates future updates to how students are stored.



VinayTanniru [20 hours ago](#)

Owner

Author

done created a method `getStudents` and used at all locations



Reply...

Resolve conversation

src/com/airtribe/learntrack/service/StudentService.java

```
51 + throw InvalidInputException.emptyField("Last Name");  
52 + }  
53 +  
54 + int id = IdGenerator.getNextStudentId();
```



airtribe-bot [2 weeks ago](#)

Use a more robust way to generate unique IDs rather than relying on `IdGenerator.getNextStudentId()` , as this may lead to conflicts in a concurrent environment.



Reply...

Resolve conversation

src/com/airtribe/learntrack/service/StudentService.java

```
79 + * @return ArrayList of all students
80 + */
81 + public ArrayList<Student> getAllStudents() {
82 +     return new ArrayList<>(students);
```



airtribe-bot [2 weeks ago](#)

Return a `List<Student>` instead of an `ArrayList<Student>` to increase flexibility and allow for easier changes to the list implementation in the future.



VinayTanniru [20 hours ago](#)

Owner

Author

done



Reply...

Resolve conversation

src/com/airtribe/learntrack/service/StudentService.java

```
87 + *
88 + * @return ArrayList of active students
89 + */
90 + public ArrayList<Student> getActiveStudents() {
```



airtribe-bot [2 weeks ago](#)

Return a `List<Student>` instead of an `ArrayList<Student>` for flexibility.



VinayTanniru [20 hours ago](#)

Owner

Author

done



Reply...

Resolve conversation

src/com/airtribe/learntrack/service/StudentService.java

```
108 + * @return The updated Student object
109 + * @throws EntityNotFoundException if student is not found
110 + */
111 + public Student updateStudent(int id, String firstName, String lastName, String email, String batch)
```



airtribe-bot [2 weeks ago](#)

Instead of updating fields in place, consider returning a new immutable `student` object after applying changes. This can help in avoiding unintended side-effects.



Reply...

Resolve conversation

src/com/airtribe/learntrack/service/StudentService.java

```
136 +      * @return The deactivated Student object
137 +      * @throws EntityNotFoundException if student is not found
138 +      */
139 +      public Student deactivateStudent(int id) throws EntityNotFoundException {
```



airtribe-bot [2 weeks ago](#)

Instead of directly manipulating the status of the student, consider using a method in the `student` class like `deactivate()` to encapsulate the operation and maintain clean code separation.



VinayTanniru [20 hours ago](#)

Owner

Author

done created the method.



Reply...

Resolve conversation

src/com/airtribe/learntrack/service/StudentService.java

```
149 +      * @return The reactivated Student object
150 +      * @throws EntityNotFoundException if student is not found
151 +      */
152 +      public Student reactivateStudent(int id) throws EntityNotFoundException {
```



airtribe-bot [2 weeks ago](#)

For reactivation, consider calling a method like `reactivate()` on the student object instead of directly setting the attribute. This encapsulates the behavior within the `student` class.



VinayTanniru [20 hours ago](#)

Owner

Author

done created the method.



[Resolve conversation](#)

airtribe-bot reviewed [2 weeks ago](#)

[View reviewed changes](#)

src/com/airtribe/learntrack/ui/ConsoleHelper.java

```
19 +    */
20 +    String getStringInput(String prompt) {
21 +        System.out.print(prompt);
22 +        return scanner.nextLine().trim();
```



airtribe-bot [2 weeks ago](#)

The use of `print` without a newline might lead to input being on the same line as the prompt. Verify if this behavior is desired.



VinayTanniru [20 hours ago](#)

Owner

Author

yes that was intentional



Open

Implemeted management console as per the requirement #1

VinayTanniru wants to merge 1 commit into `main` from `feature/project-im...`

src/com/airtribe/learntrack/ui/ConsoleHelper.java

```
60 +    }
61 +
62 +    /**
63 +     * Truncates a string to a maximum length
```



airtribe-bot [2 weeks ago](#)

The method might not behave as expected when `maxLength <= 3` because it attempts to place `"..."` even when the truncated string should be shorter. Consider handling cases where `maxLength` is too small to allow for the ellipsis.



VinayTanniru [20 hours ago](#)

Owner

Author

updated the method



Resolve conversation

Reviewers

1 more reviewer

 airtribe-bot

Still in progress? [Convert to draft](#)



Assignees

No one—[assign yourself](#)



Labels

None yet



Projects

None yet



Milestone

No milestone



Development

Successfully merging this pull request may close these issues.

None yet



2 participants

