



GIT ARCHITECTURE AND GIT CONFIGURATION



GIT ARCHITECTURE -



- ❖ After installation, first step in git is to set up Git Configuration System
- ❖ Command **git config** is used to set the git configurations on system
- ❖ Git Configuration is setup at three levels -

System	/etc/gitconfig	Applicable for all users on all Projects (Repositories)
User	~/.gitconfig	Applicable on user profile for his all projects (Repositories)
Local	/.git/config	Applicable for Particular Project (Repositories)

Git Configuration Precedence -

1st → Local → `git config --local [options]`

2nd → user → `git config --global [options]`

3rd → system → `git config --system [options]`

Git Set Environment Variables -

Q. How to set the git config environment variables a global level ?

- ❖ We need to use **git config** command along with flag **--global** to set the global environment variables.
- ❖ By default we need to set user.name and user.email environment variables after git is installed.

git config --global user.name "test"

- This sets the user.name for all projects

git config --global user.email "test@gmail.com"

- This sets user global email address for all projects

Q. How to check the git config settings ?

```
# git config --list
```

Q. How to start the tracking of a Project ?

Step 1 - Go to Project folder

Step 2 - # git init

- This will init the Project tracking by Git
- **Git will only track files and not empty folders
- It will create a .git folder in that Project Directory, we can check that by using # ls -la

Example - For git init in c++ folder that already exists

```
[root@localhost ~]# mkdir c++
[root@localhost ~]# cd c++
[root@localhost c++]# git init
Initialized empty Git repository in /root/c++/.git/
[root@localhost c++]# ls -la
total 0
drwxr-xr-x. 3 root root 18 Apr 22 14:41 .
dr-xr-x---. 6 root root 192 Apr 22 14:41 ..
drwxr-xr-x. 7 root root 119 Apr 22 14:41 .git
[root@localhost c++]#
```

```
[root@localhost c++]# cd .git
[root@localhost .git]# ls -la
total 12
drwxr-xr-x. 7 root root 119 Apr 22 14:41 .
drwxr-xr-x. 3 root root  18 Apr 22 14:41 ..
drwxr-xr-x. 2 root root   6 Apr 22 14:41 branches
-rw-r--r--. 1 root root  92 Apr 22 14:41 config
-rw-r--r--. 1 root root  73 Apr 22 14:41 description
-rw-r--r--. 1 root root  23 Apr 22 14:41 HEAD
drwxr-xr-x. 2 root root 242 Apr 22 14:41 hooks
drwxr-xr-x. 2 root root  21 Apr 22 14:41 info
drwxr-xr-x. 4 root root  30 Apr 22 14:41 objects
drwxr-xr-x. 4 root root  31 Apr 22 14:41 refs
[root@localhost .git]#
```


Q. How to start a new Project with git init ?

- Use command # git init <project_name>
- It will create directory and initiate .git folder for tracking the files

Example :

```
[root@localhost ~]# git init java_project  
Initialized empty Git repository in /root/java_project/.git/
```

Case Study :

Let us say, we started tracking wrong project or git init command was issued in a wrong folder. How to fix this ?

Fix :

Step 1 : go to project folder

Step 2 : `# rm -rf .git`

Note - Use the same command to stop tracking the Project by Git.

Case Study : To understand git config files a global level and local level -

```
[root@localhost ~]# cat .gitconfig
[user]
    name = java
    email = java@gmail.com
[root@localhost ~]# cd c++
[root@localhost c++]# cd .git
[root@localhost .git]# cat config
[core]
    repositoryformatversion = 0
    filemode = true
    bare = false
    logallrefupdates = true
[user]
    name = java1
    email = java1@gmail.com
[root@localhost .git]#
```

Q. How to check the Configuration git variables on a Project ?

```
# git config --list
```

Q. How to set the Preferred Editor using git for a Project ?

Example :

```
# git config --global core.editor "vim"
```

- It sets the editor vim at global level

Q. How to get the help on git commands ?

```
# git help <options>
```

Example : # git help config

Or

```
# git [option] --help
```

Example : # git add --help

Q. How to set the color high lighting in Git ?

```
# git config --global color.ui true
```

```
# git config --global color.status auto
```

```
# git config --global color.branch auto
```

Q. How to set the Preferred Editor using git for a Project ?

Example :

```
# git config --global core.editor "vim"
```

- It sets the editor vim at global level

Q. How to set alias to git commands?

Syntax : `# git config --global alias.<alias_name> <git_command>`

Example :

`# git config --global alias.st status`

`# git config --global alias.ct commit`

Expected Interview Questions -

Q. How to check configuration or environment variables of a project ?

Q. How to set the environment variables for global level ?

Q. What is meaning of git config --global ?

Q. Explain about the architecture of git ?

Q. Is it possible to initiate empty repository using git ?

Case Study :

Q . Let us say we have initiated the git repo already, what happens when we try to initiate it ?

Q. A project was completed using VCS git, now I want to stop the tracking of git, what to do ?

THANK YOU