Educate Elevate Enlighten

JSS Mahavidyapeetha

JSS Science And Technology University

(Established Under JSS Science and Technology University Act No. 43 of 2013)

(Formerly Known as SJCE)

JSS SCIENCE AND TECHNOLOGY UNIVERSITY MYSURU

A Mini-Project Report titled

"IMPLEMENTATION OF DHCP PROTOCOL USING CISCO PACKET TRACER"

Submitted in partial fulfilment of the curriculum requirements for the award of the degree of B.E in

INFORMATION SCIENCE AND ENGINEERING

Submitted by

HARSHA G

(01JST22UIS402)

HITESH H

(01JST22UIS403)

VEDA VYASA M

(01JST22UIS409)

VINAY K

(01JST22UIS411)

submitted to

Ms. SINDHU G

(ASSISTANT PROFESSOR)

DEPARTMENT OF INFORMATION SCIENCE AND ENGINEERING

JULY 2023

ABSTARCT

This report presents a comprehensive implementation of the Dynamic Host Configuration Protocol (DHCP) using Cisco Packet Tracer. The DHCP protocol allows network administrators to automate the assignment of IP addresses, subnet masks, default gateways, and other network configuration parameters to devices within a network. The implementation is performed using Cisco Packet Tracer, a network simulation and visualization tool widely used for network design, testing, and troubleshooting.

TABLE OF CONTENTS

Topics	Page no.
1.Introduction	1
2. how does it work	2
3. DHCP Architecture	3
4. DHCP operaions	4
5. System Requirements	6
6. Implementation	7
7, Benefits	9
8 Limitations	10
9. Testing and Future Enhancements	11
10. Conclusion	12

INTRODUCTION

Dynamic Host Configuration Protocol (DHCP) is a standardized client/server network protocol that dynamically assigns IP addresses and other related configuration information to network devices. Every device on a TCP/IP-based network must have a unique unicast IP address to access the network and its resources. Without DHCP, IP addresses for new computers or computers that are moved from one subnet to another must be configured manually.

DHCP is widely used in everyday life, for example when you:

1. turn on your cell phone and connect to the Internet
2. use a hotspot or wifi in a cafe
3. connect to your home or office network

The key thing to understand about DHCP is that it dynamically assigns IP addresses. This is in contrast with its alternative, static addressing. With static addressing, IP addresses are assigned manually to specific devices, and do not change over time as the device is used. Static addressing is typically used where the source address of the device must not change, for example, to access a service such as a printer server. With this in mind, DHCP allows reservations – these are static IP addresses within the DHCP scope that can be assigned to specific servers or devices and never given out to other devices.

DHCP provides an automated way to distribute and update IP addresses and other configuration information on a network. A DHCP server provides this information to a DHCP client through the exchange of a series of messages, known as the DHCP conversation or the DHCP transaction. If the DHCP server and DHCP clients are located on different subnets, a DHCP relay agent is used to facilitate the conversation. DHCP is based on BOOTP, and is defined in RFC 2131.

HOW DOES IT WORK?

When you access the Internet, your computer automatically requests an IP address from the network's DHCP server. The DHCP server contains a range (or scope) of IP addresses that it is allowed to give out. If there is an address available, the DHCP server will send your computer a response containing an IP address, the default gateway address, subnet mask, and the lease time that your computer can use the address for.

You might ask, "why is the IP address leased?" This is so that the range of IP addresses can be recycled and not used up, or left as 'used' by a device that has been disconnected. Leases times are configured to suit various requirements. For example, a cafe with free wifi may have leases that last/expire in 1 day, but in an Enterprise environment such as a call center with 1000 computers using the same IP addresses from a DHCP server 'permanently', they may use a lease of 100 days. This would make sure no undue network traffic was going on simply for renewing an IP address for hosts plugged in all the time

Clients renew their leases (generally at 50% of the lease time), and when the lease is renewed it will usually be the same IP address. Of course, not every device on the network needs to have a dynamic IP address. Using DHCP, you can reserve addresses for devices such as printers. As each network device has a MAC address, you can assign a static IP at the server to a specific MAC address. This allows devices such as the network printer to always get the same IP address even after it reboots and without assigning the IP address at the printer.

DHCP ARCHITECTURE

The DHCP architecture is made up of DHCP clients, DHCP servers, and DHCP relay agents. The client interacts with servers using DHCP messages in a DHCP conversation to obtain and renew IP address leases.

Here is a brief description of the DHCP components:

1. **DHCP client**

A DHCP client is any IP device connected on the network that has been configured to act as a host requesting configuration parameters such as an IP address from a DHCP server. Configuration parameters and other control information are carried in tagged data items that are stored in the Options field of the DHCP message.

DHCP uses the Options to pass additional IP settings to DHCP clients such as the default gateway IP address, DNS server address, and the DNS domain name.

2. **DHCP server**

The DHCP server is a device on the network with a pool of IP addresses at its disposal to automatically assign to devices as they join the network.

The DHCP server assigns the network device its:

1. IP address – dynamically configured
2. subnet mask – statically configured
3. default gateway for the network – statically configured
4. Primary DNS server – to match a device NAME to an IP address
5. Secondary DNS server – statically configured for redundancy and load balancing.

3. **DHCP relay agent**

DHCP relay agents pass DHCP messages between servers and clients where the DHCP server does not reside on the same IP subnet as its clients.

For example, on large networks consisting of multiple subnets, a single DHCP server may service the entire network when aided by DHCP relay agents located on the interconnecting routers. You can configure a maximum number of 400 DHCP relay agents (one per interface) on AlliedWare Plus devices.

You can use DHCP relay agent information, Option 82, to protect your switch from spoofing attacks, where untrusted hosts send requests for IP addresses to access the network. For more information on Option 82

DHCP OPERATION

The following diagram shows the changing port numbers and the source and destination addresses used during the DHCP transaction. UDP port 68 is reserved for DHCP clients, and UDP port 67 is reserved for DHCP servers.



Fig1 : DHCP OPERATION

Step 1 DHCP Discover

Sent by the client looking for the IP address. The source IP is 0.0.0.0 because the client doesn't have an IP address. The destination is 255.255.255.255, which is the broadcast address, as the client doesn't know where the DHCP server is located, so it broadcasts to all devices on the network.

Step 2 DHCP Offer

Sent by the DHCP server offering an IP address to the client. The source address is the DHCP server address. The DHCP server doesn't know the client address yet, so it broadcasts the offer to all devices on the network.

Step 3 DHCP Request

Sent by the client to the DHCP server to say "I will take that IP address, thanks." The client IP address is still 0.0.0.0 and it is again broadcast to all so that any other servers on the network that may have offered an IP address will know to stop communicating with the client for now.

Step 4 DHCP Acknowledgment

Sent by the DHCP server to the client. It confirms the IP address and other details such as subnet mask, default gateway, and lease time with the client. The source address is the DHCP server and the destination is still the broadcast address

SYSTEM REQUIREMENTS

System Requirements:

1. Cisco Packet Tracer software (version 7.3 or later)
2. A computer or laptop running the Cisco Packet Tracer software.
3. Network devices (e.g., routers, switches, PCs) compatible with Cisco Packet Tracer

IMPLEMENTATION

Implementation Steps:

Step 1: Designing the network topology:

1. Launch Cisco Packet Tracer and create a new project.
2. Drag and drop the required devices (DHCP server, clients, switch, and router) onto the workspace.
3. Connect the devices using appropriate network cables.

Step 2: Configuring the DHCP server:

1. Access the CLI (Command Line Interface) of the DHCP server.
2. Configure an IP address and subnet mask on the server's interface connected to the switch.
3. Enable the DHCP service on the server using the "ip dhcp pool" command.
4. Specify the network range, default gateway, DNS server, and lease duration for the DHCP pool.
5. Save the configuration.

Step 3: Configuring the DHCP clients:

1. Access the CLI of each DHCP client device.
2. Configure the interface connected to the switch with the "ip dhcp" command, enabling DHCP client functionality.
3. Save the configuration.

Step 4: Verifying DHCP functionality:

1. Start the simulation in Cisco Packet Tracer.
2. Monitor the DHCP server to ensure it receives and processes DHCP requests from the clients.
3. Check the DHCP clients to verify they obtain IP addresses, subnet masks, default gateways, and other configuration parameters automatically.



Fig 2 : DHCP operations



Fig 3 : IP Address Requesting

BENEFITS

Benefits of DHCP DHCP provides many benefits for network administrators, network users, and people using consumer gadgets such as mobile phones, tablets, and laptops to connect to the network. This section focuses on the benefits for network users and network administrators.

Network users

DHCP provides network users with 'plug and play' networking. This means that network users can travel anywhere on the network and automatically receive an IP address when they reconnect to the network.

Network administrators

DHCP provides network administrators with quicker and more reliable IP address configuration. DHCP minimizes configuration errors caused by manual IP address configuration, such as typographical errors, or address conflicts caused by the assignment of an IP address to more than one computer at the same time.

Network administrators find DHCP useful when they want to change the IP addresses of a large number of systems. Instead of reconfiguring all the systems, they can just edit one DHCP configuration file on the server for the new set of IP addresses. If the DNS server for an organization changes, the changes are made on the DHCP server, not on the DHCP clients.

Because DHCP is easy to configure, it minimizes operational overhead and costs associated with configuration.

DHCP includes the following features to reduce network administration:

1. The ability to define TCP/IP configurations from a central location.
2. The ability to assign a full range of additional TCP/IP configuration values by means of DHCP options.
3. The efficient handling of IP address changes for clients that must be updated frequently, such as those for portable computers that move to different locations on a wireless network. 4
4. The forwarding of initial DHCP messages by using a DHCP relay agent, which eliminates the need for a DHCP server on every subnet.

DHCP also helps conserve limited IP address space, because IP addresses no longer need to be permanently assigned to hosts.

LIMITATIONS

While DHCP is a widely used protocol for automating IP address allocation, it does have some limitations. Here are a few limitations of DHCP:

1. Reliance on DHCP Server: DHCP relies on a centralized server to allocate IP addresses. If the DHCP server becomes unavailable or experiences issues, new clients may not be able to obtain IP addresses, resulting in network connectivity problems.

2. Limited IP Address Range: The number of available IP addresses within a DHCP scope is limited by the size of the subnet and the range specified in the DHCP pool configuration. If the number of devices exceeds the available IP addresses, DHCP may fail to allocate addresses, requiring manual intervention.

3. Lack of Control over IP Address Assignment: DHCP dynamically assigns IP addresses to clients based on availability within the configured pool. This lack of control can result in non-deterministic IP assignments, making it challenging to track specific devices or implement strict IP address management policies.

4. Lease Expiration and Renewal: DHCP leases have a limited duration, after which the IP address lease must be renewed. If the lease renewal process fails or if clients are disconnected from the network during the lease expiration, IP addresses may be lost and clients may experience connectivity issues.

5. Limited Support for Network Configuration Parameters: While DHCP can assign IP addresses, subnet masks, default gateways, and DNS server addresses, it has limited support for other network configuration parameters. Complex configurations or specific requirements may necessitate manual configuration on individual devices.

6. Security Concerns: DHCP lacks built-in security mechanisms, making it susceptible to unauthorized DHCP servers or rogue DHCP servers on the network. These rogue servers can assign incorrect or malicious IP addresses, leading to potential security vulnerabilities or disruptions.

7. Network Segment Limitations: DHCP operates within a single network segment or broadcast domain. It may not extend its services across multiple network segments without the use of DHCP relay agents, which adds complexity to the network infrastructure.

8. Lack of Support for Stateless Address Autoconfiguration: DHCP does not provide support for Stateless Address Autoconfiguration (SLAAC), a mechanism used in IPv6 networks to automatically configure IP addresses without relying on a central server. This means that DHCPv4 is unable to provide the same level of automation in IPv6 networks.

While DHCP has these limitations, it remains a valuable and widely adopted protocol for automating IP address allocation. Network administrators should consider these limitations when designing and managing their networks to ensure DHCP's effective and secure implementation.

TESTING & FUTURE ENHANCEMENTS

Testing and Troubleshooting:

1. Perform various tests to ensure proper functionality of DHCP.
2. Test DHCP lease renewal by rebooting a client device and verifying that it successfully obtains the same IP address.
3. Verify DHCP lease expiration by waiting for the lease duration to elapse and checking if the client requests a new IP address.
4. Troubleshoot any issues by checking the DHCP server logs, client configurations, and network connectivity.
5. Ensure that all devices are properly connected, and DHCP configurations are accurate.

Future Enhancements:

1. Expand the network topology to include multiple DHCP servers for redundancy.
2. Implement DHCP relay agents to extend DHCP functionality across multiple subnets.
3. Explore advanced DHCP options such as DHCP options for PXE booting, VoIP, or IoT devices.

CONCLUSION

In conclusion, the implementation of DHCP using Cisco Packet Tracer offers a practical and efficient solution for automating IP address allocation within a network. By following the outlined steps and utilizing the simulation capabilities of Cisco Packet Tracer, network administrators can successfully configure and verify DHCP functionality.

By implementing DHCP, network administrators can benefit from the following:

1. **Simplified IP Address Management:** DHCP eliminates the need for manual IP address configuration on individual devices. This simplifies network administration and reduces the chances of human error, leading to more efficient IP address management.
2. **Dynamic IP Address Allocation:** DHCP dynamically assigns IP addresses to devices within the network, ensuring optimal utilization of available IP addresses. It eliminates the need for static IP address assignments, allowing devices to obtain IP addresses automatically when connected to the network.
3. **Centralized Control:** With DHCP, network administrators have centralized control over IP address allocation and configuration parameters. They can easily modify DHCP pool settings to adjust IP address ranges, lease durations, default gateways, DNS servers, and other network configuration options.
4. **Ease of Network Expansion:** DHCP simplifies the process of adding new devices to the network. New devices can connect to the network, request an IP address from the DHCP server, and automatically receive the necessary network configuration parameters, minimizing the configuration overhead.

However, it is important to consider the limitations of DHCP, such as its reliance on a centralized DHCP server, limited IP address range, lack of control over IP address assignment, and security concerns related to rogue DHCP servers. Network administrators should address these limitations appropriately and consider alternate solutions if necessary.

In conclusion, implementing DHCP using Cisco Packet Tracer provides network administrators with a powerful tool to automate IP address allocation and streamline network management. By understanding the benefits and limitations of DHCP, administrators can make informed decisions to optimize their network configurations and ensure efficient IP address management.