

```
1  import configparser
2  import fcntl
3  from itertools import combinations
4  import json
5  import math
6  import os
7  import random
8  import selectors
9  from subprocess import Popen, PIPE, STDOUT
10 import time
11
12 from configmanager import validate_configs_by_filename
13
14
15 NUM_ROUTERS = 100
16
17
18 FOLDER = 'test_configs'
19 os.makedirs(FOLDER, exist_ok=True)
20
21
22 class Test:
23     def __init__(self, neighbour_func, change_topology=None, topology_changes=1):
24         self.make_neighbours_func = neighbour_func
25         self.topology_change_func = change_topology
26         self.topology_changes_remaining = topology_changes
27
28     def make_neighbours(self, processes):
29         self.make_neighbours_func(processes)
30
31     def can_change_topology(self):
32         return self.topology_change_func != None and self.
33             topology_changes_remaining > 0
34
35     def change_topology(self, processes):
36         self.topology_changes_remaining -= 1
37         self.topology_change_func(processes)
38
39 ports = iter(range(10000, 64000))
40 def make_neighbours(p1, p2):
41     port1 = next(ports)
42     port2 = next(ports)
43     metric = random.randint(1, 15)
44     p1.add_neighbour(port1, port2, metric, p2)
45     p2.add_neighbour(port2, port1, metric, p1)
46
47 def fully_connected(processes):
48     for p1, p2 in combinations(processes, 2):
49         make_neighbours(p1, p2)
50
```

```
51 def sparsely_connected(processes):
52     rand_processes = list(processes)
53     random.shuffle(rand_processes)
54     for p1 in processes:
55         num_neighbours = 0
56         for p2 in rand_processes:
57             if p1.routerid != p2.routerid and p2.routerid not in p1.get_neighbours:
58                 make_neighbours(p1, p2)
59                 num_neighbours += 1
60                 if num_neighbours >= 1:
61                     break
62
63 def change_topology(processes):
64     processes = list(processes)
65     if random.choice([False, True]):
66         to_stop = random.sample(processes, len(processes)//2)
67         print(f'stopping {len(to_stop)} processes randomly')
68         for p in to_stop:
69             p.stop()
70     else:
71         to_start = random.sample(processes, len(processes)//2)
72         print(f'starting {len(to_start)} processes randomly')
73         for p in to_start:
74             p.start()
75
76 test1 = Test(fully_connected)
77
78 test2 = Test(sparsely_connected)
79
80 test3 = Test(fully_connected, change_topology, 5)
81
82 test4 = Test(sparsely_connected, change_topology, 10)
83
84
85 class ProcessManager:
86     def __init__(self):
87         self.processes_dict = {}
88
89     def get_processes(self):
90         return self.processes_dict.values()
91
92     def get_alive_processes(self):
93         return [p for p in self.processes_dict.values() if p.alive]
94
95     def get_process(self, id):
96         return self.processes_dict[id]
97
98     def start_processes(self):
99         for p in self.get_processes():
100             p.start()
```

```
101
102     def stop_processes(self):
103         for p in self.get_processes():
104             p.stop()
105
106     def new_processes(self):
107         self.stop_processes()
108         for i in range(1, NUM_ROUTERS+1):
109             self.processes_dict[i] = Process(i)
110
111     def setup_test(self, test):
112         self.new_processes()
113         test.make_neighbours(self.get_processes())
114         self.write_configs()
115         validate_configs_by_filename([p.filename for p in self.get_processes()])
116         self.start_processes()
117
118     def change_test_topology(self, test):
119         test.change_topology(self.get_processes())
120         for p in self.get_processes():
121             p.clear_routing_table()
122
123     def write_configs(self):
124         for p in self.get_processes():
125             p.write_config()
126
127
128 class Process:
129     def __init__(self, routerid):
130         self.routerid = routerid
131         self.inputs = []
132         self.outputs = {}
133         self.filename = f'{FOLDER}/autoconfig{self.routerid}.ini'
134         self.process = None
135         self.alive = False
136
137         self.routing_table = None
138         self.routing_table_time = math.inf
139         self.have_checked_convergence = False
140         self.converged = False
141
142
143     def __str__(self):
144         return str(self.routerid)
145
146
147     def add_neighbour(self, in_port, out_port, metric, neighbour):
148         self.inputs.append(str(in_port))
149         self.outputs[neighbour.routerid] = [neighbour, out_port, metric]
150
151
```

```
152     def get_neighbours(self):
153         return self.outputs
154
155
156     def write_config(self):
157         config = configparser.ConfigParser()
158         config['SETTINGS'] = {
159             'router-id': str(self.routerid),
160             'input-ports': ','.join(self.inputs),
161             'outputs': ','.join(f'{port}-{metric}-{id}' for id, (_, port, metric)
                                in self.outputs.items())
162         }
163         with open(self.filename, 'w') as file:
164             config.write(file)
165
166
167     def start(self):
168         """Start the process and make its stdout non-blocking."""
169         if not self.alive:
170             self.alive = True
171             self.process = Popen(["python", "daemon.py", self.filename,
                                   "--autotesting"], stdout=PIPE, stderr=STDOUT)
172             fcntl.fcntl(self.process.stdout.fileno(), fcntl.F_SETFL, os.O_NONBLOCK)
173
174
175     def stop(self):
176         self.alive = False
177         self.process.kill()
178
179
180     def get_stdout(self):
181         return self.process.stdout
182
183
184     def read_line(self):
185         line = self.process.stdout.readline()
186         if line:
187             line = line.decode().strip()
188             try:
189                 line = json.loads(line)
190             except json.decoder.JSONDecodeError as e:
191                 print(self, 'decode error', line)
192             return
193             if type(line) != list:
194                 print(self, 'received non-list', line)
195             return
196
197         if line != self.routing_table:
198             self.routing_table = line
199             self.routing_table_time = time.time()
200             self.have_checked_convergence = False
```

```
201         self.converged = False
202
203
204     def clear_routing_table(self):
205         self.routing_table = None
206         self.routing_table_time = math.inf
207         self.have_checked_convergence = False
208         self.converged = False
209
210
211     def routing_table_entries(self):
212         return {routerid:metric for routerid, _, metric, _ in self.routing_table}
213
214
215     def check_convergence(self):
216         # an offline router is considered converged
217         if not self.alive:
218             self.converged = True
219             return
220
221         # don't check for convergence again if the routing table hasn't changed
222         if self.have_checked_convergence:
223             return
224
225         # only check if routing table hasn't changed for 10 seconds
226         if time.time() - self.routing_table_time < 10:
227             return
228
229         self.calculate_convergence()
230
231
232     def calculate_convergence(self):
233         min_costs, parents = dijkstras(self.routerid)
234         routing_table_entries = self.routing_table_entries()
235
236         self.converged = True
237         for routerid, metric in min_costs.items():
238             if metric >= 16 or routerid == self.routerid:
239                 continue
240
241             if routerid not in routing_table_entries:
242                 self.converged = False
243                 print(f'{self} not converged to router {routerid} (not in routing  ↗
244                     table, cost should be: {metric})')
245                 print('Dijkstras path:', dijkstras_path(min_costs, parents, self.  ↗
246                     routerid, routerid))
247                 print()
248                 continue
249
250         actual_metric = routing_table_entries[routerid]
251         if actual_metric != metric:
```

```
250         self.converged = False
251         print(f'{self} not converged to router {routerid} (current cost: {
252             actual_metric}, should be: {metric})')
253         print('Dijkstras path:', dijsktras_path(min_costs, parents, self.
254             routerid, routerid))
255         print('Current path: ', end='')
256         print_actual_path(self.routerid, routerid)
257         print()
258
259     self.have_checked_convergence = True
260
261 def dijkstras(source_id):
262     dist = {}
263     prev = {}
264     queue = []
265     for p in processmanager.get_alive_processes():
266         id = p.routerid
267         dist[id] = math.inf
268         prev[id] = None
269         queue.append(id)
270     assert source_id in dist
271     dist[source_id] = 0
272
273     while queue:
274         u = None
275         min_dist = math.inf
276         for v in queue:
277             if dist[v] <= min_dist:
278                 u = v
279                 min_dist = dist[v]
280         queue.remove(u)
281
282         u_neighbours = processmanager.get_process(u).get_neighbours()
283         for v, [process, _, metric] in u_neighbours.items():
284             if v not in queue:
285                 continue
286
287             cost = dist[u] + metric
288             if cost <= dist[v]:
289                 dist[v] = cost
290                 prev[v] = u
291
292     return dist, prev
293
294 def dijsktras_path(dist, prev, src, dest):
295     current = dest
296     path = f'{current} ({dist[current]}')
297     while current != src:
298         current = prev[current]
```

```
299     path = f'{current} ({dist[current]}) --> ' + path
300     return path
301
302
303 def print_actual_path(src, dest, depth=0):
304     if depth > 15:
305         print('ABORTING')
306         return
307     if src == dest:
308         print(f'{src} (0)')
309         return
310
311     src_routing_table = processmanager.get_process(src).routing_table
312     if src_routing_table == None:
313         print(f'{src} (no route to {dest})')
314         return
315     for routerid, nexthop, metric, _ in src_routing_table:
316         if routerid == dest:
317             break
318     print(f'{src} ({metric}) --> ', end='')
319     print_actual_path(nexthop, dest, depth+1)
320
321
322 processmanager = ProcessManager()
323
324 def main():
325     tests = [test1, test2, test3, test4]
326     for i in range(len(tests)):
327         test = tests[i]
328         processmanager.setup_test(test)
329         print(f'test {i} starting')
330         run_to_convergence()
331         while test.can_change_topology():
332             print(f'test {i} changing topology')
333             processmanager.change_test_topology(test)
334             run_to_convergence()
335         print(f'test {i} finished')
336
337
338 def run_to_convergence():
339     selector = selectors.DefaultSelector()
340     for p in processmanager.get_processes():
341         selector.register(p.get_stdout(), selectors.EVENT_READ, p)
342
343     prev_not_converged = []
344     while True:
345         events = selector.select(timeout=1)
346         for key, _ in events:
347             p = key.data
348             p.read_line()
349
```

```
350     all_converged = True
351     not_converged = []
352     for p in processmanager.get_processes():
353         p.check_convergence()
354         if not p.converged:
355             all_converged = False
356             not_converged.append(p.routerid)
357
358     if all_converged:
359         print('all routers converged correctly')
360         return
361     elif not_converged != prev_not_converged:
362         prev_not_converged = not_converged
363         print(len(not_converged), 'routers not converged.', not_converged[:10])
364
365
366 try:
367     main()
368 except KeyboardInterrupt:
369     pass
370 finally:
371     processmanager.stop_processes()
372 print('exiting')
373
```