

Data science project Final presentation

Exploiting word embeddings for machine translation

CôngMinh DINH

Louis Monier


Maxence Philbert

Vincent Gouteux

25/11/19

I - Supervised method

Recall



I - Supervised method



Recall

- Minimization of matrix translation
(4 methods implemented : SD, SGD, MGD, analytical)

$$\min_W \sum_{i=1}^n \|Wx_i - z_i\|^2$$

- Using cosine similarity to find the closest in the target language space

$$\text{similarity} : \frac{\langle x_i, z_i \rangle}{\|x_i\| * \|z_i\|}$$






Supervised translator : results for different languages

Accuracy top @1/5 words


From French to English



Gradient descent method :
Final accuracy @1 = 58.46 %
Final accuracy @5 = 76.8 %

Analytical method :
Final accuracy @1 = 60.22 %
Final accuracy @5 = 77.14 %


From Italian to English




Analytical method :
Final accuracy @1 = 54.45 %
Final accuracy @5 = 69.67 %

Good results with supervised translator !

From Vietnamese to English




Gradient descent method :
Final accuracy @1 = 42.09 %
Final accuracy @5 = 64.59 %



II - Build an efficient unsupervised translator

Generative Adversarial Network (GAN) method

- We don't know the translations ;
We just have collections of words in source & target spaces
- Two adversarial neural networks :
 - the **generator** generates new data instances ("fake" data)
 - the **discriminator** evaluates data for authenticity
- **Objective :** Learn the matrix W by training fake ($W*x$) and real (y) data
- GAN's architecture :






Unsupervised Translator : GAN

Discriminator

Neural network




Inputs =

{**W**(chat);
House;
W(voiture);
W(soleil);
University;
W(étudiant); ... }

Outputs =

{**P**(**W**(chat) \in source);
P(House \in source);
P(**W**(voiture) \in source);
P(**W**(soleil) \in source);
P(University \in source);
P(**W**(étudiant) \in source); ... }



Unsupervised Translator : GAN

Discriminator

$$\mathcal{L}_D(\theta_D|W) = -\frac{1}{n} \sum_{i=1}^n \log P_{\theta_D}(\text{source} = 1|Wx_i) - \frac{1}{m} \sum_{i=1}^m \log P_{\theta_D}(\text{source} = 0|y_i).$$

- W matrix is fixed
- 3 layers Neural Network takes an embedding as input and returns the probability that this embedding comes from source language
-
- **Objective:** minimize the loss, adapt the weights of the network in order to recognize with high precision the language of the embedding



Unsupervised Translator : GAN

Generator



$$\mathcal{L}_W(W|\theta_D) = -\frac{1}{n} \sum_{i=1}^n \log P_{\theta_D}(\text{source} = 0 | Wx_i) - \frac{1}{m} \sum_{i=1}^m \log P_{\theta_D}(\text{source} = 1 | y_i).$$

- 1 layer “Neural Network” : takes an embedding x as input and returns the “translation” Wx
- **Objective** : Minimize the loss + adapt the weights of the network = weights of W in order to generate embeddings close to those in target space


Then, train by SGD with BCE loss function

Unsupervised Translator : GAN

Results

Tried to implement the GAN and played with all possible parameters :

- Nb of iterations
- SGD learning rate
- Nb of hidden layers discriminator
- Add smoothing
- Training spaces
- Nb of words in batch
- Initialisation of networks' weights




Need a large number of iteration to work (longer the training is, better we converge towards optimal W)

Unsupervised Translator : GAN

Results

30000 itérations training




Unsupervised method :

Final accuracy @1 = 33.72 %

Final accuracy @5 = 53.88 %

50000 itérations training



Not bad !

Unsupervised method :

Final accuracy @1 = 47.2 %

Final accuracy @5 = 66.55 %

Gradient descent method :
Final accuracy @1 = 58.46 %
Final accuracy @5 = 76.8 %

Analytical method :
Final accuracy @1 = 60.22 %
Final accuracy @5 = 77.14 %

Supervised Accuracy

Not implemented but we should have better results with Cross Domain Similarity Local Scaling measure

Unsupervised Translator : GAN

Results : examples of traductions

```
bateau --> traduction : ['boat', 'boats', 'steamer', 'capsized', 'sailboat']
--
maison --> traduction : ['house', 'cottage', 'townhouse', 'farmhouse', 'residence']
--
argent --> traduction : ['silver', 'gold', 'bronze', 'bullion', 'money']
--
ordinateur --> traduction : ['programmable', 'computer', 'computers', 'workstations', 'interface']
--
dieu --> traduction : ['god', 'divine', 'deity', 'gods', 'worshipping']
--
communiste --> traduction : ['communist', 'communists', 'comintern', 'leftist', 'socialist']
--
satan --> traduction : ['satan', 'sinners', 'evil', 'resurrection', 'antichrist']
--
amour --> traduction : ['love', 'lovers', 'lover', 'longing', 'sorrow']
```

Thanks!



Any questions?