

Synthetic Data



Preface

This book covers the foundations of machine learning, with modern approaches to solving complex problems and the systematic generation and use of synthetic data. Emphasis is on scalability, automation, testing, optimizing, and interpretability (explainable AI). For instance, regression techniques – including logistic and Lasso – are presented as a single method, without using advanced linear algebra. There is no need to learn 50 versions when one does it all and more. Confidence regions and prediction intervals are built using parametric bootstrap, without statistical models or probability distributions. Models (including generative models and mixtures) are mostly used to create rich synthetic data to test and benchmark various methods.

Topics covered include clustering and classification, GPU machine learning, ensemble methods including an original boosting technique, elements of graph modeling, deep neural networks, auto-regressive and non-periodic time series, Brownian motions and related processes, simulations, interpolation, random numbers, natural language processing (smart crawling, taxonomy creation and structuring unstructured data), computer vision (shapes generation and recognition), curve fitting, cross-validation, goodness-of-fit metrics, feature selection, curve fitting, gradient methods, optimization techniques and numerical stability.

Chapters 12 and 13 focus on synthetic data applications: fractal-like terrain generation with the diamond-square algorithm, and synthetic star clusters evolving over time and bound by gravity. The latter provides great insights to explore the past and future of our universe or studying collision graphs. It also allows you to explore alternative universes, for instance with negative masses. Chapters 14 and 16 are more advanced and may be skipped in introductory classes. The former focuses on point process applications, while the later focuses on applications a machine learning methods to discover new insights in a famous mathematical conjecture: the Riemann Hypothesis. Section 16.7.2 illustrates the use of copulas to produce synthetic data, applied to a well-known insurance dataset.

Methods are accompanied by enterprise-grade Python code, replicable datasets and visualizations, including data animations (gifs, videos, even sound done in Python). The code uses various data structures and library functions sometimes with advanced options. It constitutes a Python tutorial in itself, and an introduction to scientific computing. Some data animations and chart enhancements are done in R. The code, datasets, spreadsheets and data visualizations are also on GitHub, spread across the following repositories: [Machine Learning](#), [Point Processes](#), [Visualizations](#), and [Experimental Math](#). Chapters are mostly independent from each other, allowing you to read in random order. A glossary, index and numerous cross-references make the navigation easy and unify all the chapters.

The style is very compact, getting down to the point quickly, and suitable to business professionals eager to learn a lot of useful material in a limited amount of time. Jargon and arcane theories are absent, replaced by simple English to facilitate the reading by non-experts, and to help you discover topics usually made inaccessible to beginners. While state-of-the-art research is presented in all chapters, the prerequisites to read this book are minimal: an analytic professional background, or a first course in calculus and linear algebra. The original presentation avoids all unnecessary math and statistics, yet without eliminating advanced topics. Finally, this book is the main reference for my course on intuitive machine learning. For details about the classes, see [here](#).

About the Author

Vincent Granville is a pioneering data scientist and machine learning expert, co-founder of Data Science Central (acquired by a publicly traded company in 2020), founder of [MLTechniques.com](#), former VC-funded executive, author and patent owner. Vincent's past corporate experience includes Visa, Wells Fargo, eBay, NBC, Microsoft, and CNET.



Vincent is also a former post-doc at Cambridge University, and the National Institute of Statistical Sciences (NISS). He published in *Journal of Number Theory*, *Journal of the Royal Statistical Society* (Series B), and *IEEE Transactions on Pattern Analysis and Machine Intelligence*. He is also the author of multiple books, available [here](#). He lives in Washington state, and enjoys doing research on stochastic processes, dynamical systems, experimental math and probabilistic number theory.

Contents

List of Figures	9
List of Tables	11
1 Machine Learning Cloud Regression and Optimization	12
1.1 Introduction: circle fitting	12
1.1.1 Previous versions of my method	13
1.2 Methodology, implementation details and caveats	14
1.2.1 Solution, R-squared and backward compatibility	14
1.2.2 Upgrades to the model	15
1.3 Case studies	16
1.3.1 Logistic regression, two ways	16
1.3.2 Ellipsoid and hyperplane fitting	17
1.3.2.1 Curve fitting: 250 examples in one video	17
1.3.2.2 Confidence region for the fitted ellipse: application to meteorite shapes	18
1.3.2.3 Python code	19
1.3.3 Non-periodic sum of periodic time series: ocean tides	25
1.3.3.1 Numerical instability and how to fix it	26
1.3.3.2 Python code	27
1.3.4 Fitting a line in 3D, unsupervised clustering, and other generalizations	28
1.3.4.1 Example: confidence region for the cluster centers	29
1.3.4.2 Exact solution and caveats	30
1.3.4.3 Comparison with K-means clustering	31
1.3.4.4 Python code	33
1.4 Connection to synthetic data: meteorites, ocean tides	35
2 A Simple, Robust and Efficient Ensemble Method	36
2.1 Introduction	36
2.2 Methodology	37
2.2.1 How hidden decision trees (HDT) work	37
2.2.2 NLP case study: summary and findings	38
2.2.3 Parameters	39
2.2.4 Improving the methodology	39
2.3 Implementation details	39
2.3.1 Correcting for bias	39
2.3.1.1 Time-adjusted scores	40
2.3.2 Excel spreadsheet	40
2.3.3 Python code and dataset	40
2.4 Model-free confidence intervals and perfect nodes	44
2.4.1 Interesting asymptotic properties of confidence intervals	44
3 Gentle Introduction to Linear Algebra	46
3.1 Power of a matrix	46
3.2 Examples, generalization, and matrix inversion	47
3.2.1 Example with a non-invertible matrix	48
3.2.2 Fast computations	48
3.2.3 Square root of a matrix	48
3.3 Application to machine learning problems	49
3.3.1 Markov chains	49
3.3.2 Time series: auto-regressive processes	49

3.3.3	Linear regression	49
3.4	Mathematics of auto-regressive time series	50
3.4.1	Simulations: curious fractal time series	50
3.4.1.1	White noise: Fréchet, Weibull and exponential cases	51
3.4.1.2	Illustration	51
3.4.2	Solving Vandermonde systems: a numerically stable method	52
3.5	Math for Machine Learning: Must-Read Books	53
4	The Art of Visualizing High Dimensional Data	54
4.1	Introduction	54
4.2	Applications	55
4.2.1	Spatial time series	55
4.2.2	Prediction intervals in any dimensions	55
4.2.3	Supervised classification of an infinite dataset	56
4.2.3.1	Machine learning perspective	56
4.2.3.2	Six challenging problems	57
4.2.3.3	Mathematical background: the Riemann Hypothesis	57
4.2.3.4	Partial solutions to the six challenging problems	58
4.2.4	Algorithms with chaotic convergence	59
4.3	Python code	59
4.3.1	Path simulation	59
4.3.2	Visual convergence analysis in 2D	62
4.3.3	Supervised classification	63
4.4	Visualizations	66
5	Fast Classification and Clustering via Image Convolution Filters	69
5.1	Introduction	69
5.2	Generating the synthetic data	70
5.2.1	Simulations with logistic distribution	70
5.2.2	Mapping the raw observations onto an image bitmap	71
5.3	Classification and unsupervised clustering	71
5.3.1	Supervised classification based on convolution filters	72
5.3.2	Clustering based on histogram equalization	72
5.3.3	Fractal classification: deep neural network analogy	73
5.3.4	Generalization to higher dimensions	74
5.3.5	Towards a very fast implementation	74
5.4	Python code	75
5.4.1	Fractal classification	76
5.4.2	GPU classification and clustering	78
5.4.3	Home-made graphic library	80
6	Shape Classification via Explainable AI	83
6.1	Introduction	83
6.2	Mathematical foundations	83
6.3	Shape signature	84
6.3.1	Weighted centroid	84
6.3.2	Computing the signature	85
6.3.3	Example	86
6.4	Shape comparison	86
6.4.1	Shape classification	87
6.5	Application	87
6.6	Exercises	88
7	Synthetic Data, Interpretable Regression, and Submodels	89
7.1	Introduction	89
7.2	Synthetic data sets and the spreadsheet	90
7.2.1	Correlation structure	90
7.2.2	Standardized regression	91
7.2.3	Initial conditions	91
7.2.4	Simulations and Excel spreadsheet	91
7.3	Damping schedule and convergence acceleration	92
7.3.1	Spreadsheet implementation	92

7.3.2	Interpretable regression with no overfitting	93
7.3.3	Adaptive damping	93
7.4	Performance assessment on synthetic data	93
7.4.1	Results	94
7.4.2	Distribution-free confidence intervals	96
7.4.2.1	Parametric bootstrap	97
7.5	Feature selection	97
7.5.1	Combinatorial approach	97
7.5.2	Stepwise approach	98
7.6	Conclusion	99
8	From Interpolation to Fuzzy Regression	101
8.1	Introduction	101
8.2	Original version	102
8.3	Full, non-linear model in higher dimensions	102
8.3.1	Geometric proximity, weights, and numerical stability	103
8.3.2	Predicted values and prediction intervals	103
8.3.3	Illustration, with spreadsheet	104
8.3.3.1	Output fields	105
8.4	Results	105
8.4.1	Performance assessment	105
8.4.2	Visualization	106
8.4.3	Amplitude restoration	106
8.5	Exercises	107
8.6	Python source code and datasets	108
9	Detecting Subtle Departures from Randomness	112
9.1	Introduction	112
9.2	Pseudo-random numbers	113
9.2.1	Strong pseudo-random numbers	113
9.2.1.1	New test of randomness for PRNGs	114
9.2.1.2	Theoretical background: the law of the iterated logarithm	114
9.2.1.3	Connection to the Generalized Riemann Hypothesis	114
9.2.2	Testing well-known sequences	115
9.2.2.1	Reverse-engineering a pseudo-random sequence	116
9.2.2.2	Illustrations	117
9.3	Python code	119
9.3.1	Fixes to the faulty random function in Python	119
9.3.2	Prime test implementation to detect subtle flaws in PRNG's	119
9.3.3	Special formula to compute 10 million digits of $\sqrt{2}$	122
9.4	Military-grade PRNG Based on Quadratic Irrationals	125
9.4.1	Fast algorithm rooted in advanced analytic number theory	125
9.4.2	Fast PRNG: explanations	126
9.4.3	Python code	126
9.4.4	Computing a digit without generating the previous ones	128
9.4.5	Security and comparison with other PRNGs	128
9.4.5.1	Important comments	128
9.4.6	Curious application: a new type of lottery	129
10	Some Unusual Random Walks	130
10.1	Symmetric unbiased constrained random walks	130
10.1.1	Three fundamental properties of pure random walks	130
10.1.2	Random walks with more entropy than pure random signal	131
10.1.2.1	Applications	131
10.1.2.2	Algorithm to generate quasi-random sequences	132
10.1.2.3	Variance of the modified random walk	132
10.1.3	Random walks with less entropy than pure random signal	133
10.2	Related stochastic processes	134
10.2.1	From Brownian motions to clustered Lévy flights	134
10.2.2	Integrated Brownian motions and special auto-regressive processes	135
10.3	Python code	136
10.3.1	Computing probabilities and variances attached to S_n	136

10.3.2 Path simulations	137
11 Empirical Optimization with Divergent Fixed Point Algorithm	139
11.1 Introduction	139
11.1.1 The problem, with illustration	140
11.2 Non-converging fixed-point algorithm	141
11.2.1 Trick leading to intuitive solution	141
11.2.2 Root detection: method and parameters	141
11.2.3 Case study: factoring a product of two large primes	142
11.3 Generalization with synthetic random functions	142
11.3.1 Example	144
11.3.2 Connection to the Poisson-binomial distribution	145
11.3.2.1 Location of next root: guesstimate	145
11.3.2.2 Integer sequences with high density of primes	145
11.3.3 Python code: finding the optimum	146
11.4 Smoothing highly chaotic curves	147
11.4.1 Python code: smoothing	147
11.5 Connection to synthetic data: random functions	150
12 Synthetic Terrain Generation and AI-generated Art	151
12.1 Introduction	151
12.2 Terrain generation and the evolutionary process	153
12.2.1 Morphing and non-linear palette operations	153
12.2.2 The diamond-square algorithm	153
12.2.3 The evolutionary process	154
12.2.4 Finding optimum parameters	154
12.2.5 Mimicking real terrain: the synthesis step	154
12.3 Python code	155
12.3.1 Producing data videos with four sub-videos in parallel	155
12.3.2 Main program	156
12.4 AI-generated art with 3D contours	160
12.4.1 Python code using Matplotlib	161
12.4.2 Python code using Plotly	162
12.4.3 Tips to quickly solve new problems	163
13 Synthetic Star Clusters Generation with Collision Graphs	164
13.1 Introduction	164
13.2 Model parameters and simulation results	165
13.2.1 Explanation of color codes	165
13.2.2 Detailed description of top parameters	165
13.2.3 Interesting parameter sets	166
13.3 Analysis of star collisions and collision graph	167
13.3.1 Weighted directed graphs: visualization with NetworkX	168
13.3.2 Interesting findings: how the universe got started	168
13.4 Animated data visualizations	169
13.5 Python code and computational issues	170
13.5.1 Simulating the real and synthetic universes	170
13.5.2 Visualizing collision graphs	174
14 Perturbed-Lattice Point Process: Inference, Nearest Neighbor Graph	176
14.1 Perturbed lattices: definition and properties	176
14.1.1 Point counts distribution	177
14.1.2 Periodicity and amplitude of point count expectations	177
14.1.3 Testing the independence of point counts	178
14.1.3.1 Results and Interpretation	179
14.1.3.2 About the Spreadsheet	180
14.2 Cluster processes and nearest neighbor graphs	180
14.2.1 Synthetic, semi-rigid cluster structures	180
14.2.2 Python code to generate cluster processes	182
14.2.3 References on cluster processes	182
14.2.4 Superimposed perturbed lattices: an alternative to mixture models	183
14.2.4.1 Hexagonal lattice, nearest neighbors	184

14.2.4.2	Exercises: nearest neighbor graphs, size of connected components	185
14.2.4.3	Python code to compute connected components	186
14.3	Statistical inference for point processes	188
14.3.1	Estimation of Core Parameters	188
14.3.1.1	Intensity	189
14.3.1.2	Scaling factor	189
14.3.1.3	Alternative estimation method	189
14.3.2	Spatial statistics, nearest neighbors, clustering	190
14.3.2.1	Inference for two-dimensional processes	190
14.3.2.2	Other possible tests	190
14.3.2.3	Rayleigh test	191
14.3.2.4	Exercises	192
14.4	Special topics	193
14.4.1	Minimum contrast estimation and explainable AI	193
14.4.2	Model identifiability, hard-to-detect patterns	194
14.4.2.1	Stochastic residues	194
14.4.3	Hidden model and random permutations	194
14.4.4	Retrieving the F distribution	196
14.4.4.1	Theoretical values obtained by simulations	196
14.4.4.2	Retrieving F from the interarrival times distribution	197
14.4.5	Record distances between an observed point and its vertex	197
14.4.5.1	Distribution of records	198
14.4.5.2	Distribution of arrival times for records	199
15	New Perspective on the Riemann Hypothesis	200
15.1	Introduction	200
15.1.1	Key concepts and terminology	201
15.1.2	Orbits and holes	201
15.1.3	Industrial Applications	201
15.2	Euler products	202
15.2.1	Finite Euler Products	202
15.2.1.1	Generalization using Dirichlet characters	203
15.2.2	Infinite Euler products	204
15.2.2.1	Special products	204
15.2.2.2	Probabilistic properties and conjectures	205
15.3	Finite Dirichlet series and generalizations	206
15.3.1	Finite Dirichlet series	206
15.3.2	Non-trivial cases with infinitely many primes and a hole	208
15.3.2.1	Sums of two cubes, or cuban primes	208
15.3.2.2	Primes associated to elliptic curves	208
15.3.2.3	Analytic continuation, convergence, and functional equation	209
15.3.2.4	Hybrid Dirichlet-Taylor series	209
15.3.3	Riemann Hypothesis with cosines replaced by wavelets	210
15.3.4	Riemann Hypothesis for Beurling primes	211
15.3.5	Stochastic Euler products	212
15.4	Exercises	213
15.5	Python code	216
15.5.1	Computing the orbit of various Dirichlet series	216
15.5.2	Creating videos of the orbit	219
16	Miscellaneous Topics	222
16.1	The sound that data makes	222
16.1.1	From data visualizations to videos to data music	222
16.1.2	References	223
16.1.3	Python code	223
16.2	Data videos and enhanced visualizations in R	224
16.2.1	Cairo library to produce better charts	224
16.2.2	AV library to produce videos	225
16.3	Dual confidence regions	226
16.3.1	Case study	226
16.3.2	Standard confidence region	226

16.3.3	Dual confidence region	227
16.3.4	Simulations	227
16.3.5	Original problem with minimum contrast estimators	228
16.3.6	General shape of confidence regions	229
16.4	Fast feature selection based on predictive power	230
16.4.1	How cross-validation works	231
16.4.2	Measuring the predictive power of a feature	231
16.4.3	Efficient implementation	232
16.5	Natural language processing: taxonomy creation	233
16.5.1	Designing a keyword taxonomy	233
16.5.2	Fast clustering algorithm for keyword data	234
16.5.2.1	Computational complexity	234
16.5.2.2	Smart crawling of the whole Internet and a bit of graph theory	234
16.6	Automated detection of outliers and number of clusters	236
16.6.1	Black-box elbow rule to detect outliers	236
16.7	New developments in explainable AI and synthetic data	237
16.7.1	Sensitivity analysis, imputation and other uses of synthetic data	238
16.7.2	Using copulas to generate synthetic data	238
16.7.2.1	The insurance dataset: Python code and results	239
16.8	Advice to beginners	241
16.8.1	Getting started and learning how to learn	241
16.8.1.1	Getting help	241
16.8.1.2	Beyond Python	242
16.8.2	Automated data cleaning and exploratory analysis	242
16.8.3	Example of simple analysis: marketing attribution	242
16.8.4	Upcoming books and courses	243
Glossary		244
Bibliography		247
Index		252

List of Figures

1.1	Fitted ellipse (blue), given the training set (red) distributed around a partial arc	18
1.2	Confidence region in blue, $n = 30$ training set points; 50 training sets (left) vs 150 (right)	19
1.3	Three non-periodic time series made of periodic terms (see section 15.2.2.1)	25
1.4	Training set (red), validation set (orange), fitted curve (blue) and model (gray)	26
1.6	Biased confidence region for (θ_A^*, θ_B^*) ; same example as in Figure 1.5; true value is $(0.5, 1.0)$	29
1.5	Finding the two centers θ_A^*, θ_B^* in sample 39; $n = 1000$	30
1.7	Challenging mixture, requiring $p_A = 3, p_B = 1$ to identify the two cluster centers	31
2.1	Output from the Excel version of HDT	41
3.1	AR models, classified based on the types of roots of the characteristic polynomial	52
4.1	Scatterplot observations vs. predicted values, with prediction intervals (in any dimension)	66
4.2	Comets orbiting the sun: simulation	66
4.3	Comets orbiting the sun: snapshot in time	67
4.4	Three orbits of $\eta(\sigma + it)$: $\sigma = 0.5$ (red), 0.75 (blue) and 1.25 (yellow)	67
4.5	Sample orbit points of $\eta(\sigma + it)$: $\sigma = 0.5$ (red), 0.75 (blue) and 1.25 (yellow)	67
4.6	Sample orbit points of $\eta(\sigma + it)$: $\sigma = 0.5$ (red), 0.75 (blue) and 1.25 (yellow)	68
4.7	Raw orbit points of $\eta(\sigma + it)$: $\sigma = 0.5$ (red), 0.75 (blue) and 1.25 (yellow)	68
4.8	Convergence of partial sums of $\eta(z)$, for six $z = \sigma + it$ in the complex plane	68
5.1	Special interlacing of 4 lattice processes with $s = 0$	71
5.2	Classification of left dataset; $s = 0.15, w = 10$. One loop (middle) vs 3 (right).	72
5.3	Clustering of left dataset; $s = 0.15$, 3 loops, $w = 10$ (middle) vs 20 (right).	73
5.4	Classification ($w = 10$) and clustering ($w = 20$); $s = 0.05$, three loops.	73
5.5	Fractal classification, $s = 0.15$. Loop 6, 250 and 400.	74
5.6	Fractal classification, $s = 0.05$.Loop: 6 and 60.	74
5.7	Fast (left) vs standard method (right), 3 loops, $s = 0.15, w = 10$	75
5.8	Fast method, $s = 0.05, w = 20$. Three loops (middle), one loop (right).	75
6.1	Comparing two shapes	84
6.2	Weighted centroid, shape signature	85
6.3	Weight function used in Figure 6.2	86
6.4	Another interesting shape	87
7.1	Regression coefficients oscillating when using adaptive damping	94
7.2	Convergence of regression coefficients (left) and distribution of residual error (right)	95
7.3	Goodness-of-fit: training set (right) versus validation set (left)	95
8.1	Fuzzy regression with prediction intervals, original version, 1D	102
8.2	Fuzzy regression with prediction intervals, full model, 2D	104
8.3	Scatterplots: median vs weighted method, on validation (left) vs training set (right)	106
8.4	Dirichlet eta function (real part, bottom) and interpolation error (top)	108
9.1	Orbit of $L(z, \chi)$ at $\sigma = \frac{1}{2}$, with $0 < t < 200$ and $\chi = \chi_4$ (left) versus pseudo-random χ (right) . .	115
9.2	$L_3^*(n)$ test statistic for four sequences: Python[200] and SQRT[90,91] fail	117
9.3	$ L_3(n) $ test statistic for four sequences: Python[200] and SQRT[90,91] fail	117
9.4	Correlations are computed on sequences consisting of 300 binary digits	129
10.1	Typical path S_n with $0 \leq n \leq 50,000$ for four types of random walks	131

10.2	$\delta_n = 1 - \text{Var}[S_{n+1}] + \text{Var}[S_n]$ for four types of random walks, with $0 \leq n \leq 5000$	132
10.3	Same as Figure 10.2, using a more aesthetic but less meaningful chart type	133
10.4	Clustered Brownian process	135
10.5	AR models, classified based on the types of roots of the characteristic polynomial	136
11.1	Function $f(b)$ as a better alternative to $g(b)$ in Figure 11.2. Root at $b = 3083$.	140
11.2	Function $g(b) = 2 - \cos(2\pi b) - \cos(2\pi a/b)$, with $a = 3083 \times 7919$.	140
11.3	Transformed function f_3 , amplifying the root at $b = 3083$.	141
11.4	Signal strength ρ_n , first 130 fixed-point iterations; $n = 31$ leads to a root.	144
11.5	(b_n, ρ_n) plot. Yellow and orange dots linked to roots.	144
11.6	Signal strength ρ_n , first 130 fixed-point iterations; $n = 87$ leads to a root.	144
11.7	Random function from section 11.3.1, with root at $b = 5646$.	147
12.1	Six frames from the terrain video, each one containing four images	152
12.2	Contour plot, 3D mixture model, produced with Plotly	160
12.3	Same as Figure 12.2, produced with Matplotlib	161
13.1	Collisions graph for the biggest star eater (star 47) in video 7	168
13.2	Summary statistics for the whole collision structure: the X axis represents the time	169
13.3	Snapshots of universe 4 (left) and universe 7 (right)	170
14.1	Period and amplitude of $\phi_\tau(t)$; here $\tau = 1, \lambda = 1.4, s = 0.3$	178
14.2	A new test of independence (R-squared version)	178
14.3	Radial cluster process ($s = 0.2, \lambda = 1$) with centers in blue; zoom in on the left	181
14.4	Radial cluster process ($s = 2, \lambda = 1$) with centers in blue; zoom in on the left	181
14.5	Manufactured marble lacking true lattice randomness (left)	181
14.6	Four superimposed Poisson-binomial processes: $s = 0$ (left), $s = 5$ (right)	184
14.7	Rayleigh test to assess if a point distribution matches that of a Poisson process	192
14.8	Realization of a 5-interlacing with $s = 0.15$ and $\lambda = 1$: original (left), modulo $2/\lambda$ (right)	195
14.9	Locally random permutation σ ; $\tau(k)$ is the index of X_k 's closest neighbor to the right	195
14.10	Each arrow links a point (blue) to its vertex (red): $s = 0.2$ (left), $s = 1$ (right)	198
14.11	Distance between a point and its vertex ($\lambda = s = 1$)	199
15.1	Three orbits ($\sigma = 0.5, 0.75, 1.25$) with finite Euler product: $P = \{2, 3\}$ (left) vs $\{2, 3, 5\}$ (right)	203
15.2	Distance between orbit and location $(c, 0)$ depending on t on the X-axis	205
15.3	Distance between orbit and location $(c, 0)$ depending on t on the X-axis	205
15.4	Distance between orbit and location $(c, 0)$ depending on t on the X-axis	205
15.5	Four orbits where the “hole” (repulsion basin) is apparent	207
15.6	Three orbits with “hole” closer to the origin, showing impact of $\beta > \frac{1}{2}$ and larger n	207
15.7	Orbit of Dirichlet eta $\eta(z)$ when cosines are replaced by other periodic functions	211
16.1	Data linked to the melody: red curve for note frequencies, blue curve for note durations	223
16.2	R plot before Cairo (left), and after (right)	224
16.3	Intermediate (left) and last frame (right) of the video	225
16.4	Example of 90% dual confidence region for (p, q)	227
16.5	Minimum contrast estimation for (λ, s) using (p, q) as proxy stats	228
16.6	Non-elliptic confidence regions with various confidence levels	229
16.7	Elbow rule (right) finds $m = 3$ clusters in Brownian motion (left)	237

List of Tables

1.1	Estimated ellipse parameters vs true values ($n = 30$), for shape in Figure 1.2	19
1.2	First and last step of <code>curve_fitting</code> , approaching the model.	27
1.3	MSE for different methods and θ s, same data set as in Figure 1.5	32
1.4	MSE for different methods and θ s, same data set as in Figure 1.7	32
2.1	List of potential features to use in the model	37
2.2	Statistics for selected HDT nodes (Excel version)	40
2.3	Order of magnitude for the expectation and standard deviation of the range R_n	44
3.1	Characteristic polynomials used in the simulations	51
7.1	Regression coefficients and performance metrics r, s based on methodology	96
7.2	Correlation matrix	96
7.3	Best performance given m (number of features)	97
7.4	Feature comparison table (top 32 feature combinations)	99
7.5	Feature comparison table (bottom 31 feature combinations)	100
8.1	R -squared ρ^2 and slope β , on training and validation sets, median vs weighted	106
9.1	$L_3^*(n)$, for various sequences ($n = 20,000$); “Fail” means failing the prime test	118
11.1	High ρ_n at iterations $n = 31$ and $n = 127$ points to roots 3083 and 7919	143
13.1	Description of top parameters used in the star cluster simulator	166
13.2	Eight selected parameter sets covering various situations	167
14.1	Variance attached to F_s , as a function of s	177
14.2	Poisson process ($s = \infty$) versus $s = 39.85$	197
16.1	Extract of the mapping table used to recover (λ, s) from (p, q)	229
16.2	Eight bins: 2 features (A, B) times 2 outcomes (Good/Bad)	231
16.3	Amount of data collected at each level, when crawling the Internet	235
16.4	Comparing real data with two different synthetic copies	239

Glossary

Autoregressive process	Auto-correlated time series, as described in section 3.4. Time-continuous versions include Gaussian processes and Brownian motions, while random walks are a discrete example; two-dimensional versions exist. These processes are essentially integrated white noise. See pages 49, 97, 135
Binning	Feature binning consists of aggregating the values of a feature into a small number of bins, to avoid overfitting and reduce the number of nodes in methods such as naive Bayes, neural networks, or decision trees. Binning can be applied to two or more features simultaneously. I discuss optimum binning in this book. See pages 37, 73, 231
Boosted model	Blending of several models to get the best of each one, also referred to as ensemble methods. The concept is illustrated with hidden decision trees in this book. Other popular examples are gradient boosting and AdaBoost. See pages 36, 244
Bootstrapping	A data-driven, model-free technique to estimate parameter values, to optimize goodness-of-fit metrics. Related to resampling in the context of cross-validation. In this book, I discuss parametric bootstrap on synthetic data that mimics the actual observations. See pages 15, 96, 192, 244
Confidence Region	A confidence region of level γ is a 2D set of minimum area covering a proportion γ of the mass of a bivariate probability distribution. It is a 2D generalization of confidence intervals. In this book, I also discuss dual confidence regions – the analogous of credible regions in Bayesian inference. See pages 12, 15, 18, 20, 29, 189, 190, 226, 229
Cross-validation	Standard procedure used in bootstrapping, and to test and validate a model, by splitting your data into training and validation sets. Parameters are estimated based on training set data. An alternative to cross-validation is testing your model on synthetic data with known response. See pages 15, 37, 93, 99, 167, 231, 244
Decision trees	A simple, intuitive non-linear modeling techniques used in classification problems. It can handle missing and categorical data, as well as a large number of features, but requires appropriate feature binning. Typically one blends multiple binary trees each with a few nodes, to boost performance. See pages 36, 37, 39, 41, 244, 245
Dimension reduction	A technique to reduce the number of features in your dataset while minimizing the loss in predictive power. The most well known are principal component analysis and feature selection to maximize goodness-of-fit metrics. See pages 12, 16, 245, 246
Empirical distribution	Cumulative frequency histogram attached to a statistic (for instance, nearest neighbor distances), and based on observations. When the number of observations tends to infinity and the bin sizes tend to zero, this step function tends to the theoretical cumulative distribution function of the statistic in question. See pages 16, 96, 113, 176, 179, 185, 191, 196, 198, 210, 238
Ensemble methods	A technique consisting of blending multiple models together, such as many decision trees with logistic regression, to get the best of each method and outperform each method taken separately. Examples include boosting, bagging, and AdaBoost. In this book, I discuss hidden decision trees. See pages 36, 83, 244
Explainable AI	Automated machine learning techniques that are easy to interpret are referred to as interpretable machine learning or explainable artificial intelligence. As much as possible, the methods discussed in this book belong to that category. The goal is to design black-box systems less likely to generate unexpected results with unintended consequences. See pages 13, 35, 69, 74, 83, 90, 139, 155, 193, 237

Feature selection	Features – as opposed to the model response – are also called independent variables or predictors. Feature selection, akin to dimensionality reduction , aims at finding the minimum subset of variables with enough predictive power . It is also used to eliminate redundant features and find causality (typically using hierarchical Bayesian models), as opposed to mere correlations. Sometimes, two features have poor predictive power when taken separately, but provide improved predictions when combined together. See pages 12, 15, 37, 94, 97, 222, 230, 244, 246
Generative model	Bayesian Gaussian mixtures (GMM) combined with kernel density estimation and the EM algorithm is a classic modeling tool. In this book, I used <i>m</i>-interlacings instead. Generative adversarial networks (GAN) work as follows: the generator creates new observations and the discriminator tests whether the new observations are statistically indistinguishable from training set data. When this goal is achieved, the new observations is your synthetic data. In this book, new observations are generated with parametric bootstrap instead. See pages 35, 52, 99, 150, 151, 153, 160, 167, 246
Goodness-of-fit	A model fitting criterion or metric to assess how a model or sub-model fits to a dataset, or to measure its predictive power on a validation set . Examples include R-squared , Chi-squared, Kolmogorov-Smirnov, error rate such as false positives and other metrics discussed in this book. See pages 15, 56, 93, 94, 231, 244, 246
Gradient methods	Iterative optimization techniques to find the minimum or maximum of a function, such as the maximum likelihood . When there are numerous local minima or maxima, use swarm optimization . Gradient methods (for instance, stochastic gradient descent or Newton's method) assume that the function is differentiable. If not, other techniques such as Monte Carlo simulations or the fixed-point algorithm can be used. Constrained optimization involves using Lagrange multipliers . See pages 15, 31, 55, 89
Graph structures	Graphs are found in decision trees , in neural networks (connections between neurons), in nearest neighbors methods (NN graphs), in hierarchical Bayesian models , and more. See pages 70, 74, 168, 234, 235
Hyperparameter	An hyperparameter is used to control the learning process: for instance, the dimension, the number of features, parameters, layers (neural networks) or clusters (clustering problem), or the width of a filtering window in image processing. By contrast, the values of other parameters (typically node weights in neural networks or regression coefficients) are derived via training. See pages 29, 56, 70, 75, 101, 154, 245
Link function	A link function maps a nonlinear relationship to a linear one so that a linear model can be fit, and then mapped back to the original form using the inverse function. For instance, the logit link function is used in logistic regression . Generalizations include quantile functions and inverse sigmoids in neural network to work with additive (linear) parameters. See pages 13, 16, 245
Logistic regression	A generalized linear regression method where the binary response (fraud/non-fraud or cancer/non-cancer) is modeled as a probability via the logistic link function. Alternatives to the iterative maximum likelihood solution are discussed in this book. See pages 16, 33, 36, 40, 244, 245
Neural network	A blackbox system used for predictions, optimization, or pattern recognition especially in computer vision. It consists of layers, neurons in each layer, link functions to model non-linear interactions, parameters (weights associated to the connections between neurons) and hyperparameters . Networks with several layers are called deep neural networks . Also, neurons are sometimes called nodes. See pages 69, 73, 75, 83, 101, 244, 245
NLP	Natural language processing is a set of techniques to deal with unstructured text data, such as emails, automated customer support, or webpages downloaded with a crawler. The example discussed in section 16.5 deals with creating a keyword taxonomy based on parsing Google search results pages. See pages 36, 233
Numerical stability	This issue occurring in unstable optimization problems typically with multiple minima or maxima, is frequently overlooked and leads to poor predictions or high volatility. It is sometimes referred to as ill-conditioned problems . I explain how to fix it in several examples in this book, for instance in section 3.4.2. Not to be confused with numerical precision. See pages 12, 14, 59

Overfitting	Using too many unstable parameters resulting in excellent performance on the training set , but poor performance on future data or on the validation set . It typically occurs with numerically unstable procedures such as regression (especially polynomial regression) when the training set is not large enough, or in the presence of wide data (more features than observations) when using a method not suited to this situation. The opposite is underfitting. See pages 15, 92, 101, 238, 244, 246
Predictive power	A metric to assess the goodness-of-fit or performance of a model or subset of features, for instance in the context of dimensionality reduction or feature selection . Typical metrics include R-squared , or confusion matrices in classification. See pages 38, 40, 44, 230, 232, 237, 245
R-squared	A goodness-of-fit metric to assess the predictive power of a model, measured on a validation set . Alternatives include adjusted R-squared, mean absolute error and other metrics discussed in this book. See pages 12, 15, 35, 56, 90, 93, 95, 97, 104, 245, 246
Random number	Pseudo-random numbers are sequences of binary digits, usually grouped into blocks, satisfying properties of independent Bernoulli trials. In this book, the concept is formally defined, and strong pseudo-number generators are built and used in computer-intensive simulations. See pages 29, 112, 119, 236
Regression methods	I discuss a unified approach to all regression problems in chapter 1. Traditional techniques include linear, logistic, Bayesian, polynomial and Lasso regression (to deal with numerical instability and overfitting), solved using optimization techniques, maximum likelihood methods, linear algebra (eigenvalues and singular value decomposition) or stepwise procedures. See pages 12, 13, 15, 16, 19, 27, 36, 40, 46, 49, 52, 56, 89, 95, 101, 108, 245, 246
Supervised learning	Techniques dealing with labeled data (classification) or when the response is known (regression). The opposite is unsupervised learning , for instance clustering problems. In-between, you have semi-supervised learning and reinforcement learning (favoring good decisions). The technique described in chapter 1 fits into unsupervised regression. Adversarial learning is testing your model against extreme cases intended to make it fail, to build better models. See pages 246
Synthetic data	Artificial data simulated using a generative model , typically a mixture model , to enrich existing datasets and improve the quality of training sets . Called augmented data when blended with real data. See pages 12, 13, 15, 17, 27, 29, 33, 35, 48, 52, 55, 69, 70, 75, 88, 94, 105, 125, 131, 139, 153, 160, 167, 227, 236, 238, 244
Tensor	Matrix generalization with three or more dimensions. A matrix is a two-dimensional tensor. A triple summation with three indices is represented by a three-dimensional tensor, while a double summation involves a standard matrix. See pages 69, 74
Training set	Dataset used to train your model in supervised learning . Typically, a portion of the training set is used to train the model, the other part is used as validation set . See pages 13, 15, 17, 20, 29, 36, 40, 56, 72, 88, 95, 101, 105, 167, 231, 244, 246
Validation set	A portion of your training set , typically 20%, used to measure the actual performance of your predictive algorithm outside the training set. In cross-validation and bootstrapping, the training and validation sets are split into multiple subsets to get a better sense of variations in the predictions. See pages 15, 27, 41, 56, 93, 101, 167, 231, 238, 244, 245, 246

Bibliography

- [1] Weighted percentiles using numpy. *Forum discussion*, 2020. StackOverflow [\[Link\]](#). 101
- [2] Jan Ackmann et al. Machine-learned preconditioners for linear solvers in geophysical fluid flows. *Preprint*, pages 1–19, 2020. arXiv:2010.02866 [\[Link\]](#). 93
- [3] Noga Alon and Joel H. Spencer. *The Probabilistic Method*. Wiley, fourth edition, 2016. [\[Link\]](#). 185
- [4] José M. Amigó, Roberto Dale, and Piergiulio Tempesta. A generalized permutation entropy for random processes. *Preprint*, pages 1–9, 2012. arXiv:2003.13728 [\[Link\]](#). 196
- [5] Luc Anselin. *Point Pattern Analysis: Nearest Neighbor Statistics*. The Center for Spatial Data Science, University of Chicago, 2016. Slide presentation [\[Link\]](#). 183
- [6] Adrian Baddeley. Spatial point processes and their applications. In Weil W., editor, *Stochastic Geometry. Lecture Notes in Mathematics*, pages 1–75. Springer, Berlin, 2007. [\[Link\]](#). 182
- [7] David Bailey and Richard Crandall. Random generators and normal numbers. *Experimental Mathematics*, 11, 2002. Project Euclid [\[Link\]](#). 128
- [8] N. Balakrishnan and C.R. Rao (Editors). *Order Statistics: Theory and Methods*. North-Holland, 1998. 185, 199
- [9] Christopher Beckham and Christopher Pal. A step towards procedural terrain generation with GANs. *Preprint*, pages 1–5, 2017. arXiv:1707.03383 [\[Link\]](#). 152
- [10] Rabi Bhattacharya and Edward Waymire. *Random Walk, Brownian Motion, and Martingales*. Springer, 2021. 130
- [11] Barbara Bogacka. *Lecture Notes on Time Series*. 2008. Queen Mary University of London [\[Link\]](#). 49
- [12] B. Bollobas and P. Erdös. Cliques in random graphs. *Mathematical Proceedings of the Cambridge Philosophical Society*, 80(3):419–427, 1976. [\[Link\]](#). 186
- [13] Miklos Bona. *Combinatorics of Permutations*. Routledge, second edition, 2012. 196
- [14] Peter Borwein, Stephen K. Choi, and Michael Coons. Completely multiplicative functions taking values in $\{-1, 1\}$. *Transactions of the American Mathematical Society*, 362(12):6279–6291, 2010. [\[Link\]](#). 204
- [15] Peter Borwein and Michael Coons. Transcendence of power series for some number theoretic functions. *Proceedings of the American Mathematical Society*, 137(4):1303–1305, 2009. [\[Link\]](#). 206
- [16] Oliver Bröker and Marcus J. Groteb. Sparse approximate inverse smoothers for geometric and algebraic multigrid. *Applied Numerical Mathematics*, 41(1):61–80, 2002. 90
- [17] H. M. Bui and M. B. Milinovich. Gaps between zeros of the Riemann zeta-function. *Quarterly Journal of Mathematics*, 69(2):402–423, 2018. [\[Link\]](#). 216
- [18] Bartłomiej Błaszczyzyn and Dhandapani Yogeshwaran. Clustering and percolation of point processes. *Preprint*, pages 1–20, 2013. Project Euclid [\[Link\]](#). 182
- [19] Bartłomiej Błaszczyzyn and Dhandapani Yogeshwaran. On comparison of clustering properties of point processes. *Preprint*, pages 1–26, 2013. arXiv:1111.6017 [\[Link\]](#). 182
- [20] Bartłomiej Błaszczyzyn and Dhandapani Yogeshwaran. Clustering comparison of point processes with applications to random geometric models. *Preprint*, pages 1–44, 2014. arXiv:1212.5285 [\[Link\]](#). 182
- [21] Oliver Chikumbo and Vincent Granville. Optimal clustering and cluster identity in understanding high-dimensional data spaces with tightly distributed points. *Machine Learning and Knowledge Extraction*, 1(2):715–744, 2019. 237
- [22] Keith Conrad. *L-functions and the Riemann Hypothesis*. 2018. 2018 CTNT Summer School [\[Link\]](#). 115, 201, 204, 209
- [23] Noel Cressie. *Statistic for Spatial Data*. Wiley, revised edition, 2015. 182

- [24] D.J. Daley and D. Vere-Jones. *An Introduction to the Theory of Point Processes*. Springer, second edition, 2002. Volume 1 – Elementary Theory and Methods. [134](#)
- [25] D.J. Daley and D. Vere-Jones. *An Introduction to the Theory of Point Processes*. Springer, second edition, 2014. Volume 2 – General Theory and Structure. [134](#)
- [26] Tilman M. Davies and Martin L. Hazelton. Assessing minimum contrast parameter estimation for spatial and spatiotemporal log-Gaussian Cox processes. *Statistica Neerlandica*, 67(4):355–389, 2013. [228](#)
- [27] Marc Deisenroth, A. Faisal, and Cheng Soon Ong. *Mathematics for Machine Learning*. Cambridge University Press, 2020. [\[Link\]](#). [53](#)
- [28] Harold G. Diamond and Wen-Bin Zhang. *Beurling Generalized Numbers*. American Mathematical Society, 2016. Mathematical Surveys and Monographs, Volume 213 [\[Link\]](#). [116](#), [212](#)
- [29] D.J. Daley and D. Vere-Jones. *An Introduction to the Theory of Point Processes – Volume I: Elementary Theory and Methods*. Springer, second edition, 2013. [183](#)
- [30] D.J. Daley and D. Vere-Jones. *An Introduction to the Theory of Point Processes – Volume II: General Theory and Structure*. Springer, second edition, 2014. [183](#)
- [31] David Coupier (Editor). *Stochastic Geometry: Modern Research Frontiers*. Wiley, 2019. [193](#)
- [32] Ding-Geng Chen (Editor), Jianguo Sun (Editor), and Karl E. Peace (Editor). *Interval-Censored Time-to-Event Data: Methods and Applications*. Chapman and Hall/CRC, 2012. [184](#)
- [33] Khaled Emam, Lucy Mosquera, and Richard Hoptroff. *Practical Synthetic Data Generation*. O'Reilly, 2020. [99](#)
- [34] Paul Erdős and Alfréd Rényi. On the evolution of random graphs. In *Publication of the Mathematical Institute of the Hungarian Academy of Sciences*, volume 5, pages 17–61, 1960. [\[Link\]](#). [186](#)
- [35] Achim Zeileis et al. Colorspace: A toolbox for manipulating and assessing colors and palettes. *Preprint*, pages 1–45, 2019. arXiv:1903.06490 [\[Link\]](#) [\[R Library\]](#). [152](#)
- [36] Arash Farahmand. *Math 55 Lecture Notes*. 2021. University of Berkeley [\[Link\]](#). [47](#), [53](#)
- [37] W. Feller. On the Kolmogorov-Smirnov limit theorems for empirical distributions. *Annals of Mathematical Statistics*, 19(2):177–189, 1948. [\[Link\]](#). [185](#), [192](#)
- [38] Nikos Frantzikinakis. Ergodicity of the Liouville system implies the Chowla conjecture. *Preprint*, pages 1–41, 2016. arXiv [\[Link\]](#). [206](#)
- [39] P. M. Gauthier. Approximating the Riemann zeta-function by polynomials with restricted zeros. *Canadian Mathematical Bulletin*, 62(3):475–478, 2018. [\[Link\]](#). [216](#)
- [40] P. A. Van Der Geest. The binomial distribution with dependent Bernoulli trials. *Journal of Statistical Computation and Simulation*, pages 141–154, 2004. [\[Link\]](#). [131](#)
- [41] Stamatia Giannarou and Tania Stathaki. Shape signature matching for object identification invariant to image transformations and occlusion. 2007. ResearchGate [\[Link\]](#). [84](#)
- [42] Minas Gjoka, Emily Smith, and Carter Butts. Estimating clique composition and size distributions from sampled network data. *Preprint*, pages 1–9, 2013. arXiv:1308.3297 [\[Link\]](#). [186](#)
- [43] B.V. Gnedenko and A. N. Kolmogorov. *Limit Distributions for Sums of Independent Random Variables*. Addison-Wesley, 1954. [135](#)
- [44] Manuel González-Navarrete and Rodrigo Lambert. Non-markovian random walks with memory lapses. *Preprint*, pages 1–14, 2018. arXiv [\[Link\]](#). [130](#)
- [45] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016. [\[Link\]](#). [53](#)
- [46] Vincent Granville. Estimation of the intensity of a Poisson point process by means of nearest neighbor distances. *Statistica Neerlandica*, 52(2):112–124, 1998. [\[Link\]](#). [183](#)
- [47] Vincent Granville. *Applied Stochastic Processes, Chaos Modeling, and Probabilistic Properties of Numeration Systems*. MLTechniques.com, 2018. [\[Link\]](#). [116](#)
- [48] Vincent Granville. *Stochastic Processes and Simulations: A Machine Learning Perspective*. MLTechniques.com, 2022. [\[Link\]](#). [51](#), [59](#), [135](#), [145](#), [176](#), [177](#), [178](#), [180](#), [184](#), [186](#), [212](#), [216](#), [229](#), [243](#)
- [49] Vincent Granville, Mirko Krivanek, and Jean-Paul Rasson. Simulated annealing: A proof of convergence. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 16:652–656, 1996. [72](#)
- [50] Vincent Granville and Richard L Smith. Disaggregation of rainfall time series via Gibbs sampling. *NISS Technical Report*, pages 1–21, 1996. [\[Link\]](#). [107](#)
- [51] Kristen Grauman. Shape matching. 2008. University of Texas, Austin [\[Link\]](#). [87](#)
- [52] Hui Guo et al. Eyes tell all: Irregular pupil shapes reveal gan-generated faces. *Preprint*, pages 1–7, 2021. arXiv:2109.00162 [\[Link\]](#). [238](#)

- [53] Aurélien Géron. *Hands-On Machine Learning with Scikit-Learn, Keras & TensorFlow*. O'Reilly, third edition, 2023. [35](#)
- [54] Radim Halir and Jan Flusser. Numerically stable direct least squares fitting of ellipses. *Preprint*, pages 1–8, 1998. [\[Link\]](#). [17](#), [19](#)
- [55] Peter Hall. *Introduction to the theory of coverage processes*. Wiley, 1988. [193](#)
- [56] Adam J. Harper. Moments of random multiplicative functions, II: High moments. *Algebra and Number Theory*, 13(10):2277–2321, 2019. [\[Link\]](#). [112](#), [212](#)
- [57] Adam J. Harper. Moments of random multiplicative functions, I: Low moments, better than squareroot cancellation, and critical multiplicative chaos. *Forum of Mathematics, Pi*, 8:1–95, 2020. [\[Link\]](#). [112](#), [114](#), [212](#)
- [58] Adam J. Harper. Almost sure large fluctuations of random multiplicative functions. *Preprint*, pages 1–38, 2021. arXiv [\[Link\]](#). [114](#), [206](#), [212](#)
- [59] K. Hartmann, J. Krois, and B. Waske. *Statistics and Geospatial Data Analysis*. Freie Universität Berlin, 2018. E-Learning Project SOGA [\[Link\]](#). [179](#)
- [60] D. R. Heath-Brown. Primes represented by $x^3 + 2y^3$. *Acta Mathematica*, 186:1–84, 2001. [\[Link\]](#). [208](#)
- [61] T. W. Hilberdink and M. L. Lapidus. Beurling Zeta functions, generalised primes, and fractal membranes. *Preprint*, pages 1–31, 2004. arXiv [\[Link\]](#). [115](#), [116](#), [212](#)
- [62] Christian Hill. *Learning Scientific Programming with Python*. Cambridge University Press, 2016. [\[Link\]](#). [19](#)
- [63] Robert V. Hogg, Joseph W. McKean, and Allen T. Craig. *Introduction to Mathematical Statistics*. Pearson, eighth edition, 2016. [\[Link\]](#). [53](#)
- [64] Zhiqiu Hu and Rong-Cai Yang. A new distribution-free approach to constructing the confidence region for multiple parameters. *PLOS One*, pages 1–13, 2013. [\[Link\]](#). [227](#)
- [65] Peter Humphries. The distribution of weighted sums of the Liouville function and Pólya's conjecture. *Preprint*, pages 1–33, 2011. arXiv [\[Link\]](#). [213](#)
- [66] Timothy D. Johnson. Introduction to spatial point processes. *Preprint*, page 2008. NeuroImaging Statistics Oxford (NISOx) group [\[Link\]](#)[\[Mirror\]](#). [183](#)
- [67] Chigozie Kelechi. Towards efficiency in the residual and parametric bootstrap techniques. *American Journal of Theoretical and Applied Statistics*, 5(5), 2016. [\[Link\]](#). [97](#)
- [68] Denis Kojevnikov, Vadim Marmer, and Kyungchul Song. Limit theorems for network dependent random variables. *Journal of Econometrics*, 222(2):419–427, 2021. [\[Link\]](#). [183](#)
- [69] Samuel Kotz, Tomasz Kozubowski, and Krzysztof Podgorski. *The Laplace Distribution and Generalizations: A Revisit with Applications to Communications, Economics, Engineering, and Finance*. Springer, 2001. [197](#)
- [70] Faraj Lagum. *Stochastic Geometry-Based Tools for Spatial Modeling and Planning of Future Cellular Networks*. PhD thesis, Carleton University, 2018. [\[Link\]](#). [182](#)
- [71] Günther Last and Mathew Penrose. *Lectures on the Poisson Process*. Cambridge University Press, 2017. [182](#)
- [72] Yuk-Kam Lau, Gerald Tenenbaum, and Jie Wu. On mean values of random multiplicative functions. *Proceedings of the American Mathematical Society*, 142(2):409–420, 2013. [\[Link\]](#). [112](#), [114](#)
- [73] Jing Lei et al. Distribution-free predictive inference for regression. *Journal of the American Statistical Association*, 113:1094–1111, 2018. [\[Link\]](#). [97](#)
- [74] G. Last M.A. Klatt and D. Yogeshwaran. Hyperuniform and rigid stable matchings. *Random Structures and Algorithms*, 2:439–473, 2020. [\[Link\]](#)[\[PowerPoint\]](#). [182](#)
- [75] Jorge Mateu, Frederic P Schoenberg, and David M Diez. On distances between point patterns and their applications. *Preprint*, pages 1–29, 2010. [\[Link\]](#). [183](#)
- [76] Natarajan Meghanathan. Distribution of maximal clique size of the vertices for theoretical small-world networks and real-world networks. *Preprint*, pages 1–20, 2015. arXiv:1508.01668 [\[Link\]](#). [186](#)
- [77] Masahiro Mine. Probability density functions attached to random Euler products for automorphic L-functions. *Preprint*, pages 1–38, 2020. arXiv [\[Link\]](#). [212](#), [213](#)
- [78] Christoph Molnar. *Interpretable Machine Learning*. ChristophMolnar.com, 2022. [\[Link\]](#). [97](#), [237](#)
- [79] Marc-Andreas Muendler. Linear difference equations and autoregressive processes. 2000. University of Berkeley [\[Link\]](#). [49](#)

- [80] V. Kumar Murty. Seminar on Fermat's last theorem. In *Canadian Mathematical Society – Conference Proceedings*, volume 17, Toronto, Canada, 1995. [Link]. 209
- [81] Peter Mörters and Yuval Peres. *Brownian Motion*. Cambridge University Press, 2010. Cambridge Series in Statistical and Probabilistic Mathematics, Volume 30 [Link]. 130, 134
- [82] Jesper Møller. Introduction to spatial point processes and simulation-based inference. In *International Center for Pure and Applied Mathematics (Lecture Notes)*, Lomé, Togo, 2018. [Link][Mirror]. 183, 196, 228
- [83] Jesper Møller and Rasmus P. Waagepetersen. *An Introduction to Simulation-Based Inference for Spatial Point Processes*. Springer, 2003. 183
- [84] Jesper Møller and Rasmus P. Waagepetersen. *Statistical Inference and Simulation for Spatial Point Processes*. CRC Press, 2007. 183
- [85] S. Ghosh N., Miyoshi, and T. Shirai. Disordered complex networks: energy optimal lattices and persistent homology. *Preprint*, pages 1–44, 2020. arXiv:2009.08811. 176
- [86] Saralees Nadarajah. A modified Bessel distribution of the second kind. *Statistica*, 67(4):405–413, 2007. [Link]. 197
- [87] Hasan Nasab, Mahdi Tavana, and Mohsen Yousefu. A new heuristic algorithm for the planar minimum covering circle problem. *Production and Manufacturing Research*, pages 142–155, 2014. [Link]. 193
- [88] Guillermo Navas-Palencia. Optimal binning: mathematical programming formulation. *Preprint*, pages 1–21, 2020. arXiv:2001.08025 [Link]. 37
- [89] Nathan Ng. Large gaps between the zeros of the Riemann zeta function. *Journal of Number Theory*, 128(3):509–556, 2007. [Link]. 216
- [90] Yosihiko Ogata. Cluster analysis of spatial point patterns: posterior distribution of parents inferred from offspring. *Japanese Journal of Statistics and Data Science*, 3:367–390, 2020. 182
- [91] Fred Park. Shape descriptor / feature extraction techniques. 2011. UCI iCAMP 2011 [Link]. 84
- [92] Yuval Peres and Allan Sly. Rigidity and tolerance for perturbed lattices. *Preprint*, pages 1–20, 2020. arXiv:1409.4490 [Link]. 176, 182
- [93] Carl Rasmussen and Christopher Williams. *Gaussian Processes for Machine Learning*. MIT Press, 2006. [Link]. 52
- [94] Kamron Saniee. A simple expression for multivariate Lagrange interpolation. *SIAM Undergraduate Research Online*, 2007. SIURO [Link]. 103
- [95] Karl Sigman. Notes on the Poisson process. New York NY, 2009. IEOR 6711: Columbia University course [Link]. 182
- [96] Joshua Snoke et al. General and specific utility measures for synthetic data. *Journal of the Royal Statistical Society Series A*, 181:663–688, 2018. arXiv:1604.06651 [Link]. 35
- [97] Luuk Spreeuwiers. *Image Filtering with Neural Networks: Applications and Performance Evaluation*. PhD thesis, University of Twente, 1992. 73
- [98] J. Michael Steele. Le Cam's inequality and Poisson approximations. *The American Mathematical Monthly*, 101(1):48–54, 1994. [link]. 145
- [99] Dietrich Stoyan, Wilfrid S. Kendall, Sung Nok Chiu, and Joseph Mecke. *Stochastic Geometry and Its Applications*. Wiley, 2013. 193
- [100] E.C. Titchmarsh and D.R. Heath-Brown. *The Theory of the Riemann Zeta-Function*. Oxford Science Publications, second edition, 1987. 58, 115, 201
- [101] Chris Tofallis. Fitting equations to data with the perfect correlation relationship. *Preprint*, pages 1–11, 2015. Hertfordshire Business School Working Paper[Link]. 13
- [102] D. Umbach and K.N. Jones. A few methods for fitting circles to data. *IEEE Transactions on Instrumentation and Measurement*, 52(6):1881–1885, 2003. [Link]. 14, 17
- [103] D. A. Vaccari and H. K. Wang. Multivariate polynomial regression for identification of chaotic time series. *Mathematical and Computer Modelling of Dynamical Systems*, 13(4):1–19, 2007. [Link]. 17
- [104] Remco van der Hofstad. *Random Graphs and Complex Networks*. Cambridge University Press, 2016. [Link]. 185
- [105] Yu Vizilter and Sergey Zheltov. Geometrical correlation and matching of 2D image shapes. 2012. ResearchGate [Link]. 86
- [106] Luyao Wang and Hai Cheng. Pseudo-random number generator based on logistic chaotic system. *Entropy*, 21, 2019. [Link]. 128

- [107] Mingguang Wu, Yanjie Sun, and Yaqian Li. Adaptive transfer of color from images to maps and visualizations. *Cartography and Geographic Information Science*, pages 289–312, 2021. [\[Link\]](#). 152
- [108] Lan Wu, Yongcheng Qi, and Jingping Yang. Asymptotics for dependent Bernoulli random variables. *Statistics and Probability Letters*, pages 455–463, 2012. [\[Link\]](#). 130
- [109] Oren Yakir. Recovering the lattice from its random perturbations. *Preprint*, pages 1–18, 2020. arXiv:2002.01508 [\[Link\]](#). 182
- [110] Ruqiang Yan, Yongbin Liub, and Robert Gao. Permutation entropy: A nonlinear statistical measure for status characterization of rotary machines. *Mechanical Systems and Signal Processing*, 29:474–484, 2012. 196
- [111] Shaohong Yan, Aimin Yang, et al. Explicit algorithm to the inverse of Vandermonde matrix. In *2009 International Conference on Test and Measurement*, 2009. IEEE [\[Link\]](#). 47
- [112] D. Yogeshwaran. Geometry and topology of the boolean model on a stationary point processes : A brief survey. *Preprint*, pages 1–13, 2018. Researchgate [\[Link\]](#). 183
- [113] Tonglin Zhang. A Kolmogorov-Smirnov type test for independence between marks and points of marked point processes. *Electronic Journal of Statistics*, 8(2):2557–2584, 2014. 178

Index

- α -compositing, 57
- m -interlacing, 71, 183, 191, 194, 245
- A/B testing, 243
- AdaBoost, 36, 244
- additive number theory, 208, 215
- adversarial learning, 238, 246
- AI-art, 160
- algebraic number, 117
- analytic continuation, 202, 209
- analytic function, 115
- anisotropy, 169, 190, 196
- anti-aliasing, 55, 59, 219, 224
- association rule, 232
- attraction (point process), 181
- attraction basin, 58
- attractor distribution, 135, 185, 191, 198
- augmented data, 35, 88, 151, 153, 246
- auto-correlation, 49, 116
- auto-regressive process, 49, 135, 244
- Bailey–Borwein–Plouffe formulas, 117
- Bayesian classification, 74
- Bayesian inference, 44
 - hierarchical models, 245
 - naive Bayes, 232
- Bernoulli trials, 226
- Berry-Esseen inequality, 113
- Bessel function, 197
- Beurling primes, 116, 212
- binning, 231
 - optimum binning, 37, 244
- binomial distribution, 191
- bisection method (root finding), 142
- bootstrapping, 15, 96, 192
 - percentile method, 101
- boundary effect, 178, 179, 184, 185, 189–191, 195
- Brownian motion, 51, 130, 134, 151, 152, 167, 236, 244
 - Lévy flight, 135
- Brun's theorem, 208
- Cauchy distribution, 135
- Cauchy-Riemann equations, 115
- causality, 245
- Cayley-Hamilton theorem, 47
- CDF regression, 17
- censored data, 184
- central limit theorem, 135, 176, 226
- chaotic dynamical system, 151, 167
- character
 - principal, 204
- characteristic function, 197
- characteristic polynomial, 47, 49, 50, 136
- Chebyshev's bias (prime numbers), 115, 204
- checksum, 242
- Chi-squared test, 178
- Chowla conjecture, 206
- classification, 246
- clique (graph theory), 186
- cluster process, 180, 184, 191
- clustering, 246
- Collatz conjecture, 123
- collision graph, 167
- color model
 - RGB, 55, 225
 - RGBA, 55, 56, 76, 225
- color opacity, 161
- color transparency, 20, 153, 225
- complex random variable, 112, 212
- computational complexity, 125, 233
- computer vision, 12, 83
- confidence band, 192
- confidence interval, 44, 189, 244
- confidence level, 226, 229
- confidence region, 15, 29, 189, 190, 226, 238
 - dual region, 44, 227, 244
- conformal map, 14
- confusion matrix, 231, 246
- connected components, 168, 184–186, 190, 191, 234
- contour level, 160, 229
- contour plot, 229
- convergence
 - abscissa, 204, 209
 - absolute, 201, 202
 - alternating series, 202
 - conditional, 114, 204
 - Dirichlet test, 202
- convergence acceleration, 59
- convex linear combination, 108
- convolution of distributions, 197
- copula, 99, 238
 - counting measure, 177
- covariance matrix, 90, 226
- covering (stochastic), 193
- covering problem, 192
- credible interval, 44
- credible region (Bayesian), 227, 244
- cross-validation, 15, 167, 231
- cuban primes, 208
- curve fitting, 26

data video, 151, 160
 decision tree, 36
 Dedekind zeta function, 115, 212
 deep neural network, 73, 245
 dense set (topology), 206
 density estimation, 183
 diamond-square algorithm, 152
 Diehard tests of randomness, 114
 dimensionality reduction, 16
 Dirichlet character, 115, 116, 203, 208
 modulo 4, 204, 209, 210
 Dirichlet eta function, 216
 Dirichlet functional equation, 115, 209, 210
 Dirichlet series, 112
 Dirichlet's theorem, 115, 204, 206, 210
 Dirichlet- L function, 115, 203, 210
 dissimilarity metric, 233
 distributed architecture, 230
 distribution
 Cauchy, 135
 Fréchet, 51, 135
 Gaussian, 226
 generalized logistic, 90, 180
 Hotelling, 227
 Laplace, 197
 logistic, 16
 Lévy, 135
 modified Bessel, 197
 Poisson-binomial, 145, 199
 Poisson-exponential, 176
 Rademacher, 112, 113
 Rayleigh, 191, 192, 198
 Weibull, 51, 135, 191
 domain of attraction, 185
 dot product, 14
 dummy variable, 36
 dyadic map, 116
 dynamical systems, 116, 185
 chaotic systems, 151, 167
 dyadic map, 116
 ergodicity, 116
 logistic map, 116
 shift map, 116
 stochastic, 152
 edge effect (statistics), 184
 eigenvalue, 13, 52, 90, 246
 power iteration, 92
 elbow rule, 139, 184, 191, 236
 elliptic curve, 208
 EM algorithm, 35, 245
 empirical distribution, 16, 96, 176, 179, 185, 191, 196,
 198, 210, 238
 multivariate, 113
 empirical quantiles, 101
 ensemble methods, 36, 83
 entropy, 170, 196, 232
 equidistribution modulo 1, 119
 equilibrium distribution, 152
 Erdős-Rényi model, 186
 ergodicity, 116, 152, 189, 191, 197
 Euler product, 112, 202, 209
 random, 212
 Euler's transform, 216
 evolutionary process, 151
 experimental design, 243
 experimental math, 56, 200
 explainable AI, 13, 35, 74, 83, 90, 139, 155, 193, 237
 exploratory analysis, 242
 exponential decay, 40
 exponential sums, 209
 extrapolation, 108
 extreme value theory, 135, 198
 feature attribution, 237
 feature importance, 237
 feature selection, 15, 97, 230
 Fermat's last theorem, 209
 fixed-point algorithm, 59, 89, 139, 245
 flag vector, 232, 243
 Fourier transform, 197
 fractal dimension, 51
 fractional part function, 118
 Frobenius norm, 90
 Fruchterman and Reingold algorithm, 234
 Fréchet distribution, 51, 135
 fuzzy classification, 56
 Gamma function, 51, 135
 GAN (generative adversarial networks), 35, 245
 Gaussian circle problem, 215
 Gaussian distribution, 226
 Gaussian mixture, 35, 70
 Gaussian primes, 115, 211
 Gaussian process, 49, 244
 general linear model, 13
 generalized linear model, 13, 48
 generalized logistic distribution, 90, 190
 generative adversarial networks, 35, 155, 238, 245
 generative model, 35, 52, 99, 150, 151, 153, 160, 167,
 246
 geostatistics, 102
 Glivenko-Cantelli theorem, 210
 GMM (Gaussian mixture model), 35, 245
 Goldbach's conjecture, 208
 goodness-of-fit, 56, 231
 GPU-based clustering, 71
 gradient (optimization), 139
 gradient boosting, 244
 gradient operator, 15
 graph, 184
 collision graph, 167
 connected components, 168, 190, 234
 directed, 168
 edge, 184
 Fruchterman-Reingold, 168
 nearest neighbor graph, 186, 190
 node, 184, 186
 random graph, 185
 random nearest neighbor graph, 185
 tree, 168
 undirected, 184–186, 191

vertex, 184
 graph database, 234
 graph theory, 184
 GraphViz, 168
 greedy algorithm, 215
 grid search, 139, 154
 half-tone (music), 222
 Hartman–Wintner theorem, 130
 hash table, 126, 170, 195, 232, 233
 sparse, 232
 Hausdorff distance, 87
 Hellinger distance, 238
 hexagonal lattice, 184
 hidden decision trees, 36, 37, 244
 hidden layer, 73
 hidden process, 176, 194, 198
 hierarchical clustering, 73, 233
 Hilbert primes, 211
 histogram equalization, 71, 73
 Hoeffding inequality, 133
 homogeneity (point process), 145, 183
 Hotelling distribution, 227
 Hurst exponent, 51
 hyperparameter, 29, 56, 103, 154
 identifiability, 194, 196
 ill-conditioned problem, 26, 52, 92, 245
 image segmentation, 73
 imputation (missing values), 238
 index
 index discrepancy, 196
 intensity (stochastic process), 176, 183, 190
 interarrival times, 134, 176, 185, 189, 196
 standardized, 197
 interlaced processes, 183
 Internet of Things, 176
 inverse distance weighting, 104
 inverse square law, 164
 iterated logarithm, 113, 114, 130
 Itô integral, 52
 K-means clustering, 31, 32
 key-value pair, 37, 232
 Kolmogorov-Smirnov test, 113, 178, 185
 Kronecker's theorem, 206, 214
 Lagrange interpolation, 52
 Lagrange multiplier, 15, 245
 Laplace distribution, 197
 Lasso regression, 15, 246
 lattice, 182
 perturbed lattice, 176
 shifted, 184
 stretched, 184
 law of the iterated logarithm, 113, 114, 130, 206, 212
 Le Cam's theorem, 145, 177
 least absolute residuals, 101
 link function, 13, 16
 Liouville function, 203, 214
 log-polar map, 14
 logistic distribution, 16, 183
 logistic map, 116
 logistic regression, 16
 unsupervised, 33
 logit function, 245
 Lévy distribution, 135
 Lévy flight, 135
 Map-reduce, 230
 marketing attribution, 242
 Markov chain, 49
 MCMC, 112
 Mathematica, 229
 MaxCliqueDyn algorithm, 186
 maximum likelihood estimation, 228, 245, 246
 mean squared error, 15, 30
 medoid, 31
 Mersenne twister, 29, 116, 119, 132
 Mertens function, 203
 minimum contrast estimation, 154, 193, 196, 228
 mixture model, 29, 45, 152, 160, 176, 183, 184, 191, 229, 246
 blending, 152
 model fitting, 56, 245
 model identifiability, 15
 modulus (complex number), 136, 202
 Monte Carlo simulations, 112, 245
 morphing (computer vision), 151
 moving average, 141
 multiplicative function
 completely multiplicative, 112, 114, 203, 204, 215
 Rademacher, 112
 Möbius function, 203
 N-body problem, 164
 n-gram (NLP), 233
 naive Bayes, 232, 244
 natural language processing, 36, 233
 nearest neighbor interpolation, 101, 104
 nearest neighbors, 176, 186, 192, 245
 nearest neighbor distances, 190–192, 194, 198
 nearest neighbor graph, 190
 NetworkX, 168
 neural network, 73
 hidden layer, 73
 hyperparameter, 75
 neuron, 73, 245
 seq2seq, 150
 sparse, 69
 very deep, 73
 Newton's method, 139
 node (decision tree), 37, 244
 perfect node, 44
 usable node, 38
 normal number, 113, 206, 210
 strongly normal, 114
 numerical stability, 47
 Omega function, 203, 209
 order statistics, 198
 ordinary least squares, 49, 101
 outliers, 198, 236

overfitting, 15, 196, 238, 244
 palette, 151, 225
 parametric bootstrap, 20, 29, 35, 97, 192, 238, 244, 245
 partial least squares, 13
 path (graph theory), 184
 percentile bootstrap, 101
 permutation
 entropy, 196
 random permutation, 195
 perturbed lattices, 176
 Plotly, 160
 point count distribution, 177, 190, 193
 point process
 attractive, 191
 cluster process
 Matérn, 182
 Neyman-Scott, 182
 non-homogeneous, 145, 183
 perturbed lattice process, 182
 radial, 183
 renewal process, 182
 repulsive, 181
 Poisson point process, 134, 145, 176, 190
 Poisson-binomial distribution, 145, 176, 199
 Poisson-exponential distribution, 176
 positive semidefinite (matrix), 48, 91
 power iteration, 92
 preconditioning, 92
 prediction interval, 15, 96, 101
 predictive power, 37, 44, 231, 232, 237
 prime test (of randomness), 114, 125, 131
 principal component analysis, 47, 237, 244
 probability generating function, 131
 proxy space, 229
 pseudo-inverse matrix, 48
 pseudo-random numbers, 132, 236
 combined generators, 128
 congruential generator, 119
 Diehard tests, 114, 126
 Mersenne twister, 119, 132, 153
 prime test, 114, 131
 strongly random, 114, 117
 TestU01, 114
 Pólya conjecture, 205
 quadratic irrational, 116, 119, 125
 quantile, 227, 245
 empirical, 101, 238
 weighted, 101
 quantile function, 99, 176, 180, 191
 quantile regression, 15
 R-squared, 15, 35, 154
 Rademacher distribution, 113
 Rademacher function, 112, 206, 212
 random, 114
 random function, 144
 random graph, 185, 186
 random multiplicative function, 112
 Rademacher, 114
 random permutation, 195
 random variable
 complex, 112
 random walk, 130, 154, 244
 first hitting time, 131, 134
 zero crossing, 130
 Rayleigh distribution, 191, 192, 198
 Rayleigh test, 191
 records, 198
 regression splines, 13
 regular expression, 233, 242
 reinforcement learning, 246
 rejection sampling, 239
 renewal process, 182
 repulsion (point process), 181, 192
 repulsion basin, 202
 resampling, 96, 192
 Riemann Hypothesis, 107
 Generalized, 114, 204, 208, 210
 Riemann zeta function, 112, 115, 210, 212
 root mean squared error, 56
 scaling factor, 190, 198
 seed (random number generator), 126, 153, 238
 semi-supervised learning, 246
 shape signature, 84
 Shapley value, 237
 Shepard's method, 104
 shift map, 116
 sigmoid function, 245
 simplex, 213
 singular value decomposition, 13, 246
 singularity, 170
 six degrees of separation, 235
 Sklar's theorem, 238
 smoothing parameter, 103
 spatial statistics, 102, 182
 spectral domain, 152
 square root (matrix), 48, 91
 square-free integer, 113, 126, 206
 stable distribution, 135, 153, 197
 state space, 152
 stationary distribution, 52
 stationary process, 49, 135, 152, 167, 178, 183, 190
 stepwise regression, 98
 stochastic convergence, 152
 stochastic function, 51
 stochastic geometry, 193
 stochastic process, 176
 stochastic residues, 194
 stop word (NLP), 233
 stretching (point process), 184
 superimposition (point processes), 183
 supervised classification, 71
 surface plot, 160
 swarm optimization, 27, 245
 synthetic data, 13, 27, 29, 52, 88, 90, 125, 131, 139, 153, 160, 167, 200, 227, 238
 synthetic metric, 232
 Tarjan's algorithm, 234

tensor, 74
text normalization, 233
Theil-Sen estimator, 101
time series, 50
 auto-regressive, 50, 135
 disaggregation, 107
 Hurst exponent, 51
 non-periodic, 25
total least squares, 13
training set, 101, 167, 231
transcendental number, 117
transformer, 73, 150
tree (graph theory), 168
twin primes, 208

universality property, 202, 206, 208
unsupervised clustering, 71
unsupervised learning, 33, 246

validation set, 15, 56, 101, 167, 231, 238
Vandermonde matrix, 47, 52
vertex, 176, 184, 185, 198
video compression
 FFmpeg, 55, 59

Waring's problem, 208
Watts and Strogatz model, 235
Weibull distribution, 51, 135, 191, 198
weighted least squares, 13
weighted quantiles, 101
weighted regression, 16
white noise, 27, 49, 135, 244
wide data, 246

XOR operator, 119