

Synthetic Data and Generative AI



Preface

This book was first started in December 2022 and has been revised and augmented multiple times since the first writing. It now covers all the modern techniques on the subject as well as efficient proprietary methods developed by the author, with real industry use cases and Python implementations. The goal is to quickly help you pick up the right tool and run the code on your own dataset, in very little time. Yet the author provides enough background so that the reader understands all the aspects and interconnections of the methods involved, their strengths and weaknesses, potential enhancements, rule of thumbs, and best practices. Research-level material is also present throughout the book, and explained in simple English.

What is synthetic data and why use it?

Synthetic data is more than simulations, mimicking real data, fake (gibberish) data or noise injection to add variations to real data. It is defined by its usage and purpose. Four broad areas include:

- Data augmentation to produce richer training sets for predictive modeling; it leads to more robust predictions and reduced overfitting. For instance, to produce a better version of ChatGPT or better detection of cancer from medical images or tabular data.
- Generation of diversified data to test and benchmark machine learning algorithms, to identify their limits or to understand and improve black-box systems. Sensitivity testing fits in this category.
- Increasing security and compliance with data protection laws by strongly anonymizing data (especially for data sharing purposes), as well as reduction of algorithm bias impacting minorities.
- Data re-balancing in the presence of small segments (fraud / non-fraud, minority group), and smart data imputation. It is also useful in the presence of small samples with many features, when the data is difficult to obtain: for instance, clinical trials.

The data can be tabular (transactional), time series, graphs or consisting of images, videos, sound, text, spatial information or the result of agent-based systems. The goal is to identify and reproduce the structure (such as the autocorrelation function, shape, or correlation structure) rather than replicating the original data itself. In some instances (benchmarking), no real data is even needed.

Several techniques can be used for synthetization: GAN (generative adversarial networks), GMM (Gaussian mixture models) and other statistical models, interpolation, parametric noise with a target correlation structure, and more. Many metrics are available to assess the quality, be it cross-validation, ROC curves, statistical summaries, or Hellinger and related distances. All this material is reviewed in this book. In particular, chapter 10 discusses a GAN with replicable output especially designed for synthetization, illustrated on tabular data.

Book contents and target audience

This book covers the foundations of generative models and data synthetization. Emphasis is on scalability, automation, testing, optimizing, and interpretability (explainable AI). Models (including GMM, GAN and copulas) are often used to create rich synthetic data, augment real data, or to test and benchmark various methods. Many machine learning algorithms are revisited, simplified, unified, and generalized. For instance, regression techniques – including logistic and Lasso – are presented as a single method, without using advanced linear algebra. There is no need to learn 50 versions when one does it all and more. Confidence regions and prediction intervals are built using parametric bootstrap, without statistical models or probability distributions: it shows another usage of synthetization, with an application to meteorites shapes, for instance when the goal is to classify these celestial bodies.

With a focus on applications, synthetization and simulations, the book also covers clustering and classification, GPU machine learning, ensemble methods including an original boosting technique, elements of graph modeling, deep neural networks, auto-regressive and non-periodic time series, Brownian motions and related

processes, simulations, interpolation, strong random numbers, natural language processing (smart crawling, taxonomy creation and structuring unstructured data), computer vision (shapes generation and recognition), curve fitting, cross-validation, goodness-of-fit metrics, feature selection, curve fitting, gradient methods, optimization techniques and numerical stability.

Chapter 10 illustrates the use of copulas to produce synthetic data, applied to a well-known insurance dataset. It also features both GAN (generative adversarial networks) and copulas applied to an health industry data set, comparing results and showing how both methods can be blended for better synthetization and predictions, or even for data compression. Agent-based modeling and GIS applications are also covered, with interpolation techniques used for synthetization: fractal-like terrain generation with the diamond-square algorithm, disaggregation of ocean tides time series, and geospatial interpolation of temperatures in the Chicago area.

Image and video generation include star clusters evolving over time and bound by gravity, providing potential scenarios about the past and future of our universe, or to synthesize collision graphs. It also allows you to explore alternative universes, for instance with negative masses. Chapters 16 and 17 are more advanced and may be skipped in introductory classes. The former focuses on point processes as a simple alternative to GMM. The later features synthetic multiplicative functions to discover new insights about a famous mathematical conjecture: the Riemann Hypothesis.

Methods are accompanied by enterprise-grade Python code, replicable datasets and visualizations, including data animations (gifs, videos, even sound done in Python). The code uses various data structures and library functions sometimes with advanced options. It constitutes a solid introduction to scientific programming. The code, datasets, spreadsheets and data visualizations are also on GitHub, [here](#). Chapters are mostly independent from each other, allowing you to read in random order. A glossary, index and numerous cross-references make the navigation easy and unify all the chapters.

The style is very compact, getting down to the point quickly, and suitable to business professionals. Jargon and arcane theories are absent, replaced by simple English to facilitate the reading by non-experts, and to help you discover topics usually made inaccessible to beginners. While state-of-the-art research is presented in all chapters, the prerequisites to read this book are minimal: an analytic professional background, or a first course in calculus and linear algebra. The original presentation avoids all unnecessary math and statistics, yet without eliminating advanced topics. Finally, this book is the main reference for my course on synthetic data and generative AI.

About the author

Vincent Granville is a pioneering data scientist and machine learning expert, co-founder of Data Science Central (acquired by a publicly traded company in 2020), founder of [MLTechniques.com](#), former VC-funded executive, author and patent owner. Vincent's past corporate experience includes Visa, Wells Fargo, eBay, NBC, Microsoft, and CNET.



Vincent is also a former post-doc at Cambridge University, and the National Institute of Statistical Sciences (NISS). He published in *Journal of Number Theory*, *Journal of the Royal Statistical Society* (Series B), and *IEEE Transactions on Pattern Analysis and Machine Intelligence*. He is also the author of multiple books, available [here](#). He lives in Washington state, and enjoys doing research on stochastic processes, dynamical systems, experimental math and probabilistic number theory.

Contents

List of Figures	10
List of Tables	12
1 Machine Learning Cloud Regression and Optimization	13
1.1 Introduction: circle fitting	13
1.1.1 Previous versions of my method	14
1.2 Methodology, implementation details and caveats	15
1.2.1 Solution, R-squared and backward compatibility	15
1.2.2 Upgrades to the model	16
1.3 Case studies	17
1.3.1 Logistic regression, two ways	17
1.3.2 Ellipsoid and hyperplane fitting	18
1.3.2.1 Curve fitting: 250 examples in one video	18
1.3.2.2 Confidence region for the fitted ellipse: application to meteorite shapes	19
1.3.2.3 Python code	20
1.3.3 Non-periodic sum of periodic time series: ocean tides	26
1.3.3.1 Numerical instability and how to fix it	27
1.3.3.2 Python code	28
1.3.4 Fitting a line in 3D, unsupervised clustering, and other generalizations	29
1.3.4.1 Example: confidence region for the cluster centers	30
1.3.4.2 Exact solution and caveats	31
1.3.4.3 Comparison with K-means clustering	32
1.3.4.4 Python code	34
1.4 Connection to synthetic data: meteorites, ocean tides	36
2 A Simple, Robust and Efficient Ensemble Method	37
2.1 Introduction	37
2.2 Methodology	38
2.2.1 How hidden decision trees (HDT) work	38
2.2.2 NLP case study: summary and findings	39
2.2.3 Parameters	40
2.2.4 Improving the methodology	40
2.3 Implementation details	40
2.3.1 Correcting for bias	40
2.3.1.1 Time-adjusted scores	41
2.3.2 Excel spreadsheet	41
2.3.3 Python code and dataset	41
2.4 Model-free confidence intervals and perfect nodes	45
2.4.1 Interesting asymptotic properties of confidence intervals	45
3 Gentle Introduction to Linear Algebra – Synthetic Time Series	47
3.1 Power of a matrix	47
3.2 Examples, generalization, and matrix inversion	48
3.2.1 Example with a non-invertible matrix	49
3.2.2 Fast computations	49
3.2.3 Square root of a matrix	49
3.3 Application to machine learning problems	50
3.3.1 Markov chains	50
3.3.2 Time series: auto-regressive processes	50
3.3.3 Linear regression	51

3.4	Mathematics of auto-regressive time series	51
3.4.1	Simulations: curious fractal time series	52
3.4.1.1	White noise: Fréchet, Weibull and exponential cases	52
3.4.1.2	Illustration	52
3.4.2	Solving Vandermonde systems: a numerically stable method	53
3.5	Math for Machine Learning: Must-Read Books	54
4	Image and Video Generation	55
4.1	Introduction	55
4.2	Applications	56
4.2.1	Spatial time series	56
4.2.2	Prediction intervals in any dimensions	56
4.2.3	Supervised classification of an infinite dataset	57
4.2.3.1	Machine learning perspective	57
4.2.3.2	Six challenging problems	58
4.2.3.3	Mathematical background: the Riemann Hypothesis	58
4.2.3.4	Partial solutions to the six challenging problems	59
4.2.4	Algorithms with chaotic convergence	60
4.3	Python code	60
4.3.1	Path simulation	60
4.3.2	Visual convergence analysis in 2D	63
4.3.3	Supervised classification	64
4.4	Visualizations	67
5	Synthetic Clusters and Alternative to GMM	70
5.1	Introduction	70
5.2	Generating the synthetic data	71
5.2.1	Simulations with logistic distribution	71
5.2.2	Mapping the raw observations onto an image bitmap	72
5.3	Classification and unsupervised clustering	72
5.3.1	Supervised classification based on convolution filters	73
5.3.2	Clustering based on histogram equalization	73
5.3.3	Fractal classification: deep neural network analogy	74
5.3.4	Generalization to higher dimensions	75
5.3.5	Towards a very fast implementation	75
5.4	Python code	76
5.4.1	Fractal classification	77
5.4.2	GPU classification and clustering	79
5.4.3	Home-made graphic library	81
6	Shape Classification and Synthetization via Explainable AI	84
6.1	Introduction	84
6.2	Mathematical foundations	84
6.3	Shape signature	85
6.3.1	Weighted centroid	85
6.3.2	Computing the signature	86
6.3.3	Example	87
6.4	Shape comparison	87
6.4.1	Shape classification	88
6.5	Application	88
6.6	Exercises	89
7	Synthetic Data, Interpretable Regression, and Submodels	90
7.1	Introduction	90
7.2	Synthetic data sets and the spreadsheet	91
7.2.1	Correlation structure	91
7.2.2	Standardized regression	92
7.2.3	Initial conditions	92
7.2.4	Simulations and Excel spreadsheet	92
7.3	Damping schedule and convergence acceleration	93
7.3.1	Spreadsheet implementation	93
7.3.2	Interpretable regression with no overfitting	94
7.3.3	Adaptive damping	94

7.4	Performance assessment on synthetic data	94
7.4.1	Results	95
7.4.2	Distribution-free confidence intervals	97
7.4.2.1	Parametric bootstrap	98
7.5	Feature selection	98
7.5.1	Combinatorial approach	98
7.5.2	Stepwise approach	99
7.6	Conclusion	100
8	From Interpolation to Fuzzy Regression	102
8.1	Introduction	102
8.2	Original version	103
8.3	Full, non-linear model in higher dimensions	103
8.3.1	Geometric proximity, weights, and numerical stability	104
8.3.2	Predicted values and prediction intervals	104
8.3.3	Illustration, with spreadsheet	105
8.3.3.1	Output fields	106
8.4	Results	106
8.4.1	Performance assessment	106
8.4.2	Visualization	107
8.4.3	Amplitude restoration	107
8.5	Exercises	108
8.6	Python source code and datasets	109
9	New Interpolation Methods for Synthetization and Prediction	113
9.1	First method	113
9.1.1	Example with infinite summation	114
9.1.2	Applications: ocean tides, planet alignment	115
9.1.3	Problem in two dimensions	116
9.1.4	Spatial interpolation of the temperature dataset	117
9.2	Second method	119
9.2.1	From unstable polynomial to robust orthogonal regression	120
9.2.2	Using orthogonal functions	120
9.2.3	Application to regression	120
9.3	Python code	121
9.3.1	Time series interpolation	121
9.3.2	Geospatial temperature dataset	124
9.3.3	Regression with Fourier series	127
10	Synthetic Tabular Data: Copulas vs enhanced GANs	129
10.1	Sensitivity analysis, bias reduction and other uses of synthetic data	130
10.2	Using copulas to generate synthetic data	130
10.2.1	The insurance dataset: Python code and results	131
10.2.2	Potential improvements	133
10.3	Synthetization: GAN versus copulas	134
10.3.1	Parameterizing the copula quantiles combined with gradient descent	134
10.3.2	Feature clustering to break a big problem into smaller ones	134
10.4	Deep dive into generative adversarial networks (GAN)	135
10.4.1	Open source libraries and references	135
10.4.2	Synthesizing medical data with GAN	136
10.4.2.1	Hyperparameters	137
10.4.2.2	GAN: Main steps	138
10.4.3	Initial results	139
10.4.4	Fine-tuning the hyperparameters	140
10.4.5	Enhanced GAN: methodology and results	140
10.4.6	Feature clustering via hierarchical clustering or connected components	141
10.5	Comparing GANs with the copula method	144
10.5.1	Conclusion: getting the best out of copulas and GAN	146
10.6	Data synthetization explained in one picture	146
10.7	Python code: GAN to synthesize medical data	147
10.7.1	Classification problem with random forests	148
10.7.2	GAN method	149
10.7.3	GAN Evaluation and post-classification	151

11 High Quality Random Numbers for Data Synthetization	152
11.1 Introduction	152
11.2 Pseudo-random numbers	153
11.2.1 Strong pseudo-random numbers	153
11.2.1.1 New test of randomness for PRNGs	154
11.2.1.2 Theoretical background: the law of the iterated logarithm	154
11.2.1.3 Connection to the Generalized Riemann Hypothesis	154
11.2.2 Testing well-known sequences	155
11.2.2.1 Reverse-engineering a pseudo-random sequence	156
11.2.2.2 Illustrations	157
11.3 Python code	159
11.3.1 Fixes to the faulty random function in Python	159
11.3.2 Prime test implementation to detect subtle flaws in PRNG's	159
11.3.3 Special formula to compute 10 million digits of $\sqrt{2}$	162
11.4 Military-grade PRNG Based on Quadratic Irrationals	165
11.4.1 Fast algorithm rooted in advanced analytic number theory	165
11.4.2 Fast PRNG: explanations	166
11.4.3 Python code	166
11.4.4 Computing a digit without generating the previous ones	168
11.4.5 Security and comparison with other PRNGs	168
11.4.5.1 Important comments	169
11.4.6 Curious application: a new type of lottery	169
12 Some Unusual Random Walks	170
12.1 Symmetric unbiased constrained random walks	170
12.1.1 Three fundamental properties of pure random walks	170
12.1.2 Random walks with more entropy than pure random signal	171
12.1.2.1 Applications	171
12.1.2.2 Algorithm to generate quasi-random sequences	172
12.1.2.3 Variance of the modified random walk	172
12.1.3 Random walks with less entropy than pure random signal	173
12.2 Related stochastic processes	174
12.2.1 From Brownian motions to clustered Lévy flights	174
12.2.2 Integrated Brownian motions and special auto-regressive processes	175
12.3 Python code	176
12.3.1 Computing probabilities and variances attached to S_n	176
12.3.2 Path simulations	177
13 Divergent Optimization Algorithm and Synthetic Functions	179
13.1 Introduction	179
13.1.1 The problem, with illustration	180
13.2 Non-converging fixed-point algorithm	181
13.2.1 Trick leading to intuitive solution	181
13.2.2 Root detection: method and parameters	181
13.2.3 Case study: factoring a product of two large primes	182
13.3 Generalization with synthetic random functions	182
13.3.1 Example	184
13.3.2 Connection to the Poisson-binomial distribution	185
13.3.2.1 Location of next root: guesstimate	185
13.3.2.2 Integer sequences with high density of primes	185
13.3.3 Python code: finding the optimum	186
13.4 Smoothing highly chaotic curves	187
13.4.1 Python code: smoothing	187
13.5 Connection to synthetic data: random functions	190
14 Synthetic Terrain Generation and AI-generated Art	191
14.1 Introduction	191
14.2 Terrain generation and the evolutionary process	193
14.2.1 Morphing and non-linear palette operations	193
14.2.2 The diamond-square algorithm	193
14.2.3 The evolutionary process	194
14.2.4 Finding optimum parameters	194
14.2.5 Mimicking real terrain: the synthesis step	194

14.3	Python code	195
14.3.1	Producing data videos with four sub-videos in parallel	195
14.3.2	Main program	196
14.4	AI-generated art with 3D contours	200
14.4.1	Python code using Matplotlib	201
14.4.2	Python code using Plotly	202
14.4.3	Tips to quickly solve new problems	203
15	Synthetic Star Cluster Generation with Collision Graphs	204
15.1	Introduction	204
15.2	Model parameters and simulation results	205
15.2.1	Explanation of color codes	205
15.2.2	Detailed description of top parameters	205
15.2.3	Interesting parameter sets	206
15.3	Analysis of star collisions and collision graph	207
15.3.1	Weighted directed graphs: visualization with NetworkX	208
15.3.2	Interesting findings: how the universe got started	208
15.4	Animated data visualizations	209
15.5	Python code and computational issues	210
15.5.1	Simulating the real and synthetic universes	210
15.5.2	Visualizing collision graphs	214
16	Perturbed Lattice Point Process: Alternative to GMM	216
16.1	Perturbed lattices: definition and properties	216
16.1.1	Point counts distribution	217
16.1.2	Periodicity and amplitude of point count expectations	217
16.1.3	Testing the independence of point counts	218
16.1.3.1	Results and Interpretation	219
16.1.3.2	About the Spreadsheet	220
16.2	Cluster processes and nearest neighbor graphs	220
16.2.1	Synthetic, semi-rigid cluster structures	220
16.2.2	Python code to generate cluster processes	222
16.2.3	References on cluster processes	222
16.2.4	Superimposed perturbed lattices: an alternative to mixture models	223
16.2.4.1	Hexagonal lattice, nearest neighbors	224
16.2.4.2	Exercises: nearest neighbor graphs, size of connected components	225
16.2.4.3	Python code to compute connected components	226
16.3	Statistical inference for point processes	228
16.3.1	Estimation of Core Parameters	228
16.3.1.1	Intensity	229
16.3.1.2	Scaling factor	229
16.3.1.3	Alternative estimation method	229
16.3.2	Spatial statistics, nearest neighbors, clustering	230
16.3.2.1	Inference for two-dimensional processes	230
16.3.2.2	Other possible tests	230
16.3.2.3	Rayleigh test	231
16.3.2.4	Exercises	232
16.4	Special topics	233
16.4.1	Minimum contrast estimation and explainable AI	233
16.4.2	Model identifiability, hard-to-detect patterns	234
16.4.2.1	Stochastic residues	234
16.4.3	Hidden model and random permutations	234
16.4.4	Retrieving the F distribution	236
16.4.4.1	Theoretical values obtained by simulations	236
16.4.4.2	Retrieving F from the interarrival times distribution	237
16.4.5	Record distances between an observed point and its vertex	237
16.4.5.1	Distribution of records	238
16.4.5.2	Distribution of arrival times for records	239
17	Synthesizing Multiplicative Functions in Number Theory	240
17.1	Introduction	240
17.1.1	Key concepts and terminology	241
17.1.2	Orbits and holes	241

17.1.3	Industrial Applications	241
17.2	Euler products	242
17.2.1	Finite Euler Products	242
17.2.1.1	Generalization using Dirichlet characters	243
17.2.2	Infinite Euler products	244
17.2.2.1	Special products	244
17.2.2.2	Probabilistic properties and conjectures	245
17.3	Finite Dirichlet series and generalizations	246
17.3.1	Finite Dirichlet series	246
17.3.2	Non-trivial cases with infinitely many primes and a hole	248
17.3.2.1	Sums of two cubes, or cuban primes	248
17.3.2.2	Primes associated to elliptic curves	248
17.3.2.3	Analytic continuation, convergence, and functional equation	249
17.3.2.4	Hybrid Dirichlet-Taylor series	249
17.3.3	Riemann Hypothesis with cosines replaced by wavelets	250
17.3.4	Riemann Hypothesis for Beurling primes	251
17.3.5	Stochastic Euler products	252
17.4	Exercises	253
17.5	Python code	256
17.5.1	Computing the orbit of various Dirichlet series	256
17.5.2	Creating videos of the orbit	259
18	Text, Sound Generation and Other Topics	262
18.1	Sound generation: let your data sing!	262
18.1.1	From data visualizations to videos to data music	262
18.1.2	References	263
18.1.3	Python code	263
18.2	Data videos and enhanced visualizations in R	264
18.2.1	Cairo library to produce better charts	264
18.2.2	AV library to produce videos	265
18.3	Dual confidence regions	266
18.3.1	Case study	266
18.3.2	Standard confidence region	266
18.3.3	Dual confidence region	267
18.3.4	Simulations	267
18.3.5	Original problem with minimum contrast estimators	268
18.3.6	General shape of confidence regions	269
18.4	Fast feature selection based on predictive power	270
18.4.1	How cross-validation works	271
18.4.2	Measuring the predictive power of a feature	271
18.4.3	Efficient implementation	272
18.5	NLP: taxonomy creation and text generation	273
18.5.1	Designing a keyword taxonomy	273
18.5.2	Fast clustering algorithm for keyword data	274
18.5.2.1	Computational complexity	274
18.5.2.2	Smart crawling of the whole Internet and a bit of graph theory	275
18.6	Automated detection of outliers and number of clusters	276
18.6.1	Black-box elbow rule to detect outliers	276
18.7	Advice to beginners	277
18.7.1	Getting started and learning how to learn	277
18.7.1.1	Getting help	278
18.7.1.2	Beyond Python	278
18.7.2	Automated data cleaning and exploratory analysis	278
18.7.3	Example of simple analysis: marketing attribution	279
Glossary		280
Bibliography		283
Index		288

List of Figures

1.1	Fitted ellipse (blue), given the training set (red) distributed around a partial arc	19
1.2	Confidence region in blue, $n = 30$ training set points; 50 training sets (left) vs 150 (right)	20
1.3	Three non-periodic time series made of periodic terms (see section 17.2.2.1)	26
1.4	Training set (red), validation set (orange), fitted curve (blue) and model (gray)	27
1.6	Biased confidence region for (θ_A^*, θ_B^*) ; same example as in Figure 1.5; true value is $(0.5, 1.0)$	30
1.5	Finding the two centers θ_A^*, θ_B^* in sample 39; $n = 1000$	31
1.7	Challenging mixture, requiring $p_A = 3, p_B = 1$ to identify the two cluster centers	32
2.1	Output from the Excel version of HDT	42
3.1	AR models, classified based on the types of roots of the characteristic polynomial	53
4.1	Scatterplot observations vs. predicted values, with prediction intervals (in any dimension)	67
4.2	Comets orbiting the sun: simulation	67
4.3	Comets orbiting the sun: snapshot in time	68
4.4	Three orbits of $\eta(\sigma + it)$: $\sigma = 0.5$ (red), 0.75 (blue) and 1.25 (yellow)	68
4.5	Sample orbit points of $\eta(\sigma + it)$: $\sigma = 0.5$ (red), 0.75 (blue) and 1.25 (yellow)	68
4.6	Sample orbit points of $\eta(\sigma + it)$: $\sigma = 0.5$ (red), 0.75 (blue) and 1.25 (yellow)	69
4.7	Raw orbit points of $\eta(\sigma + it)$: $\sigma = 0.5$ (red), 0.75 (blue) and 1.25 (yellow)	69
4.8	Convergence of partial sums of $\eta(z)$, for six $z = \sigma + it$ in the complex plane	69
5.1	Special interlacing of 4 lattice processes with $s = 0$	72
5.2	Classification of left dataset; $s = 0.15, w = 10$. One loop (middle) vs 3 (right).	73
5.3	Clustering of left dataset; $s = 0.15$, 3 loops, $w = 10$ (middle) vs 20 (right).	74
5.4	Classification ($w = 10$) and clustering ($w = 20$); $s = 0.05$, three loops.	74
5.5	Fractal classification, $s = 0.15$. Loop 6, 250 and 400.	75
5.6	Fractal classification, $s = 0.05$.Loop: 6 and 60.	75
5.7	Fast (left) vs standard method (right), 3 loops, $s = 0.15, w = 10$	76
5.8	Fast method, $s = 0.05, w = 20$. Three loops (middle), one loop (right).	76
6.1	Comparing two shapes	85
6.2	Weighted centroid, shape signature	86
6.3	Weight function used in Figure 6.2	87
6.4	Another interesting shape	88
7.1	Regression coefficients oscillating when using adaptive damping	95
7.2	Convergence of regression coefficients (left) and distribution of residual error (right)	96
7.3	Goodness-of-fit: training set (right) versus validation set (left)	96
8.1	Fuzzy regression with prediction intervals, original version, 1D	103
8.2	Fuzzy regression with prediction intervals, full model, 2D	105
8.3	Scatterplots: median vs weighted method, on validation (left) vs training set (right)	107
8.4	Dirichlet eta function (real part, bottom) and interpolation error (top)	109
9.1	Interpolating the real part of $\zeta(\frac{1}{2} + it)$ based on orange points	114
9.2	Tides at Dublin (5-min data), with 80 mins between interpolating nodes	117
9.3	Temperature data: interpolation with my method (observed values at dots)	118
9.4	My method: round dots represent observed values, “+” are interpolated	118
9.5	Temperature dataset: interpolation using ordinary kriging	119
10.1	Synthetic versus real data, produced by SDV GAN + copula	135

10.2	Loss function (in orange) for 10^4 successive epochs; enhanced GAN on the right plot	137
10.3	Summary statistics, medical dataset (synth 1 and 2 correspond to GAN)	138
10.4	Correlation matrix, real vs synthetic: GAN (synth 2) and copula-based	139
10.5	Copulas superior to GANs (synth 1, 2) to capture correlations in real data	139
10.6	Feature clustering using Scipy; Y-axis is $1 - \rho $	142
10.7	Real data (left), copula (middle) and GAN synthetization (right)	145
10.8	Loss function (orange) and distance (grey), circle dataset	145
10.9	Data synthetization: general schema	147
11.1	Orbit of $L(z, \chi)$ at $\sigma = \frac{1}{2}$, with $0 < t < 200$ and $\chi = \chi_4$ (left) versus pseudo-random χ (right)	155
11.2	$L_3^*(n)$ test statistic for four sequences: Python[200] and SQRT[90,91] fail	157
11.3	$ L_3(n) $ test statistic for four sequences: Python[200] and SQRT[90,91] fail	157
11.4	Correlations are computed on sequences consisting of 300 binary digits	168
12.1	Typical path S_n with $0 \leq n \leq 50,000$ for four types of random walks	171
12.2	$\delta_n = 1 - \text{Var}[S_{n+1}] + \text{Var}[S_n]$ for four types of random walks, with $0 \leq n \leq 5000$	172
12.3	Same as Figure 12.2, using a more aesthetic but less meaningful chart type	173
12.4	Clustered Brownian process	175
12.5	AR models, classified based on the types of roots of the characteristic polynomial	176
13.1	Function $f(b)$ as a better alternative to $g(b)$ in Figure 13.2. Root at $b = 3083$	180
13.2	Function $g(b) = 2 - \cos(2\pi b) - \cos(2\pi a/b)$, with $a = 3083 \times 7919$	180
13.3	Transformed function f_3 , amplifying the root at $b = 3083$	181
13.4	Signal strength ρ_n , first 130 fixed-point iterations; $n = 31$ leads to a root	184
13.5	(b_n, ρ_n) plot. Yellow and orange dots linked to roots	184
13.6	Signal strength ρ_n , first 130 fixed-point iterations; $n = 87$ leads to a root	184
13.7	Random function from section 13.3.1, with root at $b = 5646$	187
14.1	Six frames from the terrain video, each one containing four images	192
14.2	Contour plot, 3D mixture model, produced with Plotly	200
14.3	Same as Figure 14.2, produced with Matplotlib	201
15.1	Collisions graph for the biggest star eater (star 47) in video 7	208
15.2	Summary statistics for the whole collision structure: the X axis represents the time	209
15.3	Snapshots of universe 4 (left) and universe 7 (right)	210
16.1	Period and amplitude of $\phi_\tau(t)$; here $\tau = 1, \lambda = 1.4, s = 0.3$	218
16.2	A new test of independence (R-squared version)	218
16.3	Radial cluster process ($s = 0.2, \lambda = 1$) with centers in blue; zoom in on the left	221
16.4	Radial cluster process ($s = 2, \lambda = 1$) with centers in blue; zoom in on the left	221
16.5	Manufactured marble lacking true lattice randomness (left)	221
16.6	Four superimposed Poisson-binomial processes: $s = 0$ (left), $s = 5$ (right)	224
16.7	Rayleigh test to assess if a point distribution matches that of a Poisson process	232
16.8	Realization of a 5-interlacing with $s = 0.15$ and $\lambda = 1$: original (left), modulo $2/\lambda$ (right)	235
16.9	Locally random permutation σ ; $\tau(k)$ is the index of X_k 's closest neighbor to the right	235
16.10	Each arrow links a point (blue) to its vertex (red): $s = 0.2$ (left), $s = 1$ (right)	238
16.11	Distance between a point and its vertex ($\lambda = s = 1$)	239
17.1	Three orbits ($\sigma = 0.5, 0.75, 1.25$) with finite Euler product: $P = \{2, 3\}$ (left) vs $\{2, 3, 5\}$ (right)	243
17.2	Distance between orbit and location $(c, 0)$ depending on t on the X-axis	245
17.3	Distance between orbit and location $(c, 0)$ depending on t on the X-axis	245
17.4	Distance between orbit and location $(c, 0)$ depending on t on the X-axis	245
17.5	Four orbits where the “hole” (repulsion basin) is apparent	247
17.6	Three orbits with “hole” closer to the origin, showing impact of $\beta > \frac{1}{2}$ and larger n	247
17.7	Orbit of Dirichlet eta $\eta(z)$ when cosines are replaced by other periodic functions	251
18.1	Data linked to the melody: red curve for note frequencies, blue curve for note durations	263
18.2	R plot before Cairo (left), and after (right)	264
18.3	Intermediate (left) and last frame (right) of the video	265
18.4	Example of 90% dual confidence region for (p, q)	267
18.5	Minimum contrast estimation for (λ, s) using (p, q) as proxy stats	268
18.6	Non-elliptic confidence regions with various confidence levels	269
18.7	Elbow rule (right) finds $m = 3$ clusters in Brownian motion (left)	277

List of Tables

1.1	Estimated ellipse parameters vs true values ($n = 30$), for shape in Figure 1.2	20
1.2	First and last step of <code>curve_fitting</code> , approaching the model.	28
1.3	MSE for different methods and θ s, same data set as in Figure 1.5	33
1.4	MSE for different methods and θ s, same data set as in Figure 1.7	33
2.1	List of potential features to use in the model	38
2.2	Statistics for selected HDT nodes (Excel version)	41
2.3	Order of magnitude for the expectation and standard deviation of the range R_n	45
3.1	Characteristic polynomials used in the simulations	52
7.1	Regression coefficients and performance metrics r, s based on methodology	97
7.2	Correlation matrix	97
7.3	Best performance given m (number of features)	98
7.4	Feature comparison table (top 32 feature combinations)	100
7.5	Feature comparison table (bottom 31 feature combinations)	101
8.1	R -squared ρ^2 and slope β , on training and validation sets, median vs weighted	107
10.1	Comparing real data with two different synthetic copies	132
10.2	Correlations on 9D circle dataset: real vs copula and GAN	146
11.1	$L_3^*(n)$, for various sequences ($n = 20,000$); “Fail” means failing the prime test	158
13.1	High ρ_n at iterations $n = 31$ and $n = 127$ points to roots 3083 and 7919	183
15.1	Description of top parameters used in the star cluster simulator	206
15.2	Eight selected parameter sets covering various situations	207
16.1	Variance attached to F_s , as a function of s	217
16.2	Poisson process ($s = \infty$) versus $s = 39.85$	237
18.1	Extract of the mapping table used to recover (λ, s) from (p, q)	269
18.2	Eight bins: 2 features (A, B) times 2 outcomes (Good/Bad)	271
18.3	Amount of data collected at each level, when crawling the Internet	275

Glossary

Autoregressive process	Auto-correlated time series, as described in section 3.4. Time-continuous versions include Gaussian processes and Brownian motions, while random walks are a discrete example; two-dimensional versions exist. These processes are essentially integrated white noise. See pages 50, 98, 175
Binning	Feature binning consists of aggregating the values of a feature into a small number of bins, to avoid overfitting and reduce the number of nodes in methods such as naive Bayes, neural networks, or decision trees. Binning can be applied to two or more features simultaneously. I discuss optimum binning in this book. See pages 38, 74, 271
Boosted model	Blending of several models to get the best of each one, also referred to as ensemble methods. The concept is illustrated with hidden decision trees in this book. Other popular examples are gradient boosting and AdaBoost. See pages 37, 280
Bootstrapping	A data-driven, model-free technique to estimate parameter values, to optimize goodness-of-fit metrics. Related to resampling in the context of cross-validation. In this book, I discuss parametric bootstrap on synthetic data that mimics the actual observations. See pages 16, 97, 232, 280
Confidence Region	A confidence region of level γ is a 2D set of minimum area covering a proportion γ of the mass of a bivariate probability distribution. It is a 2D generalization of confidence intervals. In this book, I also discuss dual confidence regions – the analogous of credible regions in Bayesian inference. See pages 13, 16, 19, 21, 30, 229, 230, 266, 269
Cross-validation	Standard procedure used in bootstrapping, and to test and validate a model, by splitting your data into training and validation sets. Parameters are estimated based on training set data. An alternative to cross-validation is testing your model on synthetic data with known response. See pages 16, 38, 94, 100, 138, 207, 271, 280
Decision trees	A simple, intuitive non-linear modeling techniques used in classification problems. It can handle missing and categorical data, as well as a large number of features, but requires appropriate feature binning. Typically one blends multiple binary trees each with a few nodes, to boost performance. See pages 37, 38, 40, 42, 280, 281
Dimension reduction	A technique to reduce the number of features in your dataset while minimizing the loss in predictive power. The most well known are principal component analysis and feature selection to maximize goodness-of-fit metrics. See pages 13, 17, 281, 282
Empirical distribution	Cumulative frequency histogram attached to a statistic (for instance, nearest neighbor distances), and based on observations. When the number of observations tends to infinity and the bin sizes tend to zero, this step function tends to the theoretical cumulative distribution function of the statistic in question. See pages 17, 97, 121, 130, 153, 216, 219, 225, 231, 236, 238, 250
Ensemble methods	A technique consisting of blending multiple models together, such as many decision trees with logistic regression, to get the best of each method and outperform each method taken separately. Examples include boosting, bagging, and AdaBoost. In this book, I discuss hidden decision trees. See pages 37, 84, 280

Explainable AI	Automated machine learning techniques that are easy to interpret are referred to as interpretable machine learning or explainable artificial intelligence. As much as possible, the methods discussed in this book belong to that category. The goal is to design black-box systems less likely to generate unexpected results with unintended consequences. See pages 14, 36, 70, 75, 84, 91, 129, 141, 179, 195, 233
Feature selection	Features – as opposed to the model response – are also called independent variables or predictors. Feature selection, akin to dimensionality reduction , aims at finding the minimum subset of variables with enough predictive power . It is also used to eliminate redundant features and find causality (typically using hierarchical Bayesian models), as opposed to mere correlations. Sometimes, two features have poor predictive power when taken separately, but provide improved predictions when combined together. See pages 13, 16, 38, 95, 98, 262, 270, 280, 282
Generative model	Bayesian Gaussian mixtures (GMM) combined with kernel density estimation and the EM algorithm is a classic modeling tool. In this book, I used <i>m</i>-interlacings instead. Generative adversarial networks (GAN) work as follows: the generator creates new observations and the discriminator tests whether the new observations are statistically indistinguishable from training set data. When this goal is achieved, the new observations is your synthetic data. New observations can also be generated via parametric bootstrap . See pages 36, 53, 100, 147, 190, 191, 193, 200, 207, 282
Goodness-of-fit	A model fitting criterion or metric to assess how a model or sub-model fits to a dataset, or to measure its predictive power on a validation set . Examples include R-squared , Chi-squared, Kolmogorov-Smirnov, error rate such as false positives and other metrics discussed in this book. See pages 16, 57, 94, 95, 271, 280, 282
Gradient methods	Iterative optimization techniques to find the minimum or maximum of a function, such as the maximum likelihood . When there are numerous local minima or maxima, use swarm optimization . Gradient methods (for instance, stochastic gradient descent or Newton's method) assume that the function is differentiable. If not, other techniques such as Monte Carlo simulations or the fixed-point algorithm can be used. Constrained optimization involves using Lagrange multipliers . See pages 16, 32, 56, 90
Graph structures	Graphs are found in decision trees , in neural networks (connections between neurons), in nearest neighbors methods (NN graphs), in hierarchical Bayesian models , and more. See pages 71, 75, 208, 274, 275
Hyperparameter	An hyperparameter is used to control the learning process: for instance, the dimension, the number of features, parameters, layers (neural networks) or clusters (clustering problem), or the width of a filtering window in image processing. By contrast, the values of other parameters (typically node weights in neural networks or regression coefficients) are derived via training. See pages 30, 57, 71, 76, 102, 136, 194, 281
Link function	A link function maps a nonlinear relationship to a linear one so that a linear model can be fit, and then mapped back to the original form using the inverse function. For instance, the logit link function is used in logistic regression . Generalizations include quantile functions and inverse sigmoids in neural network to work with additive (linear) parameters. See pages 14, 17, 281
Logistic regression	A generalized linear regression method where the binary response (fraud/non-fraud or cancer/non-cancer) is modeled as a probability via the logistic link function. Alternatives to the iterative maximum likelihood solution are discussed in this book. See pages 17, 34, 37, 41, 280, 281
Neural network	A blackbox system used for predictions, optimization, or pattern recognition especially in computer vision. It consists of layers, neurons in each layer, link functions to model non-linear interactions, parameters (weights associated to the connections between neurons) and hyperparameters . Networks with several layers are called deep neural networks . Also, neurons are sometimes called nodes. See pages 70, 74, 76, 84, 102, 280, 281

NLP	Natural language processing is a set of techniques to deal with unstructured text data, such as emails, automated customer support, or webpages downloaded with a crawler. The example discussed in section 18.5 deals with creating a keyword taxonomy based on parsing Google search result pages. Text generation is referred to as NLG or natural language generation , using large language models (LLM). See pages 37, 273
Numerical stability	This issue occurring in unstable optimization problems typically with multiple minima or maxima, is frequently overlooked and leads to poor predictions or high volatility. It is sometimes referred to as ill-conditioned problems . I explain how to fix it in several examples in this book, for instance in section 3.4.2. Not to be confused with numerical precision. See pages 13, 15, 60
Overfitting	Using too many unstable parameters resulting in excellent performance on the training set , but poor performance on future data or on the validation set . It typically occurs with numerically unstable procedures such as regression (especially polynomial regression) when the training set is not large enough, or in the presence of wide data (more features than observations) when using a method not suited to this situation. The opposite is underfitting. See pages 16, 93, 102, 130, 136, 280, 282
Predictive power	A metric to assess the goodness-of-fit or performance of a model or subset of features, for instance in the context of dimensionality reduction or feature selection . Typical metrics include R-squared , or confusion matrices in classification. See pages 39, 41, 45, 129, 270, 272, 281
R-squared	A goodness-of-fit metric to assess the predictive power of a model, measured on a validation set . Alternatives include adjusted R-squared, mean absolute error and other metrics discussed in this book. See pages 13, 16, 36, 57, 91, 94, 96, 98, 105, 281, 282
Random number	Pseudo-random numbers are sequences of binary digits, usually grouped into blocks, satisfying properties of independent Bernoulli trials. In this book, the concept is formally defined, and strong pseudo-number generators are built and used in computer-intensive simulations. See pages 30, 152, 159, 276
Regression methods	I discuss a unified approach to all regression problems in chapter 1. Traditional techniques include linear, logistic, Bayesian, polynomial and Lasso regression (to deal with numerical instability and overfitting), solved using optimization techniques, maximum likelihood methods, linear algebra (eigenvalues and singular value decomposition) or stepwise procedures. See pages 13, 14, 16, 17, 20, 28, 37, 41, 47, 51, 53, 57, 90, 96, 102, 109, 281, 282
Supervised learning	Techniques dealing with labeled data (classification) or when the response is known (regression). The opposite is unsupervised learning , for instance clustering problems. In-between, you have semi-supervised learning and reinforcement learning (favoring good decisions). The technique described in chapter 1 fits into unsupervised regression. Adversarial learning is testing your model against extreme cases intended to make it fail, to build better models. See pages 282
Synthetic data	Artificial data simulated using a generative model , typically a mixture model , to enrich existing datasets and improve the quality of training sets . Called augmented data when blended with real data. See pages 13, 14, 16, 18, 28, 30, 34, 36, 49, 53, 56, 70, 71, 76, 89, 95, 106, 113, 119, 130, 152, 165, 171, 179, 193, 200, 207, 267, 276, 280
Tensor	Matrix generalization with three or more dimensions. A matrix is a two-dimensional tensor. A triple summation with three indices is represented by a three-dimensional tensor, while a double summation involves a standard matrix. See pages 70, 75
Training set	Dataset used to train your model in supervised learning . Typically, a portion of the training set is used to train the model, the other part is used as validation set . See pages 14, 16, 18, 21, 30, 37, 41, 57, 73, 89, 96, 102, 106, 207, 271, 280, 282
Validation set	A portion of your training set , typically 20%, used to measure the actual performance of your predictive algorithm outside the training set. In cross-validation and bootstrapping, the training and validation sets are split into multiple subsets to get a better sense of variations in the predictions. See pages 16, 28, 42, 57, 94, 102, 130, 207, 271, 280, 281, 282

Bibliography

- [1] Weighted percentiles using numpy. *Forum discussion*, 2020. StackOverflow [\[Link\]](#). 102
- [2] Jan Ackmann et al. Machine-learned preconditioners for linear solvers in geophysical fluid flows. *Preprint*, pages 1–19, 2020. arXiv:2010.02866 [\[Link\]](#). 94
- [3] Noga Alon and Joel H. Spencer. *The Probabilistic Method*. Wiley, fourth edition, 2016. [\[Link\]](#). 225
- [4] José M. Amigó, Roberto Dale, and Piergiulio Tempesta. A generalized permutation entropy for random processes. *Preprint*, pages 1–9, 2012. arXiv:2003.13728 [\[Link\]](#). 236
- [5] Luc Anselin. *Point Pattern Analysis: Nearest Neighbor Statistics*. The Center for Spatial Data Science, University of Chicago, 2016. Slide presentation [\[Link\]](#). 223
- [6] Insaf Ashrapov. Tabular gans for uneven distribution. *Preprint*, pages 1–11, 2020. arXiv:2010.00638 [\[Link\]](#). 136
- [7] Adrian Baddeley. Spatial point processes and their applications. In Weil W., editor, *Stochastic Geometry. Lecture Notes in Mathematics*, pages 1–75. Springer, Berlin, 2007. [\[Link\]](#). 222
- [8] David Bailey and Richard Crandall. Random generators and normal numbers. *Experimental Mathematics*, 11, 2002. Project Euclid [\[Link\]](#). 169
- [9] N. Balakrishnan and C.R. Rao (Editors). *Order Statistics: Theory and Methods*. North-Holland, 1998. 225, 239
- [10] Christopher Beckham and Christopher Pal. A step towards procedural terrain generation with GANs. *Preprint*, pages 1–5, 2017. arXiv:1707.03383 [\[Link\]](#). 192
- [11] Rabi Bhattacharya and Edward Waymire. *Random Walk, Brownian Motion, and Martingales*. Springer, 2021. 170
- [12] Barbara Bogacka. *Lecture Notes on Time Series*. 2008. Queen Mary University of London [\[Link\]](#). 50
- [13] B. Bollobas and P. Erdös. Cliques in random graphs. *Mathematical Proceedings of the Cambridge Philosophical Society*, 80(3):419–427, 1976. [\[Link\]](#). 226
- [14] Miklos Bona. *Combinatorics of Permutations*. Routledge, second edition, 2012. 236
- [15] Ali Borji. Pros and cons of GAN evaluation measures: New developments. *Preprint*, pages 1–35, 2021. arXiv:2103.09396 [\[Link\]](#). 136
- [16] Peter Borwein, Stephen K. Choi, and Michael Coons. Completely multiplicative functions taking values in $\{-1, 1\}$. *Transactions of the American Mathematical Society*, 362(12):6279–6291, 2010. [\[Link\]](#). 244
- [17] Peter Borwein and Michael Coons. Transcendence of power series for some number theoretic functions. *Proceedings of the American Mathematical Society*, 137(4):1303–1305, 2009. [\[Link\]](#). 246
- [18] Oliver Bröker and Marcus J. Groteb. Sparse approximate inverse smoothers for geometric and algebraic multigrid. *Applied Numerical Mathematics*, 41(1):61–80, 2002. 91
- [19] H. M. Bui and M. B. Milinovich. Gaps between zeros of the Riemann zeta-function. *Quarterly Journal of Mathematics*, 69(2):402–423, 2018. [\[Link\]](#). 256
- [20] Bartłomiej Błaszczyzyn and Dhandapani Yogeshwaran. Clustering and percolation of point processes. *Preprint*, pages 1–20, 2013. Project Euclid [\[Link\]](#). 222
- [21] Bartłomiej Błaszczyzyn and Dhandapani Yogeshwaran. On comparison of clustering properties of point processes. *Preprint*, pages 1–26, 2013. arXiv:1111.6017 [\[Link\]](#). 222
- [22] Bartłomiej Błaszczyzyn and Dhandapani Yogeshwaran. Clustering comparison of point processes with applications to random geometric models. *Preprint*, pages 1–44, 2014. arXiv:1212.5285 [\[Link\]](#). 222
- [23] Oliver Chikumbo and Vincent Granville. Optimal clustering and cluster identity in understanding high-dimensional data spaces with tightly distributed points. *Machine Learning and Knowledge Extraction*, 1(2):715–744, 2019. 277

- [24] Keith Conrad. *L-functions and the Riemann Hypothesis*. 2018. 2018 CTNT Summer School [Link]. 155, 241, 244, 249
- [25] Noel Cressie. *Statistic for Spatial Data*. Wiley, revised edition, 2015. 222
- [26] D.J. Daley and D. Vere-Jones. *An Introduction to the Theory of Point Processes*. Springer, second edition, 2002. Volume 1 – Elementary Theory and Methods. 174
- [27] D.J. Daley and D. Vere-Jones. *An Introduction to the Theory of Point Processes*. Springer, second edition, 2014. Volume 2 – General Theory and Structure. 174
- [28] Tilman M. Davies and Martin L. Hazelton. Assessing minimum contrast parameter estimation for spatial and spatiotemporal log-Gaussian Cox processes. *Statistica Neerlandica*, 67(4):355–389, 2013. 268
- [29] Marc Deisenroth, A. Faisal, and Cheng Soon Ong. *Mathematics for Machine Learning*. Cambridge University Press, 2020. [Link]. 54
- [30] Harold G. Diamond and Wen-Bin Zhang. *Beurling Generalized Numbers*. American Mathematical Society, 2016. Mathematical Surveys and Monographs, Volume 213 [Link]. 156, 252
- [31] D.J. Daley and D. Vere-Jones. *An Introduction to the Theory of Point Processes – Volume I: Elementary Theory and Methods*. Springer, second edition, 2013. 223
- [32] D.J. Daley and D. Vere-Jones. *An Introduction to the Theory of Point Processes – Volume II: General Theory and Structure*. Springer, second edition, 2014. 223
- [33] David Coupier (Editor). *Stochastic Geometry: Modern Research Frontiers*. Wiley, 2019. 233
- [34] Ding-Geng Chen (Editor), Jianguo Sun (Editor), and Karl E. Peace (Editor). *Interval-Censored Time-to-Event Data: Methods and Applications*. Chapman and Hall/CRC, 2012. 224
- [35] Khaled Emam, Lucy Mosquera, and Richard Hoptroff. *Practical Synthetic Data Generation*. O'Reilly, 2020. 100
- [36] Paul Erdős and Alfréd Rényi. On the evolution of random graphs. In *Publication of the Mathematical Institute of the Hungarian Academy of Sciences*, volume 5, pages 17–61, 1960. [Link]. 226
- [37] Achim Zeileis et al. Colorspace: A toolbox for manipulating and assessing colors and palettes. *Preprint*, pages 1–45, 2019. arXiv:1903.06490 [Link] [R Library]. 192
- [38] Arash Farahmand. *Math 55 Lecture Notes*. 2021. University of Berkeley [Link]. 49, 54
- [39] W. Feller. On the Kolmogorov-Smirnov limit theorems for empirical distributions. *Annals of Mathematical Statistics*, 19(2):177–189, 1948. [Link]. 225, 232
- [40] Alvaro Figueira and Bruno Vaz. Survey on synthetic data generation, evaluation methods and GANs. *New Insights in Machine Learning and Deep Neural Networks*, 2022. MDPI [Link]. 136
- [41] Nikos Frantzikinakis. Ergodicity of the Liouville system implies the Chowla conjecture. *Preprint*, pages 1–41, 2016. arXiv [Link]. 246
- [42] P. M. Gauthier. Approximating the Riemann zeta-function by polynomials with restricted zeros. *Canadian Mathematical Bulletin*, 62(3):475–478, 2018. [Link]. 256
- [43] P. A. Van Der Geest. The binomial distribution with dependent Bernoulli trials. *Journal of Statistical Computation and Simulation*, pages 141–154, 2004. [Link]. 171
- [44] Stamatia Giannarou and Tania Stathaki. Shape signature matching for object identification invariant to image transformations and occlusion. 2007. ResearchGate [Link]. 85
- [45] Minas Gjoka, Emily Smith, and Carter Butts. Estimating clique composition and size distributions from sampled network data. *Preprint*, pages 1–9, 2013. arXiv:1308.3297 [Link]. 226
- [46] B.V. Gnedenko and A. N. Kolmogorov. *Limit Distributions for Sums of Independent Random Variables*. Addison-Wesley, 1954. 175
- [47] Manuel González-Navarrete and Rodrigo Lambert. Non-markovian random walks with memory lapses. *Preprint*, pages 1–14, 2018. arXiv [Link]. 170
- [48] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016. [Link]. 54
- [49] Vincent Granville. Estimation of the intensity of a Poisson point process by means of nearest neighbor distances. *Statistica Neerlandica*, 52(2):112–124, 1998. [Link]. 223
- [50] Vincent Granville. *Applied Stochastic Processes, Chaos Modeling, and Probabilistic Properties of Numeration Systems*. MLTechniques.com, 2018. [Link]. 156
- [51] Vincent Granville. *Stochastic Processes and Simulations: A Machine Learning Perspective*. MLTechniques.com, 2022. [Link]. 52, 60, 175, 185, 216, 217, 219, 220, 224, 226, 252, 256, 270
- [52] Vincent Granville, Mirko Krivanek, and Jean-Paul Rasson. Simulated annealing: A proof of convergence. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 16:652–656, 1996. 73

- [53] Vincent Granville and Richard L Smith. Disaggregation of rainfall time series via Gibbs sampling. *NISS Technical Report*, pages 1–21, 1996. [\[Link\]](#). 108
- [54] Kristen Grauman. Shape matching. 2008. University of Texas, Austin [\[Link\]](#). 88
- [55] Hui Guo et al. Eyes tell all: Irregular pupil shapes reveal gan-generated faces. *Preprint*, pages 1–7, 2021. arXiv:2109.00162 [\[Link\]](#). 129
- [56] Aurélien Géron. *Hands-On Machine Learning with Scikit-Learn, Keras & TensorFlow*. O'Reilly, third edition, 2023. 36
- [57] Radim Halir and Jan Flusser. Numerically stable direct least squares fitting of ellipses. *Preprint*, pages 1–8, 1998. [\[Link\]](#). 18, 20
- [58] Peter Hall. *Introduction to the theory of coverage processes*. Wiley, 1988. 233
- [59] Adam J. Harper. Moments of random multiplicative functions, II: High moments. *Algebra and Number Theory*, 13(10):2277–2321, 2019. [\[Link\]](#). 152, 252
- [60] Adam J. Harper. Moments of random multiplicative functions, I: Low moments, better than squareroot cancellation, and critical multiplicative chaos. *Forum of Mathematics, Pi*, 8:1–95, 2020. [\[Link\]](#). 152, 154, 252
- [61] Adam J. Harper. Almost sure large fluctuations of random multiplicative functions. *Preprint*, pages 1–38, 2021. arXiv [\[Link\]](#). 154, 246, 252
- [62] K. Hartmann, J. Krois, and B. Waske. *Statistics and Geospatial Data Analysis*. Freie Universität Berlin, 2018. E-Learning Project SOGA [\[Link\]](#). 219
- [63] D. R. Heath-Brown. Primes represented by $x^3 + 2y^3$. *Acta Mathematica*, 186:1–84, 2001. [\[Link\]](#). 248
- [64] Markus Herdin. Correlation matrix distance, a meaningful measure for evaluation of non-stationary MIMO channels. *Proc. IEEE 61st Vehicular Technology Conference*, pages 1–5, 2005. [\[Link\]](#). 136
- [65] T. W. Hilberdink and M. L. Lapidus. Beurling Zeta functions, generalised primes, and fractal membranes. *Preprint*, pages 1–31, 2004. arXiv [\[Link\]](#). 155, 156, 252
- [66] Christian Hill. *Learning Scientific Programming with Python*. Cambridge University Press, 2016. [\[Link\]](#). 20
- [67] Robert V. Hogg, Joseph W. McKean, and Allen T. Craig. *Introduction to Mathematical Statistics*. Pearson, eighth edition, 2016. [\[Link\]](#). 54
- [68] Zhiqiu Hu and Rong-Cai Yang. A new distribution-free approach to constructing the confidence region for multiple parameters. *PLOS One*, pages 1–13, 2013. [\[Link\]](#). 267
- [69] Peter Humphries. The distribution of weighted sums of the Liouville function and Pólya's conjecture. *Preprint*, pages 1–33, 2011. arXiv [\[Link\]](#). 253
- [70] Timothy D. Johnson. Introduction to spatial point processes. *Preprint*, page 2008. NeuroImaging Statistics Oxford (NISOx) group [\[Link\]](#)[\[Mirror\]](#). 223
- [71] Chigozie Kelechi. Towards efficiency in the residual and parametric bootstrap techniques. *American Journal of Theoretical and Applied Statistics*, 5(5), 2016. [\[Link\]](#). 98
- [72] Denis Kojevnikov, Vadim Marmer, and Kyungchul Song. Limit theorems for network dependent random variables. *Journal of Econometrics*, 222(2):419–427, 2021. [\[Link\]](#). 223
- [73] Samuel Kotz, Tomasz Kozubowski, and Krzysztof Podgorski. *The Laplace Distribution and Generalizations: A Revisit with Applications to Communications, Economics, Engineering, and Finance*. Springer, 2001. 237
- [74] Faraj Lagum. *Stochastic Geometry-Based Tools for Spatial Modeling and Planning of Future Cellular Networks*. PhD thesis, Carleton University, 2018. [\[Link\]](#). 222
- [75] Günther Last and Mathew Penrose. *Lectures on the Poisson Process*. Cambridge University Press, 2017. 222
- [76] Yuk-Kam Lau, Gerald Tenenbaum, and Jie Wu. On mean values of random multiplicative functions. *Proceedings of the American Mathematical Society*, 142(2):409–420, 2013. [\[Link\]](#). 152, 154
- [77] Gary R. Lawlor. A l'Hospital's rule for multivariable functions. *Preprint*, pages 1–13, 2013. arXiv:1209.0363 [\[Link\]](#). 114
- [78] Jing Lei et al. Distribution-free predictive inference for regression. *Journal of the American Statistical Association*, 113:1094–1111, 2018. [\[Link\]](#). 98
- [79] Hui Liu et al. A new model using multiple feature clustering and neural networks for forecasting hourly PM_{2.5} concentrations. *Engineering*, 6:944–956, 2020. [\[Link\]](#). 134, 141

- [80] Mario Lucic et al. Are GANs created equal? a large-scale study. *Proc. NeurIPS Conference*, pages 1–10, 2018. [\[Link\]](#). 136
- [81] G. Last M.A. Klatt and D. Yogeshwaran. Hyperuniform and rigid stable matchings. *Random Structures and Algorithms*, 2:439–473, 2020. [\[Link\]](#)[\[PowerPoint\]](#). 222
- [82] Jorge Mateu, Frederic P Schoenberg, and David M Diez. On distances between point patterns and their applications. *Preprint*, pages 1–29, 2010. [\[Link\]](#). 223
- [83] Natarajan Meghanathan. Distribution of maximal clique size of the vertices for theoretical small-world networks and real-world networks. *Preprint*, pages 1–20, 2015. arXiv:1508.01668 [\[Link\]](#). 226
- [84] Masahiro Mine. Probability density functions attached to random Euler products for automorphic L-functions. *Preprint*, pages 1–38, 2020. arXiv [\[Link\]](#). 252, 253
- [85] Christoph Molnar. *Interpretable Machine Learning*. ChristophMolnar.com, 2022. [\[Link\]](#). 98, 129
- [86] Marc-Andreas Muendler. Linear difference equations and autoregressive processes. 2000. University of Berkeley [\[Link\]](#). 50
- [87] V. Kumar Murty. Seminar on Fermat’s last theorem. In *Canadian Mathematical Society – Conference Proceedings*, volume 17, Toronto, Canada, 1995. [\[Link\]](#). 249
- [88] Peter Mörters and Yuval Peres. *Brownian Motion*. Cambridge University Press, 2010. Cambridge Series in Statistical and Probabilistic Mathematics, Volume 30 [\[Link\]](#). 170, 174
- [89] Jesper Møller. Introduction to spatial point processes and simulation-based inference. In *International Center for Pure and Applied Mathematics (Lecture Notes)*, Lomé, Togo, 2018. [\[Link\]](#)[\[Mirror\]](#). 223, 236, 268
- [90] Jesper Møller and Rasmus P. Waagepetersen. *An Introduction to Simulation-Based Inference for Spatial Point Processes*. Springer, 2003. 223
- [91] Jesper Møller and Rasmus P. Waagepetersen. *Statistical Inference and Simulation for Spatial Point Processes*. CRC Press, 2007. 223
- [92] S. Ghosh N., Miyoshi, and T. Shirai. Disordered complex networks: energy optimal lattices and persistent homology. *Preprint*, pages 1–44, 2020. arXiv:2009.08811. 216
- [93] Saralees Nadarajah. A modified Bessel distribution of the second kind. *Statistica*, 67(4):405–413, 2007. [\[Link\]](#). 237
- [94] Hasan Nasab, Mahdi Tavana, and Mohsen Yousefu. A new heuristic algorithm for the planar minimum covering circle problem. *Production and Manufacturing Research*, pages 142–155, 2014. [\[Link\]](#). 233
- [95] Guillermo Navas-Palencia. Optimal binning: mathematical programming formulation. *Preprint*, pages 1–21, 2020. arXiv:2001.08025 [\[Link\]](#). 38
- [96] Nathan Ng. Large gaps between the zeros of the Riemann zeta function. *Journal of Number Theory*, 128(3):509–556, 2007. [\[Link\]](#). 256
- [97] Sergey I. Nikolenko. *Synthetic Data for Deep Learning*. Springer, 2021. 136
- [98] Yosihiko Ogata. Cluster analysis of spatial point patterns: posterior distribution of parents inferred from offspring. *Japanese Journal of Statistics and Data Science*, 3:367–390, 2020. 222
- [99] Fred Park. Shape descriptor / feature extraction techniques. 2011. UCI iCAMP 2011 [\[Link\]](#). 85
- [100] Yuval Peres and Allan Sly. Rigidity and tolerance for perturbed lattices. *Preprint*, pages 1–20, 2020. arXiv:1409.4490 [\[Link\]](#). 216, 222
- [101] Carl Rasmussen and Christopher Williams. *Gaussian Processes for Machine Learning*. MIT Press, 2006. [\[Link\]](#). 53
- [102] Alfred R.Osborne. Multidimensional Fourier series. *International Geophysics*, 97:115–145, 2010. [\[Link\]](#). 121
- [103] Kamron Sanee. A simple expression for multivariate Lagrange interpolation. *SIAM Undergraduate Research Online*, 2007. SIURO [\[Link\]](#). 104
- [104] Mahesh Shivanand and all. Fitting random regression models with Legendre polynomial and B-spline to model the lactation curve for Indian dairy goat of semi-arid tropic. *Journal of Animal Breeding and Genetics*, pages 414–422, 2022. [\[Link\]](#). 121
- [105] Karl Sigman. Notes on the Poisson process. New York NY, 2009. IEOR 6711: Columbia University course [\[Link\]](#). 222
- [106] Joshua Snoke et al. General and specific utility measures for synthetic data. *Journal of the Royal Statistical Society Series A*, 181:663–688, 2018. arXiv:1604.06651 [\[Link\]](#). 36

- [107] Luuk Spreeuwiers. *Image Filtering with Neural Networks: Applications and Performance Evaluation*. PhD thesis, University of Twente, 1992. [74](#)
- [108] J. Michael Steele. Le Cam's inequality and Poisson approximations. *The American Mathematical Monthly*, 101(1):48–54, 1994. [\[link\]](#). [185](#)
- [109] Dietrich Stoyan, Wilfrid S. Kendall, Sung Nok Chiu, and Joseph Mecke. *Stochastic Geometry and Its Applications*. Wiley, 2013. [233](#)
- [110] E.C. Titchmarsh and D.R. Heath-Brown. *The Theory of the Riemann Zeta-Function*. Oxford Science Publications, second edition, 1987. [59](#), [155](#), [241](#)
- [111] Chris Tofallis. Fitting equations to data with the perfect correlation relationship. *Preprint*, pages 1–11, 2015. Hertfordshire Business School Working Paper[\[Link\]](#). [14](#)
- [112] D. Umbach and K.N. Jones. A few methods for fitting circles to data. *IEEE Transactions on Instrumentation and Measurement*, 52(6):1881–1885, 2003. [\[Link\]](#). [15](#), [18](#)
- [113] D. A. Vaccari and H. K. Wang. Multivariate polynomial regression for identification of chaotic time series. *Mathematical and Computer Modelling of Dynamical Systems*, 13(4):1–19, 2007. [\[Link\]](#). [18](#)
- [114] Remco van der Hofstad. *Random Graphs and Complex Networks*. Cambridge University Press, 2016. [\[Link\]](#). [225](#)
- [115] Yu Vizilter and Sergey Zheltov. Geometrical correlation and matching of 2D image shapes. 2012. ResearchGate [\[Link\]](#). [87](#)
- [116] Fengyun Wang and all. Bivariate Fourier-series-based prediction of surface residual stress fields using stresses of partial points. *Mathematics and Mechanics of Solids*, 2018. [\[Link\]](#). [121](#)
- [117] Luyao Wang and Hai Cheng. Pseudo-random number generator based on logistic chaotic system. *Entropy*, 21, 2019. [\[Link\]](#). [169](#)
- [118] Mingguang Wu, Yanjie Sun, and Yaqian Li. Adaptive transfer of color from images to maps and visualizations. *Cartography and Geographic Information Science*, pages 289–312, 2021. [\[Link\]](#). [192](#)
- [119] Lan Wu, Yongcheng Qi, and Jingping Yang. Asymptotics for dependent Bernoulli random variables. *Statistics and Probability Letters*, pages 455–463, 2012. [\[Link\]](#). [170](#)
- [120] Lei Xu and Kalyan Veeramachaneni. Synthesizing tabular data using generative adversarial networks. *Preprint*, pages 1–12, 2018. arXiv:1811.11264 [\[Link\]](#). [136](#)
- [121] Oren Yakir. Recovering the lattice from its random perturbations. *Preprint*, pages 1–18, 2020. arXiv:2002.01508 [\[Link\]](#). [222](#)
- [122] Ruqiang Yan, Yongbin Liub, and Robert Gao. Permutation entropy: A nonlinear statistical measure for status characterization of rotary machines. *Mechanical Systems and Signal Processing*, 29:474–484, 2012. [236](#)
- [123] Shaohong Yan, Aimin Yang, et al. Explicit algorithm to the inverse of Vandermonde matrix. In *2009 International Conference on Test and Measurement*, 2009. IEEE [\[Link\]](#). [48](#)
- [124] D. Yogeshwaran. Geometry and topology of the boolean model on a stationary point processes : A brief survey. *Preprint*, pages 1–13, 2018. Researchgate [\[Link\]](#). [223](#)
- [125] Tonglin Zhang. A Kolmogorov-Smirnov type test for independence between marks and points of marked point processes. *Electronic Journal of Statistics*, 8(2):2557–2584, 2014. [218](#)
- [126] Changgang Zheng et al. Reward-reinforced generative adversarial networks for multi-agent systems. *IEEE Transactions on Emerging Topics in Computational Intelligence*, 6:479–488, 2021. arXiv:2103.12192 [\[Link\]](#). [141](#)

Index

- α -compositing, 58
- m -interlacing, 72, 223, 231, 234, 281
- A/B testing, 279
- activation function, 137
- AdaBoost, 37, 280
- Adam gradient descent, 138
- additive number theory, 248, 255
- adversarial learning, 129, 282
- agent-based modeling, 191, 204
- AI art, 130, 200
- algebraic number, 157
- algorithmic bias, 130
- analytic continuation, 242, 249
- analytic function, 155
- anisotropy, 209, 230, 236
- anti-aliasing, 56, 60, 259, 264
- association rule, 272
- attraction (point process), 221
- attraction basin, 59
- attractor distribution, 175, 225, 231, 238
- augmented data, 36, 89, 191, 193, 282
- auto-correlation, 50, 156
- auto-regressive process, 50, 175, 280
- Bailey–Borwein–Plouffe formulas, 157
- Bayesian classification, 75
- Bayesian inference, 45
 - hierarchical models, 281
 - naive Bayes, 272
- Bernoulli trials, 266
- Berry-Esseen inequality, 153
- Bessel function, 237
- Beurling primes, 156, 252
- binning, 271
 - optimum binning, 38, 280
- binomial distribution, 231
- bisection method (root finding), 182
- boosted trees, 131
- bootstrapping, 16, 97, 130, 232
 - percentile method, 102
- boundary effect, 218, 219, 224, 225, 229–231, 235
- Brownian motion, 52, 170, 174, 191, 192, 207, 276, 280
 - Lévy flight, 175
- Brun’s theorem, 248
- Cauchy distribution, 175
- Cauchy-Riemann equations, 155
- causality, 281
- Cayley-Hamilton theorem, 48
- CDF regression, 18
- censored data, 224
- central limit theorem, 175, 216, 266
- chaotic dynamical system, 191, 207
- character
 - principal, 244
- characteristic function, 237
- characteristic polynomial, 48, 50–52, 176
- ChatGPT, 273
- Chebyshev’s bias (prime numbers), 155, 244
- checksum, 279
- Chi-squared test, 218
- Chowla conjecture, 246
- classification, 282
- clique (graph theory), 226
- cluster process, 220, 224, 231
- clustering, 282
- Collatz conjecture, 163
- collision graph, 207
- color model
 - RGB, 56, 265
 - RGBA, 56, 57, 77, 265
- color opacity, 201
- color transparency, 21, 193, 265
- complex random variable, 152, 252
- computational complexity, 165, 273
- computer vision, 13, 84
- confidence band, 232
- confidence interval, 45, 229, 280
- confidence level, 267, 269
- confidence region, 16, 30, 130, 229, 230, 266
 - dual region, 45, 267, 280
- conformal map, 15
- confusion matrix, 271, 282
- connected components, 141, 208, 224–226, 230, 231, 274
- contour level, 200, 269
- contour plot, 269
- convergence
 - abscissa, 244, 249
 - absolute, 113, 241, 242
 - alternating series, 242
 - conditional, 113, 154, 244
 - Dirichlet test, 242
- convergence acceleration, 60
- convex linear combination, 109
- convolution of distributions, 237
- copula, 100, 130, 147
 - Frank, 130, 136
 - Gaussian, 130
- correlation matrix distance, 136, 141, 146

cosine distance, 274
 counting measure, 217
 covariance matrix, 91, 266
 covering (stochastic), 233
 covering problem, 232
 credible interval, 45
 credible region (Bayesian), 267, 280
 critical line (number theory), 114
 cross-validation, 16, 138, 207, 271
 cuban primes, 248
 curse of dimensionality, 116
 curve fitting, 27

 data video, 191, 200
 decision tree, 37
 decorrelate, 146
 decorrelation, 140, 146
 Dedekind zeta function, 155, 252
 deep neural network, 74, 137, 281
 dense set (topology), 246
 density estimation, 223
 diamond-square algorithm, 192
 Diehard tests of randomness, 154
 dimensionality reduction, 17
 Dirichlet character, 155, 156, 243, 248
 modulo 4, 244, 249, 250
 Dirichlet eta function, 256
 Dirichlet functional equation, 155, 249, 250
 Dirichlet series, 152
 Dirichlet's theorem, 155, 244, 246, 250
 Dirichlet- L function, 155, 243, 250
 disaggregation, 115
 discrete Fourier series, 120
 discrete orthogonal functions, 120
 dissimilarity metric, 274
 distributed architecture, 270
 distribution
 Cauchy, 175
 Fréchet, 52, 175
 Gaussian, 266
 generalized logistic, 91, 220
 Hotelling, 267
 Laplace, 237
 logistic, 17
 Lévy, 175
 modified Bessel, 237
 Poisson-binomial, 185, 239
 Poisson-exponential, 216
 Rademacher, 152, 153
 Rayleigh, 231, 232, 238
 Weibull, 52, 175, 231
 domain of attraction, 225
 dot product, 15
 dummy variable, 37
 dummy variables, 137
 dyadic map, 156
 dynamical systems, 156, 225
 chaotic systems, 191, 207
 dyadic map, 156
 ergodicity, 156
 logistic map, 156
 shift map, 156
 stochastic, 192

 edge effect (statistics), 224
 eigenvalue, 14, 53, 91, 282
 power iteration, 93
 elbow rule, 179, 224, 231, 276
 elliptic curve, 248
 EM algorithm, 36, 134, 281
 empirical distribution, 17, 97, 121, 130, 216, 219, 225,
 231, 236, 238, 250
 multivariate, 153
 empirical quantiles, 102, 146
 ensemble methods, 37, 84, 131
 entropy, 210, 236, 272
 epoch, 137, 140
 equidistribution modulo 1, 158
 equilibrium distribution, 192
 Erdős–Rényi model, 226
 ergodicity, 156, 192, 229, 231, 237
 Euler product, 152, 242, 249
 random, 252
 Euler's transform, 256
 evolutionary process, 192
 experimental design, 279
 experimental math, 57, 240
 explainable AI, 14, 36, 75, 84, 91, 129, 147, 179, 195,
 233
 exploratory analysis, 278
 exponential decay, 41
 exponential sums, 249
 extrapolation, 109
 extreme value theory, 175, 238

 feature attribution, 129
 feature clustering, 134, 140, 141, 146
 feature importance, 129
 feature selection, 16, 98, 270
 Fermat's last theorem, 249
 fixed-point algorithm, 60, 90, 179, 281
 flag vector, 272, 279
 Fourier series, 120
 Fourier transform, 237
 fractal dimension, 52
 fractional part function, 158
 Frobenius norm, 91
 Fruchterman and Rheingold algorithm, 275
 Fréchet distribution, 52, 175
 fuzzy classification, 57

 Gamma function, 52, 175
 GAN (generative adversarial networks), 36, 129, 134,
 146, 195, 216, 281
 Gaussian circle problem, 255
 Gaussian distribution, 266
 Gaussian mixture model
 see GMM, 36
 Gaussian primes, 155, 251
 Gaussian process, 50, 280
 general linear model, 14
 generalized linear model, 14, 49

generalized logistic distribution, 91, 230
 generative adversarial networks
 see GAN, 36
 generative AI, 191, 204
 generative model, 36, 53, 100, 190, 191, 193, 200, 207, 282
 geostatistics, 103
 GIS, 117
 Glivenko-Cantelli theorem, 250
 GMM (Gaussian mixture model), 70, 71, 133, 134, 146, 147, 216, 281
 Goldbach's conjecture, 248
 goodness-of-fit, 57, 271
 GPU-based clustering, 72
 gradient (optimization), 179
 gradient boosting, 280
 gradient operator, 16
 Gram-Schmidt orthogonalization, 120
 graph, 224
 collision graph, 207
 connected components, 141, 208, 230, 274
 directed, 208
 edge, 224
 Fruchterman-Reingold, 208
 nearest neighbor graph, 226, 230
 node, 224, 226
 random graph, 225
 random nearest neighbor graph, 225
 tree, 208
 undirected, 141, 224–226, 231
 vertex, 224
 graph database, 275
 graph theory, 224
 GraphViz, 208
 greedy algorithm, 113, 255
 grid search, 179, 194
 half-tone (music), 262
 Hartman–Wintner theorem, 170
 hash table, 166, 210, 235, 272, 273
 sparse, 273
 Hausdorff distance, 88
 Hellinger distance, 130, 146, 147
 Hermite polynomials, 120
 hexagonal lattice, 224
 hidden decision trees, 37, 38, 280
 hidden layer, 74
 hidden process, 217, 234, 238
 hierarchical clustering, 74, 141, 273
 Hilbert primes, 251
 histogram equalization, 72, 74
 Hoeffding inequality, 173
 homogeneity (point process), 185, 223
 Hotelling distribution, 267
 Hurst exponent, 52
 hyperparameter, 30, 57, 104, 194
 hyperparameters, 136
 identifiability, 234, 236
 ill-conditioned problem, 27, 53, 93, 282
 image segmentation, 74
 imputation (missing values), 130
 index
 index discrepancy, 236
 intensity (stochastic process), 216, 223, 230
 interarrival times, 174, 216, 225, 229, 236
 standardized, 237
 interlaced processes, 223
 Internet of Things, 216
 inverse distance weighting, 105
 inverse square law, 204
 iterated logarithm, 153, 154, 170
 Itô integral, 53
 K-means clustering, 32, 33
 key-value pair, 38, 272
 Kolmogorov-Smirnov test, 130, 153, 218, 225
 kriging, 113
 Kronecker's theorem, 246, 254
 Lagrange interpolation, 53
 Lagrange multiplier, 16, 281
 Laplace distribution, 237
 large language models, 273, 282
 Lasso regression, 16, 282
 latent variables, 137
 lattice, 222
 perturbed lattice, 216
 shifted, 224
 stretched, 224
 law of the iterated logarithm, 153, 154, 170, 246, 252
 Le Cam's theorem, 185, 217
 learning rate, 136, 141, 146
 least absolute residuals, 102
 LightGBM, 136, 146
 link function, 14, 17
 Liouville function, 243, 254
 LLM (large language model), 273, 282
 log-polar map, 15
 logistic distribution, 17, 223
 logistic map, 156
 logistic regression, 17
 unsupervised, 34
 logit function, 281
 loss function, 137, 140, 146
 Lévy distribution, 175
 Lévy flight, 175
 Map-reduce, 270
 marketing attribution, 279
 Markov chain, 50
 MCMC, 152
 Mathematica, 269
 MaxCliqueDyn algorithm, 226
 maximum likelihood estimation, 268, 281, 282
 mean squared error, 16, 31
 medoid, 32
 Mersenne twister, 30, 156, 159, 172
 Mertens function, 243
 minimum contrast estimation, 194, 233, 236, 268
 mixture model, 30, 46, 192, 200, 223, 224, 231, 269, 282

blending, 192
 model fitting, 57, 281
 model identifiability, 16
 modulus (complex number), 176, 242
 Monte Carlo simulations, 152, 281
 morphing (computer vision), 191
 moving average, 181
 multidimensional Fourier series, 121
 multiple root, 114
 multiplicative function
 completely multiplicative, 152, 154, 243, 244, 255
 Rademacher, 152
 Möbius function, 243

 N-body problem, 204
 n-gram (NLP), 273
 naive Bayes, 272, 280
 natural language generation, 273, 282
 natural language processing, 37, 273
 nearest neighbor interpolation, 102, 105
 nearest neighbors, 216, 226, 232, 281
 nearest neighbor distances, 230–232, 234, 238
 nearest neighbor graph, 230
 NetworkX, 208
 neural network, 74
 activation function, 137
 epoch, 137
 hidden layer, 74
 hyperparameter, 76
 neuron, 74, 137, 281
 seq2seq, 190
 sparse, 70
 very deep, 74
 Newton's method, 179
 NLG (natural language generation), 273, 282
 node (decision tree), 38, 131, 280
 perfect node, 45
 usable node, 39
 node (interpolation), 114
 normal number, 153, 246, 250
 strongly normal, 154
 numerical stability, 48

 Omega function, 243, 249
 order statistics, 238
 ordinary least squares, 51, 102, 120
 orthogonal function, 120
 Otsuka–Ochiai coefficient, 274
 outliers, 238, 276
 overfitting, 16, 130, 136, 236, 280

 palette, 191, 265
 parametric bootstrap, 21, 30, 36, 98, 130, 232, 280, 281
 partial derivative, 114
 partial least squares, 14
 path (graph theory), 224
 percentile bootstrap, 102
 permutation
 entropy, 236
 random permutation, 235
 perturbed lattices, 216

 Plotly, 200
 point count distribution, 217, 230, 233
 point process
 attractive, 231
 cluster process
 Matérn, 222
 Neyman–Scott, 222
 non-homogeneous, 185, 223
 perturbed lattice process, 222
 radial, 223
 renewal process, 222
 repulsive, 221
 Poisson point process, 174, 185, 216, 230
 Poisson-binomial distribution, 185, 216, 239
 Poisson-exponential distribution, 216
 positive semidefinite (matrix), 49, 92
 power iteration, 93
 preconditioning, 93
 prediction interval, 16, 97, 102
 predictive power, 38, 45, 129, 271, 272
 prime test (of randomness), 154, 165, 171
 principal component analysis, 49, 129, 280
 probability generating function, 171
 proxy space, 269
 pseudo-inverse matrix, 49
 pseudo-random numbers, 172, 276
 combined generators, 169
 congruential generator, 159
 Diehard tests, 154, 166
 Mersenne twister, 159, 172, 193
 prime test, 154, 171
 strongly random, 154, 157
 TestU01, 154
 Pólya conjecture, 245

 quadratic irrational, 156, 159, 165
 quantile, 267, 281
 empirical, 102, 130
 weighted, 102
 quantile function, 100, 121, 216, 220, 231
 quantile regression, 16

 R-squared, 16, 36, 194
 Rademacher distribution, 153
 Rademacher function, 152, 246, 252
 random, 154
 random function, 184
 random graph, 225, 226
 random multiplicative function, 152
 Rademacher, 154
 random permutation, 235
 random variable
 complex, 152
 random walk, 170, 194, 280
 first hitting time, 171, 174
 zero crossing, 170
 Rayleigh distribution, 231, 232, 238
 Rayleigh test, 231
 records, 238
 regression splines, 14
 regular expression, 273, 279

reinforcement learning, 141, 147, 282
 rejection sampling, 131
 ReLU function, 137
 renewal process, 222
 repulsion (point process), 221, 232
 repulsion basin, 242
 resampling, 97, 232
 Riemann Hypothesis, 108, 114
 Generalized, 154, 244, 248, 250
 Riemann zeta function, 114, 152, 155, 250, 252
 root mean squared error, 57
 scaling factor, 230, 238
 SDV (Python library), 135
 seed (random number generator), 131, 136, 140, 166, 193
 semi-supervised learning, 282
 shape signature, 85
 Shapley value, 129
 Shepard's method, 105
 shift map, 156
 sigmoid function, 137, 281
 simplex, 253
 singular value decomposition, 14, 282
 singularity, 210
 six degrees of separation, 275
 Sklar's theorem, 130
 smoothing parameter, 104
 spatial statistics, 103, 222
 spectral domain, 192
 spline regression, 121
 square root (matrix), 49, 92, 140
 square-free integer, 153, 166, 246
 stable distribution, 175, 193, 237
 state space, 192
 stationary distribution, 53
 stationary process, 50, 175, 192, 207, 218, 223, 230
 stepwise regression, 99
 stochastic convergence, 192
 stochastic function, 52
 stochastic geometry, 233
 stochastic gradient descent, 137
 stochastic process, 216
 stochastic residues, 234
 stop word (NLP), 273
 stretching (point process), 224
 Sturm-Liouville theory, 120
 superimposition (point processes), 223
 supervised classification, 72
 surface plot, 200
 SVD (Python library), 146
 swarm optimization, 28, 281
 synthetic data, 14, 28, 30, 53, 89, 91, 113, 119, 130, 152, 165, 171, 179, 193, 200, 207, 240, 267
 synthetic metric, 272
 TabGAN (Python library), 136
 Tarjan's algorithm, 274
 tensor, 75
 TensorFlow, 136
 text normalization, 273