

Portfolio of John Vincent Pangilinan

— maintenance guide

\$ how to extend this site without breaking it

This document is the source of truth for anyone — human or AI — who changes this portfolio. It explains how the site is built, its developer-style design system, the facts it contains, and step-by-step recipes for the changes most likely to be requested. **Read it completely before editing any file, then change only what was asked.**

owner	John Vincent Pangilinan — Junior Software Engineer & Web Developer, Biñan, Laguna, Philippines
site type	Static website: 4 HTML pages, 1 CSS file, 1 JavaScript file. No build step, no framework, no package manager.
design	Version 2, “developer”: terminal / IDE visual language, dark-first, JetBrains Mono + Geist, one green accent.
local folder	<code>/Applications/XAMPP/xamppfiles/htdocs/WebApp 3/portfolio/</code> Preview: <code>http://localhost/WebApp%203/portfolio/</code>
deploys to	Any static host (Vercel, Netlify). Canonical URL today: <code>https://portfolio-five-plum-34.vercel.app/</code>
audiences	1 — Recruiters and hiring managers for junior software engineer / web developer roles. 2 — Freelance clients who need a web system built.

How to use this guide

For John — every time you ask an AI to change the portfolio:

1. Attach this PDF **and** the portfolio folder or zip to the chat.
2. Paste the prompt below and replace the last line with what you want.
3. When it's done, ask for the list of changed files, then check the site at <http://localhost/WebApp%203/portfolio/> (press **Cmd+Shift+R** to refresh).

Paalala: laging i-attach ang PDF na ito kasama ng portfolio files, para alam ng AI ang mga patakaran at idadagdag lang nito ang ipinapagawa mo — hindi nito babaguhin ang design.

prompt Copy and paste this

You are maintaining my personal portfolio website. The attached PDF, "Portfolio of John Vincent Pangilinan – maintenance guide" (version 2.1), is the source of truth. Read all of it before changing anything and follow its Golden Rules (section 01).

- Make only the change I ask for. Do not redesign, rename, reorder or rewrite anything else.
- Keep the developer design: reuse the existing CSS classes, design tokens and page patterns.
- Never invent facts, numbers, testimonials or skills. Use a bracketed placeholder or a TODO note and tell me instead.
- Keep the header, mobile menu and status-bar footer identical on all four pages.
- Run the QA checklist (section 08) and list every file you changed.

My request: [describe the change here]

contents What's inside

01	Golden rules	06	Content facts (source of truth)
02	Project map	07	Accessibility & performance
03	Design system	08	QA checklist
04	Page anatomy	09	Change log
05	Recipes — common changes		

Golden rules

These are non-negotiable. If a request seems to conflict with one of them, ask John before proceeding.

01 Change only what was asked.

No redesigns, renames, reordering, “improvements” or rewording of untouched content.

02 No frameworks, libraries or build tools.

The site is plain HTML, one stylesheet (`assets/css/main.css`) and one deferred script (`assets/js/main.js`). Do not add Tailwind, Bootstrap, React, jQuery, npm packages or icon fonts. (Laravel, React and Tailwind appear in the Tech stack as John's skills — the site itself does not use them.)

03 Use the design tokens.

Colours, font sizes, spacing, radii and motion come from the CSS custom properties at the top of `main.css`. Never hard-code new values. The only exceptions are technology brand colours on Tech stack tiles and language-dot colours on project cards.

- 04 **One accent, used sparingly.**
The accent is terminal green (`--accent`). Syntax colours (`--syn-*`) appear only inside code blocks; `--yellow` only for commit hashes and TODO notes. No gradients, glows, neon, emoji or extra colours. Radii are small (4 / 8 / 12px); shadows only on windows and hovered cards.
-
- 05 **Two typefaces only.**
JetBrains Mono for structure — headings, labels, navigation, buttons, code and data. Geist for reading text — paragraphs and descriptions. Weights 400, 500, 600. No other fonts.
-
- 06 **Keep the developer motifs consistent and tasteful.**
Paths (`~/work`), comments (`//` , `#`), window frames, the terminal, code blocks, the git log and the status bar. Reuse them — don't add matrix effects, typing animations everywhere, fake consoles or gimmicks.
-
- 07 **Stay on the grid.**
4 / 8 / 12 columns inside `.wrap` (max width 76rem). Use `.grid` , `.rail` , `.content` , `.content--narrow` on case pages.
-
- 08 **Works everywhere.**
Every change must work in light and dark themes and at 375, 428, 768, 1024, 1280, 1440 and 1920px wide, with no horizontal scrolling.
-
- 09 **Accessibility is part of the design.**
Semantic HTML, one `h1` per page, headings in order, alt text on every image, visible focus, 44px touch targets, reduced motion respected, text contrast $\geq 4.5:1$. See section 07.
-
- 10 **Never invent content.**
No made-up metrics, testimonials, clients, employers, dates or skills. Use bracketed placeholders (`[00]`) or a `.todo` note and tell John what to supply. Decorative details (commit hashes, file names) are fine.
-
- 11 **Keep the positioning.**
John is a junior software engineer and web developer who builds full-stack systems — not a UI/UX designer.
-
- 12 **Removed on purpose — do not bring back unless asked:**
testimonials (“Kind words”), the Capabilities list, Engagement options, “You get” / time estimates in How I work, the Sales associate (CLN Retail), PSA team leader and TESDA NC II entries — from Experience, About and `profile.ts` — and the version-1 Swiss/editorial styling (Switzer, Newsreader, serif statements).
-
- 13 **Shared parts are duplicated.**
The `<head>` boilerplate, header, mobile menu and status-bar footer exist in all four HTML files (no includes). Change all four; case pages use `../` paths.
-
- 14 **Images are WebP with responsive sizes.**
Generate them with `tools/make-images.sh`. Every `<img>` has `srcset` , `sizes` , `width` , `height` , `decoding="async"` and meaningful `alt` ; below-the-fold images use `loading="lazy"` .
-
- 15 **Keep numbering and file names.**
Home sections are 01–05, case-study sections 01–07. If you add or remove one, renumber and update the nav and mobile menu on every page. Don't rename files — other pages link to them.
-
- 16 **Verify before you finish.**
Run the QA checklist in section 08 and report exactly what changed.
-

02 Project map

path	what it is
<code>index.html</code>	Home: hero + terminal, selected work, about + pipeline, tech stack, experience (git log), contact.
<code>work/jar-garments.html</code>	Case study 01 — freelance e-commerce system.

path	what it is
<code>work/codelearn.html</code>	Case study 02 — capstone learning platform. The most complete page; use it as the template for new case studies.
<code>work/trimex-library.html</code>	Case study 03 — OJT library management system.
<code>assets/css/main.css</code>	The only stylesheet, in this order: tokens · base · layout · shared · header & menu · hero · work (repo cards) · about & pipeline · tech stack · experience (git log) · contact · status bar · case study pages · motion & print. (Code comments were removed from this copy.)
<code>assets/js/main.js</code>	The only script (vanilla, deferred): theme switch, header state, mobile menu, nav highlight, scroll reveals, copy-email, local clocks, grid overlay, footer year, iOS tap states.
<code>assets/img/work/<project>/</code>	Project images, WebP, named <code><name>-<width>.webp</code> at 800 / 1200 / 1600 (and 2400 for large covers).
<code>assets/img/about/</code>	Portrait: <code>portrait-480 / 800 / 1080.webp</code> (4:5).
<code>assets/img/og-image.jpg</code>	1200 × 630 link-preview card (dark, terminal style). <code>apple-touch-icon.png</code> is the 180 × 180 icon.
<code>assets/favicon.svg</code>	Favicon: green <code>>_</code> prompt on a dark rounded tile.
<code>assets/files/john-vincent-pangilinan-cv.pdf</code>	Résumé download (Experience, Contact, mobile menu, case-study CTAs).
<code>tools/make-images.sh</code>	<code>tools/make-images.sh <source> <output-path-without-size> ["800 1200 1600"]</code> — needs macOS <code>sips</code> and <code>cwebp</code> .
<code>README.md</code>	Short notes for John: placeholders to fill, deployment.

external Loaded at runtime – the only third-party requests

resource	source
Geist + JetBrains Mono	Google Fonts — <code>family=Geist:wght@400;500;600&family=JetBrainsMono:wght@400;500;600</code>
Technology logos	jsDelivr — Simple Icons v14 (<code>npm/simple-icons@14/icons/<slug>.svg</code>) and Devicon v2.16.0 (<code>gh/devicons/devicon@v2.16.0/icons/...</code>) for VS Code and MySQL.

No analytics, cookies or trackers. The only stored data is the theme choice in `localStorage` under the key `jvp-theme`.

shared Parts repeated on every page

- **Head:** meta description, canonical + Open Graph tags, two `theme-color` metas (`#fbfbfc / #0b0d11`), favicon, an inline script that applies the saved theme before first paint, the Google Fonts stylesheet, `main.css`, `main.js` (deferred).
- **Header:** brand `~/john-vincent` with a blinking cursor, desktop nav `./work ./about ./stack ./experience ./contact`, theme switch `light / dark`, toggle `menu / close`.
- **Mobile menu** (`#mobile-menu`): numbered `./` links 01–05, theme switch, email / `résumé.pdf` / `github`.
- **Footer = status bar** (`footer.site-footer.statusbar`): branch “main”, “available”, ©, Biñan clock, UTF-8, “grid” toggle, “top” link.
- On case pages nav links point to `../index.html#section` and the work link has `class="is-current"`.

Design system

Terminal / IDE language: monospace structure, quiet panels with 1px borders and small radii, a dot-grid hero, and a single terminal-green accent. Dark first, with a full light theme.

3.1 Colour tokens

token	light	dark	used for
<code>--bg</code>	 #fbfbfc	 #0b0d11	Page background
<code>--bg-2</code>	 #f3f4f6	 #11141a	Panels, windows, cards, code, status bar
<code>--bg-3</code>	 #e9ebef	 #181c23	Hover surfaces, image backgrounds
<code>--fg</code>	 #15171c	 #e6e8eb	Main text
<code>--fg-2</code>	 #4f5761	 #a7b0ba	Secondary text, logos at rest
<code>--fg-3</code>	 #67707a	 #7f8994	Labels, comments, paths, meta
<code>--line</code> <code>--line-strong</code>	fg at 10% / 20%	fg at 9% / 18%	1px borders, dividers, connectors
<code>--accent</code>	 #1a7f37	 #3fb950	Prompts, cursor, status dot, active nav, indices, primary button, focus ring
<code>--accent-soft</code>	accent at 10%	accent at 13%	Check icons, HEAD badge, button glow
<code>--yellow</code>	 #8a5d00	 #d29922	Commit hashes and TODO notes only
<code>--syn-key</code>	 #cf222e	 #ff7b72	Keywords (<code>.tk-k</code>)
<code>--syn-str</code>	 #0a3069	 #a5d6ff	Strings (<code>.tk-s</code>)
<code>--syn-fn</code>	 #8250df	 #d2a8ff	Functions (<code>.tk-f</code>)
<code>--syn-prop</code> <code>--syn-num</code>	 #0550ae	 #79c0ff	Properties and numbers (<code>.tk-p</code> , <code>.tk-n</code>); also the keys in key/value lists
<code>--syn-com</code>	 #5f6871	 #8b949e	Comments (<code>.tk-c</code>)

WCAG AA verified (lowest value on `--bg` or `--bg-2`): light — fg 16.3, fg-2 6.6, fg-3 4.6, accent 4.6, button text 5.1; dark — fg 15.0, fg-2 8.4, fg-3 5.2, accent 7.3, button text 7.7. Every syntax colour is $\geq 4.6:1$. Syntax colours appear only inside code. New text colours must reach 4.5:1.

How theming works. Light tokens live in `:root`. Dark tokens are repeated in two blocks: `@media (prefers-color-scheme: dark) { :root:not([data-theme="light"]) { ... } }` and `:root[data-theme="dark"] { ... }`. A new token must be added to all three. The theme buttons set `data-theme` and save it to `localStorage`; choosing the theme the OS already uses removes the saved value. The script's `PAPER` map holds the two `--bg` values for the `theme-color` meta.

3.2 Typography

token	size (360 → 1600px)	used for
<code>--fs-xs</code>	12px	Labels (<code>.label</code> , lowercase mono), paths, meta, status bar
<code>--fs-sm</code>	13 → 14px	Nav, buttons, card text, lists, code-ish UI
<code>--fs-base</code>	16 → 17px	Body text (Geist)
<code>--fs-lg</code>	18 → 21px	Intros (<code>.lead</code>), commit messages
<code>--fs-xl</code>	20 → 26px	Card titles, hero role, path titles
<code>--fs-2xl</code>	26 → 40px	Section titles, About statement

token	size (360 → 1600px)	used for
--fs-3xl	36 → 72px	Hero name (h1)
--font-mono JetBrains Mono for h1-h4 , labels, nav, buttons, code, data and key/value lists; --font-sans Geist for paragraphs. Ligatures are switched off in UI text (font-variant-ligatures: none) and left on in code. Headings use negative tracking (−0.02 to −0.05em). UI labels are lowercase (light / dark , read case study); headings use sentence case. Keep curly quotes (' “ ” '), en dashes for ranges (2024–2025), “résumé” with accents, and &#8209; in “full-stack”.		

3.3 Space, grid, shape and breakpoints

breakpoint	columns	gutter / margin	notes
base (phones)	4	16px / 20px	Everything stacks; menu toggle
min-width: 48em (768px)	8	24px / 32px	Repo cards show image beside text
min-width: 64em (1024px)	12	24px / 40px	Desktop nav, 2-column hero, 3 repo cards, 5-stage pipeline

.wrap

 max width 76rem (1216px). Every direct child of

.grid

 spans full width until placed. Spacing tokens

--s-1

 4px ...

--s-8

 64px;

--section-gap

 72–144px. Radii:

--r-sm

 4px (chips, badges),

--r

 8px (buttons, flow steps),

--r-lg

 12px (panels, windows, cards); pills (999px) only for the status badge and contents chips.

3.4 Motion

- data-intro

 +

style="--i: N"

 — on-load rise, staggered (hero and case headers).
- data-reveal

 — fade/slide on scroll; JS adds

.will-reveal

 only below the fold. Optional

style="--delay: 80ms"

 .
- Terminal lines appear in sequence via

style="--n: N"

 on each

.term__body

 p ; the cursor and the brand cursor blink; the status dot pulses.
- Theme changes cross-fade (View Transitions API, 300ms).

prefers-reduced-motion

 turns every animation off.

3.5 Developer motifs – how to use them

motif · class	use
Section header — .section-head__bar : 01 ~/path — meta , then .section-head__title	Every home section. Index in accent, path in --fg-3 .
Window — .window + .window__bar (.window__dots , .window__title , .window__meta)	Terminal, code blocks, portrait, case-study covers. Title = file name, command or URL.
Terminal — .term__body p with .term__ps (\$), .term__out , .term__dir , .term__ok , .cursor	Hero only. Lines must state true facts; prompts are aria-hidden .
Code — pre.code__body with .tk-k .tk-s .tk-f .tk-p .tk-n .tk-c	profile.ts in About, the “also” array in Tech stack. Lines wrap (no sideways scroll).
Key/value — dl.kv ; case pages dl.frontmatter (YAML with ---)	Hero meta; case-study facts (role, timeline, client...).
Repo card — .repo (__media __body __path __title __link __desc __foot __cta), .langs + .langs__dot (--c)	Projects. Whole card clickable via .repo__link::after .
Pipeline — .pipeline + .stage (__head __icon __name __step)	How I work: Define, Design, Prototype, Test, Deliver.
Git log — ol.gitlog + .commit (--head __head __hash __ref __date __msg __body)	Experience. commit--head + “HEAD → main” only on the newest development role.
TODO — p.todo + .todo__tag “TODO(john):”	Content John still has to supply. Delete it once filled.
Status bar — footer.site-footer.statusbar + .sb-item	Global footer on every page.
Tech tiles — .stack-grid .tech (__mark __logo __name __kind), .tech--js , .tech--also	Recipe 5.1.
Other — .btn--primary / --ghost (aliases --solid / --line), .panel , .cmd-list , .email .copy-btn , .pulse , .label .lead .muted .link .icon	Buttons, panels, contact links, utilities.

Case pages — `.case-hero` `.breadcrumb` `.case-cover` `.glance` `.toc`
`.case-section` `.case-body` `.insights` `.flow` `.case-quote` `.figure`
`.figure-pair` `.decisions` `.stack` `.metrics` `.case-next` `.cta-band`

Case-study components (section 4.2).

04

Page anatomy

4.1 Home — `index.html`

section id	no.	contents
#intro	—	Status pill · <code>h1</code> name · role line · lead · buttons “View projects” and “Get in touch” · <code>dl.kv</code> (location + clock, focus, education) · terminal window (11 lines).
#work	01	<code>~/work</code> · intro · 3 repo cards (1 col phones, image-beside-text tablets, 3 cols desktop).
#about	02	<code>//</code> statement · portrait window · 3-paragraph bio · <code>profile.ts</code> code · How I work pipeline.
#stack	03	14 logo tiles + “also” code tile + hint line.
#experience	04	Résumé panel · git logs: software & web development · education.
#contact	05	“Let’s build something that lasts.” · recruiters panel · clients panel (email + copy, Telegram) · elsewhere links + local time.

The nav highlight follows the section in view automatically (any `main section[id]`).

4.2 Case studies — `work/*.html`

- Breadcrumb path `~/work / slug` · label “Case study ON / 03 — Type” · `h1` · deck.
- `dl.frontmatter` with six keys: role, timeline, client or team, platform, stack, links or scope.
- Cover inside `.window` (title = URL or screen name), `fetchpriority="high"`.
- At a glance (problem · solution · outcome) and a contents row of chips.
- Sections with ids `context` 01 · `requirements` 02 · `system-design` 03 · `features` 04 · `build` 05 · `results` 06 · `reflection` 07; open questions as `.todo`.
- `.case-next` (01 → 02 → 03 → 01) and `.cta-band` “Need a system like this one?”.

05

Recipes — common changes

5.1 Add a technology to the Tech stack

Each tile is a single-colour logo drawn as a CSS mask: `--fg-2` at rest, brand colour on hover (tap on phones).

```
<li class="tech" style="--logo: url(https://cdn.jsdelivr.net/npm/simple-icons@14/icons/SLUG.svg); --brand: #HEX">
  <span class="tech_mark" aria-hidden="true"><span class="tech_logo"></span></span>
  <span class="tech_name">Name</span>
  <span class="tech_kind label">Category</span>
</li>
```

- Find the icon on **simpleicons.org** (slug + brand hex) and check the URL loads; if missing, use Devicon (`.../devicon@v2.16.0/icons/NAME/NAME-plain.svg` or `-original.svg`).
- Insert it in its group (languages → frameworks → database → tools); the “also” tile stays last.
- Add `--brand-dark` if the brand colour vanishes on dark (e.g. black); use a deeper official colour for `--brand` if it's too pale on light (React: `#087ea4` / `#61dafb`).
- Keep every row full.** Columns are 2 / 4 / 6. The “also” tile spans the empty cells of the last row: `span = cols - (logos mod cols)`, or `cols` when 0. Today 14 logos → spans 2 / 2 / 4 (`.tech--also` in the tech stack rules of `main.css`).

- Update the section meta ("14 tools"), the terminal's `stack.txt` line if relevant, and JSON-LD `"knowsAbout"` .
- Never add it to a project's language dots unless that project used it.

current tiles (in order)	--brand / --brand-dark
PHP · JavaScript (.tech--js) · HTML5 · CSS3	#777bb4 · #f7df1e · #e34f26 · #1572b6 / #3d9be9
Laravel · React · Tailwind CSS · Bootstrap	#ff2d20 · #087ea4 / #61dafb · #06b6d4 / #38bdf8 · #7952b3 / #9a73d6
MySQL (Devicon) · Git · GitHub	#4479a1 / #5d9bcc · #f05032 · #181717 / #f0f6fc
VS Code (Devicon) · XAMPP · Linux	#007acc / #23a9f2 · #fb7a24 · #d9a400 / #fcc624

5.2 Add a project

- Images:** 16:10 cover ≥ 1600px wide → `tools/make-images.sh cover.png assets/img/work/SLUG/cover` .
- Card:** copy a `<li class="repo">` (template below). Language dots use GitHub colours: PHP `#4f5d95` , JavaScript `#f1e05a` , MySQL `#4479a1` , Bootstrap `#7952b3` , GCash `#007dfe` ; others may omit `--c` (grey).
- Update the `#work` meta ("3 systems · 2024–2025"), the hero lead and the terminal's `ls projects/` line.
- Page:** copy `work/codelearn.html` to `work/SLUG.html` ; update title, meta, canonical/OG, breadcrumb slug, label, `h1` , deck, frontmatter, cover window title, glance, sections and next link.
- Renumber "Case study X / T" on every case page and fix the next-case chain. A 4th card starts a new row on desktop — ask John before changing the 3-column grid.

```
<li class="repo" data-reveal style="--delay: 80ms">
  <figure class="repo__media">
    
  </figure>
  <div class="repo__body">
    <p class="repo__path">~/work/<span>SLUG</span></p>
    <h3 class="repo__title"><a class="repo__link" href="work/SLUG.html">Project name</a></h3>
    <p class="repo__desc">One sentence: what the system is and what it does.</p>
    <ul class="langs" role="list" aria-label="Built with">
      <li><span class="langs__dot" style="--c: #4f5d95" aria-hidden="true"></span>PHP</li>
    </ul>
    <p class="repo__foot"><span>type · 2026</span><span class="repo__cta" aria-hidden="true">read case study <svg class="icon"
      viewBox="0 0 16 16"><path d="M2.5 8h11M9 3.5L13.5 8 9 12.5"/></svg></span></p>
  </div>
</li>
```

5.3 Replace a placeholder image

- `tools/make-images.sh ~/Desktop/shot.png assets/img/work/jar-garments/checkout` — overwrites the 800 / 1200 / 1600 files.
- Rewrite the `alt` (remove "(placeholder)"); set `width` / `height` if not 16:10; delete the matching `.todo` note once answered.

5.4 Add an experience entry (a commit)

```
<li class="commit" data-reveal>
  <p class="commit__head"><span class="commit__hash" aria-hidden="true">1a2b3c4</span><span class="commit__date"><time
    datetime="2026-01">Jan 2026</time> – <time datetime="2026-06">Jun 2026</time></span></p>
  <h4 class="commit__msg">Junior software engineer <span>@ Company · City</span></h4>
  <p class="commit__body">One or two sentences: what you built or owned, with a concrete result.</p>
</li>
```

Newest first inside the right `.log-group` . The hash is any 7 hex characters (decorative). For a new current development role, move `commit--head` and the `<span class="commit__ref" aria-hidden="true">HEAD → main</span>` badge to it.

5.5 Add a section to the home page

```
<section class="section" id="SECTION" aria-labelledby="SECTION-title">
  <div class="wrap">
    <header class="section-head" data-reveal>
      <p class="section-head__bar"><span class="section-head__index">0N</span><span>~/SECTION</span><span class="section-head__rule" aria-hidden="true"></span><span class="section-head__meta">short meta</span></p>
      <h2 class="section-head__title" id="SECTION-title">Title</h2>
    </header>
    <p class="section-intro lead" data-reveal>One-line intro.</p>
  </div>
</section>
```

Renumber the sections after it, then add the link to the desktop nav (`.site-nav__list` , max six) and the mobile menu (`.mobile-menu__list` , keep `--i` and the number in order) on **all four pages** — case pages use `../index.html#SECTION` :

```
<li><a href="#SECTION"><span aria-hidden="true">./</span>SECTION</a></li>
<li style="--i: 5"><a href="#SECTION"><span>06</span><span class="dot-slash" aria-hidden="true">./</span>SECTION</a></li>
```

5.6 Edit text safely

- The hero `h1` is the name; the role line and the lead carry the positioning. Keep the terminal lines true and in sync (role, projects, stack, status), with `-n` counting up from 0.
- Plain, specific sentences — no buzzwords (“passionate”, “seamless”, “cutting-edge”, “ninja”).
- If the positioning changes, also update `<title>` , meta description, Open Graph tags, JSON-LD `jobTitle` and `og-image.jpg` .

5.7 Résumé, contact details and domain

- Replace `assets/files/john-vincent-pangilinan-cv.pdf` (keep the name); update “PDF, 48 KB” in Experience and Contact if the size changes.
- Email, Telegram, GitHub and LinkedIn appear in several places (mobile menus, Contact, JSON-LD, case CTAs) — search the folder and replace every occurrence.
- New domain: update `canonical` , `og:url` , `og:image` on all four pages and `"url"` in the JSON-LD.
- Something truly new? Prefer existing components; otherwise add it to the matching part of `main.css` using tokens, BEM naming and the mono/sans rules, and test both themes.

06 Content facts – source of truth

Use only these facts. Anything not listed here must come from John.

6.1 Identity

name	John Vincent Pangilinan
title	Junior Software Engineer & Web Developer — builds full-stack web systems, from database to deployment
location	Biñan, Laguna, Philippines · GMT+8 (Asia/Manila)
contact	johnvincentppangilinan@gmail.com · github.com/Vincentius8 · linkedin.com/in/johnvincentpangilinan · t.me/Vincenzouu
status	Available for full-time roles and freelance projects; on-site around Laguna / Metro Manila, hybrid or remote
education	BS Information Technology, Trimex Colleges, Biñan — A.Y. 2024–2025 · Dean’s Lister 2024
languages	English (professional), Filipino (native)
tech stack	PHP, JavaScript, HTML5, CSS3, Laravel, React, Tailwind CSS, Bootstrap, MySQL, Git, GitHub, VS Code, XAMPP, Linux; also MVC, PDO, REST/JSON APIs, auth & sessions, GCash payments, RFID

6.2 Experience

dates	role	organisation
May – Sep 2025	Web developer (freelance)	JAR Garments
Jan – Apr 2025	Web developer (OJT)	Trimex Colleges, Biñan
Sep 2024 – Apr 2025	System developer, capstone (CodeLearn)	Trimex Colleges

6.3 Projects – verified facts only

jar garments	Freelance, May–Sep 2025. E-commerce for a custom-garment business: design selection, cart, GCash payments, order tracking, customer accounts, monthly and yearly sales analytics. PHP, MySQL, JavaScript, Bootstrap. Live demo: jar.kesug.com/public/dashboard.php. No public repository.
codelearn	Capstone, Sep 2024 – Apr 2025, team project. Java and C++, 38 topics per language (76 lessons) in strict reading order; exercises; quizzes at 15 seconds per question, graded on the server; in-browser code runner (JDoodle API); progress tracking. PHP MVC + MySQL; CSRF on every state-changing route; five test suites including a responsive-layout guard. Repository private — no link.
trimex library	OJT, Jan–Apr 2025. RFID attendance logging, school Gmail sign-in, browse by genre and reserve online, librarian management of books and transactions, usage analytics. PHP and MySQL, later hardened with PDO prepared statements and an environment file. Repository: github.com/Vincentius8/Trimex-Library-System.

6.4 Still open

- **Placeholders to fill (never invent):** the `[00]` results in the case studies and the eight `TODO(john)` notes (before-state, ERD notes and real figures for JAR and the library; team size and evaluation results for CodeLearn).
- **Placeholder images (8):** `jar-garments/schema`, `checkout`, `analytics` · `codelearn/lesson`, `quiz`, `runner` · `trimex-library/schema`, `rfid`, `analytics`.
- **To confirm with John:** the CodeLearn “Read-aloud (text-to-speech)” line in its Build section.

07

Accessibility & performance

- **Landmarks:** `header`, `nav` with `aria-label`, `main#main`, `footer`; the “Skip to content” link is the first element in `body`.
- **Headings:** one `h1` per page; `h2` sections, `h3` items, `h4` inside items (commits, stages); never skip a level; unique ids.
- **Decorative motifs:** prompts (`$`), `./` prefixes, window dots, commit hashes and the HEAD badge are `aria-hidden="true"`; the terminal and code blocks are real text.
- **Images:** meaningful `alt`; always `width / height`.
- **Controls:** real `<a>` / `<button>`; $\geq 44 \times 44$ px on touch screens (status bar items and contents chips grow on coarse pointers; small text links such as the breadcrumb and front-matter links get padding for a bigger tap area); visible `:focus-visible` ring (2px accent). The menu uses `aria-expanded` / `aria-controls`, closes on Escape and makes `main` and the footer inert while open.
- **External links:** `target="_blank"` `rel="noopener"` plus `<span class="visually-hidden">` (opens in a new tab)`</span>`.
- **Performance:** no new libraries; WebP images with `srcset / sizes`, lazy-loaded below the fold; one font request; the JS stays small and deferred.

08

QA checklist

- 01
- Widths**
375, 428, 768, 1024, 1280, 1440, 1920px — no horizontal scroll (`document.documentElement.scrollWidth === clientWidth`), nothing overlaps.

02	Themes Light and dark via the switch, plus the OS dark setting with no saved choice.
03	Keyboard Tab through: focus visible, skip link works, the mobile menu opens, keeps Tab inside and closes with Escape.
04	Hover and tap Repo cards, tech tiles (brand colour appears), buttons, links.
05	Links and assets Every link, <code>#anchor</code> , image and tech logo loads; no 404s.
06	Console No errors from the site's own code.
07	Structure One <code>h1</code> , headings in order, unique ids, alt text present, contrast $\geq 4.5:1$ for any new colour.
08	Reduced motion With "Reduce motion" on, nothing animates (terminal lines show at once).
09	Cache Hard-refresh (Cmd+Shift+R) when checking locally.
10	Report Tell John what changed, which files, and anything left as a placeholder.

09	Change log
version	changes
2.1 · 3 Oct 2026	John asked to remove the Sales associate, PSA team leader and TESDA NC II entries: removed from Experience (the "other experience" group is gone, "education & certification" is now "education"), from About and from <code>profile.ts</code> . Experience meta now reads 2024 — 2025.
2.0 · 3 Oct 2026	Developer redesign: JetBrains Mono + Geist, dark-first palette with terminal-green accent, terminal hero, path-style navigation and section headers, GitHub-style repo cards, <code>profile.ts</code> code block, CI pipeline for How I work, git-log experience, editor status-bar footer, YAML front matter and TODO notes on case pages, new favicon and social card. Content unchanged.
1.x · 24 Sep 2026	Editorial version; positioned as junior software engineer & web developer; compact project cards; Tech stack with hover colours (Laravel, React and Tailwind CSS added); removed Kind words, Capabilities and Engagement.

When a request changes the structure, the rules or the facts above, ask the AI to note it for the next version of this guide.