

ServiceNow Incident — Client Scripts

Extracted and neatly formatted from the supplied project document.

Task 3 — onChange Client Script: Auto set urgency for high impact

```
function onChange(control, oldValue, newValue, isLoading) {
    if (isLoading || newValue == '') {
        return;
    }

    if (newValue == '1') {
        g_form.setValue('urgency', '1');
        g_form.addInfoMessage('Urgency set to High for High impact incident.');
```

Task 4 — onSubmit Client Script: Prevent save if Assigned To is missing

```
function onSubmit() {
    if (g_form.getValue('impact') == '1' &&
        g_form.getValue('assigned_to') == '') {
        g_form.showErrorMessage(
            'assigned_to',
            'Assigned To is mandatory for High impact incidents.'
        );
        return false;
    }

    return true;
}
```

Task 5 — onCellEdit Client Script: Prevent state change via list edit

```
function onCellEdit(sysIDs, table, oldValues, newValue, callback) {
    alert('State cannot be updated using list editing. Please open the Incident.');
```

Related UI Policy Configuration

UI Policy: High Impact Control | **Table:** Incident | **Condition:** Impact is 1 – High

UI Policy Action: Assignment group mandatory; Reverse if false = true. Urgency is configured as read-only when Impact is High.