


Distributed Algorithms 2020

11a Hardness of coloring

Week 1: fast coloring



3-coloring

$O(\log^* n)$
rounds

- LOCAL model
- directed cycles

$n^{O(1)}$ -coloring

0 rounds
(*unique IDs*)

- LOCAL model
- directed cycles

$n^{O(1)}$ -coloring

0 rounds
(*unique IDs*)



3-coloring

$O(\log^* n)$
rounds

- LOCAL model
- directed cycles

$n^{O(1)}$ -coloring

0 rounds
(*unique IDs*)



3-coloring

$O(\log^* n)$
rounds

2^k -coloring



$2k$ -coloring

*Fast color
reduction*

$n^{O(1)}$ -coloring

0 rounds
(*unique IDs*)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

2^k -coloring



$2k$ -coloring

*Fast color
reduction*

$n^{O(1)}$ -coloring

0 rounds
(unique IDs)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

2^k -coloring



$2k$ -coloring

*Fast color
reduction*

Is this optimal?

Could we find 3-coloring faster?

$n^{O(1)}$ -coloring

0 rounds
(*unique IDs*)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

2^k -coloring



$2k$ -coloring

*Fast color
reduction*

*Round
elimination*

$n^{O(1)}$ -coloring

0 rounds
(*unique IDs*)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

*Round
elimination*

$n^{O(1)}$ -coloring

0 rounds
(*unique IDs*)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

k -coloring

*Round
elimination*

$n^{O(1)}$ -coloring

0 rounds
(*unique IDs*)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

2^k -coloring



k -coloring

*Round
elimination*

$n^{O(1)}$ -coloring

0 rounds
(*unique IDs*)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

2^k -coloring



k -coloring

*Round
elimination*

3-coloring

$T \ll \log^* n$
rounds

$n^{O(1)}$ -coloring

0 rounds
(unique IDs)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

2^k -coloring



k -coloring

*Round
elimination*



T steps

3-coloring

$T \ll \log^* n$
rounds

$n^{O(1)}$ -coloring

0 rounds
(unique IDs)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

2^k -coloring



k -coloring

*Round
elimination*

c -coloring

0 rounds



T steps

3-coloring

$T \ll \log^* n$
rounds

$n^{O(1)}$ -coloring

0 rounds
(unique IDs)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

c = power
tower of
height T

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

2^k -coloring



k -coloring

*Round
elimination*

c -coloring

0 rounds



T steps

3-coloring

$T \ll \log^* n$
rounds

$n^{O(1)}$ -coloring

0 rounds
(unique IDs)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

c = power
tower of
height T
 $\ll n$

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

2^k -coloring



k -coloring

*Round
elimination*

c -coloring

0 rounds



T steps

3-coloring

$T \ll \log^* n$
rounds

$n^{O(1)}$ -coloring

0 rounds
(unique IDs)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

c = power
tower of
height T
 $\ll n$

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

2^k -coloring



k -coloring

*Round
elimination*



c -coloring

0 rounds



T steps

3-coloring

$T \ll \log^* n$
rounds

$n^{O(1)}$ -coloring

0 rounds
(unique IDs)



$O(\log^* n)$ steps

3-coloring

$O(\log^* n)$
rounds

c = power
tower of
height T
 $\ll n$

2^k -coloring

$T - 1$ rounds



$2k$ -coloring

T rounds

*Fast color
reduction*

2^k -coloring



k -coloring

*Round
elimination*



c -coloring

0 rounds



T steps

3-coloring


$T \ll \log^* n$
rounds





Round elimination
assumes the **PN** model


Round elimination


assumes the **PN** model,
it does **not** work in
the **LOCAL** model

















Negative result for randomized PN ?

Negative result for randomized PN

- randomized round elimination

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds
 - A_1 solves X_1 in $T - 1$ rounds

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

3-coloring

$T \ll \log^* n$
rounds

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

w.h.p.

3-coloring

$T \ll \log^* n$
rounds

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

c-coloring
0 rounds



3-coloring
 $T \ll \log^* n$
rounds

w.h.p.

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

does not fail too often

c-coloring

0 rounds



T steps

w.h.p.

3-coloring

$T \ll \log^* n$
rounds

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

does not fail too often

w.h.p.



c-coloring

0 rounds



T steps

3-coloring

$T \ll \log^* n$
rounds



Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

Negative result for randomized LOCAL

- randomized PN can simulate randomized LOCAL



use randomness to construct
identifiers that are unique w.h.p.

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

Negative result for randomized LOCAL

- randomized PN can simulate randomized LOCAL

Negative result for deterministic LOCAL

- deterministic is a special case of randomized

Negative result for deterministic PN

Negative result for deterministic PN

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

Negative result for deterministic PN

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

Negative result for randomized LOCAL

- randomized PN can simulate randomized LOCAL

Negative result for deterministic PN

Negative result for randomized PN

- randomized round elimination:
 - A_0 solves X_0 in T rounds with probability p_0
 - A_1 solves X_1 in $T - 1$ rounds with probability $p_1 < p_0$

Negative result for randomized LOCAL

- randomized PN can simulate randomized LOCAL

Negative result for deterministic LOCAL

- deterministic is a special case of randomized