```
#include <iostream>             // Header file for input and output
#include <string>               // Header file for string
using namespace std;            // Use standard namespace

// Base class 1
class Employee
{
protected:                      // Members accessible in derived class
   int id;                      // Store employee ID
   string name;                 // Store employee name
   float salary;                // Store basic salary

public:
   void getEmployee()           // Function to accept employee details
   {
      cout << "Enter Employee ID: ";
      cin >> id;                // Accept employee ID

      cout << "Enter Employee Name: ";
      cin >> name;              // Accept employee name

      cout << "Enter Basic Salary: ";
      cin >> salary;            // Accept basic salary
   }
};

// Base class 2
class Appraisal
{
protected:
   float increment;             // Store appraisal amount

public:
   void getAppraisal()          // Function to accept appraisal amount
   {
      cout << "Enter Appraisal Amount: ";
      cin >> increment;         // Accept appraisal amount
   }
};

// Derived class using multiple inheritance
class RevisedSalary : public Employee, public Appraisal
{
```

```
public:
   void calculate()              // Function to calculate revised salary
   {
      float revised = salary + increment; // Add increment to basic salary

      cout << "\nEmployee ID: " << id;    // Display employee ID
      cout << "\nEmployee Name: " << name; // Display employee name
      cout << "\nBasic Salary: " << salary; // Display basic salary
      cout << "\nAppraisal Amount: " << increment; // Display appraisal
      cout << "\nRevised Salary: " << revised; // Display revised salary
   }
};

// Main function
int main()
{
   RevisedSalary e;              // Create object of derived class

   e.getEmployee();              // Call employee details function
   e.getAppraisal();             // Call appraisal function
   e.calculate();                // Calculate and display revised salary

   return 0;                     // End the program
}
```