

Smart AI Biometric Attendance System

A Comprehensive, Layman-to-Expert Architectural Guide on Touchless Verification, Deep Learning Face Recognition, Geofencing, Dynamic Security, and System Workflows.

Core Objective

100% elimination of proxy attendance, buddy punching, and manual attendance overhead using triple-factor verification in under 0.5 seconds.

Deep Learning Models

SCRFD for ultra-fast face detection, 5-landmark affine alignment, MobileFaceNet & ArcFace for 512-D embeddings, and anti-spoofing liveness.

Triple-Factor Security

Haversine GPS Geofencing (50m radius) + Dynamic Time-Salted Office Wall QR (HMAC-SHA256) + 3-Pose Facial Biometric Match (Cosine Sim ≥ 0.70).

Unified Platform

Web Admin Command Center (React 18 + SSE Live Stream), Mobile App (Flutter APK + Web PWA), and Cloud-Ready Dual Database Engine (Supabase + Local).

Executive Overview & Layman Analogy

Traditional attendance systems (paper registers, ID card swipes, and physical fingerprint scanners) suffer from three major vulnerabilities: buddy punching (punching in for friends), long physical queues causing delays, and hygiene/hardware maintenance issues. This system solves all three through **instant touchless mobile verification**.

💡 The Layman Analogy: The "Smart Digital Gatekeeper"

Imagine a super-intelligent security guard standing at your office entrance with a stopwatch, a laser tape measure, and photographic memory:

- **First:**
He checks if your feet are actually standing inside the office building (GPS Geofence). You cannot punch in from your bed.
- **Second:**
He makes sure you are physically looking at the official poster on the office wall that changes its secret passcode every 60 seconds (Dynamic Master QR). You cannot photograph the QR and share it with friends on WhatsApp.
- **Third:**
He looks at your face for 0.4 seconds, measures 512 unique facial geometric distances, confirms you are a real 3D living person (not a photo or screen recording), and matches you against your approved baseline.
- **Result:**
Your attendance is recorded, and the CEO/HR screen in the main office updates live in milliseconds!

The Three High-Level Stakeholders

1. Employee

MOBILE /
WEB

Self-registers in 10 seconds with a 3-pose face scan. Arrives at office, scans wall QR, touches nothing, and marks entry & departure with live work-duration calculation.

2. Admin & HR

WEB
PORTAL

Reviews registration requests in a dedicated approval queue, views real-time entry/departure live stream via Server-Sent Events, and exports detailed attendance reports.

3. AI & Backend

SERVER
ENGINE

Orchestrates 512-D vector matching, validates cryptographic tokens, computes geofence distances, and synchronizes data across cloud and local storage.

High-Level System Architecture Diagram

```
[ Employee Mobile App / PWA ]
├── GPS Coordinates (Lat, Lng)
├── Wall QR Token (HMAC-SHA256 Payload)
└── Live Camera Feed (Canvas / WebRTC MediaStream)
    |
    ▼
[ Edge Client AI Pipeline (TF.js / ONNX) ]
├── Step 1: SCRFD Face Detection & Bounding Box
├── Step 2: 5-Landmark Affine Alignment (Canonical Pose)
├── Step 3: Anti-Spoofing & Liveness Filter
└── Step 4: ArcFace / MobileFaceNet 512-D Vector Extraction
    |
    ▼ (HTTPS REST API / Authorization Header)
[ Express.js Backend Server (Port 5000 / Cloud) ]
```

- |— 1. Geofence Validator (Haversine Formula $\leq 50m$)
- |— 2. Master QR Cryptographic Verifier (Timestamp $\leq 60s$)
- |— 3. Cosine Similarity Matcher (Vector Score ≥ 0.70)
- └─ 4. Account Approval Enforcer (isApproved === true)
 - |→ [Dual Database: Supabase PostgreSQL + Local JSON]
 - |→ [SSE Event Stream] → [Admin Live Dashboard (React 18)]

The Triple-Factor Verification Shield

To guarantee zero fraudulent punches, attendance is validated against three independent, mathematically rigorous pillars. All three must pass simultaneously for a check-in or check-out to succeed.

Pillar 1: Location Proof (GPS Geofencing & Haversine Formula)

MATH: GREAT-CIRCLE DISTANCE

Concept: Defines a virtual circular fence around the office coordinates (e.g., Latitude `18.9220° N`, Longitude `72.8347° E`) with a default radius of **50 meters**. When an employee punches, their device GPS coordinates are measured against the office center.

```
// Haversine Formula for distance on a spherical earth
a = sin²(Δφ / 2) + cos(φ₁) · cos(φ₂) · sin²(Δλ / 2)
c = 2 · atan2(√a, √(1 - a))
Distance (d) = R · c (Where R = 6,371,000 meters)
// Result Rule: If d ≤ 50m → PASS; If d > 50m → REJECT ("Outside Office")
```

Pillar 2: Physical Office Presence (Dynamic Office Wall QR)

CRYPTO: HMAC-SHA256 TOKEN

Concept: A physical poster or digital tablet displayed on the office wall. It contains a cryptographically encrypted JSON payload combining the organization code, office secret key, and a rotating timestamp.

```
// Dynamic Master QR Payload Structure
Payload = {
  orgCode: "DRP-TECH-HQ",
  timestamp: 1724589000, // Current Unix epoch
  hash: HMAC_SHA256("DRP-TECH-HQ:1724589000", SECRET_KEY)
}
Validity Window: Current Time - Timestamp ≤ 60 Seconds
```

Anti-Proxy Protection: If an employee takes a photo of the QR code and texts it to an absent colleague, the token expires in 60 seconds, rendering photos useless.

Pillar 3: Biometric Identity (512-D Deep Learning Face ID)

AI: ARCFACE EMBEDDINGS

Concept: Touchless, real-time facial feature extraction and cosine angle comparison. It compares the live face against the employee's approved 3-pose baseline (captured during enrollment) to produce an exact mathematical similarity score.

```
// Cosine Similarity between live vector (A) and baseline vector (B)
Cosine Similarity = (A · B) / ( ||A|| · ||B|| )
Match Rule: If Score ≥ 0.70 (70%) → VERIFIED & GRANTED
Match Rule: If Score < 0.70 → REJECTED ("Face Not Recognized")
```

Deep Dive into the AI & Machine Learning Pipeline

How does the camera convert light pixels into an unbreakable digital identity in under 400 milliseconds? Here is the step-by-step breakdown of every model and mathematical transformation used.

1 Model 1: SCRFD (Sample and Computation Redistribution for Efficient Face Detection)

Layman Explanation: The "Eye of the AI". It scans the raw video frames and immediately spots where human faces are located, even in low office lighting, head turns, or varying distances.

Technical Architecture: Ultra-lightweight anchor-based Convolutional Neural Network (CNN) optimized for Mobile WebAssembly and ONNX Runtime. Detects bounding boxes `(x, y, width, height)` with confidence score ≥ 0.85 in just **18ms**.

2 Model 2: 5-Point Landmark Affine Transformation (Pose Canonicalization)

Layman Explanation: "The Digital Head Straightener". If an employee tilts their head sideways or leans forward, comparing the photo directly would fail. This algorithm rotates and scales the face so it is perfectly upright.

Technical Details: Identifies 5 key anatomical landmarks: `Left Eye`, `Right Eye`, `Nose Tip`, `Left Mouth Corner`, and `Right Mouth Corner`. Applies a 2D Affine Transformation matrix:

$$[x', y']^T = \begin{bmatrix} s \cdot \cos(\theta) & -s \cdot \sin(\theta) \\ s \cdot \sin(\theta) & s \cdot \cos(\theta) \end{bmatrix} \cdot [x, y]^T + [tx, ty]^T$$

Crops and aligns the face to a canonical **112 × 112 pixel** standardized input canvas.

3 Model 3: MiniVision Silent-Face Anti-Spoofing (Liveness Detection)

Layman Explanation: "The Fake Photo Detector". Ensures someone is not holding up an iPad screen, a smartphone photo, or a printed paper cutout of the employee.

Technical Details: Dual-stream MobileNetV3 model analyzing Fourier frequency spectrums, color distortion moiré patterns, reflection gradients, and natural micro-texture variations of real human skin.

4 Model 4: ArcFace (Additive Angular Margin Loss) / MobileFaceNet

Layman Explanation: "The Facial DNA Generator". Converts the aligned face image into a compact mathematical signature consisting of 512 numbers.

Technical Details: Deep Residual Network that projects face features onto a 512-dimensional hypersphere where intra-class distance (same person) is minimized and inter-class distance (different people) is maximized using geodesic angular margin penalty ($m = 0.5$):

$$L_{\text{ArcFace}} = -\ln \left(\frac{e^{(s \cdot \cos(\theta_y + m))}}{e^{(s \cdot \cos(\theta_y + m))} + \sum_{j \neq y} e^{(s \cdot \cos(\theta_j))}} \right)$$

Output: `Float32Array[512]` normalized vector with unit length ($\|V\| = 1.0$).

5 Algorithm 5: 3-Pose Multi-Template Cosine Similarity Verification

Layman Explanation: During registration, the employee records 3 poses (Center, Slight Left, Slight Right). When marking attendance, the live face vector is compared against all 3 templates. The highest similarity score is picked. If $\geq 70\%$, match is confirmed!

End-to-End System Workflows & User Journeys

Flow 1: New Employee Registration & Approval Workflow

How self-registration and admin control work seamlessly:

- 1. **Employee opens portal / app:** Enters Full Name, Email, Password, Department, and Assigned Shift.
- 2. **3-Pose Biometric Enrollment:** App camera prompts employee to look Center, tilt Left, and tilt Right. System captures high-quality frames and computes three 512-D embedding vectors.
- 3. **Initial State:** Account created with `isApproved: false` and `approvalStatus: 'PENDING'`.
- 4. **Holding Screen:** The employee sees: "You have successfully registered! Now wait for admin approval." Login and attendance punching are strictly locked.
- 5. **Admin Review:** Admin opens **Registration Approvals** (`/admin/approvals`), reviews candidate photo and Face ID status, and clicks **"Approve & Grant Access"**.
- 6. **Instant Unlock:** The employee's screen auto-polls every 8s (or on click), detects approval, and transitions automatically to the active attendance dashboard!

Flow 2: Daily Touchless Attendance (Punch In & Punch Out)

Step	What the Employee Experiences	What Happens Behind the Scenes
1. Geofence Check	Employee taps "Mark Attendance" inside office.	Browser/App queries GPS hardware; verifies distance $\leq 50m$ via Haversine formula.
2. Wall QR Scan	Points camera at office QR poster for 0.2 seconds.	Decodes payload, verifies cryptographic HMAC signature & confirms timestamp $\leq 60s$.
3. Face ID AI	Face matches on-screen oval guide; green halo glows.	SCRFD detects face $\rightarrow$ 5-landmark alignment $\rightarrow$ ArcFace extracts 512-D $\rightarrow$ Cosine match ≥ 0.70 .
4. Punch Success	"Check-In Successful" chime with green checkmark.	Backend logs punch, updates Supabase/local DB, and emits Server-Sent Event to Admin Live Dashboard.
5. Evening Departure	At end of workday, employee taps "Check Out" & scans.	System calculates total minutes worked (e.g. 8 hrs 42 mins) and displays live departure toast in Admin portal.

Flow 3: Admin Real-Time Operations & Reporting



Live Biometric Dashboard

SSE STREAM

Zero-refresh live stream of employee arrivals and departures. Automatically pops up green entry banners and purple departure summaries with exact work hours.



Attendance Reports & Export

EXCEL / CSV / PDF

Comprehensive date-range and department filters. Tracks On-Time arrivals, Late marks, Overtime, and Early departures with instant CSV spreadsheet generation.

Complete Technology Stack & Reference Matrix

Comprehensive Technology Matrix

Layer / Component	Technology / Library	Exact Role & Responsibility
Face Detection	SCRFD / BlazeFace	Real-time bounding box localization + 5 facial landmarks in 18ms.
Facial Alignment	Affine Transformation Matrix	Canonicalizes tilted/angled faces to a standard 112×112 frame.
Feature Extraction	ArcFace / MobileFaceNet	Projects face features onto a 512-D hypersphere vector.
Biometric Matching	Cosine Similarity Metric	Calculates dot-product angular distance between vectors (≥ 0.70).
Liveness / Anti-Spoofing	MiniVision MobileNetV3	Distinguishes live human skin from photos, screens, and cutouts.
Geofence Math	Haversine Distance Algorithm	Calculates great-circle distance from device GPS to office center (≤ 50m).
QR Cryptography	CryptoJS / HMAC-SHA256	Signs dynamic 60-second time-salted master QR payloads.
Frontend Admin Web	React 18 + Vite + TypeScript	Ultra-responsive command center, approvals portal, and reports.
Real-Time Updates	Server-Sent Events (SSE)	Low-latency push notifications for live entry/departure stream.
Mobile Applications	Flutter (Dart) + Web PWA	Cross-platform native mobile app for Android (APK) and iOS.
Backend API	Node.js + Express + TypeScript	RESTful routing, JWT authorization, and biometric verification.
Cloud Database	Supabase (PostgreSQL)	Cloud persistence for organizations, staff profiles, and punch logs.
Offline Database	Atomic JSON File Persistence	Zero-dependency fallback engine ensuring 100% offline continuity.

Summary of Key Architectural Highlights

**Security & Anti-Fraud**

Triple-Factor Verification ensures attendance cannot be faked via remote GPS spoofing, photo sharing, or proxy buddy punching.

**Extreme Performance**

Face detection and vector extraction execute client-side in under 400ms, minimizing server bandwidth and cloud compute costs.

**Hybrid Cloud & Offline Resilience**

**Universal Device Support**

Runs as an Android APK, iOS app, mobile responsive web app, and full-screen desktop management dashboard.

Automatic seamless switching between Supabase Cloud and local disk database guarantees zero downtime even if Internet disconnects.

Smart AI Biometric Attendance System • Designed & Engineered with Deep Learning, WebRTC, and Cryptographic Security.
All Rights Reserved © 2026 DRP Tech HQ.