

GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Tuesday, 29 October 2024, 1:50 PM
Duration	55 days 3 hours

Question 1

Correct

Marked out of 3.00

Flag question

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int num1,num2;
4     scanf("%d %d",&num1,&num2);
5     if (num1%10==num2%10)
6     {
7         printf("true\n");
8     }
9     else{
10        printf("false");
11        return 0;
12    }}
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Question **2**

Correct

Marked out of
5.00 [Flag question](#)**Objective**

In this challenge, we're getting started with conditional statements.

Task

Given an integer, *n*, perform the following conditional actions:

- If *n* is odd, print *Weird*
- If *n* is even and in the inclusive range of **2** to **5**, print ***Not Weird***
- If *n* is even and in the inclusive range of **6** to **20**, print ***Weird***
- If *n* is even and greater than **20**, print ***Not Weird***

Complete the stub code provided in your editor to print whether or not *n* is weird.

Input Format

A single line containing a positive integer, *n*.

Constraints

- $1 \leq n \leq 100$

Output Format

Print *Weird* if the number is weird; otherwise, print *Not Weird*.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Not Weird

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int n;
4     scanf("%d",&n);
5     if (n%2!=0){
6         printf("Weird\n");
7     }
8     else{
9         if(n>=3 && n<=5){
10             printf("Not Weird\n");
11         }
12         else if(n>=6&&n<=20){
13             printf("Weird");
14         }
15         else{
16             printf("Not Weird\n");
17         }
18     }
19 }
20 }
```

```

21     return 0;
22 }

```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question 3

Correct

Marked out of 7.00

Flag question

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main(){
3     int a,b,c;
4     scanf("%d %d %d",&a,&b,&c);
5     if(a*a+b*b==c*c ||
6        a*a+c*c==b*b ||
7        a*a+c*c==a*a)
8     {
9         printf("yes\n");
10    }
11    else{
12        printf("no\n");
13    }
14    return 0;
15 }

```

	Input	Expected	Got	
✓	3 5	yes	yes	✓

	4			
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review