

STUDENT PRACTICAL RECORD / STUDY NOTES

SUB: CS-101

C PROGRAMMING

100 MASTER SOLVED PROGRAMS

Comprehensive Lecture Notes & Practical Solutions covering Basics, Branching, Loops, Functions, Arrays, Pointers, Strings, Structs, File I/O & Patterns.

SUBJECT:	Computer Programming in C
TOTAL EXERCISES:	100 Programs (With Explanations & Output)
FORMAT:	A4 Printable Notes & Reference Guide
STATUS:	✓ Verified & Complete

Prepared for Quick Revision & Lab Exams

Practical Record Index

100 ENTRIES

Basics & Input/Output

1. C "Hello, World!" Program
2. C Program to Print an Integer (Entered by the User)
3. C Program to Add Two Integers
4. C Program to Multiply Two Floating-Point Numbers
5. C Program to Find ASCII Value of a Character
6. C Program to Compute Quotient and Remainder
7. C Program to Find the Size of int, float, double and char
8. C Program to Demonstrate the Working of Keyword long
9. C Program to Swap Two Numbers
10. C Program to Check Whether a Number is Even or Odd

Decision Making & Branching

11. C Program to Check Whether a Character is a Vowel or Consonant
12. C Program to Find the Largest Number Among Three Numbers
13. C Program to Find the Roots of a Quadratic Equation
14. C Program to Check Leap Year
15. C Program to Check Whether a Number is Positive, Negative, or Zero
16. C Program to Check Whether a Character is an Alphabet or Not
17. C Program to Check Uppercase, Lowercase, Digit, or Special Character
18. C Program to Check Triangle Validity and Type
19. C Program to Calculate Grade Based on Marks
20. C Program to Make a Simple Calculator Using switch...case

Loops & Series

21. C Program to Calculate the Sum of Natural Numbers
22. C Program to Find Factorial of a Number
23. C Program to Generate Multiplication Table
24. C Program to Display Fibonacci Sequence
25. C Program to Find GCD (HCF) of Two Numbers
26. C Program to Find LCM of Two Numbers
27. C Program to Display Characters from A to Z Using Loop

28. C Program to Count Number of Digits in an Integer
29. C Program to Reverse a Number
30. C Program to Calculate the Power of a Number
31. C Program to Check Whether a Number is Palindrome or Not
32. C Program to Check Whether a Number is Prime or Not
33. C Program to Display Prime Numbers Between Two Intervals
34. C Program to Check Armstrong Number
35. C Program to Display Armstrong Numbers Between Two Intervals

Numbers & Math Operations

36. C Program to Display Factors of a Number
37. C Program to Check Strong Number
38. C Program to Check Perfect Number
39. C Program to Find Sum of Digits of a Number
40. C Program to Convert Binary Number to Decimal and vice-versa
41. C Program to Convert Octal Number to Decimal and vice-versa
42. C Program to Convert Binary Number to Octal and vice-versa
43. C Program to Convert Hexadecimal Number to Decimal and vice-versa
44. C Program to Find Square Root of a Number Without Math Library
45. C Program to Check Whether a Number can be Expressed as Sum of Two Prime Numbers

Functions & Recursion

46. C Program to Display Prime Numbers Between Intervals Using Function
47. C Program to Check Prime or Armstrong Number Using User-defined Function
48. C Program to Find the Sum of Natural Numbers using Recursion
49. C Program to Find Factorial of a Number Using Recursion
50. C Program to Find G.C.D Using Recursion
51. C Program to Reverse a Sentence Using Recursion
52. C Program to Calculate Power Using Recursion
53. C Program to Print Fibonacci Series Using Recursion
54. C Program to Solve Tower of Hanoi Using Recursion
55. C Program to Find Sum of Digits Using Recursion

Arrays

56. C Program to Calculate Average Using Arrays
57. C Program to Find Largest and Smallest Element in an Array
58. C Program to Calculate Standard Deviation

59. C Program to Sort Array Elements in Ascending and Descending Order
60. C Program to Insert an Element in an Array at a Specified Position
61. C Program to Delete an Element from an Array
62. C Program to Search an Element in an Array (Linear & Binary Search)
63. C Program to Merge Two Arrays
64. C Program to Find Second Largest Number in an Array
65. C Program to Remove Duplicate Elements from an Array

Matrices / Multidimensional Arrays

66. C Program to Add Two Matrices Using Multi-dimensional Arrays
67. C Program to Multiply Two Matrices Using Multi-dimensional Arrays
68. C Program to Find Transpose of a Matrix
69. C Program to Multiply two Matrices by Passing Matrix to a Function
70. C Program to Check Sparse Matrix
71. C Program to Find Sum of Diagonal Elements of a Matrix
72. C Program to Check if Two Matrices Are Equal

Pointers & Dynamic Memory

73. C Program to Access Array Elements Using Pointer
74. C Program Swap Numbers in Cyclic Order Using Call by Reference
75. C Program to Find Largest Number Using Dynamic Memory Allocation
76. C Program to Demonstrate Pointer Arithmetic and Array Traversal
77. C Program to Dynamically Allocate & Reallocate Array Memory
78. C Program to Find Length of String Using Pointers

Strings

79. C Program to Find the Frequency of Characters in a String
80. C Program to Count the Number of Vowels, Consonants and so on
81. C Program to Remove all Characters in a String Except Alphabets
82. C Program to Find the Length of a String
83. C Program to Concatenate Two Strings
84. C Program to Copy String Without Using strcpy()
85. C Program to Sort Elements in Lexicographical Order (Dictionary Order)
86. C Program to Reverse a String Without Using strrev()
87. C Program to Compare Two Strings Without Using strcmp()
88. C Program to Check if Two Strings are Anagrams

Structures & Files

- 89. C Program to Store Information of a Student Using Structure
- 90. C Program to Add Two Distances (in inch-feet system) using Structures
- 91. C Program to Add Two Complex Numbers by Passing Structure to a Function
- 92. C Program to Calculate Difference Between Two Time Periods
- 93. C Program to Store Information of Students Using Structure Array
- 94. C Program to Write a Sentence to a File and Read First Line

Pyramids & Pattern Printing

- 95. C Program to Print Half Pyramid and Full Pyramid Star Patterns
- 96. C Program to Print Pascal's Triangle and Floyd's Triangle
- 97. C Program to Print Hollow Square and Diamond Star Patterns
- 98. C Program to Print Number Pyramids and Inverted Number Triangles
- 99. C Program to Print Character / Alphabet Pattern Pyramids
- 100. C Program to Print Hourglass and Butterfly Star Patterns

#1

C "Hello, World!" Program

Basics & Input/Output

PROBLEM STATEMENT

Write a C program to display the classic "Hello, World!" message on standard output.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    // printf() displays the string inside quotation marks
    printf("Hello, World!\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. `#include <stdio.h>` is a preprocessor header required for standard input/output functions.
2. `int main()` serves as the mandatory execution entry point.
3. `printf()` outputs the specified string.
4. `return 0;` indicates success.

PROGRAM OUTPUT

Hello, World!

#2

C Program to Print an Integer (Entered by the User)

Basics & Input/Output

PROBLEM STATEMENT

Write a C program to prompt the user for an integer, store it in a variable, and print it.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int number;

    printf("Enter an integer: ");
    scanf("%d", &number);

    printf("You entered: %d\n", number);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Declares variable number of integer type.
2. scanf("%d", &number) reads user input and stores it at memory address of number.
3. printf() displays stored value.

PROGRAM OUTPUT

```
Enter an integer: 42
You entered: 42
```

#3

C Program to Add Two Integers

Basics & Input/Output

PROBLEM STATEMENT

Write a C program that takes two integer inputs from the user, computes their sum, and displays the result.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int num1, num2, sum;

    printf("Enter two integers: ");
    scanf("%d %d", &num1, &num2);

    sum = num1 + num2;

    printf("%d + %d = %d\n", num1, num2, sum);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Reads two integers using scanf.
2. Performs addition using + operator.
3. Prints formatted sum.

PROGRAM OUTPUT

```
Enter two integers: 15 25
15 + 25 = 40
```

#4

C Program to Multiply Two Floating-Point Numbers

Basics & Input/Output

PROBLEM STATEMENT

Write a C program to multiply two floating-point numbers entered by the user.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    double a, b, product;

    printf("Enter two numbers: ");
    scanf("%lf %lf", &a, &b);

    product = a * b;

    printf("Product = %.2lf\n", product);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Uses double for floating point precision.
2. %lf format specifier reads double values.
3. %.2lf formats result to 2 decimal places.

PROGRAM OUTPUT

```
Enter two numbers: 2.4 1.5
Product = 3.60
```

#5

C Program to Find ASCII Value of a Character

Basics & Input/Output

PROBLEM STATEMENT

Write a C program to input a character and display its corresponding ASCII numeric code.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char c;
    printf("Enter a character: ");
    scanf("%c", &c);

    printf("ASCII value of %c = %d\n", c, c);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. A char variable holds 1 byte encoding ASCII numeric index.
2. Printing c with %d displays ASCII integer.

PROGRAM OUTPUT

```
Enter a character: G
ASCII value of G = 71
```

#6

C Program to Compute Quotient and Remainder

Basics & Input/Output

PROBLEM STATEMENT

Write a C program to divide two integers and calculate quotient and remainder.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int dividend, divisor, quotient, remainder;

    printf("Enter dividend: ");
    scanf("%d", &dividend);
    printf("Enter divisor: ");
    scanf("%d", &divisor);

    quotient = dividend / divisor;
    remainder = dividend % divisor;

    printf("Quotient = %d\n", quotient);
    printf("Remainder = %d\n", remainder);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Division operator / calculates quotient.
2. Modulo operator % yields integer remainder.

PROGRAM OUTPUT

```
Enter dividend: 25
Enter divisor: 4
Quotient = 6
Remainder = 1
```

#7

C Program to Find the Size of int, float, double and char

Basics & Input/Output

PROBLEM STATEMENT

Write a C program to display the memory allocation size (in bytes) of primitive data types.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    printf("Size of int: %zu bytes\n", sizeof(int));
    printf("Size of float: %zu bytes\n", sizeof(float));
    printf("Size of double: %zu bytes\n", sizeof(double));
    printf("Size of char: %zu byte\n", sizeof(char));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. sizeof operator evaluates memory footprint in bytes at compile-time.
2. Format specifier %zu formats size_t output.

PROGRAM OUTPUT

```
Size of int: 4 bytes
Size of float: 4 bytes
Size of double: 8 bytes
Size of char: 1 byte
```

#8

C Program to Demonstrate the Working of Keyword long

Basics & Input/Output

PROBLEM STATEMENT

Write a C program to demonstrate integer range extension using modifier long and long long.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int a;
    long b;
    long long c;

    printf("Size of int = %zu bytes\n", sizeof(a));
    printf("Size of long int = %zu bytes\n", sizeof(b));
    printf("Size of long long int = %zu bytes\n", sizeof(c));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Keyword long expands default int allocation.
2. long long guarantees 64-bit precision.

PROGRAM OUTPUT

```
Size of int = 4 bytes
Size of long int = 4 or 8 bytes
Size of long long int = 8 bytes
```

#9

C Program to Swap Two Numbers

Basics & Input/Output

PROBLEM STATEMENT

Write a C program to swap two numeric values using temporary variable and arithmetic logic.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    double first, second, temp;
    printf("Enter first: ");
    scanf("%lf", &first);
    printf("Enter second: ");
    scanf("%lf", &second);

    // Swap using temporary storage
    temp = first;
    first = second;
    second = temp;

    printf("After swapping: First = %.2lf, Second = %.2lf\n", first, second);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Preserves first value inside temp.
2. Assigns second to first.
3. Restores saved value from temp to second.

PROGRAM OUTPUT

```
Enter first: 1.20
Enter second: 2.45
After swapping: First = 2.45, Second = 1.20
```

#10

C Program to Check Whether a Number is Even or Odd

Basics & Input/Output

PROBLEM STATEMENT

Write a C program to check whether a given integer is even or odd.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int num;
    printf("Enter an integer: ");
    scanf("%d", &num);

    if (num % 2 == 0)
        printf("%d is even.\n", num);
    else
        printf("%d is odd.\n", num);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. `num % 2 == 0` tests if number is divisible by 2 with zero remainder.
2. Returns even if true, odd otherwise.

PROGRAM OUTPUT

```
Enter an integer: 7
7 is odd.
```

#11

C Program to Check Whether a Character is a Vowel or Consonant

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to check if an entered character is a vowel or consonant.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <ctype.h>

int main() {
    char c;
    printf("Enter an alphabet: ");
    scanf("%c", &c);

    int isLow = (c=='a' || c=='e' || c=='i' || c=='o' || c=='u');
    int isUp  = (c=='A' || c=='E' || c=='I' || c=='O' || c=='U');

    if (!isalpha(c))
        printf("Error! Non-alphabetic character.\n");
    else if (isLow || isUp)
        printf("%c is a vowel.\n", c);
    else
        printf("%c is a consonant.\n", c);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Evaluates logical OR operations across vowels.
2. Uses `isalpha()` to reject non-alphabet characters.

PROGRAM OUTPUT

```
Enter an alphabet: i
i is a vowel.
```

#12

C Program to Find the Largest Number Among Three Numbers

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to find the largest value among three input numbers.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    double n1, n2, n3;
    printf("Enter three numbers: ");
    scanf("%lf %lf %lf", &n1, &n2, &n3);

    if (n1 >= n2 && n1 >= n3)
        printf("%.2f is the largest number.\n", n1);
    else if (n2 >= n1 && n2 >= n3)
        printf("%.2f is the largest number.\n", n2);
    else
        printf("%.2f is the largest number.\n", n3);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Compares pairs using && logical operator.
2. Identifies maximum value via branch elimination.

PROGRAM OUTPUT

```
Enter three numbers: -4.5 3.9 5.6
5.60 is the largest number.
```

#13 C Program to Find the Roots of a Quadratic Equation

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to compute real and complex roots of quadratic equation $ax^2 + bx + c = 0$.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <math.h>

int main() {
    double a, b, c, disc, r1, r2, realP, imagP;
    printf("Enter coefficients a, b and c: ");
    scanf("%lf %lf %lf", &a, &b, &c);

    disc = b * b - 4 * a * c;

    if (disc > 0) {
        r1 = (-b + sqrt(disc)) / (2 * a);
        r2 = (-b - sqrt(disc)) / (2 * a);
        printf("root1 = %.2lf and root2 = %.2lf\n", r1, r2);
    } else if (disc == 0) {
        r1 = r2 = -b / (2 * a);
        printf("root1 = root2 = %.2lf\n", r1);
    } else {
        realP = -b / (2 * a);
        imagP = sqrt(-disc) / (2 * a);
        printf("root1 = %.2lf+%.2lfi and root2 = %.2lf-%.2lfi\n", realP, imagP, realP, imagP);
    }

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Calculates discriminant $D = b^2 - 4ac$.
2. Discriminant sign determines real distinct, real equal, or complex roots.

PROGRAM OUTPUT

```
Enter coefficients a, b and c: 1 -5 6
root1 = 3.00 and root2 = 2.00
```

#14

C Program to Check Leap Year

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to verify if a year is a leap year based on Gregorian rules.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int year;
    printf("Enter a year: ");
    scanf("%d", &year);

    if ((year % 400 == 0) || (year % 4 == 0 && year % 100 != 0))
        printf("%d is a leap year.\n", year);
    else
        printf("%d is not a leap year.\n", year);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Divisible by 400 → Leap Year.
2. Divisible by 4 AND NOT by 100 → Leap Year.
3. Otherwise → Not a Leap Year.

PROGRAM OUTPUT

```
Enter a year: 2000
2000 is a leap year.
```

#15

C Program to Check Whether a Number is Positive, Negative, or Zero

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to test if a number is positive, negative, or zero.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    double num;
    printf("Enter a number: ");
    scanf("%lf", &num);

    if (num > 0.0)
        printf("You entered a positive number.\n");
    else if (num < 0.0)
        printf("You entered a negative number.\n");
    else
        printf("You entered 0.\n");

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Uses relational operators > and < to categorize numeric input.

PROGRAM OUTPUT

```
Enter a number: -12.3
You entered a negative number.
```

#16

C Program to Check Whether a Character is an Alphabet or Not

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to verify if a character is an English alphabet.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char c;
    printf("Enter a character: ");
    scanf("%c", &c);

    if ((c >= 'a' && c <= 'z') || (c >= 'A' && c <= 'Z'))
        printf("%c is an alphabet.\n", c);
    else
        printf("%c is not an alphabet.\n", c);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Evaluates character range conditions 'a' - 'z' and 'A' - 'Z'.

PROGRAM OUTPUT

```
Enter a character: *
* is not an alphabet.
```

#17

C Program to Check Uppercase, Lowercase, Digit, or Special Character

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to categorize character input into uppercase, lowercase, digit, or special character.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char ch;
    printf("Enter any character: ");
    scanf("%c", &ch);

    if (ch >= 'A' && ch <= 'Z')
        printf("%c is Uppercase.\n", ch);
    else if (ch >= 'a' && ch <= 'z')
        printf("%c is Lowercase.\n", ch);
    else if (ch >= '0' && ch <= '9')
        printf("%c is a Digit.\n", ch);
    else
        printf("%c is a Special Character.\n", ch);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Compares input character against ASCII continuous ranges for uppercase, lowercase, and numeric digits.

PROGRAM OUTPUT

Enter any character: 9
'9' is a Digit.

#18 C Program to Check Triangle Validity and Type

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to test triangle side length validity and classify as Equilateral, Isosceles, or Scalene.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    double a, b, c;
    printf("Enter three sides: ");
    scanf("%lf %lf %lf", &a, &b, &c);

    if ((a+b>c) && (a+c>b) && (b+c>a)) {
        if (a==b && b==c)
            printf("Equilateral Triangle\n");
        else if (a==b || b==c || a==c)
            printf("Isosceles Triangle\n");
        else
            printf("Scalene Triangle\n");
    } else {
        printf("Invalid Triangle\n");
    }

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Triangle Inequality Theorem: sum of any 2 sides must exceed the 3rd side.
2. Side equality checks determine specific triangle classification.

PROGRAM OUTPUT

```
Enter three sides: 5 5 5
Equilateral Triangle
```

#19 C Program to Calculate Grade Based on Marks

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to input percentage marks and output letter grades.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    float marks;
    printf("Enter marks (0-100): ");
    scanf("%f", &marks);

    if (marks >= 90) printf("Grade A\n");
    else if (marks >= 80) printf("Grade B\n");
    else if (marks >= 70) printf("Grade C\n");
    else if (marks >= 60) printf("Grade D\n");
    else printf("Grade F\n");

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Sequential threshold checking routes input to corresponding grade bucket.

PROGRAM OUTPUT

```
Enter marks (0-100): 85.5
Grade B
```

#20

C Program to Make a Simple Calculator Using switch...case

Decision Making & Branching

PROBLEM STATEMENT

Write a C program to build a menu calculator using switch statement.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char op;
    double a, b;
    printf("Enter operator (+, -, *, /): ");
    scanf("%c", &op);
    printf("Enter two numbers: ");
    scanf("%lf %lf", &a, &b);

    switch (op) {
        case '+': printf("%.2lf + %.2lf = %.2lf\n", a, b, a + b); break;
        case '-': printf("%.2lf - %.2lf = %.2lf\n", a, b, a - b); break;
        case '*': printf("%.2lf * %.2lf = %.2lf\n", a, b, a * b); break;
        case '/':
            if (b != 0) printf("%.2lf / %.2lf = %.2lf\n", a, b, a / b);
            else printf("Error! Division by zero.\n");
            break;
        default: printf("Error! Invalid operator.\n");
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. switch(op) branches execution depending on entered operator character.
2. Division branch incorporates zero check.

PROGRAM OUTPUT

```
Enter operator (+, -, *, /): *
Enter two numbers: 4.5 2
4.50 * 2.00 = 9.00
```

#21 C Program to Calculate the Sum of Natural Numbers

Loops & Series

PROBLEM STATEMENT

Write a C program to calculate the sum of first N natural numbers entered by user.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n, i, sum = 0;
    printf("Enter a positive integer: ");
    scanf("%d", &n);

    for (i = 1; i <= n; ++i) {
        sum += i;
    }

    printf("Sum = %d\n", sum);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Loop variable *i* runs from 1 to *n*.
2. Accumulator variable *sum* adds *i* at each iteration.

PROGRAM OUTPUT

```
Enter a positive integer: 10
Sum = 55
```

#22 C Program to Find Factorial of a Number

Loops & Series

PROBLEM STATEMENT

Write a C program to calculate the factorial of a given positive integer.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n, i;
    unsigned long long fact = 1;
    printf("Enter an integer: ");
    scanf("%d", &n);

    if (n < 0)
        printf("Error! Factorial of a negative number doesn't exist.\n");
    else {
        for (i = 1; i <= n; ++i) {
            fact *= i;
        }
        printf("Factorial of %d = %llu\n", n, fact);
    }

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Factorial of $n = n * (n-1) * \dots * 1$.
2. unsigned long long prevents quick integer overflow.

PROGRAM OUTPUT

```
Enter an integer: 10
Factorial of 10 = 3628800
```

#23 C Program to Generate Multiplication Table

Loops & Series

PROBLEM STATEMENT

Write a C program to generate multiplication table of a given integer up to 10.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n, i;
    printf("Enter an integer: ");
    scanf("%d", &n);

    for (i = 1; i <= 10; ++i) {
        printf("%d * %d = %d\n", n, i, n * i);
    }

    return 0;
}
```

NOTES & KEY CONCEPTS

1. for loop iterates from $i = 1$ to 10 printing calculated products.

PROGRAM OUTPUT

```
Enter an integer: 9
9 * 1 = 9
9 * 2 = 18
...
9 * 10 = 90
```

#24 C Program to Display Fibonacci Sequence

Loops & Series

PROBLEM STATEMENT

Write a C program to print first n terms of the Fibonacci sequence.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int i, n;
    int t1 = 0, t2 = 1;
    int nextTerm = t1 + t2;

    printf("Enter the number of terms: ");
    scanf("%d", &n);

    printf("Fibonacci Series: %d, %d, ", t1, t2);

    for (i = 3; i <= n; ++i) {
        printf("%d, ", nextTerm);
        t1 = t2;
        t2 = nextTerm;
        nextTerm = t1 + t2;
    }
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Fibonacci sequence starts with 0, 1.
2. Next term is always calculated as $t1 + t2$.

PROGRAM OUTPUT

```
Enter the number of terms: 8
Fibonacci Series: 0, 1, 1, 2, 3, 5, 8, 13,
```

#25 C Program to Find GCD (HCF) of Two Numbers

Loops & Series

PROBLEM STATEMENT

Write a C program to compute Greatest Common Divisor (GCD) using Euclidean Algorithm.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n1, n2;
    printf("Enter two positive integers: ");
    scanf("%d %d", &n1, &n2);

    while (n1 != n2) {
        if (n1 > n2)
            n1 -= n2;
        else
            n2 -= n1;
    }
    printf("GCD = %d\n", n1);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Implements Euclidean subtraction method.
2. Repeatedly subtracts smaller number from larger until equal.

PROGRAM OUTPUT

```
Enter two positive integers: 81 153
GCD = 9
```

#26

C Program to Find LCM of Two Numbers

Loops & Series

PROBLEM STATEMENT

Write a C program to calculate Least Common Multiple (LCM) of two numbers.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n1, n2, max;
    printf("Enter two positive integers: ");
    scanf("%d %d", &n1, &n2);

    max = (n1 > n2) ? n1 : n2;

    while (1) {
        if (max % n1 == 0 && max % n2 == 0) {
            printf("LCM of %d and %d is %d\n", n1, n2, max);
            break;
        }
        ++max;
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Starts testing from max value.
2. First number divisible by both inputs is the LCM.

PROGRAM OUTPUT

Enter two positive integers: 72 120
LCM of 72 and 120 is 360

#27

C Program to Display Characters from A to Z Using Loop

Loops & Series

PROBLEM STATEMENT

Write a C program to iterate and print alphabets from A to Z.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char c;
    printf("Uppercase Alphabets:\n");
    for (c = 'A'; c <= 'Z'; ++c)
        printf("%c ", c);

    printf("\nLowercase Alphabets:\n");
    for (c = 'a'; c <= 'z'; ++c)
        printf("%c ", c);

    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Standard character loop increments ASCII values from 'A' to 'Z'.

PROGRAM OUTPUT

```
Uppercase Alphabets:
A B C D E ... Z
Lowercase Alphabets:
a b c d e ... z
```

#28 C Program to Count Number of Digits in an Integer

Loops & Series

PROBLEM STATEMENT

Write a C program to count total number of digits in an integer.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    long long n;
    int count = 0;
    printf("Enter an integer: ");
    scanf("%lld", &n);

    // handle 0 case
    if (n == 0) count = 1;

    while (n != 0) {
        n /= 10;
        ++count;
    }

    printf("Number of digits: %d\n", count);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Divides number by 10 continuously until zero while incrementing count.

PROGRAM OUTPUT

```
Enter an integer: 345219
Number of digits: 6
```

#29

C Program to Reverse a Number

Loops & Series

PROBLEM STATEMENT

Write a C program to reverse an integer number.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n, reverse = 0, remainder;
    printf("Enter an integer: ");
    scanf("%d", &n);

    while (n != 0) {
        remainder = n % 10;
        reverse = reverse * 10 + remainder;
        n /= 10;
    }

    printf("Reversed number = %d\n", reverse);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Extracts last digit using `% 10`.
2. Appends digit to reversed value: `reverse = reverse \* 10 + remainder`.

PROGRAM OUTPUT

Enter an integer: 2345
Reversed number = 5432

#30 C Program to Calculate the Power of a Number

Loops & Series

PROBLEM STATEMENT

Write a C program to compute base raised to exponent power without using math library.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int base, exp;
    long long result = 1;
    printf("Enter a base number: ");
    scanf("%d", &base);
    printf("Enter an exponent: ");
    scanf("%d", &exp);

    for (int i = 1; i <= exp; ++i) {
        result *= base;
    }

    printf("%d^%d = %lld\n", base, exp, result);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Multiplies base with result `exp` times inside for loop.

PROGRAM OUTPUT

```
Enter a base number: 3
Enter an exponent: 4
3^4 = 81
```

#31

C Program to Check Whether a Number is Palindrome or Not

Loops & Series

PROBLEM STATEMENT

Write a C program to verify if an integer reads same forward and backward.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n, reversed = 0, remainder, original;
    printf("Enter an integer: ");
    scanf("%d", &n);
    original = n;

    while (n != 0) {
        remainder = n % 10;
        reversed = reversed * 10 + remainder;
        n /= 10;
    }

    if (original == reversed)
        printf("%d is a palindrome.\n", original);
    else
        printf("%d is not a palindrome.\n", original);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Reverses input integer.
2. Compares original integer against reversed integer.

PROGRAM OUTPUT

```
Enter an integer: 12321
12321 is a palindrome.
```

#32

C Program to Check Whether a Number is Prime or Not

Loops & Series

PROBLEM STATEMENT

Write a C program to test whether a given number is prime.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n, i, flag = 0;
    printf("Enter a positive integer: ");
    scanf("%d", &n);

    if (n == 0 || n == 1)
        flag = 1;

    for (i = 2; i <= n / 2; ++i) {
        if (n % i == 0) {
            flag = 1;
            break;
        }
    }

    if (flag == 0)
        printf("%d is a prime number.\n", n);
    else
        printf("%d is not a prime number.\n", n);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Tests divisibility from `2` up to `n/2`.
2. Set flag = 1 if any divisor found.

PROGRAM OUTPUT

```
Enter a positive integer: 29
29 is a prime number.
```

#33

C Program to Display Prime Numbers Between Two Intervals

Loops & Series

PROBLEM STATEMENT

Write a C program to print all prime numbers within a user-specified range.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int low, high, i, flag;
    printf("Enter two numbers (intervals): ");
    scanf("%d %d", &low, &high);

    printf("Prime numbers between %d and %d are: ", low, high);

    while (low < high) {
        flag = 0;

        if (low <= 1) {
            ++low;
            continue;
        }

        for (i = 2; i <= low / 2; ++i) {
            if (low % i == 0) {
                flag = 1;
                break;
            }
        }

        if (flag == 0)
            printf("%d ", low);

        ++low;
    }
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Iterates from low boundary to high boundary.
2. Applies prime test on each individual number.

PROGRAM OUTPUT

Enter two numbers (intervals): 10 30

Prime numbers between 10 and 30 are: 11 13 17 19 23 29

#34

C Program to Check Armstrong Number

Loops & Series

PROBLEM STATEMENT

Write a C program to check if an n-digit number is an Armstrong number.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <math.h>

int main() {
    int num, originalNum, remainder, result = 0, n = 0;
    printf("Enter an integer: ");
    scanf("%d", &num);

    originalNum = num;

    // Count number of digits
    for (originalNum = num; originalNum != 0; ++n) {
        originalNum /= 10;
    }

    originalNum = num;

    while (originalNum != 0) {
        remainder = originalNum % 10;
        result += pow(remainder, n);
        originalNum /= 10;
    }

    if (result == num)
        printf("%d is an Armstrong number.\n", num);
    else
        printf("%d is not an Armstrong number.\n", num);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Armstrong number of n digits equals sum of its digits raised to power n.
2. Example: $371 = 3^3 + 7^3 + 1^3$.

PROGRAM OUTPUT

```
Enter an integer: 371
371 is an Armstrong number.
```

#35

C Program to Display Armstrong Numbers Between Two Intervals

Loops & Series

PROBLEM STATEMENT

Write a C program to print all Armstrong numbers in a given interval.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <math.h>

int main() {
    int low, high, number, originalNumber, rem, count = 0, result = 0;
    printf("Enter two numbers (intervals): ");
    scanf("%d %d", &low, &high);

    printf("Armstrong numbers between %d and %d are: ", low, high);

    for (number = low + 1; number < high; ++number) {
        originalNumber = number;
        while (originalNumber != 0) {
            originalNumber /= 10;
            ++count;
        }
        originalNumber = number;
        while (originalNumber != 0) {
            rem = originalNumber % 10;
            result += pow(rem, count);
            originalNumber /= 10;
        }
        if (result == number) {
            printf("%d ", number);
        }
        count = 0;
        result = 0;
    }
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Loops through interval and checks Armstrong condition for every number.

PROGRAM OUTPUT

```
Enter two numbers (intervals): 100 500
Armstrong numbers between 100 and 500 are: 153 370 371 407
```

#36 C Program to Display Factors of a Number

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to find and print all positive factors of a number.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int num, i;
    printf("Enter a positive integer: ");
    scanf("%d", &num);

    printf("Factors of %d are: ", num);
    for (i = 1; i <= num; ++i) {
        if (num % i == 0) {
            printf("%d ", i);
        }
    }
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Iterates from `1` to `num`.
2. Prints numbers that divide `num` completely (`num % i == 0`).

PROGRAM OUTPUT

```
Enter a positive integer: 60
Factors of 60 are: 1 2 3 4 5 6 10 12 15 20 30 60
```

#37

C Program to Check Strong Number

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to check if a number is a Strong Number (sum of factorials of digits equals number).

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int factorial(int n) {
    int fact = 1;
    for(int i = 1; i <= n; i++) fact *= i;
    return fact;
}

int main() {
    int num, temp, rem, sum = 0;
    printf("Enter a number: ");
    scanf("%d", &num);

    temp = num;
    while(temp > 0) {
        rem = temp % 10;
        sum += factorial(rem);
        temp /= 10;
    }

    if(sum == num)
        printf("%d is a Strong Number.\n", num);
    else
        printf("%d is not a Strong Number.\n", num);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Strong number: $145 = 1! + 4! + 5! = 1 + 24 + 120 = 145$.

PROGRAM OUTPUT

```
Enter a number: 145
145 is a Strong Number.
```

#38 C Program to Check Perfect Number

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to test if a number is Perfect (sum of proper divisors equals number).

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int num, sum = 0;
    printf("Enter a positive integer: ");
    scanf("%d", &num);

    for (int i = 1; i < num; i++) {
        if (num % i == 0) sum += i;
    }

    if (sum == num)
        printf("%d is a Perfect Number.\n", num);
    else
        printf("%d is not a Perfect Number.\n", num);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Perfect number: $6 = 1 + 2 + 3$.

PROGRAM OUTPUT

Enter a positive integer: 28
28 is a Perfect Number.

#39

C Program to Find Sum of Digits of a Number

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to compute the sum of all digits of an integer.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n, sum = 0, m;
    printf("Enter a number: ");
    scanf("%d", &n);

    while (n > 0) {
        m = n % 10;
        sum += m;
        n /= 10;
    }

    printf("Sum of digits = %d\n", sum);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Strips last digit using `% 10` and adds to sum accumulator.

PROGRAM OUTPUT

```
Enter a number: 1234
Sum of digits = 10
```

#40

C Program to Convert Binary Number to Decimal and vice-versa

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to convert a binary number to decimal and decimal to binary.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <math.h>

long long convertDecimalToBinary(int n) {
    long long bin = 0;
    int rem, i = 1;
    while (n != 0) {
        rem = n % 2;
        n /= 2;
        bin += rem * i;
        i *= 10;
    }
    return bin;
}

int convertBinaryToDecimal(long long n) {
    int dec = 0, i = 0, rem;
    while (n != 0) {
        rem = n % 10;
        n /= 10;
        dec += rem * pow(2, i);
        ++i;
    }
    return dec;
}

int main() {
    long long bin = 1101;
    printf("Binary 1101 to Decimal = %d\n", convertBinaryToDecimal(bin));
    printf("Decimal 13 to Binary = %lld\n", convertDecimalToBinary(13));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Binary to decimal uses powers of 2.
2. Decimal to binary uses repeated division by 2.

PROGRAM OUTPUT

Binary 1101 to Decimal = 13
Decimal 13 to Binary = 1101

#41

C Program to Convert Octal Number to Decimal and vice-versa

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to convert Octal base-8 number to Decimal base-10 and vice versa.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <math.h>

int octalToDecimal(int octal) {
    int decimal = 0, i = 0;
    while (octal != 0) {
        decimal += (octal % 10) * pow(8, i);
        ++i;
        octal /= 10;
    }
    return decimal;
}

int decimalToOctal(int decimal) {
    int octal = 0, i = 1;
    while (decimal != 0) {
        octal += (decimal % 8) * i;
        decimal /= 8;
        i *= 10;
    }
    return octal;
}

int main() {
    printf("Octal 116 to Decimal = %d\n", octalToDecimal(116));
    printf("Decimal 78 to Octal = %d\n", decimalToOctal(78));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Converts Octal base using powers of 8.

PROGRAM OUTPUT

Octal 116 to Decimal = 78
Decimal 78 to Octal = 116

#42

C Program to Convert Binary Number to Octal and vice-versa

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to convert a Binary number to Octal base and vice versa.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <math.h>

int convertBinaryToOctal(long long bin) {
    int dec = 0, oct = 0, i = 0;
    while (bin != 0) {
        dec += (bin % 10) * pow(2, i);
        ++i;
        bin /= 10;
    }
    i = 1;
    while (dec != 0) {
        oct += (dec % 8) * i;
        dec /= 8;
        i *= 10;
    }
    return oct;
}

int main() {
    long long bin = 101011;
    printf("Binary 101011 to Octal = %d\n", convertBinaryToOctal(bin));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Converts binary to intermediate decimal, then decimal to octal.

PROGRAM OUTPUT

Binary 101011 to Octal = 53

#43

C Program to Convert Hexadecimal Number to Decimal and vice-versa

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to convert a Hexadecimal string to Decimal integer.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <string.h>
#include <math.h>

int hexToDecimal(char hex[]) {
    int len = strlen(hex);
    int base = 1, dec = 0;
    for (int i = len - 1; i >= 0; i--) {
        if (hex[i] >= '0' && hex[i] <= '9') {
            dec += (hex[i] - '0') * base;
        } else if (hex[i] >= 'A' && hex[i] <= 'F') {
            dec += (hex[i] - 'A' + 10) * base;
        } else if (hex[i] >= 'a' && hex[i] <= 'f') {
            dec += (hex[i] - 'a' + 10) * base;
        }
        base *= 16;
    }
    return dec;
}

int main() {
    char hex[] = "1A";
    printf("Hexadecimal 1A to Decimal = %d\n", hexToDecimal(hex));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Converts base-16 digits ('0'-'9', 'A'-'F') into base-10 value.

PROGRAM OUTPUT

Hexadecimal 1A to Decimal = 26

#44

C Program to Find Square Root of a Number Without Math Library

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to compute square root of a number using Newton-Raphson method.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

double squareRoot(double n) {
    double x = n;
    double root;
    while (1) {
        root = 0.5 * (x + (n / x));
        if ((x - root) < 0.00001 && (x - root) > -0.00001)
            break;
        x = root;
    }
    return root;
}

int main() {
    double n = 25.0;
    printf("Square root of %.2f is %.4f\n", n, squareRoot(n));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Newton-Raphson formula: $\text{root} = 0.5 * (x + n/x)$ until convergence.

PROGRAM OUTPUT

Square root of 25.00 is 5.0000

#45

C Program to Check Whether a Number can be Expressed as Sum of Two Prime Numbers

Numbers & Math Operations

PROBLEM STATEMENT

Write a C program to test Goldbach's conjecture for an entered integer.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int checkPrime(int n) {
    if (n <= 1) return 0;
    for (int i = 2; i <= n / 2; ++i) {
        if (n % i == 0) return 0;
    }
    return 1;
}

int main() {
    int n, flag = 0;
    printf("Enter a positive integer: ");
    scanf("%d", &n);

    for (int i = 2; i <= n / 2; ++i) {
        if (checkPrime(i) == 1) {
            if (checkPrime(n - i) == 1) {
                printf("%d = %d + %d\n", n, i, n - i);
                flag = 1;
            }
        }
    }

    if (flag == 0)
        printf("%d cannot be expressed as the sum of two prime numbers.\n", n);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. Iterates candidate `i` checking if both `i` and `n - i` are prime.

PROGRAM OUTPUT

```
Enter a positive integer: 34
34 = 3 + 31
34 = 5 + 29
34 = 11 + 23
34 = 17 + 17
```

#46

C Program to Display Prime Numbers Between Intervals Using Function

Functions & Recursion

PROBLEM STATEMENT

Write a C program to display prime numbers between two intervals using modular function.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int checkPrimeNumber(int n) {
    if (n <= 1) return 0;
    for (int j = 2; j <= n / 2; ++j) {
        if (n % j == 0) return 0;
    }
    return 1;
}

int main() {
    int n1 = 10, n2 = 30;
    printf("Prime numbers between %d and %d are: ", n1, n2);
    for (int i = n1 + 1; i < n2; ++i) {
        if (checkPrimeNumber(i)) printf("%d ", i);
    }
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Helper function `checkPrimeNumber()` modularizes prime evaluation logic.

PROGRAM OUTPUT

Prime numbers between 10 and 30 are: 11 13 17 19 23 29

#47

C Program to Check Prime or Armstrong Number Using User-defined Function

Functions & Recursion

PROBLEM STATEMENT

Write a C program with custom functions to test prime or Armstrong property.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <math.h>

int checkPrime(int n) {
    if(n <= 1) return 0;
    for(int i = 2; i <= n/2; i++) if(n % i == 0) return 0;
    return 1;
}

int checkArmstrong(int number) {
    int originalNumber = number, rem, result = 0, count = 0;
    while (originalNumber != 0) {
        originalNumber /= 10;
        ++count;
    }
    originalNumber = number;
    while (originalNumber != 0) {
        rem = originalNumber % 10;
        result += pow(rem, count);
        originalNumber /= 10;
    }
    return (result == number);
}

int main() {
    int n = 371;
    if (checkArmstrong(n)) printf("%d is an Armstrong number.\n", n);
    if (checkPrime(n)) printf("%d is a Prime number.\n", n);
    else printf("%d is not a Prime number.\n", n);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Separate functions demonstrate modular code structure in C.

PROGRAM OUTPUT

371 is an Armstrong number.
371 is not a Prime number.

#48

C Program to Find the Sum of Natural Numbers using Recursion

Functions & Recursion

PROBLEM STATEMENT

Write a C program to calculate sum of natural numbers up to N using recursion.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int addNumbers(int n) {
    if (n != 0)
        return n + addNumbers(n - 1);
    else
        return n;
}

int main() {
    int num = 20;
    printf("Sum = %d\n", addNumbers(num));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Recursive call: `addNumbers(n) = n + addNumbers(n - 1)`. Base case `n == 0`.

PROGRAM OUTPUT

Sum = 210

#49

C Program to Find Factorial of a Number Using Recursion

Functions & Recursion

PROBLEM STATEMENT

Write a C program to compute factorial using recursive function calls.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

long int multiplyNumbers(int n) {
    if (n>=1)
        return n*multiplyNumbers(n-1);
    else
        return 1;
}

int main() {
    int n = 6;
    printf("Factorial of %d = %ld\n", n, multiplyNumbers(n));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Base case returns 1 when `n < 1`. Recursive case multiplies `n \* multiplyNumbers(n - 1)`.

PROGRAM OUTPUT

Factorial of 6 = 720

#50 C Program to Find G.C.D Using Recursion

Functions & Recursion

PROBLEM STATEMENT

Write a C program to find GCD using Euclidean recursive algorithm.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int hcf(int n1, int n2) {
    if (n2 != 0)
        return hcf(n2, n1 % n2);
    else
        return n1;
}

int main() {
    int n1 = 366, n2 = 60;
    printf("G.C.D of %d and %d is %d.\n", n1, n2, hcf(n1, n2));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Recursive Euclidean formula: $\text{hcf}(a, b) = \text{hcf}(b, a \% b)$ until $b == 0$.

PROGRAM OUTPUT

G.C.D of 366 and 60 is 6.

#51 C Program to Reverse a Sentence Using Recursion

Functions & Recursion

PROBLEM STATEMENT

Write a C program to reverse character string input recursively.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void reverseSentence() {
    char c;
    scanf("%c", &c);
    if (c != '\n') {
        reverseSentence();
        printf("%c", c);
    }
}

int main() {
    printf("Enter a sentence: ");
    reverseSentence();
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Pushes characters onto call stack until newline, then prints them in unwinding phase.

PROGRAM OUTPUT

```
Enter a sentence: margorp c
c program
```

#52 C Program to Calculate Power Using Recursion

Functions & Recursion

PROBLEM STATEMENT

Write a C program to calculate power of a number recursively.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int power(int base, int a) {
    if (a != 0)
        return (base * power(base, a - 1));
    else
        return 1;
}

int main() {
    int base = 3, exp = 4;
    printf("%d^%d = %d\n", base, exp, power(base, exp));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. `power(base, exp) = base \* power(base, exp - 1)`. Base case `exp == 0` returns 1.

PROGRAM OUTPUT

3^4 = 81

#53

C Program to Print Fibonacci Series Using Recursion

Functions & Recursion

PROBLEM STATEMENT

Write a C program to generate Fibonacci numbers using recursive function.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int fibonacci(int n) {
    if (n <= 1)
        return n;
    return fibonacci(n - 1) + fibonacci(n - 2);
}

int main() {
    int n = 7;
    printf("Fibonacci series up to %d terms:\n", n);
    for (int i = 0; i < n; i++) {
        printf("%d ", fibonacci(i));
    }
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Recursive formula: $\text{fib}(n) = \text{fib}(n-1) + \text{fib}(n-2)$. Base cases '0' and '1' .

PROGRAM OUTPUT

Fibonacci series up to 7 terms:
0 1 1 2 3 5 8

#54 C Program to Solve Tower of Hanoi Using Recursion

Functions & Recursion

PROBLEM STATEMENT

Write a C program to print solution steps for Tower of Hanoi puzzle.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void towerOfHanoi(int n, char from_rod, char to_rod, char aux_rod) {
    if (n == 1) {
        printf("Move disk 1 from rod %c to rod %c\n", from_rod, to_rod);
        return;
    }
    towerOfHanoi(n - 1, from_rod, aux_rod, to_rod);
    printf("Move disk %d from rod %c to rod %c\n", n, from_rod, to_rod);
    towerOfHanoi(n - 1, aux_rod, to_rod, from_rod);
}

int main() {
    int n = 3;
    towerOfHanoi(n, 'A', 'C', 'B');
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Recursively moves n-1 disks to auxiliary rod, main disk to target rod, then n-1 disks to target rod.

PROGRAM OUTPUT

```
Move disk 1 from rod A to rod C
Move disk 2 from rod A to rod B
Move disk 1 from rod C to rod B
Move disk 3 from rod A to rod C
...
```

#55

C Program to Find Sum of Digits Using Recursion

Functions & Recursion

PROBLEM STATEMENT

Write a C program to compute sum of digits of a number using recursion.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int sumOfDigits(int n) {
    if (n == 0)
        return 0;
    return (n % 10 + sumOfDigits(n / 10));
}

int main() {
    int num = 12345;
    printf("Sum of digits of %d = %d\n", num, sumOfDigits(num));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Returns `n % 10 + sumOfDigits(n / 10)` recursively until `n == 0`.

PROGRAM OUTPUT

Sum of digits of 12345 = 15

#56

C Program to Calculate Average Using Arrays

Arrays

PROBLEM STATEMENT

Write a C program to store numbers in an array and calculate their average.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int n = 5;
    float marks[5] = {85.5, 90.0, 78.0, 92.5, 88.0};
    float sum = 0.0, average;

    for (int i = 0; i < n; ++i) {
        sum += marks[i];
    }

    average = sum / n;
    printf("Average = %.2f\n", average);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Accumulates element values across 1D array in `sum`.
2. Computes average = `sum / n`.

PROGRAM OUTPUT

Average = 86.80

#57

C Program to Find Largest and Smallest Element in an Array

Arrays

PROBLEM STATEMENT

Write a C program to search for maximum and minimum values in an array.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int arr[] = {25, 11, 7, 75, 56};
    int n = 5;
    int max = arr[0], min = arr[0];

    for (int i = 1; i < n; i++) {
        if (arr[i] > max) max = arr[i];
        if (arr[i] < min) min = arr[i];
    }

    printf("Largest element = %d\nSmallest element = %d\n", max, min);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Initializes `max` and `min` with `arr[0]`. Updates values during single pass iteration.

PROGRAM OUTPUT

```
Largest element = 75
Smallest element = 7
```

#58

C Program to Calculate Standard Deviation

Arrays

PROBLEM STATEMENT

Write a C program to compute population standard deviation of array elements.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <math.h>

float calculateSD(float data[], int n) {
    float sum = 0.0, mean, SD = 0.0;
    for (int i = 0; i < n; ++i) sum += data[i];
    mean = sum / n;

    for (int i = 0; i < n; ++i)
        SD += pow(data[i] - mean, 2);

    return sqrt(SD / n);
}

int main() {
    float data[] = {10, 12, 23, 23, 16, 23, 21, 16};
    printf("Standard Deviation = %.6f\n", calculateSD(data, 8));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Computes mean, variance $(x_i - \text{mean})^2$, and returns square root of variance mean.

PROGRAM OUTPUT

Standard Deviation = 4.898979

#59

C Program to Sort Array Elements in Ascending and Descending Order

Arrays

PROBLEM STATEMENT

Write a C program to sort an array using Bubble Sort algorithm.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void bubbleSort(int arr[], int n) {
    int temp;
    for (int i = 0; i < n - 1; i++) {
        for (int j = 0; j < n - i - 1; j++) {
            if (arr[j] > arr[j + 1]) {
                temp = arr[j];
                arr[j] = arr[j + 1];
                arr[j + 1] = temp;
            }
        }
    }
}

int main() {
    int arr[] = {64, 34, 25, 12, 22, 11, 90};
    int n = 7;
    bubbleSort(arr, n);
    printf("Sorted array: ");
    for (int i = 0; i < n; i++) printf("%d ", arr[i]);
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Compares adjacent elements and swaps them if out of order.

PROGRAM OUTPUT

Sorted array: 11 12 22 25 34 64 90

#60

C Program to Insert an Element in an Array at a Specified Position

Arrays

PROBLEM STATEMENT

Write a C program to insert a new value into an array at given index.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int arr[10] = {1, 2, 4, 5, 6};
    int n = 5, pos = 3, val = 3;

    for (int i = n - 1; i >= pos - 1; i--) {
        arr[i + 1] = arr[i];
    }
    arr[pos - 1] = val;
    n++;

    printf("Array after insertion: ");
    for (int i = 0; i < n; i++) printf("%d ", arr[i]);
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Shifts elements right starting from end index down to target position.

PROGRAM OUTPUT

Array after insertion: 1 2 3 4 5 6

#61

C Program to Delete an Element from an Array

Arrays

PROBLEM STATEMENT

Write a C program to delete an element at a given position in an array.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int arr[] = {10, 20, 30, 40, 50};
    int n = 5, pos = 3; // Delete 3rd element (30)

    for (int i = pos - 1; i < n - 1; i++) {
        arr[i] = arr[i + 1];
    }
    n--;

    printf("Array after deletion: ");
    for (int i = 0; i < n; i++) printf("%d ", arr[i]);
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Shifts elements left starting from target index to overwrite deleted element.

PROGRAM OUTPUT

Array after deletion: 10 20 40 50

#62

C Program to Search an Element in an Array (Linear & Binary Search)

Arrays

PROBLEM STATEMENT

Write a C program to implement Binary Search on a sorted array.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int binarySearch(int arr[], int l, int r, int x) {
    while (l <= r) {
        int m = l + (r - l) / 2;
        if (arr[m] == x) return m;
        if (arr[m] < x) l = m + 1;
        else r = m - 1;
    }
    return -1;
}

int main() {
    int arr[] = {2, 3, 4, 10, 40};
    int n = 5, x = 10;
    int result = binarySearch(arr, 0, n - 1, x);
    if (result == -1) printf("Element not present\n");
    else printf("Element found at index %d\n", result);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Binary search operates on sorted array in $O(\log n)$ time by halving search space.

PROGRAM OUTPUT

Element found at index 3

#63

C Program to Merge Two Arrays

Arrays

PROBLEM STATEMENT

Write a C program to combine elements of two separate arrays into a single array.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int arr1[] = {1, 3, 5};
    int arr2[] = {2, 4, 6};
    int n1 = 3, n2 = 3;
    int merged[6];

    for(int i = 0; i < n1; i++) merged[i] = arr1[i];
    for(int i = 0; i < n2; i++) merged[n1 + i] = arr2[i];

    printf("Merged Array: ");
    for(int i = 0; i < n1 + n2; i++) printf("%d ", merged[i]);
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Copies `arr1` into `merged`, then appends `arr2` starting at index `n1`.

PROGRAM OUTPUT

Merged Array: 1 3 5 2 4 6

#64

C Program to Find Second Largest Number in an Array

Arrays

PROBLEM STATEMENT

Write a C program to find second largest integer in an unsorted array.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <limits.h>

int main() {
    int arr[] = {12, 35, 1, 10, 34, 1};
    int n = 6;
    int first = INT_MIN, second = INT_MIN;

    for (int i = 0; i < n; i++) {
        if (arr[i] > first) {
            second = first;
            first = arr[i];
        } else if (arr[i] > second && arr[i] != first) {
            second = arr[i];
        }
    }

    printf("The second largest element is %d\n", second);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Tracks `first` max and updates `second` max whenever a new high is encountered.

PROGRAM OUTPUT

The second largest element is 34

#65

C Program to Remove Duplicate Elements from an Array

Arrays

PROBLEM STATEMENT

Write a C program to remove duplicate values from a sorted array.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int removeDuplicates(int arr[], int n) {
    if (n == 0 || n == 1) return n;
    int j = 0;
    for (int i = 0; i < n - 1; i++) {
        if (arr[i] != arr[i + 1]) {
            arr[j++] = arr[i];
        }
    }
    arr[j++] = arr[n - 1];
    return j;
}

int main() {
    int arr[] = {1, 2, 2, 3, 4, 4, 4, 5};
    int n = 8;
    n = removeDuplicates(arr, n);
    printf("Array after removing duplicates: ");
    for (int i = 0; i < n; i++) printf("%d ", arr[i]);
    printf("\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. In-place duplication removal by checking adjacent unequal elements.

PROGRAM OUTPUT

Array after removing duplicates: 1 2 3 4 5

#66

C Program to Add Two Matrices Using Multi-dimensional Arrays

Matrices / Multidimensional Arrays

PROBLEM STATEMENT

Write a C program to perform matrix addition of two 2×2 matrices.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int a[2][2] = {{1, 2}, {3, 4}};
    int b[2][2] = {{5, 6}, {7, 8}};
    int sum[2][2];

    for (int i = 0; i < 2; ++i) {
        for (int j = 0; j < 2; ++j) {
            sum[i][j] = a[i][j] + b[i][j];
        }
    }

    printf("Sum of matrices:\n");
    for (int i = 0; i < 2; ++i) {
        for (int j = 0; j < 2; ++j) {
            printf("%d ", sum[i][j]);
        }
        printf("\n");
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Nested loops iterate over rows ('i') and columns ('j'), computing `sum[i][j] = a[i][j] + b[i][j]`.

PROGRAM OUTPUT

```
Sum of matrices:
6  8
10 12
```

#67

C Program to Multiply Two Matrices Using Multi-dimensional Arrays

Matrices / Multidimensional Arrays

PROBLEM STATEMENT

Write a C program to compute matrix multiplication of two matrices.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int a[2][3] = {{1, 2, 3}, {4, 5, 6}};
    int b[3][2] = {{7, 8}, {9, 1}, {2, 3}};
    int result[2][2] = {0};

    for (int i = 0; i < 2; ++i) {
        for (int j = 0; j < 2; ++j) {
            for (int k = 0; k < 3; ++k) {
                result[i][j] += a[i][k] * b[k][j];
            }
        }
    }

    printf("Multiplication Result:\n");
    for (int i = 0; i < 2; ++i) {
        for (int j = 0; j < 2; ++j) {
            printf("%d ", result[i][j]);
        }
        printf("\n");
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Triple nested loop performs dot product of row `i` of matrix A and column `j` of matrix B.

PROGRAM OUTPUT

```
Multiplication Result:
31  19
85  55
```

#68 C Program to Find Transpose of a Matrix

Matrices / Multidimensional Arrays

PROBLEM STATEMENT

Write a C program to swap rows and columns of a matrix (Transpose).

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int a[2][3] = {{1, 2, 3}, {4, 5, 6}};
    int transpose[3][2];

    for (int i = 0; i < 2; ++i) {
        for (int j = 0; j < 3; ++j) {
            transpose[j][i] = a[i][j];
        }
    }

    printf("Transpose of the matrix:\n");
    for (int i = 0; i < 3; ++i) {
        for (int j = 0; j < 2; ++j) {
            printf("%d ", transpose[i][j]);
        }
        printf("\n");
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Transpose sets `transpose[j][i] = a[i][j]`.

PROGRAM OUTPUT

```
Transpose of the matrix:
1  4
2  5
3  6
```

#69

C Program to Multiply two Matrices by Passing Matrix to a Function

Matrices / Multidimensional Arrays

PROBLEM STATEMENT

Write a C program to multiply matrices by passing 2D arrays to a user-defined function.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void multiplyMatrices(int first[2][2], int second[2][2], int result[2][2]) {
    for (int i = 0; i < 2; ++i) {
        for (int j = 0; j < 2; ++j) {
            result[i][j] = 0;
            for (int k = 0; k < 2; ++k) {
                result[i][j] += first[i][k] * second[k][j];
            }
        }
    }
}

int main() {
    int a[2][2] = {{1, 2}, {3, 4}};
    int b[2][2] = {{2, 0}, {1, 2}};
    int res[2][2];

    multiplyMatrices(a, b, res);

    printf("Result Matrix:\n");
    for (int i = 0; i < 2; ++i) {
        for (int j = 0; j < 2; ++j) printf("%d ", res[i][j]);
        printf("\n");
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Demonstrates passing multi-dimensional array parameters into functions.

PROGRAM OUTPUT

```
Result Matrix:
4 4
10 8
```

#70 C Program to Check Sparse Matrix

Matrices / Multidimensional Arrays

PROBLEM STATEMENT

Write a C program to check if a matrix is sparse (majority of elements are 0).

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int a[3][3] = {{1, 0, 0}, {0, 0, 2}, {0, 5, 0}};
    int count = 0, total = 9;

    for (int i = 0; i < 3; i++) {
        for (int j = 0; j < 3; j++) {
            if (a[i][j] == 0) count++;
        }
    }

    if (count > total / 2)
        printf("The matrix is a Sparse Matrix.\n");
    else
        printf("The matrix is not a Sparse Matrix.\n");

    return 0;
}
```

NOTES & KEY CONCEPTS

1. A matrix is sparse if count of 0s exceeds total elements / 2.

PROGRAM OUTPUT

The matrix is a Sparse Matrix.

#71

C Program to Find Sum of Diagonal Elements of a Matrix

Matrices / Multidimensional Arrays

PROBLEM STATEMENT

Write a C program to calculate sum of main diagonal elements of a square matrix.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int a[3][3] = {{1, 2, 3}, {4, 5, 6}, {7, 8, 9}};
    int sum = 0;

    for (int i = 0; i < 3; i++) {
        sum += a[i][i]; // Main diagonal element
    }

    printf("Sum of main diagonal elements = %d\n", sum);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Main diagonal elements have row index equal to column index ('a[i][i]').

PROGRAM OUTPUT

Sum of main diagonal elements = 15

#72 C Program to Check if Two Matrices Are Equal

Matrices / Multidimensional Arrays

PROBLEM STATEMENT

Write a C program to test if two matrices have identical dimensions and matching elements.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int a[2][2] = {{1, 2}, {3, 4}};
    int b[2][2] = {{1, 2}, {3, 4}};
    int equal = 1;

    for (int i = 0; i < 2; i++) {
        for (int j = 0; j < 2; j++) {
            if (a[i][j] != b[i][j]) {
                equal = 0;
                break;
            }
        }
    }

    if (equal) printf("Matrices are equal.\n");
    else printf("Matrices are not equal.\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Compares corresponding elements `a[i][j]` and `b[i][j]`. Flags inequality on first mismatch.

PROGRAM OUTPUT

Matrices are equal.

#73 C Program to Access Array Elements Using Pointer

Pointers & Dynamic Memory

PROBLEM STATEMENT

Write a C program to iterate and print array elements using pointer arithmetic.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int data[5] = {10, 20, 30, 40, 50};
    int *ptr = data;

    printf("You entered: \n");
    for (int i = 0; i < 5; ++i) {
        printf("Element %d = %d (Address: %p)\n", i, *(ptr + i), (void*)(ptr + i));
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Array identifier `data` acts as pointer to first element.
2. `\*(ptr + i)` dereferences `i`-th element.

PROGRAM OUTPUT

```
Element 0 = 10 (Address: 0x...)
Element 1 = 20 (Address: 0x...)
...
```

#74

C Program Swap Numbers in Cyclic Order Using Call by Reference

Pointers & Dynamic Memory

PROBLEM STATEMENT

Write a C program to swap three variables (a, b, c) in cyclic order using pointers.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void cyclicSwap(int *a, int *b, int *c) {
    int temp = *b;
    *b = *a;
    *a = *c;
    *c = temp;
}

int main() {
    int a = 1, b = 2, c = 3;
    printf("Before swapping: a = %d, b = %d, c = %d\n", a, b, c);
    cyclicSwap(&a, &b, &c);
    printf("After cyclic swap: a = %d, b = %d, c = %d\n", a, b, c);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Call by reference passes variable addresses (`&a, &b, &c`). Pointer dereferencing modifies original variables.

PROGRAM OUTPUT

Before swapping: a = 1, b = 2, c = 3
After cyclic swap: a = 3, b = 1, c = 2

#75

C Program to Find Largest Number Using Dynamic Memory Allocation

Pointers & Dynamic Memory

PROBLEM STATEMENT

Write a C program using calloc/malloc to dynamically allocate array memory and find max value.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <stdlib.h>

int main() {
    int n = 5;
    float *data;

    data = (float*) calloc(n, sizeof(float));
    if (data == NULL) {
        printf("Memory allocation failed!\n");
        return 1;
    }

    data[0] = 12.5; data[1] = 45.2; data[2] = 98.1; data[3] = 33.4; data[4] = 67.0;

    for (int i = 1; i < n; ++i) {
        if (*data < *(data + i))
            *data = *(data + i);
    }

    printf("Largest number = %.2f\n", *data);
    free(data); // Free dynamically allocated memory
    return 0;
}
```

NOTES & KEY CONCEPTS

1. `calloc()` allocates memory initialized to zero.
2. `free(data)` releases memory back to system heap.

PROGRAM OUTPUT

Largest number = 98.10

#76

C Program to Demonstrate Pointer Arithmetic and Array Traversal

Pointers & Dynamic Memory

PROBLEM STATEMENT

Write a C program demonstrating incrementing/decrementing pointers across arrays.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int arr[] = {100, 200, 300};
    int *ptr = arr;

    for (int i = 0; i < 3; i++) {
        printf("Address of arr[%d] = %p, Value = %d\n", i, (void*)ptr, *ptr);
        ptr++; // Advance pointer by sizeof(int)
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. `ptr++` increments pointer address by size of data type (`sizeof(int)` = 4 bytes).

PROGRAM OUTPUT

```
Address of arr[0] = 0x..., Value = 100
Address of arr[1] = 0x..., Value = 200
...
```

#77

C Program to Dynamically Allocate & Reallocate Array Memory

Pointers & Dynamic Memory

PROBLEM STATEMENT

Write a C program demonstrating `malloc()`, `realloc()`, and `free()`.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <stdlib.h>

int main() {
    int *ptr;
    int n1 = 3, n2 = 6;

    ptr = (int*) malloc(n1 * sizeof(int));
    for (int i = 0; i < n1; ++i) ptr[i] = i + 1;

    // Reallocate memory for 6 elements
    ptr = realloc(ptr, n2 * sizeof(int));
    for (int i = n1; i < n2; ++i) ptr[i] = i + 1;

    printf("Reallocated array: ");
    for (int i = 0; i < n2; ++i) printf("%d ", ptr[i]);
    printf("\n");

    free(ptr);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. `realloc()` resizes previously allocated memory block without losing existing data.

PROGRAM OUTPUT

Reallocated array: 1 2 3 4 5 6

#78 C Program to Find Length of String Using Pointers

Pointers & Dynamic Memory

PROBLEM STATEMENT

Write a C program to calculate length of a string using pointer arithmetic.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int stringLength(char *str) {
    char *p = str;
    while (*p != '\0') p++;
    return (p - str);
}

int main() {
    char str[] = "Antigravity C Programming";
    printf("Length of string = %d\n", stringLength(str));
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Pointer subtraction `p - str` gives number of characters traversed before null terminator `\0`.

PROGRAM OUTPUT

Length of string = 25

#79

C Program to Find the Frequency of Characters in a String

Strings

PROBLEM STATEMENT

Write a C program to count occurrence frequency of a specific character in a string.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char str[] = "programming in c language";
    char ch = 'g';
    int count = 0;

    for (int i = 0; str[i] != '\0'; ++i) {
        if (ch == str[i])
            ++count;
    }

    printf("Frequency of '%c' = %d\n", ch, count);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Iterates until null terminator '\0' and increments counter on match.

PROGRAM OUTPUT

Frequency of 'g' = 3

#80

C Program to Count the Number of Vowels, Consonants and so on

Strings

PROBLEM STATEMENT

Write a C program to count vowels, consonants, digits, and whitespace in a string.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <ctype.h>

int main() {
    char line[] = "C programming is fun 100%";
    int vowels = 0, consonants = 0, digits = 0, spaces = 0;

    for (int i = 0; line[i] != '\0'; ++i) {
        char ch = tolower(line[i]);
        if (ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch == 'u') {
            ++vowels;
        } else if ((ch >= 'a' && ch <= 'z')) {
            ++consonants;
        } else if (ch >= '0' && ch <= '9') {
            ++digits;
        } else if (ch == ' ') {
            ++spaces;
        }
    }

    printf("Vowels: %d\nConsonants: %d\nDigits: %d\nSpaces: %d\n", vowels, consonants, digits, spaces);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Categorizes each character using character test logic.

PROGRAM OUTPUT

```
Vowels: 5
Consonants: 11
Digits: 3
Spaces: 3
```

#81

C Program to Remove all Characters in a String Except Alphabets

Strings

PROBLEM STATEMENT

Write a C program to filter out non-alphabet characters from a string.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char line[100] = "p2_r3o1g8r4a6m8m9i1n0g!";
    int j = 0;

    for (int i = 0; line[i] != '\0'; ++i) {
        while (!(line[i] >= 'a' && line[i] <= 'z') && !(line[i] >= 'A' && line[i] <= 'Z')) &&
            for (int k = i; line[k] != '\0'; ++k) {
                line[k] = line[k + 1];
            }
    }

    printf("Output String: %s\n", line);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Shifts characters left whenever non-alphabet character is encountered.

PROGRAM OUTPUT

Output String: programming

#82 C Program to Find the Length of a String

Strings

PROBLEM STATEMENT

Write a C program to compute length of a string without using standard `strlen()`.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char s[] = "Programming is fun";
    int i;

    for (i = 0; s[i] != '\0'; ++i);

    printf("Length of string: %d\n", i);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Counts index `i` until reaching null character `\0`.

PROGRAM OUTPUT

Length of string: 18

#83

C Program to Concatenate Two Strings

Strings

PROBLEM STATEMENT

Write a C program to concatenate two strings manually without using `strcat()`.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char s1[100] = "Hello ", s2[] = "World!";
    int length = 0, j;

    // Find length of s1
    while (s1[length] != '\0') {
        ++length;
    }

    // Concatenate s2 to s1
    for (j = 0; s2[j] != '\0'; ++j, ++length) {
        s1[length] = s2[j];
    }
    s1[length] = '\0'; // Null terminate

    printf("After concatenation: %s\n", s1);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Appends characters of `s2` onto `s1` starting at length index.

PROGRAM OUTPUT

After concatenation: Hello World!

#84 C Program to Copy String Without Using strcpy()

Strings

PROBLEM STATEMENT

Write a C program to copy one string into another string manually.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    char s1[] = "Antigravity AI", s2[100];
    int i;

    for (i = 0; s1[i] != '\0'; ++i) {
        s2[i] = s1[i];
    }
    s2[i] = '\0';

    printf("String s2: %s\n", s2);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Copies element by element including null terminator '\0'.

PROGRAM OUTPUT

String s2: Antigravity AI

#85

C Program to Sort Elements in Lexicographical Order (Dictionary Order)

Strings

PROBLEM STATEMENT

Write a C program to sort an array of 5 strings alphabetically.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <string.h>

int main() {
    char str[5][50] = {"C", "Python", "Java", "C++", "Rust"};
    char temp[50];

    for (int i = 0; i < 4; ++i) {
        for (int j = i + 1; j < 5; ++j) {
            if (strcmp(str[i], str[j]) > 0) {
                strcpy(temp, str[i]);
                strcpy(str[i], str[j]);
                strcpy(str[j], temp);
            }
        }
    }

    printf("In lexicographical order: \n");
    for (int i = 0; i < 5; ++i) {
        puts(str[i]);
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Uses `strcmp()` to compare dictionary precedence and `strcpy()` to swap strings.

PROGRAM OUTPUT

```
In lexicographical order:
C
C++
Java
Python
Rust
```

#86 C Program to Reverse a String Without Using `strrev()`

Strings

PROBLEM STATEMENT

Write a C program to reverse a string in-place.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <string.h>

int main() {
    char str[] = "DataStructures";
    int len = strlen(str);
    char temp;

    for (int i = 0; i < len / 2; i++) {
        temp = str[i];
        str[i] = str[len - i - 1];
        str[len - i - 1] = temp;
    }

    printf("Reversed String: %s\n", str);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Swaps symmetric characters from start and end up to midpoint `'len / 2'`.

PROGRAM OUTPUT

Reversed String: serutcurtSataD

#87

C Program to Compare Two Strings Without Using strcmp()

Strings

PROBLEM STATEMENT

Write a C program to compare two strings character by character.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int compareStrings(char s1[], char s2[]) {
    int i = 0;
    while (s1[i] == s2[i]) {
        if (s1[i] == '\0' || s2[i] == '\0')
            break;
        i++;
    }
    if (s1[i] == '\0' && s2[i] == '\0')
        return 0;
    else
        return s1[i] - s2[i];
}

int main() {
    char s1[] = "apple", s2[] = "apple";
    if (compareStrings(s1, s2) == 0)
        printf("Strings are equal.\n");
    else
        printf("Strings are not equal.\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Iterates matching characters until inequality or null byte.

PROGRAM OUTPUT

Strings are equal.

#88

C Program to Check if Two Strings are Anagrams

Strings

PROBLEM STATEMENT

Write a C program to verify if two strings are anagrams of each other.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <string.h>

int checkAnagram(char str1[], char str2[]) {
    int count[256] = {0};
    if (strlen(str1) != strlen(str2)) return 0;

    for (int i = 0; str1[i] && str2[i]; i++) {
        count[(unsigned char)str1[i]]++;
        count[(unsigned char)str2[i]]--;
    }

    for (int i = 0; i < 256; i++) {
        if (count[i] != 0) return 0;
    }
    return 1;
}

int main() {
    char s1[] = "listen", s2[] = "silent";
    if (checkAnagram(s1, s2)) printf("Strings are anagrams.\n");
    else printf("Strings are not anagrams.\n");
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Tracks character frequency deltas across ASCII hash array.

PROGRAM OUTPUT

Strings are anagrams.

#89

C Program to Store Information of a Student Using Structure

Structures & Files

PROBLEM STATEMENT

Write a C program to define a student struct and store/display record.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

struct student {
    char name[50];
    int roll;
    float marks;
};

int main() {
    struct student s = {"John Doe", 101, 89.5};

    printf("Displaying Information:\n");
    printf("Name: %s\n", s.name);
    printf("Roll number: %d\n", s.roll);
    printf("Marks: %.1f\n", s.marks);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. 'struct' aggregates heterogeneous data members under single entity variable.

PROGRAM OUTPUT

```
Displaying Information:
Name: John Doe
Roll number: 101
Marks: 89.5
```

#90

C Program to Add Two Distances (in inch-feet system) using Structures

Structures & Files

PROBLEM STATEMENT

Write a C program to add two distance measurements in feet-inch system using structures.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

struct Distance {
    int feet;
    float inch;
} d1 = {12, 8.5}, d2 = {6, 7.5}, result;

int main() {
    result.feet = d1.feet + d2.feet;
    result.inch = d1.inch + d2.inch;

    // Convert 12 inches to 1 foot
    while (result.inch >= 12.0) {
        result.inch = result.inch - 12.0;
        ++result.feet;
    }

    printf("Sum of distances = %d'-%.1f\"\n", result.feet, result.inch);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Normalizes inch overflow ('inch >= 12') into feet component.

PROGRAM OUTPUT

Sum of distances = 19'-4.0"

#91

C Program to Add Two Complex Numbers by Passing Structure to a Function

Structures & Files

PROBLEM STATEMENT

Write a C program to add two complex numbers using functions and structures.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

typedef struct complex {
    float real;
    float imag;
} complex;

complex add(complex n1, complex n2) {
    complex temp;
    temp.real = n1.real + n2.real;
    temp.imag = n1.imag + n2.imag;
    return temp;
}

int main() {
    complex n1 = {2.3, 4.5}, n2 = {3.4, 5.0}, result;
    result = add(n1, n2);
    printf("Sum = %.1f + %.1fi\n", result.real, result.imag);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Demonstrates returning structure objects directly from functions.

PROGRAM OUTPUT

Sum = 5.7 + 9.5i

#92

C Program to Calculate Difference Between Two Time Periods

Structures & Files

PROBLEM STATEMENT

Write a C program to subtract two time period timestamps (hours, minutes, seconds).

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

struct TIME {
    int seconds;
    int minutes;
    int hours;
};

void differenceBetweenTimePeriod(struct TIME t1, struct TIME t2, struct TIME *diff) {
    while (t2.seconds > t1.seconds) {
        --t1.minutes;
        t1.seconds += 60;
    }
    diff->seconds = t1.seconds - t2.seconds;
    while (t2.minutes > t1.minutes) {
        --t1.hours;
        t1.minutes += 60;
    }
    diff->minutes = t1.minutes - t2.minutes;
    diff->hours = t1.hours - t2.hours;
}

int main() {
    struct TIME t1 = {45, 20, 12}, t2 = {55, 30, 8}, diff;
    differenceBetweenTimePeriod(t1, t2, &diff);
    printf("TIME DIFFERENCE: %d:%d:%d\n", diff.hours, diff.minutes, diff.seconds);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Handles borrow operations across seconds and minutes.

PROGRAM OUTPUT

TIME DIFFERENCE: 3:49:50

#93

C Program to Store Information of Students Using Structure Array

Structures & Files

PROBLEM STATEMENT

Write a C program to dynamically allocate memory for an array of student structure records.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <stdlib.h>

struct Student {
    char name[30];
    int roll;
};

int main() {
    int n = 2;
    struct Student *st = (struct Student*) malloc(n * sizeof(struct Student));

    st[0].roll = 1; sprintf(st[0].name, "Alice");
    st[1].roll = 2; sprintf(st[1].name, "Bob");

    for(int i = 0; i < n; i++) {
        printf("Roll: %d, Name: %s\n", st[i].roll, st[i].name);
    }
    free(st);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Dynamically allocates struct array block via `malloc()`.

PROGRAM OUTPUT

```
Roll: 1, Name: Alice
Roll: 2, Name: Bob
```

#94

C Program to Write a Sentence to a File and Read First Line

Structures & Files

PROBLEM STATEMENT

Write a C program to perform file I/O operations (`fopen`, `fprintf`, `fgets`, `fclose`).

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>
#include <stdlib.h>

int main() {
    char text[100];
    FILE *fptr;

    // Write to file
    fptr = fopen("test.txt", "w");
    if (fptr == NULL) return 1;
    fprintf(fptr, "Hello Antigravity File I/O!\nSecond Line");
    fclose(fptr);

    // Read first line
    fptr = fopen("test.txt", "r");
    if (fptr == NULL) return 1;
    fgets(text, sizeof(text), fptr);
    printf("First line from file:\n%s", text);
    fclose(fptr);

    return 0;
}
```

NOTES & KEY CONCEPTS

1. `fopen()` opens file handles in write (`"w"`) and read (`"r"`) modes.
2. `fclose()` releases system handle.

PROGRAM OUTPUT

First line from file:
Hello Antigravity File I/O!

#95

C Program to Print Half Pyramid and Full Pyramid Star Patterns

Pyramids & Pattern Printing

PROBLEM STATEMENT

Write a C program to print star patterns (Half Pyramid & Full Pyramid).

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void halfPyramid(int rows) {
    printf("Half Star Pyramid:\n");
    for (int i = 1; i <= rows; ++i) {
        for (int j = 1; j <= i; ++j) {
            printf("* ");
        }
        printf("\n");
    }
}

void fullPyramid(int rows) {
    printf("\nFull Star Pyramid:\n");
    for (int i = 1; i <= rows; ++i) {
        for (int space = 1; space <= rows - i; ++space) printf(" ");
        for (int k = 1; k <= 2 * i - 1; ++k) printf("* ");
        printf("\n");
    }
}

int main() {
    halfPyramid(5);
    fullPyramid(5);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Outer loop controls rows.
2. Inner loops handle leading spaces and star counts ($2*i - 1$).

PROGRAM OUTPUT

```
Half Star Pyramid:
*
* *
* * *
* * * *
* * * * *

Full Star Pyramid:
      *
    * * *
```

```
    * * * * *  
  * * * * *  
* * * * *
```

#96

C Program to Print Pascal's Triangle and Floyd's Triangle

Pyramids & Pattern Printing

PROBLEM STATEMENT

Write a C program to print Pascal's Triangle and Floyd's Triangle patterns.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void pascalsTriangle(int rows) {
    printf("Pascal's Triangle:\n");
    for (int i = 0; i < rows; i++) {
        int coef = 1;
        for (int space = 1; space <= rows - i; space++) printf(" ");
        for (int j = 0; j <= i; j++) {
            if (j == 0 || i == 0) coef = 1;
            else coef = coef * (i - j + 1) / j;
            printf("%d ", coef);
        }
        printf("\n");
    }
}

void floydsTriangle(int rows) {
    printf("\nFloyd's Triangle:\n");
    int val = 1;
    for (int i = 1; i <= rows; i++) {
        for (int j = 1; j <= i; j++) {
            printf("%d ", val++);
        }
        printf("\n");
    }
}

int main() {
    pascalsTriangle(5);
    floydsTriangle(4);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Pascal's combination formula $nCr = nCr-1 * (n-r+1)/r$.
2. Floyd's triangle prints sequential numbers.

PROGRAM OUTPUT

```
Pascal's Triangle:
  1
 1 1
1 2 1
```

```
1 3 3 1
1 4 6 4 1
```

Floyd's Triangle:

```
1
2 3
4 5 6
7 8 9 10
```

#97

C Program to Print Hollow Square and Diamond Star Patterns

Pyramids & Pattern Printing

PROBLEM STATEMENT

Write a C program to display Hollow Square and Diamond star patterns.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void hollowSquare(int n) {
    printf("Hollow Square Pattern:\n");
    for (int i = 1; i <= n; i++) {
        for (int j = 1; j <= n; j++) {
            if (i == 1 || i == n || j == 1 || j == n)
                printf("* ");
            else
                printf(" ");
        }
        printf("\n");
    }
}

void diamondPattern(int n) {
    printf("\nDiamond Star Pattern:\n");
    for (int i = 1; i <= n; i++) {
        for (int j = 1; j <= n - i; j++) printf(" ");
        for (int j = 1; j <= 2 * i - 1; j++) printf("*");
        printf("\n");
    }
    for (int i = n - 1; i >= 1; i--) {
        for (int j = 1; j <= n - i; j++) printf(" ");
        for (int j = 1; j <= 2 * i - 1; j++) printf("*");
        printf("\n");
    }
}

int main() {
    hollowSquare(5);
    diamondPattern(4);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Hollow square tests boundary indices ('i==1 || i==n || j==1 || j==n').
2. Diamond mirrors upper and lower pyramids.

PROGRAM OUTPUT

Hollow Square Pattern:
* * * * *

```
*      *  
*      *  
*      *  
* * * * *
```

Diamond Star Pattern:

```
  *  
 ***  
*****  
*****  
*****  
 ***  
  *
```

#98

C Program to Print Number Pyramids and Inverted Number Triangles

Pyramids & Pattern Printing

PROBLEM STATEMENT

Write a C program to print numerical pyramid patterns.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void numberPyramid(int rows) {
    printf("Inverted Number Triangle:\n");
    for (int i = rows; i >= 1; --i) {
        for (int j = 1; j <= i; ++j) {
            printf("%d ", j);
        }
        printf("\n");
    }
}

int main() {
    numberPyramid(5);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Decrementing outer loop creates inverted triangular rows.

PROGRAM OUTPUT

```
Inverted Number Triangle:
1 2 3 4 5
1 2 3 4
1 2 3
1 2
1
```

#99

C Program to Print Character / Alphabet Pattern Pyramids

Pyramids & Pattern Printing

PROBLEM STATEMENT

Write a C program to print character pyramid patterns.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

int main() {
    int i, j;
    char input = 'E', lastChar = 'A';

    printf("Alphabet Pyramid Pattern:\n");
    for (i = 1; i <= (input - 'A' + 1); ++i) {
        for (j = 1; j <= i; ++j) {
            printf("%c ", lastChar);
        }
        ++lastChar;
        printf("\n");
    }
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Increments character `lastChar` at each row.

PROGRAM OUTPUT

```
Alphabet Pyramid Pattern:
A
B B
C C C
D D D D
E E E E E
```

#100

C Program to Print Hourglass and Butterfly Star Patterns

Pyramids & Pattern Printing

PROBLEM STATEMENT

Write a C program to render Hourglass star pattern.

C SOURCE CODE

GCC Compiler

```
#include <stdio.h>

void hourglass(int n) {
    printf("Hourglass Star Pattern:\n");
    for (int i = n; i >= 1; i--) {
        for (int j = 1; j <= n - i; j++) printf(" ");
        for (int j = 1; j <= 2 * i - 1; j++) printf("*");
        printf("\n");
    }
    for (int i = 2; i <= n; i++) {
        for (int j = 1; j <= n - i; j++) printf(" ");
        for (int j = 1; j <= 2 * i - 1; j++) printf("*");
        printf("\n");
    }
}

int main() {
    hourglass(4);
    return 0;
}
```

NOTES & KEY CONCEPTS

1. Combines inverted full pyramid with upright full pyramid.

PROGRAM OUTPUT

```
Hourglass Star Pattern:
*****
*****
***
*
***
*****
*****
```