


MAXGBoost: A Fast Novel Heuristic Approach to Adaptive Learning Rates in Gradient Boosted Decision Trees

By: Anirudh Chintaluri, Vini Rezanejad


Fundamentals

- GBDTs initialize with a decision tree that's evaluated using a loss function
- The model minimizes loss by moving in the direction of the negative gradient
- This process is similar to neural networks' backpropagation, but creates an ensemble decision tree model

A Gradient Boosting Decision Trees Structure




A Decision Trees Structure




Learning Rate Mechanics

- The algorithm adds new decision trees scaled by a learning rate (η)
- Learning rate determines how far down the loss function the tree will go
- Low η ensures convergence but requires more iterations and computational cost
- High η speeds up convergence but risks overshooting the optimal solution




Learning Rate Optimization

- Optimal learning rate depends on both dataset and loss function
- Tuning requires iterative experimentation
- Adaptive strategies help reduce need for extensive hyperparameter searches
- Particularly important for datasets with high sparsity




Introduction to MAXGBoost

- Momentum Approximation
XGBoost dynamically adjusts learning rate based on loss momentum
- Enables faster convergence
- Reduces need for manual optimization while maintaining high detection accuracy



The Dataset

- Credit Card Fraud Detection
- 284,807 total instances
- 31 total attributes
- Notable Features:
 - Time
 - Amount
 - V1-V38 -> Result of PCA
- 492 instances marked as fraud
 - $< 0.2\%$ of data
- Dataset already preprocessed



The Algorithm - Traditional Neural Network

$$w_{t+1} = w_t - \eta \nabla L$$

The Algorithm - Neural Network with Momentum

- v = velocity
- β = how influential past velocities are on the new velocity calculated
- Converges faster than with a constant learning rate

$$v_{t+1} = \beta v_t + (1 - \beta) \nabla L$$

$$w_{t+1} = w_t - \eta v_{t+1}$$

The Algorithm - MAXGBoost

- Combines GBDT and momentum-based updates
- Approximates ∇L
- Using momentum to update the **learning rate**
 - Loss increase = η increase
 - Loss decrease = η decrease

$$v_{t+1} = \beta v_t + (1 - \beta)(L_{t+1} - L_t)$$

$$\eta_{t+1} = \eta_t(1 + v_{t+1})$$

Experiments - Dataset

Splits

- 68%: Training
- 12%: Validation
- 20%: Testing

Analysis

- 5-fold Cross-validation
- Results based on best fold per model

Experiments - Models

Decision Tree	Single Decision Tree
Random Forest	Ensemble Voting Decision Tree Model
Constant η XGBoost	XGBoost with a constant learning rate
Exponential Decay XGBoost	XGBoost with a learning rate multiplied by constant every iteration
MAXGBoost	XGBoost with Momentum Approximation

Experiments - Hyperparameters

Decision Tree	Max Depth = 4
Random Forest	Estimators = 5
Constant η XGBoost	Estimators = 423, η = 0.08
Exponential Decay XGBoost	Estimators = 423, α = 0.9
MAXGBoost	Estimators = 423, Initial η = 0.89, β = 0.99

Results

Model	Accuracy	Precision	Recall	AUC
Decision Tree	0.99946	0.86813	0.80612	0.90296
Random Forest	0.99951	0.77000	0.93902	0.96931
Constant η	0.99977	0.88636	0.96296	0.98139
Exponential decay	0.99979	0.88764	0.97531	0.98757
MAXGBoost	0.99980	0.93827	0.92683	0.96337

Discussion - MAXGBoost Strengths

● Best Precision in Fraud Detection

- Exceptional performance in minimizing false positives
- Effective for high-stakes financial environments
 - Reduces customer friction from false alerts
 - Minimizes operational costs from investigation overhead

Discussion - MAXGBoost Limitations

- Relatively low AUC for Fraud Detection
 - Rapid learning rate **decrease** with small loss improvements
 - **Limited exploration of feature space**
 - Over-emphasis on strongly discriminative features
 - Underweighting of subtle fraud patterns

Conclusion

- Decision Tree-based models effective in classifying positive class of fraud in **< 0.2% of data**
 - Increases the ability for law enforcement to correctly catch frauds
- MAXGBoost best model comparing accuracy and precision
 - MAXGBoost most effective in **preventing false accusations of fraud** and increasing customer satisfaction
- Exponential decay XGBoost most effective in **catching fraudulent cases**, compromising false accusations

Future Work

- **Hybrid Model Development**
 - Combine strengths of EGB and MAXGBoost
 - Create integrated momentum-decay approach
- Feature-specific momentum updates
- Class-aware momentum adjustments

Thanks!

Questions?

References

- Andrej Baranovskij. (2019, March 12). *Selecting Optimal Parameters for XGBoost Model Training*. Medium; Towards Data Science. <https://medium.com/towards-data-science/selecting-optimal-parameters-for-xgboost-model-training-c7cd9ed5e45e>
- Beja-Battais, P. (2023, October 6). *Overview of AdaBoost: Reconciling its views to better understand its dynamics*. ArXiv.org. <https://doi.org/10.48550/arXiv.2310.18323>
- Brownlee, J. (2016, September 15). *Tune Learning Rate for Gradient Boosting with XGBoost in Python*. Machine Learning Mastery. <https://machinelearningmastery.com/tune-learning-rate-for-gradient-boosting-with-xgboost-in-python/>
- Chen, T., & Guestrin, C. (2016). XGBoost: a Scalable Tree Boosting System. *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining - KDD '16*, 785–794. <https://doi.org/10.1145/2939672.2939785>
- Credit Card Fraud Detection. (n.d.). Kaggle. <https://www.kaggle.com/datasets/mlg-ulb/creditcardfraud/data>
- Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., & Liu, T.-Y. (2017). *LightGBM: A Highly Efficient Gradient Boosting Decision Tree*. Neural Information Processing Systems; Curran Associates, Inc. https://papers.nips.cc/paper_files/paper/2017/hash/6449f44a102fde848669bdd9eb6b76fa-Abstract.html
- Learning rate. (n.d.). Wikipedia. https://en.wikipedia.org/wiki/Learning_rate
- Mohan, A. (2021, April 6). *IEEE-CIS Fraud Detection - Top 5% Solution - Towards Data Science*. Medium; Towards Data Science. <https://medium.com/towards-data-science/ieee-cis-fraud-detection-top-5-solution-5488fc66e95f>
- Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Müller, A., Nothman, J., Louppe, G., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., & Duchesnay, É. (2018). Scikit-learn: Machine Learning in Python. *ArXiv:1201.0490 [Cs]*. <https://arxiv.org/abs/1201.0490>
- Vitaly Bushaev. (2017, December 4). *Stochastic Gradient Descent with momentum - Towards Data Science*. Medium; Towards Data Science. <https://medium.com/towards-data-science/stochastic-gradient-descent-with-momentum-a84097641a5d>
- Wang, C., Wang, Z., Ouyang, Y., & Soleimani, B. H. (2024, May 27). *Adaptive Learning Rates for Gradient Boosting Machines*. Proceedings of the Canadian Conference on Artificial Intelligence. <https://caiac.pubpub.org/pub/py65wd3c/release/1>