```
No.     Time            Source            Destination        Protocol Length Info
   1735 49.609617       IntelCor_d1:b6:4f  Cisco-Li_f7:1d:51  802.11   54     Deauthentication, SN=1605, FN=0, Flags=........C
Frame 1735: 54 bytes on wire (432 bits), 54 bytes captured (432 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Deauthentication, Flags: ........C
    Type/Subtype: Deauthentication (0x000c)
    Frame Control Field: 0xc000
        .... ..00 = Version: 0
        .... 00.. = Type: Management frame (0)
        1100 .... = Subtype: 12
        Flags: 0x00
            .... ..00 = DS status: Not leaving DS or network is operating in AD-HOC mode (To DS: 0 From DS: 0) (0x0)
            .... .0.. = More Fragments: This is the last fragment
            .... 0... = Retry: Frame is not being retransmitted
            ...0 .... = PWR MGT: STA will stay up
            ..0. .... = More Data: No data buffered
            .0.. .... = Protected flag: Data is not protected
            0... .... = +HTC/Order flag: Not strictly ordered
    .000 0000 0010 1100 = Duration: 44 microseconds
    Receiver address: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    Destination address: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    Transmitter address: IntelCor_d1:b6:4f (00:13:02:d1:b6:4f)
    Source address: IntelCor_d1:b6:4f (00:13:02:d1:b6:4f)
    BSS Id: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    .... .... .... 0000 = Fragment number: 0
    0110 0100 0101 .... = Sequence number: 1605
    Frame check sequence: 0x3b4a8b9c [unverified]
    [FCS Status: Unverified]
IEEE 802.11 Wireless Management
    Fixed parameters (2 bytes)
        Reason code: Unspecified reason (0x0001)
```