```
No.     Time           Source              Destination         Protocol Length Info
   2162 63.169910      IntelCor_d1:b6:4f   Cisco-Li_f7:1d:51   802.11   89     Association Request, SN=1648, FN=0,
Flags=........C, SSID="30 Munroe St"
Frame 2162: 89 bytes on wire (712 bits), 89 bytes captured (712 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Association Request, Flags: ........C
    Type/Subtype: Association Request (0x0000)
    Frame Control Field: 0x0000
        .... ..00 = Version: 0
        .... 00.. = Type: Management frame (0)
        0000 .... = Subtype: 0
        Flags: 0x00
            .... ..00 = DS status: Not leaving DS or network is operating in AD-HOC mode (To DS: 0 From DS: 0) (0x0)
            .... .0.. = More Fragments: This is the last fragment
            .... 0... = Retry: Frame is not being retransmitted
            ...0 .... = PWR MGT: STA will stay up
            ..0. .... = More Data: No data buffered
            .0.. .... = Protected flag: Data is not protected
            0... .... = +HTC/Order flag: Not strictly ordered
        .000 0000 0010 1100 = Duration: 44 microseconds
    Receiver address: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    Destination address: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    Transmitter address: IntelCor_d1:b6:4f (00:13:02:d1:b6:4f)
    Source address: IntelCor_d1:b6:4f (00:13:02:d1:b6:4f)
    BSS Id: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    .... .... .... 0000 = Fragment number: 0
    0110 0111 0000 .... = Sequence number: 1648
    Frame check sequence: 0xfe3badc6 [unverified]
    [FCS Status: Unverified]
IEEE 802.11 Wireless Management
    Fixed parameters (4 bytes)
        Capabilities Information: 0xce01
        Listen Interval: 0x000a
    Tagged parameters (33 bytes)
        Tag: SSID parameter set: "30 Munroe St"
        Tag: Supported Rates 1(B), 2(B), 5.5(B), 11(B), 6(B), 9, 12(B), 18, [Mbit/sec]
        Tag: QoS Capability
        Tag: Extended Supported Rates 24(B), 36, 48, 54, [Mbit/sec]
```