```
No.      Time           Source                Destination           Protocol Length Info
   2153 63.142451      Cisco-Li_f7:1d:51     IntelCor_d1:b6:4f      802.11   177    Probe Response, SN=3724, FN=0, Flags=........C,
BI=100, SSID="30 Munroe St"
Frame 2153: 177 bytes on wire (1416 bits), 177 bytes captured (1416 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 Probe Response, Flags: ........C
    Type/Subtype: Probe Response (0x0005)
    Frame Control Field: 0x5000
        .... ..00 = Version: 0
        .... 00.. = Type: Management frame (0)
        0101 .... = Subtype: 5
        Flags: 0x00
            .... ..00 = DS status: Not leaving DS or network is operating in AD-HOC mode (To DS: 0 From DS: 0) (0x0)
            .... .0.. = More Fragments: This is the last fragment
            .... 0... = Retry: Frame is not being retransmitted
            ...0 .... = PWR MGT: STA will stay up
            ..0. .... = More Data: No data buffered
            .0.. .... = Protected flag: Data is not protected
            0... .... = +HTC/Order flag: Not strictly ordered
    .000 0001 0011 1010 = Duration: 314 microseconds
    Receiver address: IntelCor_d1:b6:4f (00:13:02:d1:b6:4f)
    Destination address: IntelCor_d1:b6:4f (00:13:02:d1:b6:4f)
    Transmitter address: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    Source address: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    BSS Id: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    .... .... .... 0000 = Fragment number: 0
    1110 1000 1100 .... = Sequence number: 3724
    Frame check sequence: 0xcf29e2af [unverified]
    [FCS Status: Unverified]
IEEE 802.11 Wireless Management
    Fixed parameters (12 bytes)
        Timestamp: 174382164375
        Beacon Interval: 0.102400 [Seconds]
        Capabilities Information: 0x0601
    Tagged parameters (113 bytes)
        Tag: SSID parameter set: "30 Munroe St"
        Tag: Supported Rates 1(B), 2(B), 5.5(B), 11(B), [Mbit/sec]
        Tag: DS Parameter set: Current Channel: 6
        Tag: Country Information: Country Code US, Environment Indoor
        Tag: EDCA Parameter Set
        Tag: ERP Information
        Tag: Extended Supported Rates 6(B), 9, 12(B), 18, 24(B), 36, 48, 54, [Mbit/sec]
        Tag: Vendor Specific: Airgo Networks, Inc.
        Tag: Vendor Specific: Microsoft Corp.: WMM/WME: Parameter Element
```