```
No.      Time            Source              Destination         Protocol Length Info
   476 24.827751       128.119.245.12      192.168.1.109       TCP      110    80 → 2538 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0
SACK_PERM
Frame 476: 110 bytes on wire (880 bits), 110 bytes captured (880 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 QoS Data, Flags: ..mP..F.C
    Type/Subtype: QoS Data (0x0028)
    Frame Control Field: 0x8832
    Duration/ID: 11560 (reserved)
    Receiver address: 91:2a:b0:49:b6:4f (91:2a:b0:49:b6:4f)
    Transmitter address: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    Destination address: 91:2a:b0:49:b6:4f (91:2a:b0:49:b6:4f)
    Source address: Cisco-Li_f4:eb:a8 (00:16:b6:f4:eb:a8)
    BSS Id: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    STA address: 91:2a:b0:49:b6:4f (91:2a:b0:49:b6:4f)
    .... .... .... 0000 = Fragment number: 0
    1100 0011 0100 .... = Sequence number: 3124
    Frame check sequence: 0xecdc407d [unverified]
    [FCS Status: Unverified]
    Qos Control: 0x0100
Logical-Link Control
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.1.109
Transmission Control Protocol, Src Port: 80, Dst Port: 2538, Seq: 0, Ack: 1, Len: 0
```