```
No.     Time            Source              Destination         Protocol Length Info
    474 24.811093       192.168.1.109       128.119.245.12      TCP      110    2538 → 80 [SYN] Seq=0 Win=16384 Len=0 MSS=1460
SACK_PERM
Frame 474: 110 bytes on wire (880 bits), 110 bytes captured (880 bits)
Radiotap Header v0, Length 24
802.11 radio information
IEEE 802.11 QoS Data, Flags: .......TC
    Type/Subtype: QoS Data (0x0028)
    Frame Control Field: 0x8801
    .000 0000 0010 1100 = Duration: 44 microseconds
    Receiver address: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    Transmitter address: IntelCor_d1:b6:4f (00:13:02:d1:b6:4f)
    Destination address: Cisco-Li_f4:eb:a8 (00:16:b6:f4:eb:a8)
    Source address: IntelCor_d1:b6:4f (00:13:02:d1:b6:4f)
    BSS Id: Cisco-Li_f7:1d:51 (00:16:b6:f7:1d:51)
    STA address: IntelCor_d1:b6:4f (00:13:02:d1:b6:4f)
    .... .... .... 0000 = Fragment number: 0
    0000 0011 0001 .... = Sequence number: 49
    Frame check sequence: 0xad57fce0 [unverified]
    [FCS Status: Unverified]
    Qos Control: 0x0000
Logical-Link Control
Internet Protocol Version 4, Src: 192.168.1.109, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 2538, Dst Port: 80, Seq: 0, Len: 0
```