



REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	PR722	05-MAY-06	LEL

6. ALL AC VOLTAGES ARE +/- 10%.
5. THIS SCHEMATIC IS FOR PCB FABRICATION P/N CAX722PCP000005 AND PCB ASSEMBLY P/N CAX722PCAO000008.
4. ALL DC VOLTAGES ARE MEASURED WITH NO SIGNAL.
3. ALL POLARIZED CAPACITORS IN  $\mu$ F, 20% OR BETTER; 50V MINIMUM.
2. ALL UNPOLARIZED CAPACITORS IN  $\mu$ F, 10% OR BETTER; 50V MINIMUM.
1. ALL RESISTORS IN OHMS, 5%; 1/4W.
- NOTES: (UNLESS OTHERWISE NOTED)

THIS DOCUMENT CONTAINS INFORMATION OF A PROPRIETARY NATURE TO FENDER MUSICAL INSTRUMENTS AND IS SUBMITTED TO YOU IN CONFERENCE AND SHALL NOT BE DISCLOSED OR TRANSMITTED TO OTHERS WITHOUT AUTHORIZATION FROM FENDER MUSICAL INSTRUMENTS.		<b>Fender</b> MUSICAL INSTRUMENTS Corona, CA U.S.A.	
CHECKED BY: _____		TITLE: SERVICE DIAGRAM, COMBINED (schematic)	
DATE: _____		CHAMPION 600	
APPROVED BY: _____		AMPLIFIER	
DATE: _____		SIZE <b>D</b>	DRAWING NUMBER <b>722CAX003</b>
DRAWN: LORENZEN [ENGR: LORENZEN]		REV. <b>A</b>	
DATABASE FILE: CAX722PCB000005.PCB		RELEASE DATE: 05-MAY-06	SHEET: 1 OF 2

