


Module_1

Tuesday, April 28, 2026 8:58 PM

1. Start with the Big Picture (Hierarchy)







- **AI (Artificial Intelligence)** = Big umbrella
- **ML (Machine Learning)** = Subset of AI
- **DL (Deep Learning)** = Subset of ML
- **GenAI (Generative AI)** = Subset of DL (mostly)

2. Define Each in Simple Words

AI (Artificial Intelligence)

- Goal: Make machines *behave intelligently*
- Rule-based or learning-based

Examples:

- Chess engine
- Rule-based chatbots
- Spam filters


ML (Machine Learning)

- Machines **learn from data** instead of rules

Examples:

- Email spam detection
- Netflix recommendations
- Fraud detection

"Instead of coding rules, we give data and let the system learn patterns."



DL (Deep Learning)

- Uses **neural networks** (brain-like structures)
- Works well with images, audio, text

Examples:

- Face recognition
- Voice assistants
- Self-driving perception

"Deep learning is ML on steroids using neural networks."

GenAI (Generative AI)

- Creates **new content** (text, images, code, video)

Examples:

- ChatGPT (text generation)
- DALL·E (image generation)
- Code generation tools

"Not just predicting—but creating something new."

3. One Example to Rule Them All (Best Teaching Trick)

Use **YouTube Recommendation System**:

- **AI** → Entire intelligent system
- **ML** → Learns what you like
- **DL** → Understands video, thumbnails, voice
- **GenAI** → Generates video titles, thumbnails, scripts


4. Super Simple Table (Students LOVE this)


Type	Works How?	Key Idea	Output
AI	Rules + Logic	Intelligence	Decisions
ML	Learns from data	Patterns	Predictions
DL	Neural networks	Complex patterns	Recognition
GenAI	Generates data	Creativity	New content

5. Analogy (Very Powerful)

Human Brain Analogy

- **AI** = Entire brain
- **ML** = Learning ability
- **DL** = Deep thinking neurons
- **GenAI** = Creativity (writing, drawing)





1 Artificial Intelligence (AI)

Definition

Artificial Intelligence (AI) is the ability of a machine to **think, learn, and make decisions like a human**.

Example

- Google Maps suggesting routes
- Face unlock in phone

Machine is making a **decision**

2 Machine Learning (ML)

Definition

Machine Learning (ML) is a subset of AI where machines **learn from data instead of being explicitly programmed**.

Example


- Email spam detection
- YouTube recommendations

System learns from **past data**

3 Deep Learning (DL)

Definition

Deep Learning (DL) is a type of ML that uses **neural networks (brain-like structures)** to learn complex patterns.



3️⃣ Deep Learning (DL)


Definition

Deep Learning (DL) is a type of ML that uses **neural networks (brain-like structures)** to learn complex patterns.

Example

- Face recognition
- Self-driving cars

👉 Works like **human brain neurons**



4️⃣ Generative AI (GenAI)

Definition

Generative AI (GenAI) is a type of AI that can **create new content like text, images, music, or code**.


Example

- ChatGPT → text generation
- AI image generator → images


👉 It **creates**, not just predicts

👉 **GenAI = Create new content**

Aspect	Artificial Intelligence (AI)	Machine Learning (ML)	Deep Learning (DL)	Generative AI (GenAI)
Definition	Broad concept of making machines intelligent	Machines learn patterns from data	ML using multi-layer neural networks	AI that generates new content
Relationship	Parent category	Subset of AI	Subset of ML	Subset of DL
Learning Required	Not always	Yes	Yes	Yes
Data Type	Rules or data	Mostly structured data	Large unstructured data	Massive unstructured data
Human Rules	Often required	Reduced	Minimal	Minimal
Feature Engineering	Manual	Mostly manual	Automatic	Automatic
Model Complexity	Low to high	Medium	High	Very high
Compute Requirement	Low	Medium	High (GPUs)	Very high (GPUs/TPUs)
Output Type	Decisions / actions	Predictions / classifications	Predictions	New content
Examples	Rule-based chatbot, chess AI	Spam detection, fraud detection	Face recognition, speech-to-text	Chatbots, image generators
Accuracy Dependency	Rules quality	Data quality	Data + compute	Data + compute + prompt quality
Risk Factors	Logic errors	Data drift	Overfitting	Hallucinations, bias
Real-World Use	Automation	Prediction systems	Vision, speech	Content creation




Symbolic




```
if fever:
    print("Take medicine")
```


❌ Problems


- Cannot handle complex situations
- Needs too many rules
- Not flexible



Statistical

Statistical AI learns patterns from data instead of using fixed rules






Advantages

- More flexible than rules → data →
- Improves with more data

❌ Problems

- Needs a lot of data
- May not understand complex things deeply



Neural AI (Deep Learning)
Neural AI uses neural networks inspired by the human brain to learn complex patterns.

Example

- Face recognition
- Voice assistants
- Self-driving cars

👉 Learns like a **human brain**


Advantages

Example
- Face recognition
- Voice assistants
- Self-driving cars

Learns like a **human brain**

Advantages
- Very powerful
- High accuracy
- Handles complex data (images, voice)

Problems
- Needs high computing power
- Hard to understand (black box)




1️⃣ Foundation Model

Definition
A foundation model is a large AI model that can do many different tasks.

Simple Example
ChatGPT can:
- answer questions
- write code
- translate language

One model → many tasks



Simple Line
Foundation = One model, many uses

2️⃣ Multimodal Model

Definition
A multimodal model is an AI that can understand different types of inputs like text, images, or audio.

Simple Example
You upload an image + ask a question

AI explains the image

Example:
- Image + text → answer

Simple Line
Multimodal = Multiple inputs

3️⃣ Open-Source Model

Definition
An open-source model is an AI model that is free to use and can be modified by anyone.

Simple Example
You download a model and:
- run it on your laptop
- change it
- build your own app

Simple Line
Open-source = Free + customizable


🧠 2. Feature Engineering (Core Idea)

Imagine you want to predict **house prices**

You have raw data:
- Size = 1000 sq ft
- Bedrooms = 2
- Location = City

Question: Is this enough for good prediction?

Answer: Not always!



Simple Definition
Feature Engineering = converting raw data into better inputs for the model

In simple words:


"Making data smarter so the model learns better"

🏠 Example (Very Important)

❌ Raw Data
- Size = 1000
- Bedrooms = 2

✅ After Feature Engineering
- Price per sq ft = Price / Size
- Size per bedroom = Size / Bedrooms
- Location → Convert into numbers (encoding)

Now model understands patterns better



🧠 One-Line Explanation
Garbage in → Garbage out


Better features → Better model

⚠️ 3. Underfitting (Too Simple Model)

Definition
Model is too simple → cannot learn patterns

🎯 Example
Trying to fit a straight line for complex data

But real data is curved




🧠 Intuition
- Model is lazy 😴
- Doesn't understand data

📊 Signs
- Low accuracy on training data
- Low accuracy on test data

🎯 Real-life Example
Predicting marks using only:
- "Study hours"

Ignoring:
- Sleep
- Practice
- IQ



⚠️ 4. Overfitting (Too Complex Model)

Definition
Model learns too much (including noise)

🎯 Example
Very complex curve fitting every point

🧠 Intuition
- Model is over-smart 🤓
- Memorizes instead of learning

📊 Signs
- High accuracy on training data
- Low accuracy on test data




🎯 Real-life Example
Student memorizing answers instead of understanding concepts

🧘 5. Perfect Model (Balanced)

Goal
Not too simple, not too complex

Learns pattern but ignores noise



Student memorizing answers instead of understanding concepts


5. Perfect Model (Balanced)

Goal

Not too simple, not too complex

Learns pattern but ignores noise

Visual Comparison





What is ML Life Cycle?

It is the **end-to-end process of building, deploying, and maintaining an ML model**

1 Problem Definition

Understand **what you are solving**

Example:

- Predict house price
- Detect spam emails

Key Questions:

- What is input?
- What is output?
- Is it classification or regression?

2 Data Collection

Gather data from different sources

Sources:

- Databases
- APIs
- Sensors
- Web scraping

Example:

- House price → location, size, rooms

3 Data Preprocessing (Most Important 🔥)

Tasks:

- Handle missing values
- Remove duplicates
- Encoding (categorical → numeric)
- Feature scaling

4 Feature Engineering

Create better inputs for model

Example:

- Date → day, month, year
- Total price = quantity × price

Good features = Better model

5 Model Selection

Choose algorithm

Examples:

- Linear Regression
- Decision Tree
- Random Forest
- Neural Networks

6 Model Training

Train model using data

Concept:

- Model learns patterns from data

7 Model Evaluation

Check performance

Metrics:

- Accuracy
- Precision / Recall
- RMSE

Avoid:

- Overfitting
- Underfitting

8 Model Tuning

Improve performance

Techniques:

- Hyperparameter tuning
- Cross-validation

9 Deployment

Make model usable in real world

Examples:

- API
- Mobile app
- Website

10 Monitoring & Maintenance

Keep checking model performance

Why?

- Data changes over time (**data drift**)

Actions:

- Retrain model
- Update data

Simple Flow to Remember

Problem → Data → Clean → Features → Model → Train → Evaluate → Deploy → Monitor

Prompt Engineering — Core Concepts (Deep + Practical)

1. Prompt Tuning (Definition)

Definition:

Prompt Tuning is a technique where we optimize or design prompts (instead of retraining the model) to get better outputs from a pre-trained LLM.

Instead of changing model weights, we change **how we ask the question**.

Example:

Normal Prompt:

Explain machine learning

Tuned Prompt:

You are an AI professor. Explain machine learning to a beginner using simple language and 2 real-world examples in under 100 words.

Why Prompt Tuning is Important

- No need to retrain large models (cost-saving)
- Faster experimentation
- Works across multiple tasks
- Improves accuracy and relevance
- Essential for building:
  - Chatbots
  - AI assistants
  - Automation systems

2. Prompting Types (with Examples)

Zero-Shot Prompting

Definition:

No examples are provided. Model relies on prior knowledge.

Example:

Classify the sentiment: "This product is amazing"

Output: Positive

Few-Shot Prompting

Definition:

Provide examples to guide the model.

Example:

Text: I love this → Positive

Text: I hate this → Negative

Text: This is okay →

Output: Neutral

Role-Based Prompting

Definition:

Assign a role/persona to guide tone and expertise.

Example:

Act as a senior data scientist and explain overfitting with a real-world example.

3. Instruction / Constraint-Based Prompt

Definition:

Clearly specify **what to do + limitations**

Example:

Explain logistic regression

- Use simple English
- Limit to 5 bullet points
- Include one real-world example

Why it works:

- Reduces ambiguity
- Controls output format
- Improves consistency

4. Chain-of-Thought Prompt (Reasoning)

Definition:

Encourages the model to **think step-by-step before answering**

Example:

Solve: A car travels 60 km in 1 hour. How far in 3 hours?

Explain step-by-step.

Output:

- Speed = 60 km/h
- Time = 3 hours
- Distance = Speed × Time = 180 km

Benefit:

- Better reasoning
- Fewer mistakes
- Reduced hallucination

5. Temperature (Creativity & Randomness Control)

Definition:

Temperature controls randomness in output generation

Intuition (MOST IMPORTANT)

Think of temperature like:

- Low → Safe, predictable answers
- High → Creative, random answers

Example:

Prompt:

Write a tagline for a coffee brand

Temperature = 0.2

"Fresh coffee for your daily energy"

Temperature = 0.9

"Awaken your soul with every magical sip of roasted dreams"

Temperature Ranges

Range	Behavior
0.0–0.3	Deterministic (same output)
0.4–0.7	Balanced
0.8–1.2	Creative
1.2+	Very random (can be messy)

7. Top-k Sampling

Definition:

Top-k selects from **top K most probable tokens**

Intuition:

Only choose from **fixed number of best options**

Example:

If Top-k = 3

Model chooses from:

- blue
- gray
- dark

Benefit:

- Limits randomness
- Ensures quality

Top-p (Nucleus Sampling)

Benefit:

- Limits randomness
- Ensures quality

Top-p (Nucleus Sampling)

Top-p means the model chooses words only from the most likely group of options whose total probability adds up to "p".

👉 Instead of looking at *all possible words*, it focuses on the **most relevant ones**.

Intuition (Very Important)

Think of it like this:

You ask:

"The sky is ___"

The model thinks:

- blue → 50%
- clear → 20%
- cloudy → 15%
- dark → 10%
- green → 5%

Case 1: Top-p = 0.9

Model will pick words until total probability ≥ 0.9:

- blue (50%)
- clear (20%) → total = 70%
- cloudy (15%) → total = 85%
- dark (10%) → total = 95% ☑ stop

👉 So choices are:

blue, clear, cloudy, dark

🚫 "green" is ignored (too unlikely)

Case 2: Top-p = 0.6

- blue (50%)
- clear (10%) → total = 10% ☑ stop

👉 Choices:

blue, clear only

➡ Less variety, more safe

Case 3: Top-p = 1.0

👉 All words allowed (even bad ones)

➡ More randomness

Key Idea

👉 Top-p controls:

"How many *likely* words should the model consider?"

Real Example

Prompt:

Write a slogan for a gym

Top-p = 0.5

👉 "Stay fit. Stay strong."

(Safe, common)

Top-p = 0.9

👉 "Push your limits. Build your power."

(Balanced + creative)

Top-p = 1.0

👉 "Unleash the beast within your unstoppable fitness journey!"

(Very creative, slightly unpredictable)

9. Best-Practice Prompt Formula (Golden Rule)

Formula:

[Role] + [Task] + [Context] + [Instructions] + [Constraints] + [Output Format]

Example:

You are a Python expert.
Write code for linear regression using scikit-learn.
Use a housing dataset.
Include training and prediction steps.
Limit explanation to 5 lines.
Output in code + explanation format.

Why this works:

- Clear role → sets expertise
- Context → improves relevance
- Constraints → avoids noise
- Format → structured output

What is Hallucination (in LLMs)?

Hallucination = when an AI gives incorrect or made-up answers that sound confident.

👉 Even if the answer looks real, it may be **wrong or fabricated**.

Simple Example (your use case)

User says:

"I ate 1 plate biryani"

AI might reply:

"Calories: 450 kcal"

⚠ Problem:

- Real biryani can be **600–1200 kcal**
- AI is just **guessing**

👉 That's hallucination.

Why Hallucination Happens

- LLMs don't "know facts" — they **predict text**
- No real measurement (no weighing food)
- Ambiguous input ("1 plate" means different things)
- No database grounding

Types of Hallucination

1. ❌ Factual hallucination

Wrong facts

→ "Banana has 50g protein" (wrong)

2. ❓ Assumption hallucination

Fills missing info

→ Assumes portion size

3. 📦 Fabricated details

Adds fake precision

→ "Contains 12.3 mg Vitamin B12"

Why This Matters for YOU

In your app:

- Wrong calories = wrong diet advice
- Users may lose trust quickly

How to Reduce Hallucination (Practical)

1. 🔍 Ask for Clarification (BEST SIMPLE FIX)

Instead of guessing:

👉 Ask:

"How many pieces / grams?"

2. 📋 Use Structured Prompts

Force AI to be careful:

If unsure, say "approximate"
Do not assume portion size
Ask for clarification if needed.

3. 🗄 Use a Database (Better Approach)

Combine:

- LLM + nutrition database

Example:

- "Idli" → lookup calories from DB
- LLM only formats response

👉 This reduces guessing

3. Use a Database (Better Approach)

Combine:

- LLM + nutrition database

Example:

- "idli" → lookup calories from DB
- LLM only formats response

👉 This reduces guessing

4. Give Ranges Instead of Exact Numbers

Instead of:

450 kcal ❌

Say:

600–800 kcal ☑

5. Add Safety Instruction

Tell AI:

If confidence < 70%, ask user instead of answering.

6. Validate Output

- Check if values are realistic
- Example:
  - Protein > 100g for idli → reject
- Fact-check with APIs or databases

What is a *token* (quick recap)

- A token ≠ word
- It's a **piece of text** (word, subword, punctuation)

Example:

"I ate 2 dosas"

→ ~5–7 tokens

Token usage in RAG

In RAG, tokens are used in **3 places**:

1. User input

2. Retrieved context (from vector DB)

3. LLM output

👉 All together must fit inside the **model's token limit**

Token limit (very important)

Each model has a **maximum context window**

For example (approx):

- GPT-4 / GPT-4o → ~128K tokens
- Smaller models → 8K / 16K / 32K

👉 This limit includes:

input tokens + output tokens ≤ max limit

RAG problem: Token overflow

In RAG, you add:

- Multiple chunks from DB

If you retrieve too much:

User input (100 tokens)

+ Context (10,000 tokens ❌)

+ Output (500 tokens)

= ❌ exceeds limit

How RAG handles token limits

1. Chunking (VERY IMPORTANT)

Break documents into small pieces:

- 200–500 tokens per chunk

👉 This prevents overload

2. Top-K retrieval

Only send **best matches**, not everything

Example:

- Top 3 chunks instead of 20

3. Context trimming

If too long:

- Remove less relevant chunks
- Or summarize

4. Max output tokens

Limit response size:

max_tokens = 300

Rule of thumb

👉 Keep total input under **70–80% of model limit**

So:

- 128K model → use ~90K max
- Leave space for output

Practical design tips

For your app:

Ideal setup

- Chunk size: **300 tokens**
- Top-K: **3–5 chunks**
- Max output: **200–500 tokens**

Common mistake

❌ Sending entire PDF / dataset to LLM

👉 This breaks token limit + costs more

What is a *Context Window*?

👉 **Context window = the maximum number of tokens an LLM can "see" at once**

It includes everything:

- User input
- System prompt
- RAG retrieved context
- Conversation history
- Model output

Simple definition

👉 **Context window = input tokens + output tokens limit**

Example

If a model has **8,000 token context window**:

User input → 500 tokens

RAG context → 2,000 tokens

Chat history → 1,000 tokens

Total input → 3,500 tokens

Remaining for output → 4,500 tokens

☑ This works because total ≤ 8,000

If you exceed it

👉 The model will:

- ❌ Reject request (error)

OR

- ❌ Truncate (lose important info)

Why it matters in RAG (VERY IMPORTANT)

In RAG, you are adding extra data:

- Retrieved chunks
- History

👉 This eats up the context window quickly

Real model examples (approx)

- Small models → 4K–8K tokens
- Medium → 16K–32K
- Advanced models → 100K+ tokens

Relation to tokens

👉 Think like this:

- **Token = unit**
- **Context window = total capacity**

Like:

- Token = 1 rupee 🪙
- Context window = your wallet capacity

Context Management (in LLM Systems)

What it means

Context management = controlling what information the model sees while generating a response

In LLMs, the model doesn't "remember" everything—it only uses the **current context window** (prompt + history + retrieved data).

Where context comes from

A typical input to an LLM looks like:

[System Instructions]

+ [User Query]

+ [Chat History]

+ [Retrieved Documents (RAG)]

= Final Prompt (Context)

Why context management is critical

1. Token limit

- Models have fixed limits (e.g., 8K, 32K, 128K tokens)
- You **cannot send everything**

2. Relevance

- Irrelevant context → bad answers
- Too much context → confusion

3. Cost & latency

- More tokens = more cost + slower response

Ethics in AI

What is Ethics?

Rules that ensure AI is used **fairly, safely, and responsibly**.

Key Ethical Issues

1. Bias

- AI can be unfair
- Example: Hiring system rejecting certain groups

👉 Why?

Rules that ensure AI is used **fairly, safely, and responsibly.**

Key Ethical Issues

1. Bias
- AI can be unfair
- Example: Hiring system rejecting certain groups

Why?
Because training data is biased

2. Privacy
- AI uses personal data

Example:
- Face recognition
- Health data

3. Transparency
- AI decisions are not always explainable

Example:
- "Why was my loan rejected?"

4. Accountability
- Who is responsible if AI fails?

Example:
- Self-driving car accident

Privacy in AI

Problem
AI needs **a lot of data**, often personal.

Real Example:
- Apps tracking your:
  - Location
  - Search history
  - Voice

Solutions
- Data anonymization
- Encryption
- Federated Learning (data stays on device)

Bias in AI (Very Important)

What is Bias?
When AI favors or discriminates against certain groups.

Example:
- Face recognition works poorly on darker skin tones
- Resume screening favors men over women

Types of Bias:
- Data bias
- Algorithm bias
- Human bias

Bias Mitigation (How to Fix It)

1. Better Data
- Use diverse datasets

2. Fairness Techniques
- Re-weighting data
- Removing sensitive features

3. Model Evaluation
- Check performance across groups

4. Human Oversight
- Keep humans in decision loop

Simple Analogy (Good for Teaching)

AI is like a **student**
- If you teach wrong → student learns wrong
- If data is biased → AI becomes biased

Discussion Questions (for your class)

1. Should AI replace doctors?
2. Is face recognition safe?
3. Who is responsible for AI mistakes?
4. Can AI ever be 100% fair?

Quick Summary (1-minute recap)
- AI is used everywhere (healthcare, transport, shopping)
- Major concerns:
  - Ethics → right vs wrong
  - Privacy → data safety
  - Bias → fairness
- Solution:
  - Better data
  - Transparent models
  - Human control

Responsible AI — Core Concepts (practical, system-focused)

What it means
Responsible AI = designing, training, and deploying AI systems that are **fair, safe, transparent, and accountable**—not just accurate.


The Pillars

1. Fairness (Bias & Equity)


2. Transparency & Explainability

3. Privacy & Data Protection

4. Safety & Robustness



5. Accountability & Governance



API vs Local LLM — Practical Comparison

Action	Output	Action
Maximum Oversight	Monitored Autonomy	Human Authority

API vs Local LLM — Practical Comparison

Big Picture

API LLM = model runs on a provider's servers
Local LLM = model runs on your own machine / infrastructure

Core Difference

Aspect	API LLM	Local LLM
Where it runs	Cloud (provider)	Your system (PC/server)
Setup	No setup	Heavy setup
Control	Limited	Full control
Cost model	Pay per usage	One-time + infra cost

Deep Comparison

1. Performance & Quality

- **API LLM**
  - Access to latest, largest models
  - Best accuracy & reasoning
- **Local LLM**
  - Smaller models (unless you have GPUs)
  - Performance depends on hardware

Reality:
API models are usually **much stronger**

2. Latency

- **API**
  - Network delay
  - Depends on server load
- **Local**
  - No network
  - Faster for small models

Trade-off:
- Fast locally vs powerful in cloud

3. Cost

- **API**
  - Pay per token/request
  - Can scale expensive
- **Local**
  - No per-call cost
  - But:
    - GPU cost
    - Electricity
    - Maintenance

Rule:
- Small usage → API
- Heavy usage → Local (sometimes)

4. Privacy & Security

- **API**
  - Data sent to external servers
  - Depends on provider policies
- **Local**
  - Data stays with you
  - Full privacy control

Critical for:
- Healthcare
- Finance
- Enterprise data

5. Customization

- **API**
  - Limited control
  - Mostly prompting + fine-tuning (if allowed)
- **Local**
  - Full control:
    - Fine-tune
    - Modify architecture
    - Custom pipelines

6. Scalability

- **API**
  - Instantly scalable
  - No infra management
- **Local**
  - You must scale:
    - Servers
    - GPUs
    - Load balancing

7. Maintenance

- **API**
  - Provider handles everything
- **Local**
  - You manage:
    - Updates
    - Bugs
    - Performance

When to Use What

Use API when:

- You want **best performance quickly**
- Building MVP / startup
- No infra team
- Need latest models

Use Local when:

- You need **data privacy**
- Offline usage required
- High-volume usage (cost control)
- Custom research / fine-tuning

Hybrid Approach (Most Common Today)

Best systems use **both**

Example:
- API → general reasoning
- Local → sensitive data processing
- RAG → connect both

Real Example (Your WhatsApp AI Agent)

- API LLM → conversation + reasoning
- Local model → classify sensitive messages
- Vector DB → store user context

This balances:
- Cost
- Privacy
- Performance

Key Insight

This is not a "which is better" question—it's a **trade-off between control vs convenience**

🚀 MLOps (Machine Learning Operations)

🔹 What it is

MLOps is the practice of **managing the end-to-end lifecycle of machine learning models**—from development to deployment and monitoring.

👉 It combines:

- Machine Learning
- DevOps
- Data Engineering

🔹 Why it exists

Building a model is easy.
Keeping it **working in production** is hard.
Problems it solves:

- Models breaking after deployment
- Data changing over time (data drift)
- No version control
- Difficult collaboration

🔹 MLOps Lifecycle

1. Data Collection & Preparation

- Gather data
- Clean and preprocess
- Feature engineering

2. Model Training

- Train multiple models
- Hyperparameter tuning
- Select best model

3. Model Evaluation

- Metrics (accuracy, RMSE, etc.)
- Validation

4. Deployment

- API (Flask/FastAPI)
- Batch jobs
- Real-time inference

5. Monitoring

- Data drift
- Model performance
- Logging

6. Retraining

- Update model with new data

🔹 Key Tools in MLOps

- Versioning → Git, DVC
- Experiment tracking → MLflow
- Deployment → Docker, Kubernetes
- Pipelines → Airflow

🔹 Simple Flow

👉 Data → Model → API → Monitoring → Retrain

🤖 LLMOps (Large Language Model Operations)

🔹 What it is

LLMOps focuses on **deploying, managing, and improving Large Language Models (LLMs)**like GPT-based systems.

👉 It is a specialized extension of MLOps for:

- Generative AI
- Prompt-based systems

🔹 Why LLMOps is different

Traditional ML:

- Train model → deploy

LLMs:

- Use **pretrained models**
- Control behavior using:
  - Prompts
  - Retrieval (RAG)
  - Fine-tuning

◇ LLMOps Lifecycle

1. Model Selection

- Choose base model (OpenAI, open-source, etc.)

2. Prompt Engineering

- Design prompts
- Improve responses

3. Retrieval (RAG)

- Connect to external data
- Example: PDF, database

4. Evaluation

- Response quality
- Hallucination checks

5. Deployment

- Chatbots
- APIs
- Assistants

6. Monitoring

- Output quality
- Latency
- Cost

7. Iteration

- Improve prompts
- Add tools
- Fine-tune if needed

◇ Key Tools in LLMOps

- Frameworks → LangChain, LlamaIndex
- Vector DB → Pinecone, FAISS
- Monitoring → LangSmith
- APIs → OpenAI

💧 Key Difference (Core Idea)

MLOps	LLMOps
Train models	Use pretrained models
Focus on data + features	Focus on prompts + context
Metrics driven	Quality + human feedback
Static predictions	Dynamic text generation

🧠 CPU vs GPU — Fundamentals

◇ Big Picture

CPU = optimized for **sequential, general-purpose tasks**
GPU = optimized for **massively parallel computations**

🏵 Core Difference

Feature	CPU	GPU
Cores	Few (4–32)	Thousands
Focus	Flexibility	Parallelism
Task type	Sequential logic	Repetitive math
Speed	Fast per core	Fast overall (parallel)

🔍 How they work

◇ CPU (Central Processing Unit)

- Designed for:
  - Complex logic
  - Branching (if/else)
  - OS, applications

👉 Example:

- Running a program step-by-step
  Think: **"one smart worker solving tasks carefully"**

◇ GPU (Graphics Processing Unit)

- Designed for:
  - Same operation on many data points
- Executes thousands of operations **simultaneously**

👉 Example:

- Matrix multiplication in neural networks
  Think: **"thousands of workers doing the same task together"**

🧮 Why GPU is powerful for AI

Deep learning = lots of matrix operations

Example:

C = A \times B

- CPU: computes row by row
- GPU: computes many elements **in parallel**

👉 Result:

- Training time drops from **days → hours**

💧 Real Example

Task: Multiply 1 million numbers

- CPU:
  - Processes sequentially
- GPU:
  - Splits across thousands of cores

👉 GPU wins massively

⚡ Key Differences (Intuition)

CPU	GPU
Brain	Muscle
Flexible	Specialized
Low parallelism	High parallelism
Good for control	Good for computation

🎯 In AI / ML Context

- **CPU**
  - Data preprocessing
  - Control flow
  - Light inference
- **GPU**
  - Model training
  - Deep learning
  - Large matrix ops

🚀 When to use what

☑ CPU

- Small models
- Logic-heavy tasks
- Backend systems

☑ GPU

- Deep learning
- Large datasets
- Training models

💡 Key Insight

AI became practical because GPUs made **large-scale parallel computation possible**