

The screenshot shows the VS Code editor interface for a project named 'project3'. The file explorer on the left shows the project structure with folders like 'frontend', 'node_modules', 'public', 'src', 'assets', 'components', and files like 'LoginStatus.jsx', 'App.css', 'App.jsx', 'index.css', 'main.jsx', '.gitignore', 'eslint.config.js', 'index.html', 'package-lock.json', 'package.json', 'README.md', and 'vite.config.js'. The main editor area displays the 'App.jsx' file with the following code:


```
1 import React from "react";
2 import LoginStatus from "../components/LoginStatus";
3
4 function App() {
5   return (
6     <div>
7       <h1>React Login Status Display</h1>
8       <LoginStatus />
9     </div>
10  );
11 }
12
13 export default App;
```

The status bar at the bottom indicates the current line and column (Ln 14, Col 1), the number of spaces (2), the encoding (UTF-8), the line ending (LF), the language (JavaScript/JSX), and the active extensions (Go Live, Prettier).

The screenshot shows the VS Code editor interface for the same project 'project3', but now displaying the 'LoginStatus.jsx' file. The file explorer on the left shows the project structure with the 'LoginStatus.jsx' file selected. The main editor area displays the 'LoginStatus.jsx' file with the following code:

```
1 import React, { useState } from "react";
2
3 function LoginStatus() {
4   // Step 1: create a boolean state variable
5   const [isLoggedIn, setIsLoggedIn] = useState(false);
6
7   // Step 2: function to toggle login status
8   const toggleLogin = () => {
9     setIsLoggedIn(!isLoggedIn); // flip true <-> false
10  };
11
12  return (
13    <div style={{ padding: "20px" }}>
14      <h2>Login Status Example</h2>
15
16      /* Step 3: short-circuit rendering */
17      {isLoggedIn && <p style={{ color: "green" }}>You are logged in <input checked="" type="checkbox"/></p>}
18
19      /* Step 4: button to toggle login state */
20      <button
21        onClick={toggleLogin}
22        style={{ padding: "8px 16px", cursor: "pointer", marginTop: "10px" }}
23      >
24        {isLoggedIn ? "Logout" : "Login"}
25      </button>
26    </div>
27  );
28 }
29
30 export default LoginStatus;
```

The status bar at the bottom indicates the current line and column (Ln 31, Col 1), the number of spaces (4), the encoding (UTF-8), the line ending (CRLF), the language (JavaScript/JSX), and the active extensions (Go Live, Prettier).



React Login Status Display

Login Status Example

You are logged in 

Logout

