

# Logistic\_Regression\_and\_Naive\_Bayes\_Titanic\_Survival\_Prediction

March 19, 2025

```
[ ]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
```

```
[ ]: # Read the data using pandas dataframe
titanic_df = pd.read_csv('/content/titanic.csv')
```

```
[ ]: # Show the data head!
titanic_df.head()
```

```
[ ]: PassengerId  Survived  Pclass  \
0             1         0         3
1             2         1         1
2             3         1         3
3             4         1         1
4             5         0         3
```

```
                                Name    Sex  Age  SibSp  \
0                Braund, Mr. Owen Harris  male  22.0     1
1  Cumings, Mrs. John Bradley (Florence Briggs Th... female  38.0     1
2                Heikkinen, Miss. Laina  female  26.0     0
3  Futrelle, Mrs. Jacques Heath (Lily May Peel)  female  35.0     1
4                Allen, Mr. William Henry   male  35.0     0
```

```
    Parch    Ticket   Fare Cabin Embarked
0      0  A/5 21171   7.2500   NaN        S
1      0    PC 17599  71.2833   C85        C
2      0 STON/O2. 3101282   7.9250   NaN        S
3      0    113803  53.1000  C123        S
4      0    373450   8.0500   NaN        S
```

```
[ ]: # Let's count the number of survivors and non-survivors
survived_df = titanic_df[titanic_df['Survived'] == 1]
no_survived_df = titanic_df[titanic_df['Survived'] == 0]
```

```
[ ]: # Count the survived and deceased
print("Total =", len(titanic_df))



print("Number of passengers who survived =", len(survived_df))
print("Percentage Survived =", 1. * len(survived_df) / len(titanic_df) * 100.0,
      ↪ "%")

print("Number of passengers who did not Survive =", len(no_survived_df))
print("Percentage who did not survive =", 1. * len(no_survived_df) /
      ↪ len(titanic_df) * 100.0, "%")
```

```
Total = 891
Number of passengers who survived = 342
Percentage Survived = 38.38383838383838 %
Number of passengers who did not Survive = 549
Percentage who did not survive = 61.61616161616161 %
```



```
[ ]: # Bar Chart to indicate the number of people who survived based on their class
# If you are a first class, you have a higher chance of survival
plt.figure(figsize = [10, 10])
plt.subplot(211)
sns.countplot(x = 'Pclass', data = titanic_df)
plt.subplot(212)
sns.countplot(x = 'Pclass', hue = 'Survived', data = titanic_df)
```

```
[ ]: <Axes: xlabel='Pclass', ylabel='count'>
```




```
[ ]: # Bar Chart to indicate the number of people survived based on their siblings
      ↳status
      # If you have 1 siblings (SibSp = 1), you have a higher chance of survival
      ↳compared to being alone (SibSp = 0)
      plt.figure(figsize = [10, 10])
      plt.subplot(211)
      sns.countplot(x = 'SibSp', data = titanic_df)
      plt.subplot(212)
      sns.countplot(x = 'SibSp', hue = 'Survived', data = titanic_df)
```

```
[ ]: <Axes: xlabel='SibSp', ylabel='count'>
```




```
[ ]: # Bar Chart to indicate the number of people survived based on their Parch
      ↳ status (how many parents onboard)
# If you have 1, 2, or 3 family members (Parch = 1,2), you have a higher chance
↳ of survival compared to being alone (Parch = 0)
plt.figure(figsize = [15, 10])
plt.subplot(211)
sns.countplot(x = 'Parch', data = titanic_df)
plt.subplot(212)
sns.countplot(x = 'Parch', hue = 'Survived', data = titanic_df);
```




```
[ ]: # Bar Chart to indicate the number of people survived based on their sex
# If you are a female, you have a higher chance of survival compared to other
ports!
plt.figure(figsize = [15, 10])
plt.subplot(211)
sns.countplot(x = 'Sex', data = titanic_df)
plt.subplot(212)
sns.countplot(x = 'Sex', hue = 'Survived', data = titanic_df)
```

```
[ ]: <Axes: xlabel='Sex', ylabel='count'>
```




```
[ ]: # Age Histogram
plt.figure(figsize=[15, 10])
titanic_df['Age'].hist(bins = 40)
```

```
[ ]: <Axes: >
```



```
[ ]: # Fare Histogram
plt.figure(figsize=[10, 10])
titanic_df['Fare'].hist(bins = 40)
```


```
[ ]: <Axes: >
```



```
[ ]: # Let's explore which dataset is missing
sns.heatmap(titanic_df.isnull(), yticklabels = False, cbar = False,
            cmap="Blues")
```

```
[ ]: <Axes: >
```





```
[ ]: # Let's drop the cabin coloumn and test with inplace = true and false
titanic_df.drop('Cabin', axis = 1, inplace = True)
```

```
[ ]: # Let's drop the embarked, Ticket, passengerID, and Name as well
titanic_df.drop(['Name', 'Ticket', 'Embarked', 'PassengerId'], axis = 1,
↳inplace = True)
```

```
[ ]: titanic_df
```

```
[ ]:
Survived  Pclass  Sex  Age  SibSp  Parch  Fare
0         0      3  male  22.0    1     0   7.2500
1         1      1 female  38.0    1     0  71.2833
2         1      3 female  26.0    0     0   7.9250
3         1      1 female  35.0    1     0  53.1000
4         0      3  male  35.0    0     0   8.0500
..      ...    ...  ...  ...    ...    ...
886        0      2  male  27.0    0     0  13.0000
887        1      1 female  19.0    0     0  30.0000
```

```

888      0      3  female  NaN      1      2  23.4500
889      1      1   male  26.0      0      0  30.0000
890      0      3   male  32.0      0      0   7.7500

```


[891 rows x 7 columns]

```

[ ]: # Let's view the data one more time!
sns.heatmap(titanic_df.isnull(), yticklabels = False, cbar = False,
            cmap="Blues")

```

[ ]: <Axes: >




```

[ ]: # Let's get the average age for male (~29) and female (~25)
plt.figure(figsize=(15, 10))
plt.subplot(211)
sns.boxplot(x = 'Sex', y = 'Age', data = titanic_df)

```

[ ]: <Axes: xlabel='Sex', ylabel='Age'>



```
[ ]: def fill_age(data):
    """Fills missing age values based on sex, Male=29, Female=25.

    Args:
        data: A pandas Series containing 'Age' and 'Sex' columns.


    Returns:
        A pandas Series with filled age values.
    """
    age = data['Age']
    sex = data['Sex']

    # Use loc to fill NaN values based on sex
    data.loc[pd.isnull(age) & (sex == 'male'), 'Age'] = 29
    data.loc[pd.isnull(age) & (sex == 'female'), 'Age'] = 25

    return data
```

```
[ ]: # Let's view the data one more time!
sns.heatmap(titanic_df.isnull(), yticklabels = False, cbar = False,
            cmap="Blues")
```

```
[ ]: <Axes: >
```



```
[ ]: # You just need one column only to represent male or female
pd.get_dummies(titanic_df['Sex'])
```

```
[ ]:
   female  male
0    False   True
1     True  False
2     True  False
3     True  False
4    False   True
..      ...   ...
886  False   True
887   True  False
888   True  False
889  False   True
890  False   True

[891 rows x 2 columns]
```

```
[ ]: male = pd.get_dummies(titanic_df['Sex'], drop_first = True)
```

```
[ ]: # first let's drop the embarked and sex
titanic_df.drop(['Sex'], axis = 1, inplace = True)
```

```
[ ]: titanic_df
```

```
[ ]:      Survived  Pclass   Age  SibSp  Parch    Fare
0          0        3  22.0     1      0   7.2500
1          1        1  38.0     1      0  71.2833
2          1        3  26.0     0      0   7.9250
3          1        1  35.0     1      0  53.1000
4          0        3  35.0     0      0   8.0500
..      ...      ...      ...      ...      ...
886         0        2  27.0     0      0  13.0000
887         1        1  19.0     0      0  30.0000
888         0        3   NaN     1      2  23.4500
889         1        1  26.0     0      0  30.0000
890         0        3  32.0     0      0   7.7500
```

[891 rows x 6 columns]

```
[ ]: # Now let's add the encoded column male again
titanic_df = pd.concat([titanic_df, male], axis = 1)
```

```
[ ]: titanic_df
```

```
[ ]:      Survived  Pclass   Age  SibSp  Parch    Fare  male
0          0        3  22.0     1      0   7.2500   True
1          1        1  38.0     1      0  71.2833  False
2          1        3  26.0     0      0   7.9250  False
3          1        1  35.0     1      0  53.1000  False
4          0        3  35.0     0      0   8.0500   True
..      ...      ...      ...      ...      ...      ...
886         0        2  27.0     0      0  13.0000   True
887         1        1  19.0     0      0  30.0000  False
888         0        3   NaN     1      2  23.4500  False
889         1        1  26.0     0      0  30.0000   True
890         0        3  32.0     0      0   7.7500   True
```

[891 rows x 7 columns]

## Train Logistic Regression Classifier Model

```
[ ]: from sklearn.impute import SimpleImputer
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
# 1. Create an imputer object with a strategy (e.g., mean, median)
imputer = SimpleImputer(strategy='mean') # or strategy='median'
```

```
[ ]: #Let's drop the target coloumn before we do train test split
X = titanic_df.drop('Survived', axis = 1).values
```

```
y = titanic_df['Survived'].values
```

```
[ ]: from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
↳ random_state=10)
```

```
[ ]: # 3. Fit the imputer on the training data and transform both train and test sets
X_train = imputer.fit_transform(X_train) # Fit on training data and transform
X_test = imputer.transform(X_test)      # Transform the test data
```

```
[ ]: # 4. Now, fit your Logistic Regression model
classifier = LogisticRegression(random_state=0)
classifier.fit(X_train, y_train)
```

```
[ ]: LogisticRegression(random_state=0)
```

Assess Trained Model Performance


```
[ ]: #Assess Trained Model Performance
y_predict_test = classifier.predict(X_test)
y_predict_test
```

```
[ ]: array([0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 0, 1, 0, 0, 0,
          1, 0, 0, 0, 0, 1, 0, 1, 1, 0, 1, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 0,
          0, 1, 0, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1, 0, 0,
          0, 0, 0, 1, 0, 0, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 0, 1, 1, 0, 1, 1,
          0, 1, 0, 0, 1, 0, 1, 1, 1, 0, 1, 0, 0, 0, 0, 0, 1, 1, 0, 1, 1, 0,
          1, 0, 1, 0, 0, 0, 0, 1, 1, 0, 1, 0, 1, 1, 0, 1, 1, 0, 0, 0, 1, 0,
          0, 1, 1, 1, 0, 1, 1, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0,
          0, 1, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 1, 0, 1, 0, 0, 1, 0, 0,
          0, 0, 1])
```

```
[ ]: from sklearn.metrics import confusion_matrix

cm = confusion_matrix(y_test, y_predict_test)
sns.heatmap(cm, annot = True, fmt = "d")
```

```
[ ]: <Axes: >
```



```
[ ]: from sklearn.metrics import classification_report
print(classification_report(y_test, y_predict_test))
```

	precision	recall	f1-score	support
0	0.86	0.85	0.86	117
1	0.73	0.74	0.74	62
accuracy			0.82	179
macro avg	0.80	0.80	0.80	179
weighted avg	0.82	0.82	0.82	179

### Fitting Naive Bayes Classifier Model

```
[ ]: # Fitting Naive Bayes Classifier Model
from sklearn.naive_bayes import MultinomialNB
classifier = MultinomialNB()
classifier.fit(X_train, y_train)
```


```
[ ]: MultinomialNB()
```

```
[ ]: y_predict_test = classifier.predict(X_test)
y_predict_test

cm = confusion_matrix(y_test, y_predict_test)
sns.heatmap(cm, annot = True, fmt = "d")

print(classification_report(y_test, y_predict_test))
```

	precision	recall	f1-score	support
0	0.79	0.89	0.84	117
1	0.72	0.55	0.62	62
accuracy			0.77	179
macro avg	0.76	0.72	0.73	179
weighted avg	0.77	0.77	0.76	179



```
[1]: !sudo apt-get update
!sudo apt-get install texlive-xetex pandoc
```

```
Get:1 https://developer.download.nvidia.com/compute/cuda/repos/ubuntu2204/x86_64
InRelease [1,581 B]
```



```

Get:2 https://cloud.r-project.org/bin/linux/ubuntu jammy-cran40/ InRelease
[3,632 B]
Get:3 https://developer.download.nvidia.com/compute/cuda/repos/ubuntu2204/x86_64
Packages [1,378 kB]
Get:4 http://security.ubuntu.com/ubuntu jammy-security InRelease [129 kB]
Hit:5 http://archive.ubuntu.com/ubuntu jammy InRelease
Get:6 http://archive.ubuntu.com/ubuntu jammy-updates InRelease [128 kB]
Get:7 https://cloud.r-project.org/bin/linux/ubuntu jammy-cran40/ Packages [69.9
kB]
Get:8 https://r2u.stat.illinois.edu/ubuntu jammy InRelease [6,555 B]
Hit:9 https://ppa.launchpadcontent.net/deadsnakes/ppa/ubuntu jammy InRelease
Hit:10 https://ppa.launchpadcontent.net/graphics-drivers/ppa/ubuntu jammy
InRelease
Get:11 https://r2u.stat.illinois.edu/ubuntu jammy/main all Packages [8,754 kB]
Hit:12 https://ppa.launchpadcontent.net/ubuntugis/ppa/ubuntu jammy InRelease
Get:13 http://archive.ubuntu.com/ubuntu jammy-backports InRelease [127 kB]
Get:14 http://security.ubuntu.com/ubuntu jammy-security/main amd64 Packages
[2,692 kB]
Get:15 http://archive.ubuntu.com/ubuntu jammy-updates/universe amd64 Packages
[1,535 kB]
Get:16 http://security.ubuntu.com/ubuntu jammy-security/universe amd64 Packages
[1,236 kB]
Get:17 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 Packages [3,000
kB]
Get:18 https://r2u.stat.illinois.edu/ubuntu jammy/main amd64 Packages [2,675 kB]
Fetched 21.7 MB in 7s (3,005 kB/s)
Reading package lists... Done
W: Skipping acquire of configured file 'main/source/Sources' as repository
'https://r2u.stat.illinois.edu/ubuntu jammy InRelease' does not seem to provide
it (sources.list entry misspelt?)
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  dvisvgm fonts-droid-fallback fonts-lato fonts-lmodern fonts-noto-mono
  fonts-texgyre fonts-urw-base35 libapache-pom-java
  libcmark-gfm-extensions0.29.0.gfm.3 libcmark-gfm0.29.0.gfm.3
  libcommons-logging-java libcommons-parent-java libfontbox-java libfontenc1
  libgs9 libgs9-common libidn12 libijs-0.35 libjbig2dec0 libkpathsea6
  libpdfbox-java libptexenc1 libruby3.0 libsynchronet2 libteckit0 libtexlua53
  libtexluajit2 libwoff1 libzip-0-13 lmodern pandoc-data poppler-data
  preview-latex-style rake ruby ruby-net-telnet ruby-rubygems ruby-webrick
  ruby-xmlrpc ruby3.0 rubygems-integration tclutils teckit tex-common tex-gyre
  texlive-base texlive-binaries texlive-fonts-recommended texlive-latex-base
  texlive-latex-extra texlive-latex-recommended texlive-pictures
  texlive-plain-generic tipa xfonts-encodings xfonts-utils
Suggested packages:
  fonts-noto fonts-freefont-otf | fonts-freefont-ttf libavalon-framework-java

```

```

libcommons-logging-java-doc libexcalibur-logkit-java liblog4j1.2-java
texlive-luatex pandoc-citeproc context wkhtmltopdf librsvg2-bin groff ghc
nodejs php python libjs-mathjax libjs-katex citation-style-language-styles
poppler-utils ghostscript fonts-japanese-mincho | fonts-ipafont-mincho
fonts-japanese-gothic | fonts-ipafont-gothic fonts-arphic-ukai
fonts-arphic-uming fonts-nanum ri ruby-dev bundler debhelper gv
| postscript-viewer perl-tk xpdf | pdf-viewer xzdec
texlive-fonts-recommended-doc texlive-latex-base-doc python3-pygments
icc-profiles libfile-which-perl libspreadsheet-parseexcel-perl
texlive-latex-extra-doc texlive-latex-recommended-doc texlive-pstricks
dot2tex prerex texlive-pictures-doc vprerex default-jre-headless tipa-doc
The following NEW packages will be installed:
dvisvgm fonts-droid-fallback fonts-lato fonts-lmodern fonts-noto-mono
fonts-texgyre fonts-urw-base35 libapache-pom-java
libcmark-gfm-extensions0.29.0.gfm.3 libcmark-gfm0.29.0.gfm.3
libcommons-logging-java libcommons-parent-java libfontbox-java libfontenc1
libgs9 libgs9-common libidn12 libijs-0.35 libjbig2dec0 libkpathsea6
libpdfbox-java libptexenc1 libruby3.0 libsynchronet2 libteckit0 libtexlua53
libtexluajit2 libwoff1 libzip-0-13 lmodern pandoc pandoc-data poppler-data
preview-latex-style rake ruby ruby-net-telnet ruby-rubygems ruby-webrick
ruby-xmlrpc ruby3.0 rubygems-integration t1utils teckit tex-common tex-gyre
texlive-base texlive-binaries texlive-fonts-recommended texlive-latex-base
texlive-latex-extra texlive-latex-recommended texlive-pictures
texlive-plain-generic texlive-xetex tipa xfonts-encodings xfonts-utils
0 upgraded, 58 newly installed, 0 to remove and 35 not upgraded.
Need to get 202 MB of archives.
After this operation, 728 MB of additional disk space will be used.
Get:1 http://archive.ubuntu.com/ubuntu jammy/main amd64 fonts-droid-fallback all
1:6.0.1r16-1.1build1 [1,805 kB]
Get:2 http://archive.ubuntu.com/ubuntu jammy/main amd64 fonts-lato all 2.0-2.1
[2,696 kB]
Get:3 http://archive.ubuntu.com/ubuntu jammy/main amd64 poppler-data all
0.4.11-1 [2,171 kB]
Get:4 http://archive.ubuntu.com/ubuntu jammy/universe amd64 tex-common all 6.17
[33.7 kB]
Get:5 http://archive.ubuntu.com/ubuntu jammy/main amd64 fonts-urw-base35 all
20200910-1 [6,367 kB]
Get:6 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 libgs9-common
all 9.55.0~dfsg1-0ubuntu5.10 [752 kB]
Get:7 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 libidn12 amd64
1.38-4ubuntu1 [60.0 kB]
Get:8 http://archive.ubuntu.com/ubuntu jammy/main amd64 libijs-0.35 amd64
0.35-15build2 [16.5 kB]
Get:9 http://archive.ubuntu.com/ubuntu jammy/main amd64 libjbig2dec0 amd64
0.19-3build2 [64.7 kB]
Get:10 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 libgs9 amd64
9.55.0~dfsg1-0ubuntu5.10 [5,031 kB]
Get:11 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 libkpathsea6

```

amd64 2021.20210626.59705-1ubuntu0.2 [60.4 kB]  
Get:12 http://archive.ubuntu.com/ubuntu jammy/main amd64 libwoff1 amd64  
1.0.2-1build4 [45.2 kB]  
Get:13 http://archive.ubuntu.com/ubuntu jammy/universe amd64 dvisvgm amd64  
2.13.1-1 [1,221 kB]  
Get:14 http://archive.ubuntu.com/ubuntu jammy/universe amd64 fonts-lmodern all  
2.004.5-6.1 [4,532 kB]  
Get:15 http://archive.ubuntu.com/ubuntu jammy/main amd64 fonts-noto-mono all  
20201225-1build1 [397 kB]  
Get:16 http://archive.ubuntu.com/ubuntu jammy/universe amd64 fonts-texgyre all  
20180621-3.1 [10.2 MB]  
Get:17 http://archive.ubuntu.com/ubuntu jammy/universe amd64 libapache-pom-java  
all 18-1 [4,720 B]  
Get:18 http://archive.ubuntu.com/ubuntu jammy/universe amd64 libcmark-  
gfm0.29.0.gfm.3 amd64 0.29.0.gfm.3-3 [115 kB]  
Get:19 http://archive.ubuntu.com/ubuntu jammy/universe amd64 libcmark-gfm-  
extensions0.29.0.gfm.3 amd64 0.29.0.gfm.3-3 [25.1 kB]  
Get:20 http://archive.ubuntu.com/ubuntu jammy/universe amd64 libcommons-parent-  
java all 43-1 [10.8 kB]  
Get:21 http://archive.ubuntu.com/ubuntu jammy/universe amd64 libcommons-logging-  
java all 1.2-2 [60.3 kB]  
Get:22 http://archive.ubuntu.com/ubuntu jammy/main amd64 libfontenc1 amd64  
1:1.1.4-1build3 [14.7 kB]  
Get:23 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 libptexenc1  
amd64 2021.20210626.59705-1ubuntu0.2 [39.1 kB]  
Get:24 http://archive.ubuntu.com/ubuntu jammy/main amd64 rubygems-integration  
all 1.18 [5,336 B]  
Get:25 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 ruby3.0 amd64  
3.0.2-7ubuntu2.8 [50.1 kB]  
Get:26 http://archive.ubuntu.com/ubuntu jammy/main amd64 ruby-rubygems all  
3.3.5-2 [228 kB]  
Get:27 http://archive.ubuntu.com/ubuntu jammy/main amd64 ruby amd64 1:3.0~exp1  
[5,100 B]  
Get:28 http://archive.ubuntu.com/ubuntu jammy/main amd64 rake all 13.0.6-2 [61.7  
kB]  
Get:29 http://archive.ubuntu.com/ubuntu jammy/main amd64 ruby-net-telnet all  
0.1.1-2 [12.6 kB]  
Get:30 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 ruby-webrick  
all 1.7.0-3ubuntu0.1 [52.1 kB]  
Get:31 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 ruby-xmlrpc all  
0.3.2-1ubuntu0.1 [24.9 kB]  
Get:32 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 libruby3.0  
amd64 3.0.2-7ubuntu2.8 [5,113 kB]  
Get:33 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 libsynchronet2  
amd64 2021.20210626.59705-1ubuntu0.2 [55.6 kB]  
Get:34 http://archive.ubuntu.com/ubuntu jammy/universe amd64 libteckit0 amd64  
2.5.11+ds1-1 [421 kB]  
Get:35 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 libtexlua53

```

amd64 2021.20210626.59705-1ubuntu0.2 [120 kB]
Get:36 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 libtexluaajit2
amd64 2021.20210626.59705-1ubuntu0.2 [267 kB]
Get:37 http://archive.ubuntu.com/ubuntu jammy/universe amd64 libzzip-0-13 amd64
0.13.72+dfsg.1-1.1 [27.0 kB]
Get:38 http://archive.ubuntu.com/ubuntu jammy/main amd64 xfonts-encodings all
1:1.0.5-0ubuntu2 [578 kB]
Get:39 http://archive.ubuntu.com/ubuntu jammy/main amd64 xfonts-utils amd64
1:7.7+6build2 [94.6 kB]
Get:40 http://archive.ubuntu.com/ubuntu jammy/universe amd64 lmodern all
2.004.5-6.1 [9,471 kB]
Get:41 http://archive.ubuntu.com/ubuntu jammy/universe amd64 pandoc-data all
2.9.2.1-3ubuntu2 [81.8 kB]
Get:42 http://archive.ubuntu.com/ubuntu jammy/universe amd64 pandoc amd64
2.9.2.1-3ubuntu2 [20.3 MB]
Get:43 http://archive.ubuntu.com/ubuntu jammy/universe amd64 preview-latex-style
all 12.2-1ubuntu1 [185 kB]
Get:44 http://archive.ubuntu.com/ubuntu jammy/main amd64 t1utils amd64
1.41-4build2 [61.3 kB]
Get:45 http://archive.ubuntu.com/ubuntu jammy/universe amd64 teckit amd64
2.5.11+ds1-1 [699 kB]
Get:46 http://archive.ubuntu.com/ubuntu jammy/universe amd64 tex-gyre all
20180621-3.1 [6,209 kB]
Get:47 http://archive.ubuntu.com/ubuntu jammy-updates/universe amd64 texlive-
binaries amd64 2021.20210626.59705-1ubuntu0.2 [9,860 kB]
Get:48 http://archive.ubuntu.com/ubuntu jammy/universe amd64 texlive-base all
2021.20220204-1 [21.0 MB]
Get:49 http://archive.ubuntu.com/ubuntu jammy/universe amd64 texlive-fonts-
recommended all 2021.20220204-1 [4,972 kB]
Get:50 http://archive.ubuntu.com/ubuntu jammy/universe amd64 texlive-latex-base
all 2021.20220204-1 [1,128 kB]
Get:51 http://archive.ubuntu.com/ubuntu jammy/universe amd64 libfontbox-java all
1:1.8.16-2 [207 kB]
Get:52 http://archive.ubuntu.com/ubuntu jammy/universe amd64 libpdfbox-java all
1:1.8.16-2 [5,199 kB]
Get:53 http://archive.ubuntu.com/ubuntu jammy/universe amd64 texlive-latex-
recommended all 2021.20220204-1 [14.4 MB]
Get:54 http://archive.ubuntu.com/ubuntu jammy/universe amd64 texlive-pictures
all 2021.20220204-1 [8,720 kB]
Get:55 http://archive.ubuntu.com/ubuntu jammy/universe amd64 texlive-latex-extra
all 2021.20220204-1 [13.9 MB]
Get:56 http://archive.ubuntu.com/ubuntu jammy/universe amd64 texlive-plain-
generic all 2021.20220204-1 [27.5 MB]
Get:57 http://archive.ubuntu.com/ubuntu jammy/universe amd64 tipa all 2:1.3-21
[2,967 kB]
Get:58 http://archive.ubuntu.com/ubuntu jammy/universe amd64 texlive-xetex all
2021.20220204-1 [12.4 MB]
Fetched 202 MB in 15s (13.9 MB/s)

```

```

debconf: unable to initialize frontend: Dialog
debconf: (No usable dialog-like program is installed, so the dialog based
frontend cannot be used. at /usr/share/perl5/Debconf/FrontEnd/Dialog.pm line 78,
<> line 58.)
debconf: falling back to frontend: Readline
debconf: unable to initialize frontend: Readline
debconf: (This frontend requires a controlling tty.)
debconf: falling back to frontend: Teletype
dpkg-preconfigure: unable to re-open stdin:
Selecting previously unselected package fonts-droid-fallback.
(Reading database ... 125044 files and directories currently installed.)
Preparing to unpack .../00-fonts-droid-fallback_1%3a6.0.1r16-1.1build1_all.deb
...
Unpacking fonts-droid-fallback (1:6.0.1r16-1.1build1) ...
Selecting previously unselected package fonts-lato.
Preparing to unpack .../01-fonts-lato_2.0-2.1_all.deb ...
Unpacking fonts-lato (2.0-2.1) ...
Selecting previously unselected package poppler-data.
Preparing to unpack .../02-poppler-data_0.4.11-1_all.deb ...
Unpacking poppler-data (0.4.11-1) ...
Selecting previously unselected package tex-common.
Preparing to unpack .../03-tex-common_6.17_all.deb ...
Unpacking tex-common (6.17) ...
Selecting previously unselected package fonts-urw-base35.
Preparing to unpack .../04-fonts-urw-base35_20200910-1_all.deb ...
Unpacking fonts-urw-base35 (20200910-1) ...
Selecting previously unselected package libgs9-common.
Preparing to unpack .../05-libgs9-common_9.55.0~dfsg1-0ubuntu5.10_all.deb ...
Unpacking libgs9-common (9.55.0~dfsg1-0ubuntu5.10) ...
Selecting previously unselected package libidn12:amd64.
Preparing to unpack .../06-libidn12_1.38-4ubuntu1_amd64.deb ...
Unpacking libidn12:amd64 (1.38-4ubuntu1) ...
Selecting previously unselected package libijs-0.35:amd64.
Preparing to unpack .../07-libijs-0.35_0.35-15build2_amd64.deb ...
Unpacking libijs-0.35:amd64 (0.35-15build2) ...
Selecting previously unselected package libjbig2dec0:amd64.
Preparing to unpack .../08-libjbig2dec0_0.19-3build2_amd64.deb ...
Unpacking libjbig2dec0:amd64 (0.19-3build2) ...
Selecting previously unselected package libgs9:amd64.
Preparing to unpack .../09-libgs9_9.55.0~dfsg1-0ubuntu5.10_amd64.deb ...
Unpacking libgs9:amd64 (9.55.0~dfsg1-0ubuntu5.10) ...
Selecting previously unselected package libkpathsea6:amd64.
Preparing to unpack .../10-libkpathsea6_2021.20210626.59705-1ubuntu0.2_amd64.deb
...
Unpacking libkpathsea6:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Selecting previously unselected package libwoff1:amd64.
Preparing to unpack .../11-libwoff1_1.0.2-1build4_amd64.deb ...
Unpacking libwoff1:amd64 (1.0.2-1build4) ...

```

```

Selecting previously unselected package dvisvgm.
Preparing to unpack .../12-dvisvgm_2.13.1-1_amd64.deb ...
Unpacking dvisvgm (2.13.1-1) ...
Selecting previously unselected package fonts-lmodern.
Preparing to unpack .../13-fonts-lmodern_2.004.5-6.1_all.deb ...
Unpacking fonts-lmodern (2.004.5-6.1) ...
Selecting previously unselected package fonts-noto-mono.
Preparing to unpack .../14-fonts-noto-mono_20201225-1build1_all.deb ...
Unpacking fonts-noto-mono (20201225-1build1) ...
Selecting previously unselected package fonts-texgyre.
Preparing to unpack .../15-fonts-texgyre_20180621-3.1_all.deb ...
Unpacking fonts-texgyre (20180621-3.1) ...
Selecting previously unselected package libapache-pom-java.
Preparing to unpack .../16-libapache-pom-java_18-1_all.deb ...
Unpacking libapache-pom-java (18-1) ...
Selecting previously unselected package libcmark-gfm0.29.0.gfm.3:amd64.
Preparing to unpack .../17-libcmark-gfm0.29.0.gfm.3_0.29.0.gfm.3-3_amd64.deb ...
Unpacking libcmark-gfm0.29.0.gfm.3:amd64 (0.29.0.gfm.3-3) ...
Selecting previously unselected package libcmark-gfm-
extensions0.29.0.gfm.3:amd64.
Preparing to unpack .../18-libcmark-gfm-
extensions0.29.0.gfm.3_0.29.0.gfm.3-3_amd64.deb ...
Unpacking libcmark-gfm-extensions0.29.0.gfm.3:amd64 (0.29.0.gfm.3-3) ...
Selecting previously unselected package libcommons-parent-java.
Preparing to unpack .../19-libcommons-parent-java_43-1_all.deb ...
Unpacking libcommons-parent-java (43-1) ...
Selecting previously unselected package libcommons-logging-java.
Preparing to unpack .../20-libcommons-logging-java_1.2-2_all.deb ...
Unpacking libcommons-logging-java (1.2-2) ...
Selecting previously unselected package libfontenc1:amd64.
Preparing to unpack .../21-libfontenc1_1%3a1.1.4-1build3_amd64.deb ...
Unpacking libfontenc1:amd64 (1:1.1.4-1build3) ...
Selecting previously unselected package libptexenc1:amd64.
Preparing to unpack .../22-libptexenc1_2021.20210626.59705-1ubuntu0.2_amd64.deb
...
Unpacking libptexenc1:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Selecting previously unselected package rubygems-integration.
Preparing to unpack .../23-rubygems-integration_1.18_all.deb ...
Unpacking rubygems-integration (1.18) ...
Selecting previously unselected package ruby3.0.
Preparing to unpack .../24-ruby3.0_3.0.2-7ubuntu2.8_amd64.deb ...
Unpacking ruby3.0 (3.0.2-7ubuntu2.8) ...
Selecting previously unselected package ruby-rubygems.
Preparing to unpack .../25-ruby-rubygems_3.3.5-2_all.deb ...
Unpacking ruby-rubygems (3.3.5-2) ...
Selecting previously unselected package ruby.
Preparing to unpack .../26-ruby_1%3a3.0~exp1_amd64.deb ...
Unpacking ruby (1:3.0~exp1) ...

```

```

Selecting previously unselected package rake.
Preparing to unpack .../27-rake_13.0.6-2_all.deb ...
Unpacking rake (13.0.6-2) ...
Selecting previously unselected package ruby-net-telnet.
Preparing to unpack .../28-ruby-net-telnet_0.1.1-2_all.deb ...
Unpacking ruby-net-telnet (0.1.1-2) ...
Selecting previously unselected package ruby-webrick.
Preparing to unpack .../29-ruby-webrick_1.7.0-3ubuntu0.1_all.deb ...
Unpacking ruby-webrick (1.7.0-3ubuntu0.1) ...
Selecting previously unselected package ruby-xmlrpc.
Preparing to unpack .../30-ruby-xmlrpc_0.3.2-1ubuntu0.1_all.deb ...
Unpacking ruby-xmlrpc (0.3.2-1ubuntu0.1) ...
Selecting previously unselected package libruby3.0:amd64.
Preparing to unpack .../31-libruby3.0_3.0.2-7ubuntu2.8_amd64.deb ...
Unpacking libruby3.0:amd64 (3.0.2-7ubuntu2.8) ...
Selecting previously unselected package libsyntax2:amd64.
Preparing to unpack .../32-libsyntax2_2021.20210626.59705-1ubuntu0.2_amd64.deb
...
Unpacking libsyntax2:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Selecting previously unselected package libteckit0:amd64.
Preparing to unpack .../33-libteckit0_2.5.11+ds1-1_amd64.deb ...
Unpacking libteckit0:amd64 (2.5.11+ds1-1) ...
Selecting previously unselected package libtexlua53:amd64.
Preparing to unpack .../34-libtexlua53_2021.20210626.59705-1ubuntu0.2_amd64.deb
...
Unpacking libtexlua53:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Selecting previously unselected package libtexluaajit2:amd64.
Preparing to unpack
.../35-libtexluaajit2_2021.20210626.59705-1ubuntu0.2_amd64.deb ...
Unpacking libtexluaajit2:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Selecting previously unselected package libzip-0-13:amd64.
Preparing to unpack .../36-libzip-0-13_0.13.72+dfsg.1-1.1_amd64.deb ...
Unpacking libzip-0-13:amd64 (0.13.72+dfsg.1-1.1) ...
Selecting previously unselected package xfonts-encodings.
Preparing to unpack .../37-xfonts-encodings_1%3a1.0.5-0ubuntu2_all.deb ...
Unpacking xfonts-encodings (1:1.0.5-0ubuntu2) ...
Selecting previously unselected package xfonts-utils.
Preparing to unpack .../38-xfonts-utils_1%3a7.7+6build2_amd64.deb ...
Unpacking xfonts-utils (1:7.7+6build2) ...
Selecting previously unselected package lmodern.
Preparing to unpack .../39-lmodern_2.004.5-6.1_all.deb ...
Unpacking lmodern (2.004.5-6.1) ...
Selecting previously unselected package pandoc-data.
Preparing to unpack .../40-pandoc-data_2.9.2.1-3ubuntu2_all.deb ...
Unpacking pandoc-data (2.9.2.1-3ubuntu2) ...
Selecting previously unselected package pandoc.
Preparing to unpack .../41-pandoc_2.9.2.1-3ubuntu2_amd64.deb ...
Unpacking pandoc (2.9.2.1-3ubuntu2) ...

```

```

Selecting previously unselected package preview-latex-style.
Preparing to unpack .../42-preview-latex-style_12.2-1ubuntu1_all.deb ...
Unpacking preview-latex-style (12.2-1ubuntu1) ...
Selecting previously unselected package t1utils.
Preparing to unpack .../43-t1utils_1.41-4build2_amd64.deb ...
Unpacking t1utils (1.41-4build2) ...
Selecting previously unselected package teckit.
Preparing to unpack .../44-teckit_2.5.11+ds1-1_amd64.deb ...
Unpacking teckit (2.5.11+ds1-1) ...
Selecting previously unselected package tex-gyre.
Preparing to unpack .../45-tex-gyre_20180621-3.1_all.deb ...
Unpacking tex-gyre (20180621-3.1) ...
Selecting previously unselected package texlive-binaries.
Preparing to unpack .../46-texlive-
binaries_2021.20210626.59705-1ubuntu0.2_amd64.deb ...
Unpacking texlive-binaries (2021.20210626.59705-1ubuntu0.2) ...
Selecting previously unselected package texlive-base.
Preparing to unpack .../47-texlive-base_2021.20220204-1_all.deb ...
Unpacking texlive-base (2021.20220204-1) ...
Selecting previously unselected package texlive-fonts-recommended.
Preparing to unpack .../48-texlive-fonts-recommended_2021.20220204-1_all.deb ...
Unpacking texlive-fonts-recommended (2021.20220204-1) ...
Selecting previously unselected package texlive-latex-base.
Preparing to unpack .../49-texlive-latex-base_2021.20220204-1_all.deb ...
Unpacking texlive-latex-base (2021.20220204-1) ...
Selecting previously unselected package libfontbox-java.
Preparing to unpack .../50-libfontbox-java_1%3a1.8.16-2_all.deb ...
Unpacking libfontbox-java (1:1.8.16-2) ...
Selecting previously unselected package libpdfbox-java.
Preparing to unpack .../51-libpdfbox-java_1%3a1.8.16-2_all.deb ...
Unpacking libpdfbox-java (1:1.8.16-2) ...
Selecting previously unselected package texlive-latex-recommended.
Preparing to unpack .../52-texlive-latex-recommended_2021.20220204-1_all.deb ...
Unpacking texlive-latex-recommended (2021.20220204-1) ...
Selecting previously unselected package texlive-pictures.
Preparing to unpack .../53-texlive-pictures_2021.20220204-1_all.deb ...
Unpacking texlive-pictures (2021.20220204-1) ...
Selecting previously unselected package texlive-latex-extra.
Preparing to unpack .../54-texlive-latex-extra_2021.20220204-1_all.deb ...
Unpacking texlive-latex-extra (2021.20220204-1) ...
Selecting previously unselected package texlive-plain-generic.
Preparing to unpack .../55-texlive-plain-generic_2021.20220204-1_all.deb ...
Unpacking texlive-plain-generic (2021.20220204-1) ...
Selecting previously unselected package tipa.
Preparing to unpack .../56-tipa_2%3a1.3-21_all.deb ...
Unpacking tipa (2:1.3-21) ...
Selecting previously unselected package texlive-xetex.
Preparing to unpack .../57-texlive-xetex_2021.20220204-1_all.deb ...

```



```

Unpacking texlive-xetex (2021.20220204-1) ...
Setting up fonts-lato (2.0-2.1) ...
Setting up fonts-noto-mono (20201225-1build1) ...
Setting up libwoff1:amd64 (1.0.2-1build4) ...
Setting up libtexlua53:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Setting up libijs-0.35:amd64 (0.35-15build2) ...
Setting up libtexluajit2:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Setting up libfontbox-java (1:1.8.16-2) ...
Setting up rubygems-integration (1.18) ...
Setting up libzip-0-13:amd64 (0.13.72+dfsg.1-1.1) ...
Setting up fonts-urw-base35 (20200910-1) ...
Setting up poppler-data (0.4.11-1) ...
Setting up tex-common (6.17) ...
debconf: unable to initialize frontend: Dialog
debconf: (No usable dialog-like program is installed, so the dialog based
frontend cannot be used. at /usr/share/perl5/Debconf/FrontEnd/Dialog.pm line
78.)
debconf: falling back to frontend: Readline
update-language: texlive-base not installed and configured, doing nothing!
Setting up libfontenc1:amd64 (1:1.1.4-1build3) ...
Setting up libjbig2dec0:amd64 (0.19-3build2) ...
Setting up libteckit0:amd64 (2.5.11+ds1-1) ...
Setting up libapache-pom-java (18-1) ...
Setting up ruby-net-telnet (0.1.1-2) ...
Setting up xfonts-encodings (1:1.0.5-0ubuntu2) ...
Setting up t1utils (1.41-4build2) ...
Setting up libidn12:amd64 (1.38-4ubuntu1) ...
Setting up fonts-texgyre (20180621-3.1) ...
Setting up libkpathsea6:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Setting up ruby-webrick (1.7.0-3ubuntu0.1) ...
Setting up libcmark-gfm0.29.0.gfm.3:amd64 (0.29.0.gfm.3-3) ...
Setting up fonts-lmodern (2.004.5-6.1) ...
Setting up libcmark-gfm-extensions0.29.0.gfm.3:amd64 (0.29.0.gfm.3-3) ...
Setting up fonts-droid-fallback (1:6.0.1r16-1.1build1) ...
Setting up pandoc-data (2.9.2.1-3ubuntu2) ...
Setting up ruby-xmlrpc (0.3.2-1ubuntu0.1) ...
Setting up libsynchronet2:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Setting up libgs9-common (9.55.0~dfsg1-0ubuntu5.10) ...
Setting up teckit (2.5.11+ds1-1) ...
Setting up libpdfbox-java (1:1.8.16-2) ...
Setting up libgs9:amd64 (9.55.0~dfsg1-0ubuntu5.10) ...
Setting up preview-latex-style (12.2-1ubuntu1) ...
Setting up libcommons-parent-java (43-1) ...
Setting up dvisvgm (2.13.1-1) ...
Setting up libcommons-logging-java (1.2-2) ...
Setting up xfonts-utils (1:7.7+6build2) ...
Setting up libptexenc1:amd64 (2021.20210626.59705-1ubuntu0.2) ...
Setting up pandoc (2.9.2.1-3ubuntu2) ...

```

```

Setting up texlive-binaries (2021.20210626.59705-1ubuntu0.2) ...
update-alternatives: using /usr/bin/xdvi-xaw to provide /usr/bin/xdvi.bin
(xdvi.bin) in auto mode
update-alternatives: using /usr/bin/bibtex.original to provide /usr/bin/bibtex
(bibtex) in auto mode
Setting up lmodern (2.004.5-6.1) ...
Setting up texlive-base (2021.20220204-1) ...
/usr/bin/ucfr
/usr/bin/ucfr
/usr/bin/ucfr
/usr/bin/ucfr
mktexlsr: Updating /var/lib/texmf/ls-R-TEXLIVEDIST...
mktexlsr: Updating /var/lib/texmf/ls-R-TEXMFMAIN...
mktexlsr: Updating /var/lib/texmf/ls-R...
mktexlsr: Done.
tl-paper: setting paper size for dvips to a4:
/var/lib/texmf/dvips/config/config-paper.ps
tl-paper: setting paper size for dvipdfmx to a4:
/var/lib/texmf/dvipdfmx/dvipdfmx-paper.cfg
tl-paper: setting paper size for xdvi to a4: /var/lib/texmf/xdvi/XDvi-paper
tl-paper: setting paper size for pdftex to a4: /var/lib/texmf/tex/generic/tex-
ini-files/pdftexconfig.tex
debconf: unable to initialize frontend: Dialog
debconf: (No usable dialog-like program is installed, so the dialog based
frontend cannot be used. at /usr/share/perl5/Debconf/FrontEnd/Dialog.pm line
78.)
debconf: falling back to frontend: Readline
Setting up tex-gyre (20180621-3.1) ...
Setting up texlive-plain-generic (2021.20220204-1) ...
Setting up texlive-latex-base (2021.20220204-1) ...
Setting up texlive-latex-recommended (2021.20220204-1) ...
Setting up texlive-pictures (2021.20220204-1) ...
Setting up texlive-fonts-recommended (2021.20220204-1) ...
Setting up tipa (2:1.3-21) ...
Setting up texlive-latex-extra (2021.20220204-1) ...
Setting up texlive-xetex (2021.20220204-1) ...
Setting up rake (13.0.6-2) ...
Setting up libruby3.0:amd64 (3.0.2-7ubuntu2.8) ...
Setting up ruby3.0 (3.0.2-7ubuntu2.8) ...
Setting up ruby (1:3.0~exp1) ...
Setting up ruby-rubygems (3.3.5-2) ...
Processing triggers for man-db (2.10.2-1) ...
Processing triggers for mailcap (3.70+nmulubuntu1) ...
Processing triggers for fontconfig (2.13.1-4.2ubuntu5) ...
Processing triggers for libc-bin (2.35-0ubuntu3.8) ...
/sbin/ldconfig.real: /usr/local/lib/libtbb.so.12 is not a symbolic link

/sbin/ldconfig.real: /usr/local/lib/libtbbbind_2_5.so.3 is not a symbolic link

```

```

/sbin/ldconfig.real: /usr/local/lib/libtbbbind.so.3 is not a symbolic link

/sbin/ldconfig.real: /usr/local/lib/libur_adapter_opencl.so.0 is not a symbolic
link

/sbin/ldconfig.real: /usr/local/lib/libtbbbind_2_0.so.3 is not a symbolic link

/sbin/ldconfig.real: /usr/local/lib/libtbbmalloc.so.2 is not a symbolic link

/sbin/ldconfig.real: /usr/local/lib/libumf.so.0 is not a symbolic link

/sbin/ldconfig.real: /usr/local/lib/libur_loader.so.0 is not a symbolic link

/sbin/ldconfig.real: /usr/local/lib/libtcm.so.1 is not a symbolic link

/sbin/ldconfig.real: /usr/local/lib/libhwloc.so.15 is not a symbolic link

/sbin/ldconfig.real: /usr/local/lib/libtcm_debug.so.1 is not a symbolic link

/sbin/ldconfig.real: /usr/local/lib/libtbbmalloc_proxy.so.2 is not a symbolic
link

/sbin/ldconfig.real: /usr/local/lib/libur_adapter_level_zero.so.0 is not a
symbolic link

```

```

Processing triggers for tex-common (6.17) ...
debconf: unable to initialize frontend: Dialog
debconf: (No usable dialog-like program is installed, so the dialog based
frontend cannot be used. at /usr/share/perl5/Debconf/FrontEnd/Dialog.pm line
78.)
debconf: falling back to frontend: Readline
Running updmap-sys. This may take some time... done.
Running mktexlsr /var/lib/texmf ... done.
Building format(s) --all.
    This may take some time... done.

```

```

[2]: !jupyter nbconvert --to pdf "/content/drive/MyDrive/Colab_Notebooks/Projects/
↳Logistic_Regression_and_Naive_Bayes_Titanic_Survival_Prediction.ipynb"

```

```

[NbConvertApp] WARNING | pattern '/content/drive/MyDrive/Colab_Notebooks/Project
s/Logistic_Regression_and_Naive_Bayes_Titanic_Survival_Prediction.ipynb' matched
no files
This application is used to convert notebook files (*.ipynb)
    to various other formats.

```

```

WARNING: THE COMMANDLINE INTERFACE MAY CHANGE IN FUTURE RELEASES.

```

## Options

=====

The options below are convenience aliases to configurable class-options, as listed in the "Equivalent to" description-line of the aliases.

To see all configurable class-options for some <cmd>, use:

<cmd> --help-all

### --debug

set log level to logging.DEBUG (maximize logging output)

Equivalent to: [--Application.log\_level=10]

### --show-config

Show the application's configuration (human-readable format)

Equivalent to: [--Application.show\_config=True]

### --show-config-json

Show the application's configuration (json format)

Equivalent to: [--Application.show\_config\_json=True]

### --generate-config

generate default config file

Equivalent to: [--JupyterApp.generate\_config=True]

### -y

Answer yes to any questions instead of prompting.

Equivalent to: [--JupyterApp.answer\_yes=True]

### --execute

Execute the notebook prior to export.

Equivalent to: [--ExecutePreprocessor.enabled=True]

### --allow-errors

Continue notebook execution even if one of the cells throws an error and include the error message in the cell output (the default behaviour is to abort conversion). This flag is only relevant if '--execute' was specified, too.

Equivalent to: [--ExecutePreprocessor.allow\_errors=True]

### --stdin

read a single notebook file from stdin. Write the resulting notebook with default basename 'notebook.\*'

Equivalent to: [--NbConvertApp.from\_stdin=True]

### --stdout

Write notebook output to stdout instead of files.

Equivalent to: [--NbConvertApp.writer\_class=StdoutWriter]

### --inplace

Run nbconvert in place, overwriting the existing notebook (only relevant when converting to notebook format)

Equivalent to: [--NbConvertApp.use\_output\_suffix=False]

--NbConvertApp.export\_format=notebook --FilesWriter.build\_directory=]

### --clear-output

Clear output of current file and save in place, overwriting the existing notebook.

Equivalent to: [--NbConvertApp.use\_output\_suffix=False]

--NbConvertApp.export\_format=notebook --FilesWriter.build\_directory=

--ClearOutputPreprocessor.enabled=True]

```

--coalesce-streams
    Coalesce consecutive stdout and stderr outputs into one stream (within each
    cell).
    Equivalent to: [--NbConvertApp.use_output_suffix=False
--NbConvertApp.export_format=notebook --FilesWriter.build_directory=
--CoalesceStreamsPreprocessor.enabled=True]
--no-prompt
    Exclude input and output prompts from converted document.
    Equivalent to: [--TemplateExporter.exclude_input_prompt=True
--TemplateExporter.exclude_output_prompt=True]
--no-input
    Exclude input cells and output prompts from converted document.
    This mode is ideal for generating code-free reports.
    Equivalent to: [--TemplateExporter.exclude_output_prompt=True
--TemplateExporter.exclude_input=True
--TemplateExporter.exclude_input_prompt=True]
--allow-chromium-download
    Whether to allow downloading chromium if no suitable version is found on the
    system.
    Equivalent to: [--WebPDFExporter.allow_chromium_download=True]
--disable-chromium-sandbox
    Disable chromium security sandbox when converting to PDF..
    Equivalent to: [--WebPDFExporter.disable_sandbox=True]
--show-input
    Shows code input. This flag is only useful for dejavu users.
    Equivalent to: [--TemplateExporter.exclude_input=False]
--embed-images
    Embed the images as base64 dataurls in the output. This flag is only useful
    for the HTML/WebPDF/Slides exports.
    Equivalent to: [--HTMLExporter.embed_images=True]
--sanitize-html
    Whether the HTML in Markdown cells and cell outputs should be sanitized..
    Equivalent to: [--HTMLExporter.sanitize_html=True]
--log-level=<Enum>
    Set the log level by value or name.
    Choices: any of [0, 10, 20, 30, 40, 50, 'DEBUG', 'INFO', 'WARN', 'ERROR',
'CRITICAL']
    Default: 30
    Equivalent to: [--Application.log_level]
--config=<Unicode>
    Full path of a config file.
    Default: ''
    Equivalent to: [--JupyterApp.config_file]
--to=<Unicode>
    The export format to be used, either one of the built-in formats
    ['asciidoc', 'custom', 'html', 'latex', 'markdown', 'notebook',
'pdf', 'python', 'qtpdf', 'qtpng', 'rst', 'script', 'slides', 'webpdf']
    or a dotted object name that represents the import path for an

```

```

        ``Exporter`` class
    Default: ''
    Equivalent to: [--NbConvertApp.export_format]
--template=<Unicode>
    Name of the template to use
    Default: ''
    Equivalent to: [--TemplateExporter.template_name]
--template-file=<Unicode>
    Name of the template file to use
    Default: None
    Equivalent to: [--TemplateExporter.template_file]
--theme=<Unicode>
    Template specific theme(e.g. the name of a JupyterLab CSS theme distributed
    as prebuilt extension for the lab template)
    Default: 'light'
    Equivalent to: [--HTMLExporter.theme]
--sanitize_html=<Bool>
    Whether the HTML in Markdown cells and cell outputs should be sanitized.This
    should be set to True by nbviewer or similar tools.
    Default: False
    Equivalent to: [--HTMLExporter.sanitize_html]
--writer=<DottedObjectName>
    Writer class used to write the
                                results of the conversion
    Default: 'FilesWriter'
    Equivalent to: [--NbConvertApp.writer_class]
--post=<DottedOrNone>
    PostProcessor class used to write the
                                results of the conversion
    Default: ''
    Equivalent to: [--NbConvertApp.postprocessor_class]
--output=<Unicode>
    Overwrite base name use for output files.
                                Supports pattern replacements '{notebook_name}'.
    Default: '{notebook_name}'
    Equivalent to: [--NbConvertApp.output_base]
--output-dir=<Unicode>
    Directory to write output(s) to. Defaults
                                to output to the directory of each notebook.
To recover
                                previous default behaviour (outputting to the
current
                                working directory) use . as the flag value.
    Default: ''
    Equivalent to: [--FilesWriter.build_directory]
--reveal-prefix=<Unicode>
    The URL prefix for reveal.js (version 3.x).
                                This defaults to the reveal CDN, but can be any url pointing to a

```

copy

of reveal.js.

For speaker notes to work, this must be a relative path to a local copy of reveal.js: e.g., "reveal.js".

If a relative path is given, it must be a subdirectory of the current directory (from which the server is run).

See the usage documentation

(<https://nbconvert.readthedocs.io/en/latest/usage.html#reveal-js-html-slideshow>)

for more details.

Default: ''

Equivalent to: [--SlidesExporter.reveal\_url\_prefix]

--nbformat=<Enum>

The nbformat version to write.

Use this to downgrade notebooks.

Choices: any of [1, 2, 3, 4]

Default: 4

Equivalent to: [--NotebookExporter.nbformat\_version]

Examples

-----

The simplest way to use nbconvert is

```
> jupyter nbconvert mynotebook.ipynb --to html
```

Options include ['asciidoc', 'custom', 'html', 'latex', 'markdown', 'notebook', 'pdf', 'python', 'qtpdf', 'qtpng', 'rst', 'script', 'slides', 'webpdf'].

```
> jupyter nbconvert --to latex mynotebook.ipynb
```

Both HTML and LaTeX support multiple output templates. LaTeX includes

'base', 'article' and 'report'. HTML includes 'basic', 'lab' and 'classic'. You can specify the flavor of the format used.

```
> jupyter nbconvert --to html --template lab mynotebook.ipynb
```

You can also pipe the output to stdout, rather than a file

```
> jupyter nbconvert mynotebook.ipynb --stdout
```

PDF is generated via latex

```
> jupyter nbconvert mynotebook.ipynb --to pdf
```

You can get (and serve) a Reveal.js-powered slideshow

```
> jupyter nbconvert myslides.ipynb --to slides --post serve
```

Multiple notebooks can be given at the command line in a couple of different ways:

```
> jupyter nbconvert notebook*.ipynb
> jupyter nbconvert notebook1.ipynb notebook2.ipynb
```

or you can specify the notebooks list in a config file, containing::

```
c.NbConvertApp.notebooks = ["my_notebook.ipynb"]
```

```
> jupyter nbconvert --config mycfg.py
```

To see all available configurables, use `--help-all`.