

Docker registry:

It is a storage component for Docker images.

We can store the images in either public / private repositories.

Docker Hub is Docker's very own cloud repo.

Why use?

Control where your images are being stored.

Integrate image storage in-house development

with your workflow.

Docker Architecture & components.

Docker -v - to check version
 docker search node - to search any application in docker hub
 docker pull node - It pulls the image from docker hub.
 docker images - to check whether the image is stored.
 docker create - Launch the command and keeps idle.
 ps -a - It shows all the containers
 ps - It shows only running containers.
 docker start container name - Makes running container idle
 " stop " -
 docker rm " - Removes the container.
 docker rm -f " = forcefully remove
 docker ~~run~~ ^{run} -d --name (jic - devops)
 to execute in background. cont name httpd -
 Apache
 docker exec (-it) interactive terminal container name /bin/bash
 docker save -o ~~backupfile~~ backupfile .tar saving: 1.0.0
 name
 hostport: containerport (To save a backup

docker images

docker rmi ~~img~~  imaging:1.0

docker rmi -f  imaging:1.0

docker load -i backupfilename.tar

Docker file:

Docker can build images automatically by reading the instructions from a dockerfile. A dockerfile is a text document that contains all the commands as you could call on the command line to assemble an image.

Docker file syntax:

INSTRUCTION arguments

FROM - specify the base image

RUN - Manual commands to run

COPY - Local file to img dir

EXPOSE - specify the img's default port.

WORKDIR - Home dir

CMD - Default commands to run.

ENTRYPOINT - Can't override.

Docker Network types:

Bridge - Building intercomm b/w containers

~~None~~ None - No network allocation.

host - Docker host can only communicate