

# 笔杆检测报告单 (全文标明引文)

全文标明引文

全文对照

打印

检测说明

标题: 202018010212\_Final\_Report

作者: Alber Wu

报告编号: BG202405052344175747

提交时间: 2024-05-05 23:45:02

去除引用文献复制比: 2.3%

去除本人已发表文献复制比: 2.3%

单篇最大文字复制比: 8.4%



重复字数: 1,515

总字数: 64,855

检测范围

## 202018010212\_Final\_Report\_第1部分

### 原文内容

UNDERGRADUATE PROJECT REPORT  
Project Title: DIRA-Net on Breast Cancer Diagnosis  
Surname: Wu  
First Name: Albert  
Student Number: 202018102012  
Supervisor Name: Dr Grace Ugochi Nneji  
Module Code: CHC 6096  
Module Name: Project  
Date Submitted: May 5, 2023  
Chengdu University of Technology Oxford Brookes College  
Chengdu University of Technology  
BSc (Single Honours) Degree Project  
Programme Name: Projects  
Module No.: CHC 6096  
Surname: Wu  
First Name: Albert  
Project Title: DIRA-Net on Breast Cancer Diagnosis  
Student No.: 202018010212  
Supervisor: Dr. Grace Ugochi Nneji  
Date submitted: 6rd May 2024  
A report submitted as part of the requirements for the degree of BSc (Hons) in Computer Science  
At  
Chengdu University of Technology Oxford Brookes College  
Declaration  
Student Conduct Regulations:  
Please ensure you are familiar with the regulations in relation to Academic Integrity. The University takes this issue very seriously and students have been expelled or had their degrees withheld for cheating in assessment. It is important that students having difficulties with their work should seek help from their tutors rather than be tempted to use unfair means to gain marks. Students should not risk losing their degree and undermining all the work they have done towards it. You are expected to have familiarised yourself with these regulations.  
<https://www.brookes.ac.uk/regulations/current/appeals-complaints-and-conduct/c1-1/>  
Guidance on the correct use of references can be found on [www.brookes.ac.uk/services/library](https://www.brookes.ac.uk/services/library), and also in a handout in the Library.  
The full regulations may be accessed online at <https://www.brookes.ac.uk/students/sirt/student-conduct/>  
If you do not understand what any of these terms mean, you should ask your Project Supervisor to clarify them for you.  
I declare that I have read and understood Regulations C1.1.4 of the Regulations governing Academic Misconduct, and that the work I submit is fully in accordance with them.  
Signature Date 6th May 2024  
**REGULATIONS GOVERNING THE DEPOSIT AND USE OF OXFORD BROOKES UNIVERSITY MODULAR PROGRAMME PROJECTS AND DISSERTATIONS**  
Copies of projects/dissertations, submitted in fulfillment of Modular Programme requirements and achieving marks of 60% or above, shall normally be kept by the Oxford Brookes University Library.  
I agree that this dissertation may be available for reading and photocopying in accordance with the Regulations governing the use of the Oxford Brookes University Library.  
Signature Date 6th May 2024.  
Acknowledgment  
In completing my project on the application of deep learning in breast cancer detection, I am immensely grateful for the guidance and support of Dr. Grace Ugochi Nneji, my supervisor, and Joojo Walker, my Module Leader. Dr. Grace provided valuable insights and rigorous supervision throughout the research.

h process, greatly enhancing my work. Joojo Walker, while primarily responsible for delivering course content, also offered significant help that facilitated my understanding and application of complex concepts. Their combined support was crucial in the successful completion of my project. Thank you for your dedication and assistance.

## Table of Contents

Declaration	i
Acknowledgment	iii
Table of Contents	iv
List of Figures	vii
List of Tables	xi
Abstract	xii
Abbreviations	xiii
Glossary	xv
Chapter 1 Introduction	1
1.1 Background	1
1.1.1 Convolution Neural Network Overview	2
1.1.2 Convolution Layer	3
1.1.3 Pooling Layers	5
1.1.4 Batch Normalization	5
1.1.5 Fully Connected Layers	6
1.1.6 Dropout Layers	6
1.1.7 Rectifier Linear Unit	6
1.1.8 Kernel initializer - He Initialization	7
1.1.9 Loss Function	7
1.2 Aim	8
1.3 Objectives	8
1.4 Project Overview	9
1.4.1 Scope	9
1.4.2 Audience	9
Chapter 2 Background Review	11
Chapter 3 Methodology	14
3.1 Approach	14
3.1.1 Model Construction	14
3.1.1.1 Inception Network Version 4	14
3.1.1.2 Residual Network	16
3.1.1.3 Depthwise Convolution Model	16
3.1.1.4 Attention Mechanism	16
3.1.1.5 Inception-ResNet Model	17
3.1.1.6 Depthwise-Inception-ResNet Model	18
3.1.1.7 Depthwise-Inception-ResNet-Attention Model	19
3.1.1.8 The Proposed Model	19
3.2 Dataset	20
3.2.1 Dataset Introduction	20
3.2.2 Data Separation	21
3.2.3 Data Balance	22
3.2.4 Data Resize	23
3.2.5 Data Color Channel Modification	23
3.2.6 Data Augmentation	24
3.2.7 Data Preprocessing Summary	24
3.3 Technology	24
3.4 Data Testing and Evaluation Plan	25
3.4.1 Data Testing	25
3.4.2 Model Performance Evaluation Criteria	26
Chapter 4 Experiment and Results	28
4.1 Experiment Phases	28
4.2 Inception-Net Training on Four Magnification	28
4.3 ResNet Training on Four Magnification	34
4.4 Depthwise Network Training on 40X Magnification	37
4.5 Inception-ResNet (IR-Net) Training on 40X Magnification	38
4.6 Depthwise-Inception-ResNet (DIR-Net) Training on 40X Magnification	40
4.7 DIRA-Net Training on 40X Magnification	42
4.8 CLAHE Experiment	43
4.9 Model Evolution Summary	43
4.10 Fine Tune	44
4.11 Comparison Analysis	54
4.12 Model Visualization	56

4.13 Model Deployment	57
Chapter 5 Project Management	60
5.1 Activities	60
5.1.1 Schedule	61
5.1.2 Project Version Management	61
5.1.3 Project Data Management	62
5.1.4 Project Deliverable	62
5.2 Risk Analysis	62
5.3 Professional Issues	63
Chapter 6 Conclusion	65
Reference	66
Appendices	71
List of Figures	
Figure 1 : Convolutional Neural Network Overview	3
Figure 2 : Convolutional Layer and Calculation	4
Figure 3 : Sliding operation of filters	4
Figure 4 : Two types of Padding Methods	5

## 202018010212\_Final\_Report\_第2部分

### 原文内容

Figure 5 : Two types of Pooling Layers.	5
Figure 6 : ReLU and Leaky ReLU Graph	7
Figure 7 : Inception V4 Architecture	14
Figure 8 : InceptionV4 STEM Block	14
Figure 9 : Detail Blocks within InceptionV4.	15
Figure 10 : Basic ResNet Block	16
Figure 11 : Depthwise Convolution	16
Figure 12 : Attention Block	17
Figure 13 : Inception-ResNet-Prototype	17
Figure 14 : STEM Block of Inception-ResNet Prototype Model	17
Figure 15 : Detail structure of Inception-ResNet model	18
Figure 16 : Depthwise-Inception-ResNet Model	19
Figure 17 : Depthwise-Inception-ResNet STEM block with attention mechanism	19
Figure 18 : The proposed model DIRA-Net	20
Figure 19 : Examples of BreakHis Images	21
Figure 20 : Dataset Structure after Separation	22
Figure 21 : Number of images within Benign and Malignant Before Balancing	22
Figure 22 : Images Number After Balancing	23
Figure 23 : Images Transformation	23
Figure 24 : Augmented image example	24
Figure 25 : Initial Inception Model for experiment	28
Figure 26 : Inception-Net Accuracy and Loss on 40X Raw Images	29
Figure 27 : Inception-Net Accuracy and Loss on 100X Raw Images	29
Figure 28 : Inception-Net Accuracy and Loss on 200X Raw Images	30
Figure 29 : Inception-Net Accuracy and Loss on 400X Raw Images	30
Figure 30 : Inception-Net Accuracy and Loss on 40X Resize Images	31
Figure 31 : Inception-Net Accuracy and Loss on 100X Resize Images	31
Figure 32 : Inception-Net Accuracy and Loss on 200X Resize Images	32
Figure 33 : Inception-Net Accuracy and Loss on 400X Resize Images	32
Figure 34 : Inception-Net Comparison Accuracy	33
Figure 35 : Inception-Net Comparison of Validation Loss	33
Figure 36 : Initial ResNet Structure for experiment	34
Figure 37 : ResNet Accuracy and Loss on 40X Resized Images	34
Figure 38 : ResNet Accuracy and Loss on 100X Resized Images	35
Figure 39 : ResNet Accuracy and Loss on 200X Resized Images	35
Figure 40 : ResNet Accuracy and Loss on 400X Resized Images	36
Figure 41 : ResNet Validation Accuracy Comparison	37
Figure 42 : ResNet Validation Loss Comparison	37
Figure 43 : Depthwise CNN for experiment	38
Figure 44 : Depthwise-CNN Accuracy and Loss on 40X Magnified Images	38
Figure 45 : Inception-ResNet STEM block.	39
Figure 46 : Inception-ResNet Structure for experiment	40
Figure 47 : InceptionResNet Accuracy and Loss on 40X Resized Images	40
Figure 48 : Depthwise-Inception-ResNet Block A	41
Figure 49 : DIR model overview.	41

Figure 50 : DIR-Net Accuracy and Loss on 40X Magnified Images 41

Figure 51 : STEM Block with attention mechanism 42

Figure 52 : Initial DIRA-Net 42

Figure 53 : Initial DIRA-Net accuracy and loss 43

Figure 54 : CLAHE Test Results 43

Figure 55 : DIRA-Net Fine-tune result 1 46

Figure 56 : DIRA-Net Fine-tune result 2 47

Figure 57 : DIRA-Net Fine-tune result 3 47

Figure 58 : DIRA-Net Fine-tune result 4 48

Figure 59 : DIRA-Net Fine-tune result 5 49

Figure 60 : DIRA-Net Fine-tune result 6 49

Figure 61 : DIRA-Net Fine-tune result 7 50

Figure 62 : DIRA-Net Fine-tune result 8 50

Figure 63 : DIRA-Net Fine-tune result 9 (Proposed One) 51

Figure 64 : DIRA-Net evaluation metrix 53

Figure 65 : DIRA-Net Validation Accuracy Comparison with Pre-trained Models 55

Figure 66 : DIRA-Net Validation Loss Comparison with Pre-trained Models 56

Figure 67 : SHAP Visualization 57

Figure 68 : Grad-CAM Visualization 57

Figure 69 : Main Page 58

Figure 70 : Dataset Introduction Cards 58

Figure 71 : Diagnosis Page before Diagnosis 59

Figure 72 : Malignant Diagnosis 59

Figure 73 : Benign Diagnosis 59

List of Tables

Table 1 : Summary of Related Works 1

Table 2 : Upsampling detail for each magnification 24

Table 3 : Different Augmentation of Different Magnification 24

Table 4 : Summary of Relevant Technology involved in this project 25

Table 5 : Model Evolution Summary 44

Table 6 : Hyperparameters of the initial DIRA-Net 45

Table 7 : Hyperparameters of model fine tune version 1 45

Table 8 : Hyperparameters of version 2 46

Table 9 : Hyperparameters for version 3 47

Table 10 : Hyperparameters of Version 4 48

Table 11 : Hyperparameters of Version 5 48

Table 12 : Hyperparameters of Version 6 49

Table 13 : Hyperparameters of Version 7 49

Table 14 : Hyperparameters of Version 8 50

Table 15 : Hyperparameter of Proposed Version 51

Table 16 : Fine tune process and results summary 54

Table 17 : Comparison Analysis with Previous Works 55

Table 18 : Results Comparison of DIRA-Net with Pre-trained Models 56

Table 19 : Activities of the Project 60

Table 20 : Gantt Graph 61

Table 21 : Version Control Progress 62

Table 22 : Risk Analysis 63

Abstract

Breast Cancer ranks among the deadliest diseases globally, posing significant diagnostic challenges that demand the expertise of radiologist, state-of-art equipment, and considerable resources. Traditional diagnostic methods have struggled with accuracy, leading to misdiagnosis. Although advancements in medical image processing have improved outcomes, inaccuracies in breast cancer diagnosis remain a critical issue. This project leverages deep learning to enhance diagnostic precision through the development of a novel convolutional neural network (CNN) model, termed the Depthwise-Inception-ResNet, incorporating an attention mechanism. This innovative model combines the strengths of the Inception and Residual networks with attention block, enabling it to focus on granular features while maintaining sufficient depth to extract critical feature for accurate breast cancer classification. Trained and validated on histopathological images from public BreakHis dataset, the model achieved remarkable performance metrics:96.45% accuracy,93% AUC, and 92.14% F1-Score. These results underscore the model's efficacy in the nuanced classification of breast cancer, heralding a significant advancement in diagnostic methodologies.

## 202018010212\_Final\_Report\_第3部分

### 原文内容

Keywords: CNN, Breast Cancer, Deep Learning, Inception-Net, ResNet, Depthwise-Net, Attention Mechanism

#### Abbreviations

CNN Convolutional Neural Network

ResNet Residual Network

GAP Global Average Pooling

TP True Positive  
 TN True Negative  
 FP False Positive  
 FN False Negative  
 ReLU Rectified Linear Unit  
 IR-Net Inception Residual Network  
 DIR-Net Depthwise Inception Residual Network  
 DIRA-Net Depthwise Inception Residual Attention Network  
 Acc Accuracy  
 Prec Precision  
 Spec Specificity  
 Para Parameters  
 F1 F1-Score  
 Rec Recall  
 AUC Area Under Curve  
 CLAHE Contrast Limited Adaptive Histogram Equalization  
 MRI Magnetic Resonance Imaging  
 RR Rotation Range  
 WS Width Shift  
 HS Height Shift  
 SR Shear Range  
 ZR Zoom Range  
 HF Horizontal Flip  
 FM Fill Mode  
 LR Learning Rate  
 VN Version Number  
 BS Batch Size  
 L2 L2 Regularization  
 FN First Three Layers Filter Number of STEM Block

#### Glossary

Convolutional Neural Network: An architecture of network utilized for deep learning mission which are commonly used for computer vision projects

Residual Network: A deep learning architecture that uses skip connections to prevent gradient issues in very deep networks.

Inception-V4: An advanced deep learning model that enhances the Inception architecture with more complex and efficient structures to improve accuracy and speed.

Depthwise Convolution: A convolutional operation that separates the filtering and combining steps, allowing for reduced computational cost and model size in deep neural networks.

**Data Augmentation: A technique used to increase the diversity of data available for training models by applying random transformations to training images.**

Data Separation: The process of dividing data into distinct sets, typically for training, validation, and testing purposes.

Data Balance: The concept of ensuring that each class in a dataset is equally represented to prevent model bias and improve generalization across different categories.

Color Channel Modification: Adjusting the intensity values of the color channels in an image to alter its appearance or to perform normalization.

Resize: Changing the dimensions of an image, often to meet the input size requirements of a neural network.

Pre-trained Model: A model that has been previously trained on a large dataset and can be fine-tuned or used directly for similar tasks.

Fine tune: The process of adjusting the parameters of a pre-trained model to make it more suitable for a specific, often related task.

#### Chapter 1 Introduction

##### 1.1 Background

Breast Cancer is one of the most fatal diseases so far in the world. It is said by American Cancer Society Surveillance that one of eight women is affected by it [1]. **According to statistics recorded by the World Health Organization (WHO)[2] among the 9.6 million cancer-related deaths, 627,000 females passed away due to breast cancer in 2018, in addition, WHO had also predicted that 43,600 women would die from breast cancer in 2021[3], which indicates that breast cancer remains the leading cause of women deaths.**

Breast cancer is similar to other types of cancer which has early-stage (Benign) and later-stage (Malignant). Once the disease reaches the malignant stage, cancer might spread to other parts of the body which leads to catastrophic consequences, therefore, it is crucial to detect breast cancer at the early stage in order to provide appropriate treatment [4]. Mammography serves as a common approach for breast cancer detection in which the picture is normally taken through Magnetic Resonance Imaging (MRI), X-Ray, and Ultrasound, and a study had confirmed that these images raised survival rate [5]-[6]. Another method which is also widely used is biopsy. It relies on tissue samples from the cancer area of breasts and complete the analysis, classification, and detection under the microscope [5]. Furthermore, breast cancer were also analyzed on cytological level [7].

However it is unfortunate that the diagnosis still faces troubles even with numerous methods applied for correctly diagnosing the area of breast cancer and classifying the category in medical image processing [8]. Manual diagnosis through medical images or microscope is time-intensive, expensive and prone to errors, as symptoms are likely to be overseen [9]. For example, ultrasound breast image detection highly depends on the experience, capability and knowledge of radiologists and diagnosticians [10], which most likely to be an issue with the lack of facilities, resources, and manpower in small hospitals.

**Recent years, with the rapid evolution of deep learning in medical image processing, the application of Computer-Aided-Diagnosis has been widely acknowledged [5].** As the demand for accuracy and speed in breast cancer image analysis continues to increase, the application of deep learning technology has become a major trend in this field [11].

Within the realm of breast cancer research, CNNs stand as a pivotal element, particularly in the classification and diagnosis of the disease. CNNs are renowned not only for their precision in feature extraction and accurate classification but also for their capability in managing image pattern matching tasks with extensive datasets [5]. These networks excel in processing a vast array of medical images, including mammograms, ultrasound, MRI, and histopathological images, to differentiate between benign and malignant lesions effectively. The primary aim of this project is to harness the power of CNNs through the development and deployment of a deep-learning-based system dedicated to the classification and diagnosis of breast cancer. This initiative seeks to reduce the reliance on manual diagnostic efforts, target treatments more precisely, decrease mortality rates, and ultimately save lives by enhancing the accuracy and efficiency of breast cancer detection. The integration of CNNs into this project underscores their critical role in advancing diagnostic methodologies, ensuring optimal resource utilization, and improving patient care outcomes.

#### 1.1.1 Convolutional Neural Network Overview

Before getting into the details of this project, the following part will introduce the knowledge of CNNs and the specific techniques within the project. The basic concept includes convolution, pooling, activation function, loss function, batch normalization, etc.

CNNs are sophisticated models comprising three primary types of layers: the input layer, hidden layers, and the output layer. The essence of a CNN lies within its hidden layers, which dictate the model's structure through a series of convolutional layers, pooling layers, activation functions, and padding, among other components. These layers work collectively to downsample and process image data, a technique crucial for reducing complexity while retaining significant information [12].

Upon entry into a CNN, an image is defined by its height, width, and depth—the latter representing color channels. It then undergoes a sequential transformation through various layers, each performing mathematical operations to extract features and reduce dimension. This process includes the application of non-linearity to interpret the image's content, leading to predictions or classifications. Through this intricate sequence of transformations, known as convolution, the network leverages learned patterns to efficiently analyze images. The original high-dimensional input is methodically condensed into a form that emphasizes essential information, facilitating effective output. This streamlined overview of CNNs illustrates their capacity to interpret and classify images, highlighting the role of their hierarchical structure in image processing. Figure 1 depicts an overview of the CNN structure, including its processes.

Figure 1: Convolutional Neural Network Overview

#### 1.1.2 Convolution Layer

Convolutional layers perform feature extraction with convolution operations. The operation is complete by using filters set with size and strides which varies from model to model. Filters are matrices used to detect specific types of features by performing element-wise multiplications followed by a sum wherever it is slid through in order to produce an output feature map [13]. This feature map indicates the presence and intensity of those features across the image. Note that adjusting the filter size, stride, and padding affects how the layer captures and scales these features, enabling the network to learn complex patterns and structures from visual data effectively. The construction process of a typical convolutional layer is depicted in Figure 2.

## 202018010212\_Final\_Report\_第4部分

### 原文内容

Figure 2: Convolutional Layer and Calculation

Stride determines the movement of filters across the input, and padding allows for adjustment of the input's spatial dimensions to preserve edge information in the output. Each affects spatial dimensions and theoretical integrity respectively. Figure 3 displays the sliding of filters and the padding operation.

Figure 3: Sliding operation of filters

There are two patterns of padding in this project, "Same" and "Valid". "Same" pattern only starts calculating when the center of the filters overlap with the input image whereas valid starts calculating only when the full size of filter has entered the input image area. Figure 4 illustrates the padding mode.

Padding of mode "same" Padding of mode "valid"

Figure 4: a) and b) illustrates two padding modes which is frequently used in this project. K represents the center of the kernel, Gray area displays the full size of the filter, blue area is the overlapping area of filter and input images.

#### 1.1.3 Pooling Layers

Pooling layers simplify the information in feature maps by summarizing the presence of features in patches of the feature map. Two of the pooling layers are frequently used in the project, Max Pooling and Global Average Pooling.

Max Pooling picks the largest value from each patch of the feature map, preserving the most prominent features while reducing dimensionality.

Global Average Pooling calculates the average of all values in each feature map, condensing each map to a single value. This helps reduce the complexity of the model and aids classification tasks by focusing on the overall presence of features across the map. Overview how both pooling layers function is in Figure 5.

a) Max Pooling Layer b) Global Average Pooling

Figure 5: a) and b) represents two pooling layers where a) is operated under a pooling filter of 2\*2, which selects the biggest number in each zone. GAP on the other hand calculates the mean average of each channel to get the output.

#### 1.1.4 Batch Normalization

Batch normalization (BN) is a technique widely used in deep learning to normalize the inputs of each layer. It helps in stabilizing and speeding up the training process [14]. The basic equation is in Equation (1).

$$BN(x) = \gamma x - \mu_B + \sigma_B^2 + \epsilon + \beta \quad \text{Equation (1)}$$

X represents the input,  $\mu_B$  is the mean of the batch,  $\sigma_B^2$  is the variance of the batch,  $\epsilon$  is the small constant added for numerical stability, and  $\gamma$  and  $\beta$  are learnable parameters for scale and shift, respectively.

#### 1.1.5 Fully Connected Layers

Fully connected (dense) layers integrate and summarize features extracted by previous layers to make predictions. Each neuron connects to every neuron in the preceding layer, enabling the model to consider all learned features for tasks like classification or regression. Positioned after convolutional and pooling layers, they translate complex feature representations into outcomes.

#### 1.1.6 Dropout Layers

Dropout serves as a regularization technique in neural networks to prevent overfitting. It operates by randomly setting a fraction of neurons into zero within each update during training which effectively shrinks the network temporarily. The dropout rate is typically defined as hyperparameter "p", representing the probability of neuron being dropped. Dropout operation is not applied during testing, however, neuron outputs are scaled by "p" therefore maintaining the consistency of the overall network.

### 1.1.7 Rectifier Linear Unit

Non-linearity is introduced through activation functions like ReLU (Rectified Linear Unit), is crucial in neural networks to enable the modeling of complex patterns.

ReLU and Leaky ReLU are popular activation functions in deep neural networks, particularly effective in addressing non-linear problems.

ReLU activation possesses a quicker convergence rate and calculation speed due to its linear operation, and Leaky ReLU function with leak correction variants from the classical ReLU activation resolves the issue of ReLU might cause neuron deaths when the input value is negative [15]. The function graph and equation is illustrated in Figure 6 and Equation (2) to Equation (3).

Figure 6: ReLU and Leaky ReLU function graph, where  $k$  is fixed for Leaky ReLU

Leaky-ReLU  $(x) = \max(kx, x) = \{x, \text{ if } x > 0; kx, \text{ if } x \leq 0\}$  Equation (2)

ReLU  $(x) = \max(kx, x) = \{x, \text{ if } x > 0; 0, \text{ if } x \leq 0\}$  (Activate State) Equation (3)

### 1.1.8 Kernel initializer - He Initialization

According to He et al., [16], introduces an initialization method that is particularly effective for layers using rectifier activation (ReLU or its deviations) functions. This method, commonly known as "He Initialization". This concept was built to address the problem of gradient vanish and exploding which frequently appears in deep neural networks.

He Initialization sets the initial network weights close to zero but scaled by  $2/n$ , ensuring stable gradients and faster convergence of the model equation is provided in Equation (4).

$W \sim N(0, 2/n)$  Equation (4)

$W$  is the weight matrix for a layer in the neural network,  $N(0, 2/n)$  displays the normal (Gaussian) distribution with mean 0 and standard deviation.  $n$  represents the number of incoming connections (fan-in) to the layer. The biases are normally initialized to 0.

### 1.1.9 Loss Function

Loss function measures the difference between the model's predictions and the actual data, acting as the objective for optimization; the measurement is essential for guiding the network through the learning process, enabling it to accurately interpret input data. By minimizing the loss function, the network adjusts its internal parameters to improve prediction accuracy, serving as the foundational mechanism for the model's adaptation and refinement [14].

### 1.2 Aim

Various models in deep learning diagnosis utilize a specific single model or single mechanism, however, by doing so, there are chances that flaws of specific models could affect the performance in a negative way. To eliminate the drawbacks and maximize the performance, this project aims to develop and deploy a novel CNN model including Inception-ResNet mechanism to classify the levels of breast cancer. Based on Wang et al. [17], Inception-ResNet possesses a remarkable balance between model accuracy and resource efficiency.

### 1.3 Objectives

The project will collect breast cancer symptom data from online sources, utilizing public datasets BreakHis. BreakHis has benign and malignant categories with 9,109 microscope images from 82 patients. The data will be divided into training and testing sets for four different scaled images, with an 75% portion allocated for training and a 15% portion for testing. Within the training set, 15% of the images will be randomly selected as a validation set. It is essential to include both benign and malignant samples in both sets.

The project aims to build a Depthwise-Inception-ResNet-Attention model, with hyperparameter adjustments such as batch size, learning rate, dropout rate etc. Although primarily focused on binary classification, the project also approaches it as a multi-class problem which facilitates future generalization on detail symptoms.

In addition, the evaluation of the model will include metrics such as "Accuracy" and "Loss." Moreover, performance will be assessed using "Precision", "Recall", "F1-Score", "AUC-ROC", "AUC-PR", "Specificity", "Sensitivity", and the "Confusion Matrix".

Lastly, the project will be deployed through a website which allows uploading medical pictures of breast cancer, and then give the classification results.

### 1.4 Project Overview

This section explores the potential of Inception-ResNet for improving breast cancer diagnosis, highlighting key stakeholders who will benefit from these advancements in medical image processing.

#### 1.4.1 Scope

CNNs were introduced to medical image processing in the 1980s and have become the dominant approach in this field [9]-[10]. While Inception-ResNet delivers impressive performance, models not tailored to specific scenarios often encounter issues like gradient vanishing, local minima, and overfitting. Therefore, enhancing Inception-ResNet through the incorporation of depthwise operations is imperative. By using depthwise operations, it enhances network efficiency and effectiveness by reducing parameter count and conserving computational resources by eliminating unnecessary parameters. [18].

## 202018010212\_Final\_Report\_第5部分

### 原文内容

The following are the significance of this project and potential contributions:

- Enhanced Breast Cancer Diagnosis Accessibility
- Improved Diagnosis Efficiency
  - Reduced Misdiagnosis Rate
  - Early detection and Prevention
  - Conserved Medical Resources and Improved Allocation
- Increased Life Saving Rate
  - Cost-Effective Healthcare Solutions
  - Promotion of Public Health Awareness

#### 1.4.2 Audience

The development of a specialized system for breast cancer diagnosis will bring about significant benefits to various stakeholders.

**Medical Professionals:** Radiologists and oncologists will benefit from the enhanced accuracy and efficiency of breast cancer diagnosis. The CNN can aid in early detection, reducing the chances of misdiagnosis and allowing for more timely interventions.

**Hospitals and Clinics:** Healthcare institutions will experience improved workflow and reduced diagnostic errors, which can lead to better patient care and outcomes. It can also streamline the diagnostic process, potentially reducing the burden on healthcare resources.

**Breast Cancer Patients:** Patients will benefit from faster and more accurate diagnosis, resulting in quicker treatment initiation and improved chances of survival. Additionally, reduced false positives and negatives can alleviate the emotional stress associated with diagnostic uncertainty.

**Medical Researchers:** Researchers can access a valuable tool for analyzing a vast amount of medical imaging data, facilitating advancements in breast cancer research and treatment methods.

In summary, the proposed depthwise-Inception-ResNet-attention model promises benefits for medical professionals, healthcare institutions, breast cancer patients, and the broader research community by enhancing the accuracy, efficiency, and overall quality of breast cancer diagnosis and care.

## Chapter 2 Background Review

Various researchers have proposed different networks for the enhancement of the classification of breast cancer. This section will present works that have been done for breast cancer classification by numerous researchers.

Hirra et al.,[1] proposed Pa-DBN-BC, a patch-based deep learning method, achieving 86% accuracy in diagnosing cancer from histopathology images. Sahu et al.,[9] introduced a model trained on mini-DDSM, yielding 99.17% and 97.75% accuracy for abnormalities and malignancy. Liang and Meng [19] achieved high accuracy in binary and eight-class classification with BreakHis datasets. Alkhaldi and Salari utilized ensemble optimization, attaining 92.874% accuracy in Invasive Ductal Carcinoma classification [20].

Xu et al.,[21] introduced an attention mechanism network with 98% accuracy, albeit limited by the smaller BreakHis dataset. Wu et al.,[22] trained on 224,426 mammography images, reaching an AUC of 0.895. Chougrad et al.,[23] employed transfer learning, achieving 98.94% accuracy post-merging datasets. Yu et al.,[24] used SCDA data augmentation with ResNet-50, obtaining 95.74% accuracy, 98.55% specificity, and 92.83% sensitivity. Arya and Saha [25] developed a stacked-based ensemble model with 90.2% accuracy for breast cancer prognosis. Whitney et al.,[10] highlighted the efficacy of CNN transfer learning in diverse imaging modalities for accurate breast cancer diagnosis.

Chattopadhyay et al.,[26] developed the MTRRE-Net, a deep learning model, for breast cancer detection from histopathological images, demonstrating superior accuracy with up to 97.81% on various magnification levels of the BreakHis dataset, showcasing its effectiveness in medical diagnostics.

Addo et al.,[27] introduced BCHI-CovNet, a novel lightweight AI model for classifying histopathological breast cancer images, achieving remarkable accuracies: 99.15% at 40X magnification, 99.08% at 100X, 99.22% at 200X, and 98.87% at 400X on the BreakHis dataset, and 99.38% on the BACH dataset. A summary of the different researchers and their findings and possible results can be found in Table 1.

### Author Datasets Methods Results

Hirra et al.,[1] Histopathology images Patch-based deep learning & Deep belief

Network Acc =86%

Sahu et al.,[9] Mini-DDSM AlexNet

+ ResNet

+ MobileNetV2 Abnormalities: Acc =99.17%

Malignancy:

Acc =97.75%

Liang and Meng [19] BreakHis Convolutional Block

Attention

Module and

Convolutional Multi-Layer Perceptron Acc =95.5%

Alkhaldi and Salari [20] Invasive-Ductal-Carcinoma (IDC) Multi-ResNet CNN Acc =92.874%

Xu et al.,[21] BreakHis DeNet Acc =98%

Wu et al.,[22] 224,426 mammography Ensemble of

Four ResNets AUC =89.5%

Chougrad et al.,[23] INbreast, DDSM, BCDR VGG16, ResNet50, InceptionV3 DDSM:

Acc =97%

AUC =98%

INbreast:

Acc =95.5%

AUC =97%

BCDR:

Acc =96.67%

AUC =96%

Independent database (MIAS):

Acc =98.23%

AUC =99%

Yu et al.,[24] INbreast, mini-DDSM SCDA augmentation

& ResNet-50 Acc =95.74%

Spec =98.55

Sens =92.83%

Arya and Saha [25] 1,980 patients'

breast cancer

data stacked ensemble model Acc =90.2%

AUC =0.93

Chattopadhyay et al.,[26] BreakHis MTRRE-Net All in Acc

40X:97.12%

100X:95.2%

200X:96.8%

400X:97.81%



Addo et al.,[27] BreakHis BCHI-ConvNet All in Acc  
40X:99.21%

100X:99.10%  
200X:99.36%  
400X:98.93%

Table 1: Summary of Related Works

Chapter 3 Methodology

1.1 Approach

The proposed CNN model comprises two individual models with two mechanisms. The basic idea is to combine Inception-V4 Model, Residual Network, and integrate attention mechanism and depthwise convolution which are respectively used to concentrate on relevant features and to reduce the computation resources.

1.1.1 Model Construction

In this phase, the model will be separated into their single model, dual connection model and down to the formation of the proposed model called DIRA-Net in the subsequent subsection.

Inception Network Version 4

Inception V4, as shown in Figure 7 to Figure 9, introduced by Google researchers in 2016, is a deep learning architecture renowned for its advanced techniques, including inception modules that efficiently learn local and global features using filters of varying sizes. It excels in image recognition and offers scalability [28].

Figure 7: Inception V4 Architecture

Figure 8: InceptionV4 STEM Block

a) Inception Block A b) Inception Block B

c) Inception Block C

d) Reduction Block A e) Reduction Block B

Figure 9: a) to e) demonstrate the basic structure of each block within the original Inception V4 which includes three traditional inception block and two parameters reduction block.

Residual Network

ResNet blocks, as illustrated in Figure 10, were introduced to incorporate residual connections, effectively mitigating gradient-related challenges in deep networks and leading to enhanced training efficiency [29].

Figure 10: Basic ResNet Block

Depthwise Convolution Model

Depthwise Convolution as provided in Figure 11 is a convolutional approach that separates convolution into channels to reduce computational load and parameters while preserving input spatial resolution and efficiency [30].

Figure 11: Depthwise Convolution

Attention Mechanism

Networks with attention mechanisms, displayed in Figure 12 focus on specific areas for more relevant task-related features [31]. Attention combines a reference with keys to calculate scores, which are then used to determine importance, allowing concentration on specific information. The equations are provided from Equation (5) to Equation (7).

Attention Score (Q, K) =  $Q \cdot K^T$  Equation (5)

Attention Weights (Q, K) =  $\text{softmax}(\text{Attention Score (Q, K)})$  Equation (6)

Attention Values (Q, K, V) =  $\text{Attention Weights (Q, K)} \cdot V$  Equation (7)

Figure 12: Attention Block

Inception-ResNet Model

Figure 13 to Figure 15 illustrate the fusion of Inception with ResNet Blocks, creating the prototype Inception-ResNet Blocks structure of this project. This hybrid design incorporates the multi-path feature extraction of Inception with the gradient-enhancing properties of ResNet. By combining these elements, Inception-ResNet Blocks enable efficient learning of intricate features, leading to more accurate and effective deep learning models [29]. The diagram showcases the amalgamation of these techniques, highlighting their collaborative strength in enhancing the network's capabilities.

## 202018010212\_Final\_Report\_第6部分

### 原文内容

Figure 13: Inception-ResNet-Prototype

Figure 14: STEM Block of Inception-ResNet Prototype Model

a) Inception-ResNet-Block-A b) Inception-ResNet-Block-B c) Inception-ResNet-Block-C

d) Inception-ResNet-Reduction-Block-A e) Inception-ResNet-Reduction-Block-B

Figure 15: a) to e) showcases the detail structure of Inception-ResNet model

Depthwise-Inception-ResNet Model

In order to increase the complexity and while keeping the parameters within a reasonable range, depthwise convolution operation is added to the IR-Block A. And other blocks remain the same. Figure 16 demonstrates the integration of Depthwise mechanism within the IR-Block A.

Figure 16: Depthwise-Inception-ResNet Model

Depthwise-Inception-ResNet-Attention Model

At last, the model is improved through integrating attention mechanism into the STEM block which is placed in Figure 17 so as to create valuable feature map. Other blocks remain the same as above.

Figure 17: Depthwise-Inception-ResNet STEM block with attention mechanism

The Proposed Model

Figure 18 depicts the proposed model, DIRA-Net, which integrates the Attention STEM block, DIR-Block A, IR-Block B, IR-Block C and two IR-Reduction blocks. It combines Depthwise convolution, Inception, Residual blocks, and an Attention mechanism within the STEM to provide a robust solution for complex

x tasks like breast cancer image classification. It addresses the issue of gradient vanishing in deep networks by leveraging residual connections from IR-bloc ks. The proposed model achieved parameter efficiency by separating channel from spatial dimensions, reducing the number of parameters without sacrificin g the performance. The integration of Attention STEM block enhanced with L2 regularization can capture nuanced features and prevent overfitting in traini ng. Furthermore, He\_normal initialization is applied at each layer to ensure effective weight setting from the outset. This architectural modification promotes precision and complexity management while maintaining a lean parameter profile, increase computational efficiency. And thus, this model is particularly suit able for deployment on devices with limited computational capabilities in medical field.

Figure 18: The proposed model DIRA-Net

1.1Dataset

Following will be providing crucial information about the dataset this project used.

1.1.1Dataset Introduction

During the training process, BreakHis will be the main dataset used for model training. The BreakHis dataset provides 9,109 histopathological images from 82 patients, categorized into 2,480 benign and 5,429 malignant samples at magnifications of 40X to 400X. Each RGB image has a resolution of 700\*460 pixels. This dataset, created with the P&D Laboratory in Parana, Brazil, is instrumental for benchmarking in medical image analysis. It differentiates between non-invasive benign tumors and invasive malignant tumors capable of metastasis. Breast tumors are subtyped into **adenosis, fibroadenoma, phyllodes tumor, and tubular adenoma for benign, and ductal carcinoma, lobular carcinoma, mucinous carcinoma, and papillary carcinoma for malignant**, enabling detailed research studies. The nomenclature of each image provides insights into the biopsy type, tumor classification, patient ID, and magnification used. Figure 19 displays examples of BreakHis images.

Figure 19: Examples of BreakHis Images

1.1.2Data Separation

The BreakHis file has four symptoms in each benign and malignant. And each symptom contains four different magnifications. In the case that binary classification is the main goal of the project, the data are separated based on the magnifications of images. Then, inside each magnification, there are "train" folder and "test" folder which all contain benign and malignant. The above maneuver was completed through Python codes which had imported PIL (Pillow library) specialized for file management.

After copying the file into corresponding directories, data are then split using a random file selecting Python code to randomly move a proportion of images into test folders so as to reach the ratio of 85%:15% between train folder and test folder. Rest of the separation of validation and training data will be done within the model, which will dynamically select 15% of the total images from the training set for validation during each training session, ultimately achieving a distribution of 70% for training, 15% for validation, and 15% for testing. The structure of the data separation is provided in Figure 20.

Figure 20: Dataset Structure after Separation

1.1.3Data Balance

Firstly, based on the Figure 21 provided below, it is noticeable that within each magnification folder, the benign images are far less than malignant images, which makes the data unbalanced. Therefore, this project had applied oversampling to balance the dataset, which is shown in Figure 22.

Figure 21: Number of images within Benign and Malignant Before Balancing

Figure 22: Images Number After Balancing

1.1.4Data Resize

As the introduction mentioned, the image resolution is 700\*460 pixels, which does not fit in the proposed model input. And therefore, this project had resized the images of all magnifications into 224\*224.

1.1.5Data Color Channel Modification

This project had modified the images utilizing Contrast Limited Adaptive Histogram Equalization (CLAHE) which are then compared with the original image training results in order to select the better one. CLAHE operates by adaptively dividing the image into several small blocks, then performing histogram equalization on each of these blocks within certain contrast limits [32]. This approach improves the histogram distribution of the image, which is essential for enhancing detail and image quality. Images are displayed in the following Figure 23.

Figure 23: Images Transformation

1.1.6Data Augmentation

The BreakHis dataset is augmented with rotations (20 degrees), shifts (20% width and height), shear (20%), zoom (20%), and horizontal flips, alongside rescaling the pixel values by 1/255. Figure 24 displays the augmentation of the image.

Figure 24: Augmented image example

1.1.7Data Preprocessing Summary

Table 2 displays the numbers of images after upsampling and are then used through the whole project. Table 3 shows the augmentation.

Magnification	Train	Test	Total
Benign			
Malignant			

40X 13001300932052898

100X 12001222962152733

200X 11801182932082663

400X 10501048881842370

Table 2: Upsampling detail for each magnification

Magnification	RR	WS	HS	SR	ZR	HF	FM
---------------	----	----	----	----	----	----	----

40X 0.20.20.20.20.2 True Nearest

100X 0.20.20.20.20.1 True Nearest

200X 0.40.30.20.30.1 True Nearest

400X 0.40.10.10.1 None True Nearest

Table 3: Different Augmentation of Different Magnification

1.2Technology

The technology used in this project is displayed in Table 4

Software Framework Tensorflow 2.9.0

CuDNN 8.9

Cuda 11.2  
 Language Python 2.9.0  
 Libraries and Application Numpy 1.25.3  
 Keras 2.9.0  
 Matplotlib 3.7  
 TensorFlow-Addons 2.10.0  
 Cloud Repository Github Repository  
 Hardware Central Processing Unit(CPU) Intel(R) Core(TM)  
 i7-8750H CPU @  
 2.2PGHz(12 CPUs),  
 ~2.2GHz  
 Graphic Processing Unit(GPU) NVIDIA GeForce GTX2060

Table 4: Summary of Relevant Technology involved in this project

### 1.3 Data Testing and Evaluation Plan

#### 1.3.1 Data Testing

By checking the BreakHis datasets downloaded from Kaggle, it is estimated that some techniques of data pre-processing will be implemented which will be displayed below.

1 This project will re-divide the original BreakHis datasets for binary classification. Considering the fact that there are four groups of magnifications of the histogram, this project will create four magnifications which contains two categories of breast cancer level from the original datasets.

2 The project will check the image size inside each magnification category and ensure the size of images are consistent, otherwise, resize techniques will be applied.

3 The project must separate the data into specific ratio for the purpose of training, validation and testing.

4 This project must check the number of each set, aimed at balancing the two categories. It will affect the model learning and diagnosis accuracy otherwise.

## 202018010212\_Final\_Report\_第7部分

### 原文内容

5 This project will apply methods of data pre-processing on the datasets and test on model training in case there are any factors such as color or contrast that affects training results.

#### 1.3.2 Model Performance Evaluation Criteria

This project will evaluate the performance of the model through following standards.

Accuracy: Accuracy is a quite intuitive metric and a criteria for evaluating model performances, which displays the overall correctness of a classification model. It calculates the ratio of the correctly predictions among the total predictions. The Equation (8) is displayed below, where T, P, N, F represents, true, **p** **ositive, negative and false**. TP, TN, FP, and FN represent the counts of correctly identified positive cases, correctly identified negative cases, incorrectly identified positive cases, and incorrectly identified negative cases, respectively, in a classification model.

Accuracy =  $\frac{TP + TN}{TP + TN + FP + FN}$  Equation (8)

Loss: This criteria measures the gap between results of prediction labels and actual labels. Below shows Equation (9) for classification.

Loss =  $- \sum_{i=1}^n \log(p_i)$  Equation (9)

Precision: This is the criteria that shows the proportion of images that are positively classified as positive. Equation (10) is shown below.

Micro Precision =  $\frac{\sum_{i=1}^n TP_i}{\sum_{i=1}^n TP_i + \sum_{i=1}^n FP_i}$  Equation (10)

Recall: This is the criteria that displays the proportion positively identified as positive samples among the actual positive samples. Equation (11) depicts recall calculation.

Micro Recall =  $\frac{\sum_{i=1}^n TP_i}{\sum_{i=1}^n TP_i + \sum_{i=1}^n FN_i}$  Equation (11)

F1-Score: F1-Score measures the performance of model by calculating the harmonic mean of Precision and Recall. Equation (12) illustrates F1-Score calculation.

Micro F1-Score =  $2 * \frac{\text{Micro Precision} * \text{Micro Recall}}{\text{Micro Precision} + \text{Micro Recall}}$  Equation (12)

Confusion Matrix: It displays the accurate number of the **True Positive, True Negative, False Positive and False Negative**.

ROC: **Receiver Operating Characteristic (ROC)**, which displays the trade-off relationships between the **True Positive Rate(also known as sensitivity or recall)** and the **False Positive Rate of a model at different thresholds**.

AUC: Area Under the ROC curve, which demonstrates the overall ability to distinguish between positive and negative samples. In the classification circumstance, AUC acts as metric to evaluate the performance of model for both classes. Generally speaking, a model is considered well performed when the curve rises towards the upper-left corner of the graph, and therefore, leaving more space to AUC. In a nut shell, the closer AUC gets to 1, the better the model is.

In summary, in order to evaluate the model performance on the binary classification of the level of breast cancer, this project will conduct a comprehensive evaluation, involving Accuracy, Loss, Precision, Recall, Precision-Recall Graph, F1-Score, Confusion Matrix, ROC graph, and AUC.

### Chapter 4 Experiment and Results

#### 1.1 Experiment Phases

1 Testing each single model such as InceptionNet, ResNet, DepthwiseNet on

the pre-processed dataset with 40X, 100X, 200X and 400X magnification. And therefore deciding which magnification is the best to train on.

2 Select the best magnification and train the model of IR-Net on the selected magnification of the dataset.

3 Build and train the DIR-Net on the selected magnification.

4 Build and train the DIRA-Net on the selected magnification.

5 Fine tune the model to achieve a better result and compare with the existed pre-trained model.

6Existing pre-trained model comparison and results comparison with previous Work.

### 1.2Inception-Net Training on Four Magnification

The first two individual models provide not only the initial judgement of the performance on the BreakHis dataset, but also insights of which magnification works better for model training.

The pure Inception-Net is trained with original (700\*460) and resize (244\*244) version images which help deciding which scale of images should remain for further training. Model structure is provided in Figure 25.

Figure 25: Initial Inception Model for experiment

Figure 26 to Figure 29 show the results of Inception-Net training on raw images.

a) Train Acc =0.9584, Val Acc =0.9497 b) Train Loss =0.1047, Val Loss =0.1362

Figure 26: a) and b) present InceptionNet Accuracy and Loss of Train and Validation sets on 40X Raw Images

a) Train Acc =0.8985, Val Acc =0.8323 b) Train Loss =0.2617, Val Loss =0.3980

Figure 27: a) and b) display the InceptionNet Train and Validation Accuracy and Loss on 100X Raw Images

a) Train Acc =0.8799, Val Acc =0.9005 b) Train Loss =0.3298, Val Loss =0.3123

Figure 28: a) and b) illustrate InceptionNet Train, Validation Accuracy and Loss on 200X Raw Images

a) Train Acc =0.9012, Val Acc =0.7782 b) Train Loss =0.2804, Val Loss =0.8079

Figure 29: a) and b) demonstrate InceptionNet Train, Validation Accuracy and Loss on 400X Raw Images

Based on Figures 26 to 29, it is evident that without resizing the images, the model's performance during training varies among four magnification factors: 40X, 100X, 200X, and 400X. Notably, the model exhibits the best fitting performance when trained on images with a 40X magnification factor among the four options.

a) Train Acc =0.9332, Val Acc =0.9438 b) Train Loss =0.1709, Val Loss =0.1617

Figure 30: a) and b) display InceptionNet Train, Validation Accuracy and Loss on 40X Resize Images

a) Train Acc =0.9295, Val Acc =0.8259 b) Train Loss =0.1918, Val Loss =0.4495

Figure 31: a) and b) display InceptionNet Train, Validation Accuracy and Loss on 100X Resize Images

a) Train Acc =0.9406, Val Acc =0.8241 b) Train Loss =0.1361, Val Loss =0.4191

Figure 32: a) and b) present InceptionNet Train, Validation Accuracy and Loss on 200X Resize Images

a) Train Acc =0.8973, Val Acc =0.7030 b) Train Loss =0.2782, Val Loss =1.0301

Figure 33: a) and b) demonstrate InceptionNet Train, Validation Accuracy and Loss on 400X Resize Images

In Figures 30 to Figure 33, after resizing the images to a size of 224 x 224 pixels to match the model input settings for this project, it is observed that, under the same four scenarios, the training performance of images with a 40X magnification factor continues to outperform the other three magnification factors.

However, considering Figure 34 and Figure 35, it becomes evident that most of the resized results surpass those without resizing. Furthermore, within the context, the training performance of images with a 40X magnification factor stands out as the most favorable. This phenomenon may be attributed to the fact that, at this magnification level, more details are captured, resulting in a richer set of features. The upcoming experiment will further validate the suitability of magnification factors on resized images.

Figure 34: Comprehensive Comparison of Validation Accuracy Among Raw and Resized Images of Four Magnifications

Figure 35: Comprehensive Comparison of Validation Loss Among Raw and Resized Images of Four Magnifications

### 1.3ResNet Training on Four Magnification

Given that the final model will be complicated, with a large number of parameters, depth, and branching, gradient vanish is quite expected. Therefore, residual structure is examined on the dataset. The initial ResNet was trained on four magnifications with resized images based on the last part results. Model details and results are presented from Figure 36 to Figure 42.

Figure 36: Initial ResNet for experiment

a) Train Acc =0.9947, Val Acc =0.9941 b) Train Loss =0.0199, Val Loss =0.0298

Figure 37: a) and b) illustrate ResNet Train, Validation Accuracy and Loss on 40X Resized Images

a) Train Acc =0.9948, Val Acc =0.8956 b) Train Loss =0.0143, Val Loss =0.6940

Figure 38: a) and b) display ResNet Train and Validation Accuracy and Loss on 100X Resized Images

a) Train Acc =0.9918, Val Acc =0.8931 b) Train Loss =0.0293, Val Loss =0.5330

Figure 39: a) and b) display ResNet Train, Validation Accuracy and Loss on 200X Resized Images

a) Train Acc =0.9837, Val Acc =0.8308 b) Train Loss =0.0459, Val Loss =0.8232

## 202018010212\_Final\_Report\_第8部分

### 原文内容

Figure 40: a) and b) display ResNet Train, Validation Accuracy and Loss on 400X Resized Images

According to Figure 37 to Figure 40, the ResNet model's performance at various magnifications post-resizing reveals high training and validation accuracy rates at 40X, indicating successful feature capture. This is crucial for practical applications where the balance between resolution and recognizable features is delicate. However, at 100X, 200X, and 400X magnifications, there is a divergence between training and validation accuracy, suggesting overfitting. This could suggest the need for more complex models or refined training strategies to prevent the model from latching onto noise. Alternatively, sophisticated data preprocessing or augmentation techniques could help the model focus on relevant features.

Moreover, through the observation in Figure 41 and Figure 42, model's validation accuracy is best at 40X magnification, demonstrating minimal volatility. This balance captures enough detail for accurate classification without complexity. Future model development should focus on 40X magnification, aligning with the model's strengths and aiming for efficient diagnostic accuracy. This approach could simplify learning features, enhance predictive performance, and potentially increase clinical value.

Figure 41: ResNet Validation Accuracy Comparison

Figure 42: ResNet Validation Loss Comparison

### 1.4Depthwise Network Training on 40X Magnification

Both prior structures performed well in diagnosing the BreakHis dataset at 40X magnification. However, the basic notion of stacking numerous Inception-ResNet blocks may result in a large increase in the number of training parameters. To overcome this, depthwise convolution was included in the experiment. This addition reduces the number of parameters and computational burden while maintaining the model's efficiency and effectiveness. This network serves as an experiment on how depthwise structured network performs on the dataset therefore foresees how this network will affect the combined network. Architectures and results are illustrated within Figure 43 and Figure 44.

Figure 43: Depthwise CNN for experiment

a) Train Acc =0.9500, Val Acc =0.9763 b) Train Loss =0.1334, Val Loss =0.0929

Figure 44: a) and b) display Depthwise-CNN Train, Validation Accuracy and Loss on 40X Magnified Images

The depthwise convolution in 40X magnification network training has shown improved efficiency in parameter utilization and computation. The model maintains high training accuracy and mirrors this performance in validation metrics, a quality that Inception and ResNet structures may not fully achieve due to larger parameter sets. The stability in the validation loss curve indicates the depthwise network is less susceptible to fluctuations during learning, indicating a robust model capable of generalizing beyond training data without overfitting. This efficiency is expected to contribute to the integrated model, potentially playing a critical role in the training process and overall model performance.

1.5 Inception-ResNet (IR-Net) Training on 40X Magnification

To establish a foundational blueprint for the final model, we've constructed an initial Inception-ResNet model. This step aims to harness Inception's detailed feature extraction and ResNet's efficient backpropagation to create a robust structure. Testing this model at 40X magnification will help assess its training effectiveness and inform its influence on the final model's performance. Figure 45 and 46 represent the structure of Inception-ResNet, and Figure 47 illustrates the results training on the 40X magnified images.

Figure 45: Inception-ResNet STEM block. This prototype model is the same as the prototype in chapter 3.

a) Inception-ResNet-Block-A b) Inception-ResNet-Block-B c) Inception-ResNet-Block-C

d) Inception-ResNet-Reduction-Block-A e) Inception-ResNet-Reduction-Block-B

Figure 46: Inception-ResNet Structure for experiment

a) Train Acc =0.9527, Val Acc =0.9467 b) Train Loss =0.1302, Val Loss =0.1354

Figure 47: a) and b) display InceptionResNet Train, Validation Accuracy and Loss on 40X Magnified BreakHis Resized images

The Inception-ResNet model trained at 40X magnification shows promising results, with rapid convergence in both training and validation accuracy. The model's loss graph shows a sharp decrease and plateau, indicating it's not overfitting and minimizing loss effectively. The model's stability at high values is crucial for clinical applicability, ensuring reliable diagnoses. The fusion of these architectures potentially primes the final model for robust performance.

1.6 Depthwise-Inception-ResNet (DIR-Net) Training on 40X Magnification

A unified model, DIR-NET, has been developed, introducing depthwise convolutional layers to the Inception-ResNet framework, aiming to add complexity without increasing computational load. The goal is to maintain a deep network design while achieving an efficient training process. Figures 48 to 50 illustrate the modified Inception-ResNet block A and the DIR model along with the results.

Figure 48: Depthwise-Inception-ResNet Block A

Figure 49: DIR model overview. Rest of the blocks remain the same as in Inception-ResNet in 4.5

a) Train Acc =0.9310, Val Acc =0.9438 b) Train Loss =0.1699, Val Loss =0.1496

Figure 50: a) and b) demonstrate Depthwise-Inception-ResNet Train, Validation Accuracy and Loss on 40X Magnified Images

The DIR-Net trained on 40X magnification shows a positive trend in learning, with steady increases in model accuracy and a decrease in loss over epochs. Both training and validation accuracies show an upward trajectory, indicating effective learning. However, fluctuations in validation accuracy suggest room for improvement in model stability. These fluctuations may be due to the model responding to complex patterns or sensitivity to validation set specifics. Integrating an attention mechanism in subsequent iterations could address these oscillations, focusing on salient input data, reducing performance variance, and mitigating underfitting by leveraging more informative features.

1.7 DIRA-Net Training on 40X Magnification

This part added the attention mechanism into the STEM block of the DIR-Net and while maintaining other blocks same as they were in 4.5 and 4.6. Following Figure 51 and Figure 52 represent the modification which will be the final structure of STEM block as mentioned in Chapter 3, and Figure 53 depicts the results for the initial DIRA-net.

Figure 51: STEM Block with attention mechanism

Figure 52: Initial DIRA-Net (With DIR-Block used 5 times, IR Block B and C used 10 and 5 times respectively)

a) Train Acc =0.9567, Val Acc =0.9852 b) Train Loss =0.1005, Val Loss =0.0570

Figure 53: a) and b) demonstrates the model accuracy and loss

1.8 CLAHE Experiment

After implementing the original DIRA-Net model, it is vital to determine whether the color of the picture affects performance, therefore CLAHE images were compared to earlier images, and the findings are shown in Figure 54.

a) Train and Val Acc b) Train and Val Loss

Figure 54: CLAHE Test Results

The DIRA-Net model's performance was evaluated, finding that CLAHE-enhanced images had suboptimal accuracy, suggesting distortion of information. Standard RGB images performed better, highlighting the importance of color in maintaining diagnostic accuracy. Therefore, CLAHE color alterations were excluded.

1.9 Model Evolution Summary

Table 5 displays the training results throughout the evolution of model from the first single model to the initial version of the proposed model before fine tune.

Magnification Magnification & Size Validation Accuracy Validation Loss

Individual InceptionNet Raw Images

40X 0.94970.1362

100X 0.83230.3980

200X 0.90050.3123

400X 0.77820.8079

Resized:224\*224  
40X 0.94380.1617  
100x 0.82590.4495  
200x 0.82410.4191  
400x 0.70301.0301  
Individual ResNet Resize:224\*224  
40X 0.99410.0298  
100X 0.89560.6940  
200X 0.89310.5330  
Depthwise-  
CNN Resize:224\*224

## 202018010212\_Final\_Report\_第9部分

### 原文内容

40X 0.97630.0929  
IR-Net Resize:224\*224  
40X 0.94670.1354  
DIR-Net Resize:224\*224  
40X 0.94380.1496  
DIRA-Net Resize:224\*224  
40X 0.98520.0570  
Table 5: Model Evolution Summary  
1.10Fine Tune

The fine-tuning step focuses on improving the model's architecture and hyperparameters to get the greatest potential performance. To vary the model's depth, adjust the number of times of Depthwise Inception ResNet Blocks as well as Inception-ResNet Blocks B and C being used. Furthermore, fine-tuning will entail adjusting the dropout rates to avoid overfitting and building a learning rate scheduler for more effective training. Table 6 details the essential parameters in the preliminary version of the proposed model, establishing the framework for these fine-tuning modifications.

Batch Size DIR-Block Called Times IR-Block-B Called Times IR-Block-C Called Times LR Dropout Epoch Para  
3251050.010.5150486,321

Table 6: Hyperparameters of the initial DIRA-Net

The results and details of hyperparameters of modifications are shown in the following graphs and tables, where Times is the number of times each of these three blocks were used.

First attempt of fine-tuning, as detailed in Figure 55 and Table 7, entailed reducing IR-Block B's frequency to eight and applying a dynamic learning rate reduction from 0.01. The diminished results, showcasing a minimal accuracy gap between validation and training only at the endpoint, indicate potential structural issues in the model, which may be too complex or simple for the given task. Subsequent steps will involve reinstating the original frequency of layer usage and examining the impact of batch size, filter number, and learning rate to discern their individual effects.

VN BS FN Times LR Patience Dropout Epoch L2  
132165,8,50.01100.5150 No

Table 7: Hyperparameters of model fine tune version 1

a) Train Acc =0.9412, Val Acc =0.9497 b) Train Loss =0.1517, Val Loss =0.1262

Figure 55: a) and b) are training results when DIR-Block is called 5 times, IR-Block-B is called 8 times, and IR-Block-C is called 5 times

As shown in Figure 56 and Table 8, by reducing the batch size to 16 and maintaining the frequency of each layer, it does not significantly resolve the underfitting problem. It indicates that batch size and filter numbers of STEM Block layers could not be the main effect of model performance which could be decreased afterwards to reduce parameters and maintain high accuracy. Additionally, model performance might still be limited by each part's usage, learning rate, dropout, and whether regularization is used.

VN BS FN Times LR Patience Dropout Epoch L2  
21685,10,50.01100.5150 No

Table 8: Hyperparameters of version 2

a) Train Acc =0.9293, Val Acc =0.9438 b) Train Loss =0.1870, Val Loss =0.1543

Figure 56: a) and b) training results when DIR-Block is called 5 times, IR-Block-B is called 10 times, and IR-Block-C is called 5 times with 16 Batch Size, with the first layer of STEM Block using 8 filters

Figure 57 and table 9 shows notable improvement with learning rate starting from 0.001. This suggests that the initial learning rate may have been high, and that lower starting point is more conducive for the model to effectively learn and properly converge.

VN BS FN Times LR Patience Dropout Epoch L2  
33285,10,50.001100.5150 No

Table 9: Hyperparameters for version 3

a) Train Acc =0.9536, Val Acc =0.9497 b) Train Loss =0.1221, Val Loss =0.1221

Figure 57: a) and b) demonstrate results of DIR-Block Called 5 times, IR-Block-B called 10 times, IR-Block-C called 5 times, batch size 32, with the first layer of attention stem block using 8 filters

In order to further optimize the model, regularization is added with reduction of filter numbers in STEM block in Table 10. However, the resulting underfitting in Figure 58 suggests that while regularization helps in controlling model complexity, the parameter tuning might have been too stringent which cannot capture enough patterns from the data.

VN BS FN Times LR Patience Dropout Epoch L2  
43245,10,50.001100.5150 Yes

Table 10: Hyperparameters of Version 4

a) Train Acc =0.9244, Val Acc =0.9467 b) Train Loss =0.2002, Val Loss =0.1655

Figure 58: a) and b) illustrate results of DIR-Block Called 5 times, IR-Block-B called 10 times, IR-Block-C called 5 times. And added L2 regularization  
Moving into the fifth modification, Figure 59 and Table 11 display an increase in IR-Block C frequency to address model's oversimplification from L2 regularization. It led to further underfitting, which hints that the mode might be more sensitive to block usage frequency.

VN BS FN Times LR Patience Dropout Epoch L2

53245,10,70.001100.4150 Yes

Table 11: Hyperparameters of Version 5

a) Train Acc =0.9156, Val Acc =0.9408 b) Train Loss =0.2133, Val Loss =0.1582

Figure 59: a) and b) display results of DIR-Block Called 5 times, IR-Block-B called 10 times, IR-Block-C called 6 times. And added L2 regularization  
Few attempts of usage frequency were conducted, only the following three possess significant changes and could indicate the impact of blocks.  
Looking into Figure 60 and Table 12, the obvious reduction of three blocks and a lower dropout rate had led to better model performance evidently through the smaller gap between train and validation accuracy and the lowering losses.

VN BS FN Times LR Patience Dropout Epoch L2

63244,5,40.001100.4150 Yes

Table 12: Hyperparameters of Version 6

a) Train Acc =0.9770, Val Acc =0.9763 b) Train Loss =0.0905, Val Loss =0.0889

Figure 60: a) and b) are results of DIR-Block Called 4 times, IR-Block-B called 5 times, IR-Block-C called 4 times. And added L2 regularization  
However, table 13 and figure 61 displayed an arresting underfitting while the IR-Block C usage frequency once again stand out from the issue. This suggests that the overuse of IR-Block C indeed causes some levels of underfitting.

VN BS FN Times LR Patience Dropout Epoch L2

73241,2,50.001100.3150 Yes

Table 13: Hyperparameters of Version 7

a) Train Acc =0.9501, Val Acc =0.9675 b) Train Loss =0.1500, Val Loss =0.1380

Figure 61: a) and b) are results of DIR-Block Called 1 times, IR-Block-B called 2 times, IR-Block-C called 5 times. And added L2 regularization  
According to table 14 and figure 62, performance of model had increased and underfitting were prominently resolved with an extreme reduction of the usage frequency which indicates that complexity of model was high due to the numbers of branches and layers within each block.

VN BS FN Times LR Patience Dropout Epoch L2

83241,1,10.001100.3150 Yes

Table 14: Hyperparameters of Version 8

a) Train Acc =0.9390, Val Acc =0.9379 b) Train Loss =0.1641, Val Loss =0.1796

Figure 62: a) and b) show results of DIR-Block Called 1 times, IR-Block-B called 1 times, IR-Block-C called 1 times. And added L2 regularization  
Finally, table 15 and figure 63 displayed the results of the last attempt, which perfectly resolve the performance issue by adding layers into the model with the slight usage frequency increase of IR-Block B.

VN BS FN Times LR Patience Dropout Epoch L2

9

(Proposed)3241,2,10.001100.3150 Yes

Table 15: Hyperparameter of Proposed Version

a) Train Acc =0.9753, Val Acc =0.9645 b) Train Loss =0.0929, Val Loss =0.1070

Figure 63: a) and b) demonstrate results of DIR-Block Called 1 times, IR-Block-B called 2 times, IR-Block-C called 1 times. And added L2 regularization  
After fine-tuning, the model achieved a balance between structural complexity and performance, avoiding overfitting or underfitting. The consistency in loss and accuracy graphs confirmed its competence. The final structure delivered commendable statistical metrics and proven capability in practical breast cancer classification scenarios. Figure 64 displays all the evaluation matrix of the proposed model. Table 16 summarizes the modified results and parameters in each round, where Acc, Loss, F1, Rec, Prec, Spec, Para represents Accuracy, Loss, F1-Score, Recall, Precision, Specificity, Area Under Curve, Total Parameters, which are all statistics of validation.

## 202018010212\_Final\_Report\_第10部分

### 原文内容

And Table 16 summarized the fine-tune process.

a) Train Acc =0.9753, Val Acc =0.9645 b) Train Loss =0.0929, Val Loss =0.1070

c) Train Prec =0.9753, Val Prec =0.9645 d) Train Recall=0.9753, Val Recall=0.9645

e) Train F1=0.9753, Val F1=0.9645 f) Train AUC=0.9968, Val AUC=0.9968

g) Confusion Matrix, where Class 0 and Class 1 represents Benign and Malignant h) ROC Curve Graph AUC =0.93

i) Precision-Recall Curve

Figure 64: a) to i) represents all the matrix of the proposed model, as micro-f1 score, micro-precision, micro-recall has the same calculation in binary which results in similar graph.

VN Acc

(%) Loss

(%) F1(%) Rec (%) Prec

(%) Spec

(%) AUC

(%) Para

194.9712.6293.9895.5891.2492.9494448,121

294.3815.4390.9492.3894.4191.2092490,033

394.9712.2189.8491.3294.8790.2191505,821

494.6716.5591.1793.4594.6790.2490505,812

594.088.8993.7392.2494.4691.26911,152,825  
697.638.9093.2694.4197.6293.4094372,989  
796.7513.8094.3096.4896.7592.1394703,533  
893.7917.9690.6793.9693.7987.6491273,617  
9(Proposed)96.4510.7096.4592.2496.4594.4493313,597

Table 16: Fine tune process and results summary

#### 1.11 Comparison Analysis

Table 17 and 18 below shows the comparison analysis of the proposed model and previous works, figure 65 and 66 displays the comparison with pre-trained models.

Authors	Datasets	Acc (%)	Loss (%)	AUC (%)	f1 (%)	Sen (%)	Spec (%)	Prec (%)
Hirra et al.[1]	Histopathology images	86.15	X	X	87.98	X		
Sahu et al.[9]	Mini-DDSM	99.17	X	99.99	99.09	99.5	X	
	Ultrasound Images	(BUSI)96.92	X	96.98	98.89	94.62	X	
Liang and Meng [19]	BreakHis	95.50	X	X	X	X	X	X
Alkhalidi and Salari [20]	Invasive-Ductal-Carcinoma (IDC)	92.87	X	X	90.85	99.09	98.93	6
Xu et al.[21]	BreakHis	98.0	X	X	X	X	X	X
Wu et al.[22]	224,426 mammography	X	X	89	X	X	X	X
Chougrad et al.[23]	DDSM	97.35	X	98	X	X	X	X
INbreast	95.50	X	97	X	X	X	X	X
BCDR	96.67	X	96	X	X	X	X	X
Yu et al.[24]	INbreast mini-DDSM	(Merged)96.11	X	X	X	92.89	85.59	5.7
Arya and Saha [25]	1,980 patients' breast cancer data	90.2	X	93	X	X	X	X
Chattopadhyay et al.,[26]	BreakHis	97.12	X	X	96.96	X	97	
Addo et al.,[27]	BreakHis	99.15	X	X	X	X	X	X
Proposed	BreakHis	96.45	10.07	93.92	92.94	97		

Table 17: Comparison Analysis with Previous Works

Based on Table 17, the proposed model had reached ideal results comparing to previous researches. It is noticeable that the accuracy had surpassed some of those using histopathological images and reached similar performance as others. Moreover, other evaluation statistics such as AUC, sensitivity, specificity F1-Score and precision were also either higher or similar to previous models. Moving on, a comparison with two popular pre-trained models were conducted, and results are provided in Figure 65, Figure 66 and Table 18.

Figure 65: DIRA-Net Validation Accuracy Comparison with Pre-trained Models

Figure 66: DIRA-Net Validation Loss Comparison with Pre-trained Models

#### Model Acc

Model	Acc (%)	Loss (%)	F1 (%)	Rec (%)	Prec (%)	Spec (%)	AUC (%)	Para
ResNet50V2-Pretrained	99.41	2.57	94.18	98.42	99.41	87.47	93.24	6,14,914
InceptionV3-Pretrained	94.67	14.70	88.69	94.52	90.67	81.31	88.22	852,898
DIRA-Net	96.45	10.17	96.45	96.45	93.09	94.44	93.31	3,597

Table 18: Results Comparison of DIRA-Net with Pre-trained Models

In comparison with existing pre-trained models, DIRA-Net not only matches their accuracy levels but also ensures higher efficiency with far fewer parameters, as demonstrated in the tables. This underlines the advantages of the proposed model, showcasing its ability to achieve optimal performance with a more compact and efficient architecture.

#### 1.12 Model Visualization

Figure 67 and 68 visualize the focus point of the model on images which involved using both SHAP and Grad-CAM.

SHAP is a method that enhances interpretability of machine learning-based equalizers, especially in short-reach intensity modulation and direct detection systems. It visualizes and analyzes trained equalizers, reducing feature count without compromising performance, and offers a universal technique for system optimization and feature selection [33].

In SHAP analysis, red represents features that influence the model's prediction toward a specific class, while blue indicates features that contradict it. Using Figure 64 as an example, the first image shows predominantly blue in the 'benign' part and red in the malignant section of the heatmap, indicating a malignant forecast. In the second figure, the 'benign' part has larger red area, whereas malignant section has wider blue area, indicating a benign prediction.



Figure 67: SHAP Visualization

Grad-CAM is a technique that visualizes Convolutional Neural Networks (CNNs) by highlighting localizations in images which enhances the interpretability of the model and extracts important variables [34]. How it works is that, the more blue the area is, the more focus the model is.

Figure 68: Grad-CAM Visualization

#### 1.13 Model Deployment

The provided figures showcase the deployment website for our proposed model. On the homepage, users can find essential details and links to the breast cancer dataset. The "Get Diagnosis" button navigates users to the diagnostic page, where, upon scrolling down, one can find a description of the dataset accompanied by a link to its Kaggle source. This link directs users to the detailed data source as depicted in Figures 69 and Figure 70.

Figure 69: Main Page

Figure 70: Dataset Introduction Cards

The diagnosis page features an intuitive drag-and-drop area for image uploads, and upon submitting an image with the "Get Diagnose" button, the page presents the classification results. For instance, as illustrated in Figure 71 and Figure 73, The system uses BreakHis dataset images to determine benign or malignant cases, with a bar chart indicating the model's confidence in the prediction, with green bars representing benign cases and red bars representing malignancy.

Figure 71: Diagnosis Page before Diagnosis

Figure 72: Malignant Diagnosis

Figure 73: Benign Diagnosis

## Chapter 5 Project Management

### 1.1 Activities

#### Phase Task Status

- 1-1 Conduct Breast Cancer Diagnosis Research Complete
- 1-2 Identify and Narrow issues Complete
- 1-3 Dig into solutions of deep learning method for breast cancer diagnosis Complete
- 1-4 Study classification methods and models Complete
- 2-1 Research on breast cancer diagnosis specifically in CNNs Complete
- 2-2 Study six CNN models and relevant programming methods Complete
- 2-3 Understand evaluation methods of CNNs Complete
- 2-4 Investigate mechanisms to improve models and performances Complete
- 3-1 Gather 1 to 3 datasets from Kaggle and select one suitable dataset Complete
- 3-2 Complete basic data separation and preprocessing Complete
- 3-3 Test the processed data on pre-trained models Complete
- 4-1 Construct models with different combination of different mechanisms Complete
- 4-2 Train the different combinations of model on the dataset Complete
- 4-3 Conduct selection of mechanisms based on the training results Complete
- 4-4 Sort out the experiments process and start fine-tuning Complete
- 5-1 Compare the fine-tuned model with original final model and other existing model Complete
- 5-2 Deploy the model with website application Complete
- 5-3 Finish the final report, deployment and presentation preparation Complete

Table 19: Activities of the Project

#### 1.1.1 Schedule

The schedule is shown in Table 20.

Table 20: Gantt Graph

#### 1.1.2 Project Version Management

To manage the different versions of codes modification, I plan to use Github as the version management tools for keeping code updated and secure.

URL is as follow: [https://github.com/Vio1etV/Final\\_Year\\_Project](https://github.com/Vio1etV/Final_Year_Project)

Version Number Code Name Content Results

##### 1 Initial experiment

models Experiments of Inception-Net, Res-Net, Depthwise-Net.

Raw and preprocessed images. Training results,

CSV files of

training,

initial model

design diagrams

##### 2 Combination of

models Experiments of IR-Net, DIR-Net, initial DIRA-Net. Training results

CSV file of

training,

initial design

diagrams,

.h5 file of initial DIRA-Net.

##### 3 DIRA-Net fine tune All the .ipynb files of each

## 202018010212\_Final\_Report\_第11部分

### 原文内容

fine-tuned model. .h5 files of

DIRA-Net,

training results,

Model verification files

4 Model deployment The web-application program where the model can be added.

Model .h5 file Web application and model .h5 files

Table 21: Version Control Progress

1.1.3Project Data Management

.All files including datasets, model codes, references, weekly reports and all sorts will be replicated into three copies for fail safe, one on local computer, one on hard drive, one on github.

.Upload the project to github for every modification, synchronize latest version.

Following are documents of the Project for uploading and synchronization:

1.Reports (Weekly, Proposal, Progress, Final)& Presentation PPT

2.CNN model diagram

3.References

4.Datasets Link

5.Model evaluation documents

6.CNN model codes (Different versions)

7.Model Deployment Codes

1.1.4Project Deliverable

.The project proposal

.Weekly report

.Progress Report

.Final Project Report

.Project codes (Model codes & Deployment Codes)

.Project presentation slides

1.2Risk Analysis

Table 22 displays the analyzed risks during the project progress.

Risk ID Potential Risk Cause ID Potential Causes Severity Likelihood Risk Mitigation

ID Mitigation

R

1.1 Loss of Project Data C

1.1.1 Poor version Control 414 M1.1.1 Regularly update project to cloud

Physical Hardware Failure 414 M1.1.2 Hardware

Check & Backup

R

1.2 Memory Leakage C

1.2.1 Model training exceeds the hardware ability 4312 M1.2.1 Use cloud service

R

1.3 Model training issues C

1.3.1 Data imbalance 248 M1.3.1 Augmentation & Upsampling

C

1.3.2 Low data quality 414 M1.3.2 Find trusted source on kaggle

R

1.4 Software issues C

1.4.1 Virtual environment error 414 M1.4.1 Keep Virtual Environment Clean

R

2.1 Miss deadline C

2.1.1 Illness 313 M2.1.1 Keep healthy

C

1.3.2 Poor time

management 414 M2.1.2 Strictly follow a schedule

Table 22: Risk Analysis

1.3Professional Issues

In the course of this project' s development, **it is critical to address a wide spectrum of legal, social, ethical,** and environmental concerns. This involves obeying the professional standards set forth by institutions like ACM(**Association for Computing Machinery**) and the BCS (**The British Computer Society**).

**Legal:** Legal issues surrounding the use of deep learning technologies in breast cancer diagnosis are influenced by strict privacy standards like HIPAA and GDPR. These protocols govern the handling of sensitive patient information, including data anonymization and encryption. Legal elements include liability for diagnostic accuracy and intellectual property, ensuring that models respect all parties' legal rights during development, use, and sharing.

**Social:** Deep learning for breast cancer diagnosis necessitates a social approach, ensuring accessibility, reducing healthcare inequities, and fostering public confidence. Clear communication about benefits and drawbacks, managing relationships with diverse stakeholders, and encouraging an inclusive approach can improve health outcomes and public trust.

**Ethical:** Deep learning in breast cancer detection requires a cautious approach to ensure accurate and impartial diagnosis. This includes reducing biases, increasing openness, and ensuring informed consent. Patients should be informed about AI usage and consequences, and continuous ethical oversight is necessary to monitor and assess the technology's impact. This proactive governance ensures AI systems' integrity and trustworthiness in healthcare.

Environment: From an environmental perspective, the use of deep learning models in breast cancer detection has implications such as a significant energy consumption and carbon footprint due to the computational intensity of training these models. It's important to consider and strive for energy-efficient computing practices to mitigate this impact.

Using deep learning for breast cancer detection raises complex legal, social, ethical, and environmental considerations, including data privacy, equitable access, algorithmic fairness, transparency, and energy efficiency. If handled and operated properly, the aforementioned issues associated with using deep learning for breast cancer detection can be effectively mitigated.

#### Chapter 6 Conclusion

Throughout the project, a novel deep learning model, DIRA-Net, was successfully constructed and validated on BreakHis public dataset, aims to improve breast cancer diagnostic accuracy using histopathological pictures. The model combines Inception and ResNet architectures, depthwise convolutions and an attention mechanism, resulting in impressive performance metrics. DIRA-Net achieved an accuracy of 96.45%, an AUC of 93%, and an F1-Score of 92.14%, sensitivity of 92.42, specificity of 94.44% and overall 93.09% precision, indicating its potential as a critical tool in medical diagnostics.

The model's efficiency and accessibility, especially for real-time diagnostic applications, were enhanced by reducing the number of trainable parameters. The project's thorough methodology, including dataset preparation, model construction and various experiments, demonstrated its effectiveness and practical usage. Comparative analysis further supported the model's unique features. It also illustrates how diverse deep learning techniques can be seamlessly integrated to improve diagnostic performance in medical imaging.

Although DIRA-Net has shown great performance in binary classification of breast cancer using histopathological images, its capacity to handle more complicated diagnostic situations is restricted. The model's multi-class classification proficiency now requires additional enhancement in order to properly discriminate between different forms of breast cancer on the BreakHis dataset. Improving this component of DIRA-Net would allow for more complete symptom analysis and precisely targeted treatment programs, making it more comprehensive and useful in clinical settings.

To enhance the robustness and utility of DIRA-Net, it is crucial to verify its performance on various public breast cancer datasets beyond BreakHis. This will improve diagnostic accuracy and clinical effect, expanding its influence on medical imaging and patient care in the breast cancer community. Future studies will enhance the model's generalizability and advance the development of more adaptable and effective diagnostic tools.

#### Reference

- [1]J. Hirra et al., "Breast Cancer Classification From Histopathological Images Using Patch-Based Deep Learning Modeling," IEEE Access, vol. 9, pp. 24273–24287, 2021, doi: 10.1109/ACCESS.2021.3056516.
- [2]M. Desai and M. Shah, "An anatomization on breast cancer detection and diagnosis employing multi-layer perceptron neural network (MLP) and Convolutional neural network (CNN)," Clin. EHealth, vol. 4, pp. 1–11, 2021, doi: 10.1016/j.ceh.2020.11.002.
- [3]G. Hamed, M. Marey, S. E. Amin, and M. F. Tolba, "Automated Breast Cancer Detection and Classification in Full Field Digital Mammograms Using Two Full and Cropped Detection Paths Approach," IEEE Access, vol. 9, pp. 116898–116913, 2021, doi: 10.1109/ACCESS.2021.3105924.
- [4]F. F. Ting, Y. J. Tan, and K. S. Sim, "Convolutional neural network improvement for breast cancer classification," Expert Syst. Appl., vol. 120, pp. 103–115, Apr. 2019, doi: 10.1016/j.eswa.2018.11.008.
- [5]H. Aljuaid, N. Alturki, N. Alsubaie, L. Cavallaro, and A. Liotta, "Computer-aided diagnosis for breast cancer classification using deep neural networks and transfer learning," Comput. Methods Programs Biomed., vol. 223, p. 106951, Aug. 2022, doi: 10.1016/j.cmpb.2022.106951.
- [6]A. Chetlen, J. Mack, and T. Chan, "Breast cancer screening controversies: who, when, why, and how?," Clin. Imaging, vol. 40, no. 2, pp. 279–282, Mar. 2016, doi: 10.1016/j.clinimag.2015.05.017.

## 202018010212\_Final\_Report\_第12部分

### 原文内容

- [7]Y. M. George, H. H. Zayed, M. I. Roushdy, and B. M. Elbagoury, "Remote Computer-Aided Breast Cancer Detection and Diagnosis System Based on Cytological Images," IEEE Syst. J., vol. 8, no. 3, pp. 949–964, Sep. 2014, doi: 10.1109/JSYST.2013.2279415.
- [8]M. T. McCann, J. A. Ozolek, C. A. Castro, B. Parvin, and J. Kovacevic, "Automated Histology Analysis: Opportunities for signal processing," IEEE Signal Process. Mag., vol. 32, no. 1, pp. 78–87, Jan. 2015, doi: 10.1109/MSP.2014.2346443.
- [9]A. Sahu, P. K. Das, and S. Meher, "An efficient deep learning scheme to detect breast cancer using mammogram and ultrasound breast images," Bio med. Signal Process. Control, vol. 87, p. 105377, Jan. 2024, doi: 10.1016/j.bspc.2023.105377.
- [10]H. Lee, J. Park, and J. Y. Hwang, "Channel Attention Module with Multi-scale Grid Average Pooling for Breast Cancer Segmentation in an Ultrasound Image," IEEE Trans. Ultrason. Ferroelectr. Freq. Control, pp. 1–1, 2020, doi: 10.1109/TUFFC.2020.2972573.
- [11]M. Toğaçar, K. B. Özkurt, B. Ergen, and Z. Cömert, "BreastNet: A novel convolutional neural network model through histopathological images for the diagnosis of breast cancer," Phys. Stat. Mech. Its Appl., vol. 545, p. 123592, May 2020, doi: 10.1016/j.physa.2019.123592.
- [12]S. Jiang and V. Zavala, "Convolutional Neural Nets in Chemical Engineering: Foundations, Computations, and Applications," AIChE J., vol. 67, May 2021, doi: 10.1002/aic.17282.
- [13]S. Albawi, T. A. Mohammed, and S. Al-Zawi, "Understanding of a convolutional neural network," in 2017 International Conference on Engineering and Technology (ICET), Aug. 2017, pp. 1–6. doi: 10.1109/ICEngTechnol.2017.8308186.
- [14]J. Schmidhuber, "Deep learning in neural networks: An overview," Neural Netw., vol. 61, pp. 85–117, Jan. 2015, doi: 10.1016/j.neunet.2014.09.003.
- [15]J. Xu, Z. Li, B. Du, M. Zhang, and J. Liu, "Reluplex made more practical: Leaky ReLU" .
- [16]K. He, X. Zhang, S. Ren, and J. Sun, "Delving Deep into Rectifiers: Surpassing Human-Level Performance on ImageNet Classification," in 2015 IEEE International Conference on Computer Vision (ICCV), Santiago, Chile: IEEE, Dec. 2015, pp. 1026–1034. doi: 10.1109/ICCV.2015.123.
- [17]H. Wang, S. Xu, K. Fang, Z.-S. Dai, G.-Z. Wei, and L.-F. Chen, "Contrast-enhanced magnetic resonance image segmentation based on improved U-Net and Inception-ResNet in the diagnosis of spinal metastases," J. Bone Oncol., vol. 42, p. 100498, Oct. 2023, doi: 10.1016/j.jbo.2023.100498.
- [18]I. U. Haq, H. Ali, H. Y. Wang, C. Lei, and H. Ali, "Feature fusion and Ensemble learning-based CNN model for mammographic image classification," J. King Saud Univ. - Comput. Inf. Sci., vol. 34, no. 6, pp. 3310–3318, Jun. 2022, doi: 10.1016/j.jksuci.2022.03.023.
- [19]Y. Liang and Z. Meng, "Brea-Net: An Interpretable Dual-Attention Network for Imbalanced Breast Cancer Classification," IEEE Access, vol. 11, pp. 100508–100517, 2023, doi: 10.1109/ACCESS.2023.3314978.
- [20]E. Alkhalidi and E. Salari, "Ensemble Optimization for Invasive Ductal Carcinoma (IDC) Classification Using Differential Cartesian Genetic Programming," IEEE Access, vol. 10, pp. 128790–128799, 2022, doi:

10.1109/ACCESS.2022.3228176.

[21]B. Xu et al., "Attention by Selection: A Deep Selective Attention Approach to Breast Cancer Classification," IEEE Trans. Med. Imaging, vol. 39, no. 6, pp. 1930–1941, Jun. 2020, doi: 10.1109/TMI.2019.2962013.

[22]N. Wu et al., "Deep Neural Networks Improve Radiologists' Performance in Breast Cancer Screening," IEEE Trans. Med. Imaging, vol. 39, no. 4, p. 1184–1194, Apr. 2020, doi: 10.1109/TMI.2019.2945514.

[23]H. Chougrad, H. Zouaki, and O. Alheyane, "Deep Convolutional Neural Networks for breast cancer screening," Comput. Methods Programs Biomed., vol. 157, pp. 19–30, Apr. 2018, doi: 10.1016/j.cmpb.2018.01.011.

[24]X. Yu, C. Kang, D. S. Guttery, S. Kadry, Y. Chen, and Y.-D. Zhang, "ResNet-SCDA-50 for Breast Abnormality Classification," IEEE/ACM Trans. Comput. Biol. Bioinform., vol. 18, no. 1, pp. 94–102, Jan. 2021, doi: 10.1109/TCBB.2020.2986544.

[25]N. Arya and S. Saha, "Multi-modal classification for human breast cancer prognosis prediction: Proposal of deep-learning based stacked ensemble model," IEEE/ACM Trans. Comput. Biol. Bioinform., pp. 1–1, 2020, doi: 10.1109/TCBB.2020.3018467.

[26]S. Chattopadhyay, A. Dey, P. K. Singh, D. Oliva, E. Cuevas, and R. Sarkar, "MTRRE-Net: A deep learning model for detection of breast cancer from histopathological images," Comput. Biol. Med., vol. 150, p. 106155, Nov. 2022, doi: 10.1016/j.combiomed.2022.106155.

[27]D. Addo et al., "A hybrid lightweight breast cancer classification framework using the histopathological images," Biocybern. Biomed. Eng., vol. 44, no. 1, pp. 31–54, Jan. 2024, doi: 10.1016/j.bbe.2023.12.003.

[28]R. Athilakshmi, R. Jansi, and R. Upadhyay, "Enhancing Diabetic Retinopathy Diagnosis with Inception v4: A Deep Learning Approach," in 2023 5th International Conference on Inventive Research in Computing Applications (ICIRCA), Coimbatore, India: IEEE, Aug. 2023, pp. 905–910. doi: 10.1109/ICIRCA57980.2023.10220890.

[29]C. Szegedy, S. Ioffe, V. Vanhoucke, and A. Alemi, "Inception-v4, Inception-ResNet and the Impact of Residual Connections on Learning," arXiv, Aug. 23, 2016. Accessed: Mar. 12, 2024. [Online]. Available: <http://arxiv.org/abs/1602.07261>

[30]Y. Wang, Z. Yang, S. Ren, X. Gouliu, J. Gao, and T. Wang, "DDRSNet-Rail Surface Defects Classification Based on Depthwise-Dilated Convolution," in 2023 International Conference on Image Processing, Computer Vision and Machine Learning (ICICML), Nov. 2023, pp. 721–724. doi: 10.1109/ICICML60161.2023.10424928.

[31]Y. Jiang, Z. Huang, L. Li, and Q. Dong, "Local-global dual attention network (LGA-Net) for population estimation using remote sensing imagery," Resour. Environ. Sustain., vol. 14, p. 100136, Dec. 2023, doi: 10.1016/j.resenv.2023.100136.

[32]A. Wanto, Y. Yuhandri, and O. Okfalisa, "Optimization Accuracy of CNN Model by Utilizing CLAHE Parameters in Image Classification Problems," in 2023 International Conference on Networking, Electrical Engineering, Computer Science, and Technology (IConNECT), Bandar Lampung, Indonesia: IEEE, Aug. 2023, pp. 253–258. doi: 10.1109/IConNECT56593.2023.10327100.

[33]C. Wang, X. Miao, Y. Xi, M. Bi, L. Li, and W. Hu, "Interpretable and visualized SHAP-based equalizer with feature selection in IMDD system," in Optical Fiber Communication Conference (OFC) 2021, Washington, DC: Optica Publishing Group, 2021, p. Th1A.1. doi: 10.1364/OFC.2021.Th1A.1.

[34]T. He et al., "MediMLP: Using Grad-CAM to Extract Crucial Variables for Lung Cancer Postoperative Complication Prediction," IEEE J. Biomed. Health Inform., vol. 24, no. 6, pp. 1762–1771, Jun. 2020, doi: 10.1109/JBHI.2019.2949601.

#### Appendices

The project is on Github, URL is as follow:

[https://github.com/Vio1etV/Final\\_Year\\_Project](https://github.com/Vio1etV/Final_Year_Project)

The dataset link:

BreakHis (kaggle.com)

说明：1.指标是由系统根据《学术论文不端行为的界定标准》自动生成的

2.本报告单仅对您所选择比对资源范围内检测结果负责

#### 写作辅助工具

##### 选题分析

帮您选择合适的论文题目

##### 资料搜集

提供最全最好的参考文章

##### 提纲推荐

辅助生成文章大纲

##### 在线写作

规范写作，提供灵感

##### 参考文献

规范参考文献，查漏补缺

# 笔杆检测报告单 (全文对照)

全文标明引文

全文对照

打印

检测说明

标题: 202018010212\_Final\_Report

作者: Alber Wu

报告编号: BG202405052344175747

提交时间: 2024-05-05 23:45:02

去除引用文献复制比: 2.3%

去除本人已发表文献复制比: 2.3%

单篇最大文字复制比: 8.4%



重复字数: 1,515

总字数: 64,855

检测范围

复制比部分	章
14.233% (386)	202018010212_Final_Report_第1部分 (总2,712字)
0% (0)	202018010212_Final_Report_第2部分 (总1,077字)
5.01% (366)	202018010212_Final_Report_第3部分 (总7,305字)
0% (0)	202018010212_Final_Report_第4部分 (总7,083字)
0% (0)	202018010212_Final_Report_第5部分 (总6,998字)
2.175% (152)	202018010212_Final_Report_第6部分 (总6,987字)
7.139% (484)	202018010212_Final_Report_第7部分 (总6,780字)
0% (0)	202018010212_Final_Report_第8部分 (总6,880字)
0% (0)	202018010212_Final_Report_第9部分 (总6,763字)
0% (0)	202018010212_Final_Report_第10部分 (总6,772字)
2.364% (127)	202018010212_Final_Report_第11部分 (总5,373字)
0% (0)	202018010212_Final_Report_第12部分 (总125字)

( 无问题部分    复制比部分    引用部分 )

## 202018010212\_Final\_Report\_第1部分

### 相似文献列表

文献名	复制比	是否引证
1.英国ACCA论文代写 BSc (Hons) in Applied Accounting and Research and Analysis Project [24] 英语论文网 - 《网页》 -	9.8%(266字)	否
2.Business SchoolDissertation Modules [19] 英语论文网 - 《网页》 -	9.1%(248字)	否
3.A randomised controlled trial to test a non-metallic deodorant used during a course of radiotherapy Gee, A; Moffitt, D; Churn, M; Errington, R.D. - 《Journal of Radiotherapy in Practice》 - 2000	3.3%(90字)	否
4.The Exceptions to Patent Rights under the WTO-TRIPs Agreement: Is the Right to Health Denied? Jafri, Z. - 《SSRN Electronic Journal》 - 2009	3.2%(88字)	否
5.TRI SERVICE ACCOMMODATION REGULATIONS (TSARs)--PART 3 SINGLE LIVING ACCOMMODATION AND SUBSTITUTE SINGLE LIVING ACCOMMODATION - 《》 - 2008	3.2%(87字)	否

查看更多相似文献

### 全文对照

原文内容	相似内容来源
------	--------

<p>1.relation to Academic Integrity. The University takes this issue very seriously and students have been expelled or had their degrees withheld for cheating in assessment.</p>	<p>1. The University takes this issue very seriously and students have been expelled or had their degrees withheld for cheating in assessments. If you are having difficulty with your work it is important to seek help from your tutor rather than be tempted to use unfair means to gain marks. Do not risk losing your degree and all the work you have done. The University's regulations define a number</p> <p>——网页 - 《英国ACCA论文代写 BSc (Hons) in Applied Accounting and Research and Analysis Project [24]英语论文网》 - (是否引证: 否)</p>
<p>2.their work should seek help from their tutors rather than be tempted to use unfair means to gain marks. Students should not risk losing their degree and undermining all the work they have done towards it.</p>	<p>1. If you are having difficulty with your work it is important to seek help from your tutor rather than be tempted to use unfair means to gain marks. Do not risk losing your degree and all the work you have done.</p> <p>——网页 - 《英国ACCA论文代写 BSc (Hons) in Applied Accounting and Research and Analysis Project [24]英语论文网》 - (是否引证: 否)</p>
<p>3.REGULATIONS GOVERNING THE DEPOSIT AND USE OF OXFORD BROOKES UNIVERSITY MODULAR PROGRAMME PROJECTS AND DISSERTATIONS</p>	<p>1.OXFORD BROOKES UNIVERSITY THE BUSINESS SCHOOL;Statement of originality;Except for those parts in which it is explicitly stated to the contrary, this project is my own work. It has not been submitted for any degree at this or any other academic or professional institutions.;Signature Date;Regulations Governing the Deposit and Use of Oxford Brookes University Modular;Programme Projects and Dissertations;1. The 'top' copies of projects, dissertations submitted in fulfilment of Modular Programme;requirements shall normally be kept by Schools.;2. The author shall sign a declaration agreeing that the project/dissertation be available</p> <p>——网页 - 《Business SchoolDissertation Modules [19]英语论文网》 - (是否引证: 否)</p>

202018010212\_Final\_Report\_第2部分

相似文献列表

文献名	复制比	是否引证
1.Breast Cancer Multi-classification from Histopathological Images with Structured Deep Learning Model Han, Zhongyi; Wei, Benzheng; Zheng, Yuanjie; Yin, Yilong; Li, Kejian; Li, Shuo - 《Scientific Reports 》 - 2017	8.2%(88字)	否
2.Breast Cancer Multi-classification from Histopathological Images with Structured Deep Learning Model Zhongyi Han;Benzheng Wei;Yuanjie Zheng;Yilong Yin;Kejian Li;Shuo Li - 《 》 -	8.2%(88字)	否
3.Monitoring of combustion regimes based on the visualization of the flame and machine learning Tokarev, M P;Abdurakipov, S S;Gobyzov, O A;Seredkin, A V;Dulin, V M - 《Journal of Physics Conference Series 》 - 2018	7.6%(82字)	否
4.PICTURE-BASED VEHICLE LOSS ASSESSMENT METHOD AND APPARATUS, AND ELECTRONIC DEVICE ZHANG, Haitao ;XU, Juan ;HOU, Jinlong ;WANG, Jian ;GUO, Xin ;CHENG, Danni ;HU, Yue ;WU, Bokun ;CHEN, Yanging - 《 》 - 2018	7%(75字)	否

全文对照

202018010212\_Final\_Report\_第3部分

相似文献列表

文献名	复制比	是否引证
1.BoxCars: Improving Fine-Grained Recognition of Vehicles using 3D Bounding Boxes in Traffic Surveillance Jakub Sochor;Jakub vSpavnhel;Adam Herout - 《 》 -	1.7%(126字)	否
2.Realizing Social-Media-Based Analytics for Smart Agriculture Saravanan, M.;Perepu, Satheesh K. - 《The Review of Socionetwork Strategies 》 - 2019	1.4%(101字)	否
3.[IEEE 2017 International Conference on Information, Communication and Engineering (ICICE) - Xiamen, Fujian, China (2017.11.17-2017.11.20)] 2017 International Conference on Information, Communication and Engineering (ICICE) - Enhancing Convolutional Neural Network Deep Learning for Remaining Useful Life Estimation in Smart Factory Applications Jiang, Jehn-Ruey; Kuo, Chang-Kuei - 《 》 - 2017	1.4%(100字)	否
4.ENHANCING TRUST IN THE SMART GRID BY APPLYING A MODIFIED EXPONENTIALLY WEIGHTED MOVING AVERAGES ALGORITHM Andrew T. Kasperek - 《 》 - 2012	1.3%(96字)	否
5.Image-to-Video Person Re-Identification with Temporally Memorized Similarity Learning Zhang, Dongyu; Wu, Wenxi; Cheng, Hui; Zhang, Ruimao; Dong, Zhenjiang; Cai, Zhaoquan - 《IEEE Transactions on Circuits and Systems for Video Technology 》 - 2017	1.3%(93字)	否

[查看更多相似文献](#)

全文对照

原文内容	相似内容来源
<p>1.Data Augmentation: A technique used to increase the diversity of data a vailable for training models by applying random transformations to traini g images.</p>	<p>1.ET) used in [35] for document ;of network. analysis is applied to the origi nal images to increase the ;Data augmentation is a technique that artificial ly diversity of data samples. Furthermore, gaussian blur ;increasing the vol ume of the training set by applying (GB),</p> <p>——Journal of Biophotonics Fan, Haoyi; Zhang, Fengbin; Xi, Liang; Li, Zuoyong; Liu, Guanghai; Xu, Yong - 《LeukocyteMask: An automated localization and segmentation method for leukocyte in blood smear images using deep neural networks》-2019 (是否引证: 否)</p> <p>2.2) a set of masks that represent the ground truth of the segmentation. A data set augmentation technique has been used to increase the number of ISIC training samples. In particular, we used vertical and horizontal imag e flipping,</p> <p>——Youssef, Ali; Bloisi, Domenico D.; Muscio, Mario; Pennisi, Andrea; Nardi, Daniele; Facchiano, Antonio - 《[IEEE 2018 IEEE International Symposium on Medical Measurements and Applications (MeMeA) - Rome, Italy (2018.6.11-2018.6.13)] 2018 IEEE International Symposium on Medical Measurements and Applications (MeMeA) - Deep Convolutional Pixel-wise Labeling for Skin Lesion Image Segmentation》-2018 (是否引证: 否)</p>
<p>2.affected by it [1]. According to statistics recorded by the World Health Organization (WHO)[2] among the 9.6 million cancer-related deaths,</p>	<p>1.Lung cancer (LC)1 remains the leading cause of mortality from malignan t tumors worldwide (1,2). According to the World Health Organization (W HO), among the 8.8 million cancer-related deaths in 2015, LC caused 1.69 million deaths worldwide (3). In the most populated country China,</p> <p>——Molecular &amp; Cellular Proteomics : MCP Jianbo Pan; Guang Song; Dunyan Chen; Yadong Li; Shuang Liu; Shaohui Hu; Christian Rosa; Daniel Eichinger; Ignacio Pino; Heng Zhu; Jiang Qian; Yi Huang- 《Identification of Serological Biomarkers for Early Diagnosis of Lung Cancer Using a Protein Array-Based Approach*》-2017 (是否引证: 否)</p> <p>2. Leprosy is caused by the bacterium Mycobacterium leprae, which attac ks the peripheral nerves of affected people. According to statistics gathere d by the World Health Organization, an estimated 1.15 million people have leprosy worldwide.</p> <p>——网页 - 《Peripheral Neuropathy   Encyclopedia.com》- (是否引证: 否)</p> <p>3. cancer has emerged as the leading cause of disease-related mortality. A ccording to a recent report by the World Health Organization (WHO), app roximately 13 million cancer-related deaths are likely to occur every year i n the next couple of decades (Globocan 2012).</p> <p>——Gandhi, Varsha; Mehta, Kapil; Grover, Rajesh; Pathak, Sen; Aggarwal, Bharat B.- 《Multi-Targeted Approach to Treatment of Cancer    》-2015 (是否引证: 否)</p>
<p>3.Recent years, with the rapid evolution of deep learning in medical image processing, the application of Computer-Aided-Diagnosis has been widely acknowledged [5].</p>	<p>1. background segmentation. These methods usually use features like Haa r feature[3], LBP feature[4], HOG feature[5], SIFT feature[6], etc. But the ac curacy of the above methods is greatly reduced under the conditions in w hich the target is moving or its’ characteristic is not obvious enough. In r ecent years, deep learning in the field of image processing has made great progress.</p> <p>——Yao, Haodi; Yu, Qingtao; Xing, Xiaowei; He, Fenghua; Ma, Jie- 《[IEEE 2017 36th Chinese Control Conference (CCC) - Dalian, China (2017.7.26-2017.7.28)] 2017 36th Chinese Control Conference (CCC) - Deep-learning- based moving target detection for unmanned air vehicles》-2017 (是否引证: 否)</p> <p>2.J].;Contemporary Medicine,2009,15(17)276-277.;[2] Du Yan, Li Yi. The A pplication of Computer Aided Image ;Processing for Medical Image Diagn osis [J]. Journal Of ShenYang ;Institute of Technology 2003,22(3):33-35.; [3] Wang Yajing, Dou Zhenghai.</p> <p>——Computer and Automation Engineering (ICCAE), 2010 The 2nd International Conference on Xu Yijia; Zhang Junfei; Su Qianmin; Sun Xiankun- 《Digital Subtract Angiography System based on ActiveMIL》- (是否引证: 否)</p> <p>3. Keywords——Semantic Similarity Chinese Stop Words TongyiciCilin I. INT RODUCTION In recent years, with the deep learning image processing [1, 2], speech recognition [3] and other fields made major breakthroughs.</p> <p>——Shancheng, Tang; Yunyue, Bai; Fuyu, Ma- 《[IEEE 2017 6th International Conference on Computer Science and Network Technology (ICCSNT) - Dalian, China (2017.10.21-2017.10.22)] 2017 6th International Conference on Computer Science and Network Technology (ICCSNT) - A Chinese short text semantic similarity computation model based on stop words and TongyiciCilin》-2017 (是否引证: 否)</p>

202018010212\_Final\_Report\_第4部分

相似文献列表

文献名	复制比	是否引证
1.[ACM Press the 6th International Conference - Dalian Liaoning, China (2017.08.17-2017.08.18)] Proceedings of the 6th International Conference on Information Engineering - ICIE \'17 - A recommendation algorithm of we-media articles Sun, Feiqiang; Wang, Peng; Liu, Xiaoxia; Zhai, Lidong - 《 》 - 2017	1.2%(86字)	否
2.Deep Learning in Medical ImagingKim, Yun, Cho, Shin, Jang, Bae, and Kim: Deep Learning in Medical Imaging - 《网页》 -	1.2%(86字)	否
3.Optimal Distributed Online Prediction using Mini-Batches Ofer Dekel;Ran Gilad-Bachrach;Ohad Shamir;Lin Xiao - 《Journal of Machine Learning Research》 -	1.2%(84字)	否
4.PREDICTIVE ANALYSIS METHODS AND SYSTEMS HE, Xiangnan ;CHUA, Tat-Seng - 《 》 - 2018	1.2%(84字)	否
5.Methods to interpolate soil categorical variables from profile observations: Lessons from Iran Tomislav Hengl; Norair Toomanian; Hannes I. Reuter ; Mohammad J. Malakouti - 《Geoderma》 - 2007	1.2%(83字)	否

[查看更多相似文献](#)

全文对照

202018010212\_Final\_Report\_第5部分

相似文献列表

文献名	复制比	是否引证
1.RetainVis: Visual Analytics with Interpretable and Interactive Recurrent Neural Networks on Electronic Medical Records Kwon, Bum Chul; Choi, Min-Je; Kim, Joanne Taery; Choi, Edward; Kim, Young Bin; Kwon, Soonwook; Sun, Jimeng; Choo, Jaegul - 《IEEE Transactions on Visualization and Computer Graphics》 - 2018	1.4%(100字)	否
2.Question classification in Persian using word vectors and frequencies Razzaghnoori, Mohammad; Sajedi, Hedieh; Jazani, Iman Khani - 《Cognitive Systems Research》 - 2018	1.4%(99字)	否
3.Breast Cancer Multi-classification from Histopathological Images with Structured Deep Learning Model Zhongyi Han;Benzheng Wei;Yuanjie Zheng;Yilong Yin;Kejian Li;Shuo Li - 《 》 -	1.3%(94字)	否
4.Deep Learning Based Analysis of Histopathological Images of Breast Cancer Xie, Juanying;Liu, Ran;Luttrell, Joseph;Zhang, Chaoyang - 《Frontiers in Genetics》 - 2019	1.3%(94字)	否
5.Leveraging Big Data for Personalized Treatment of Anxiety and Depression: Review and Possible Future Directions Thomas Homescu Anne - 《SSRN Electronic Journal》 - 2018	1.3%(93字)	否

[查看更多相似文献](#)

全文对照

202018010212\_Final\_Report\_第6部分

相似文献列表

文献名	复制比	是否引证
1.Breast Cancer Multi-classification from Histopathological Images with Structured Deep Learning Model Zhongyi Han;Benzheng Wei;Yuanjie Zheng;Yilong Yin;Kejian Li;Shuo Li - 《Scientific Reports》 -	4.2%(296字)	否
2.Breast Cancer Multi-classification from Histopathological Images with Structured Deep Learning Model Han, Zhongyi; Wei, Benzheng; Zheng, Yuanjie; Yin, Yilong; Li, Kejian; Li, Shuo - 《Scientific Reports》 - 2017	3.9%(269字)	否
3.Breast Cancer Multi-classification from Histopathological Images with Structured Deep Learning Model Zhongyi Han;Benzheng Wei;Yuanjie Zheng;Yilong Yin;Kejian Li;Shuo Li - 《 》 -	3.9%(269字)	否
4Automatic prediction of tumour malignancy in breast cancer with fractal dimension Chan, Alan; Tuszynski, Jack A. - 《Royal Society Open Science》 - 2016	3.5%(247字)	否
5Automatic prediction of tumour malignancy in breast cancer with fractal dimension Alan Chan;Jack A. Tuszynski - 《Royal Society Open Science》 -	3.4%(238字)	否

[查看更多相似文献](#)

全文对照

原文内容	相似内容来源
------	--------



<p>1. It differentiates between non-invasive benign tumors and invasive malignant tumors capable of metastasis. Breast tumors are subtyped into <b>adenosis</b>, <b>fibroadenoma</b>, <b>phyllodes tumor</b>, and <b>tubular adenoma</b> for benign, and <b>ductal carcinoma</b>, <b>lobular carcinoma</b>, <b>mucinous carcinoma</b>, and <b>papillary carcinoma</b> for malignant,</p>	<p>1. <b>adenosis</b> (A), <b>fibroadenoma</b> (F);<b>phyllodes tumor</b> (PT), and <b>tubular adenoma</b> (TA); And four malignant tumors: <b>ductal carcinoma</b> (DC), <b>lobular carcinoma</b> (LC), <b>mucinous carcinoma</b> (MC), and <b>papillary carcinoma</b> (PC)12. Images are of three-channel RGB,</p> <p>—— Zhongyi Han; Benzheng Wei; Yuanjie Zheng; Yilong Yin; Kejian Li; Shuo Li- 《Breast Cancer Multi-classification from Histopathological Images with Structured Deep Learning Model》- （是否引证：否）</p> <p>2.classifier is responsible for;predicting four subtypes of Benign BC [<b>adenosis</b> (A), <b>fibroadenoma</b> (F), tubular adenoma;(TA), and <b>phyllodes tumor</b> (PT)]. Furthermore, the M2 classifier is responsible for classifying;the images into four distinct subtypes of malignant BC [<b>ductal carcinoma</b> (DC), <b>lobular carcinoma</b> (LC), <b>mucinous carcinoma</b> (MC), and <b>papillary carcinoma</b> (PC)].</p> <p>——Multimedia Tools and Applications Murtaza, Ghulam; Shuib, Liyana; Mujtaba, Ghulam; Raza, Ghulam - 《Breast Cancer Multi-classification through Deep Neural Network and Hierarchical Classification Approach》-2019 （是否引证：否）</p> <p>3. Benign: <b>adenosis</b> (A), <b>fibroadenoma</b> (F), phyllodes tumour (PT) and <b>tubular adenoma</b> (TA). Malignant: <b>ductal carcinoma</b> (DC), <b>lobular carcinoma</b> (LC), <b>mucinous carcinoma</b> (MC) and <b>papillary carcinoma</b> (PC). The distribution of images of benign tumours in BreakHis, from [18].</p> <p>——Royal Society Open Science Alan Chan; Jack A. Tuszynski- 《Automatic prediction of tumour malignancy in breast cancer with fractal dimension》- （是否引证：否）</p> <p>4. The breast images consist of adenosis, <b>fibroadenoma</b>, <b>phyllodes tumor</b>, tubular adenoma, <b>ductal carcinoma</b>, <b>lobular carcinoma</b>, <b>mucinous carcinoma</b>, and <b>papillary carcinoma</b>. The objectives of our study are:(a)</p> <p>——IEEE Access Bardou, Dalal; Zhang, Kun; Ahmad, Sayed Mohammad- 《Classification of Breast Cancer Based on Histology Images Using Convolutional Neural Networks》-2018 （是否引证：否）</p>
--	---

202018010212\_Final\_Report\_第7部分

相似文献列表

文献名	复制比	是否引证
1.Deep Learning Based Analysis of Histopathological Images of Breast Cancer Xie, Juanying;Liu, Ran;Luttrell, Joseph;Zhang, Chaoyang - 《Frontiers in Genetics 》- 2019	2.1%(145字)	否
2.[IEEE 2017 Brazilian Conference on Intelligent Systems (BRACIS) - Uberlandia, Brazil (2017.10.2-2017.10.5)] 2017 Brazilian Conference on Intelligent Systems (BRACIS) - Efficient Gaussian Process-Based Inference for Modelling Spatio-Temporal Dengue Fever Albinati, Julio; Meira, Wagner; Pappa, Gisele L.; Wilson, Andrew G. - 《 》- 2017	1.9%(129字)	否
3.Confidence interval construction for the Youden index based on partially validated series Poon, Wai-Yin; Qiu, Shi-Fang; Tang, Man-Lai - 《Computational Statistics & Data Analysis 》- 2015	1.7%(117字)	否
4.NCLscan: accurate identification of non-co-linear transcripts (fusion, trans-splicing and circular RNA) with a good balance between sensitivity and precision Trees-Juen Chuang;Chan-Shuo Wu;Chia-Ying Chen;Li-Yuan Hung;Tai-Wei Chiang;Min-Yu Yang - 《Nucleic Acids Research 》- 2016	1.7%(115字)	否
5.Maximum Likelihood Cost Functions for Neural Network Models of Air Quality Data Stephen R. Dorling;Robert J. Foxall;Danilo P. Mandic;Gavin C. Cawley - 《 》-	1.7%(114字)	否

[查看更多相似文献](#)

全文对照

原文内容	相似内容来源
<p>1. <b>positive</b>, <b>negative</b> and <b>false</b>. TP, TN, FP, and FN represent the counts of correctly identified positive cases, correctly identified negative cases, incorrectly identified positive cases,</p>	<p>1. <b>True negative</b> = number of negative cases correctly identified, <b>False positive</b> = number of negative cases incorrectly identified, <b>bAccuracy</b> = proportion of correctly identified cases out of total population (both positive and negative),</p> <p>—— Dang, Shilpa; Chaudhury, Santanu; Lall, Brejesh; Roy, Prasun Kumar- 《 [ACM Press the Tenth Indian Conference - Guwahati, Assam, India (2016.12.18-2016.12.22)] Proceedings of the Tenth Indian Conference on Computer Vision, Graphics and Image Processing - ICVGIP \`16 - Autoregressive hidden Markov model with missing data for modelling functional MR imaging data》-2016 （是否引证：否）</p> <p>2. FP is the number of negative cases incorrectly identified, <b>TN is the number of negative cases correctly identified</b>, and finally, <b>FN is the number of positive cases incorrectly identified</b>. Sensitivity measures the proportion of actual positive cases which are correctly identified,</p>

	<p>——Signal, Image and Video Processing Ayas, Selen; Ekinci, Murat-《Random forest-based tuberculosis bacteria classification in images of ZN-stained sputum smear samples》-2014 (是否引证: 否)</p> <p><math>3. TP + FP + FN</math> represent the number of correctly identified NCL events, the number of incorrectly identified NCL events and the number of missing NCL events,</p> <p>——Nucleic Acids Research Trees-Juen Chuang; Chan-Shuo Wu; Chia-Ying Chen; Li-Yuan Hung; Tai-Wei Chiang; Min-Yu Yang-《NCLscan: accurate identification of non-co-linear transcripts (fusion, trans-splicing and circular RNA) with a good balance between sensitivity and precision》-2016 (是否引证: 否)</p>
2.True Positive, True Negative, False Positive and False Negative.	<p>1. The costs of each of the four diagnosis groups (true positive, false negative, true negative and false positive) were assessed from a National Health Service payer perspective. The procalcitonin test was more accurate (sensitivity=0.89,95%CI=0.</p> <p>——百科 - 《Clinical and Cost-Effectiveness of Procalcitonin Test for Prodromal Meningococcal Disease-A Meta-Analysis — Queen's University Belfast》-2020 (是否引证: 否)</p>
3.ROC: Receiver Operating Characteristic (ROC), which displays the trade-off relationships between the True Positive Rate(also known as sensitivity or recall) and the False Positive Rate of a model at different thresholds.	<p>1. For each incidence level and city, we calculate the receiver operating characteristic (ROC) curve, which indicates the trade-off between true positive rate (sensitivity or recall) and false positive rate (1 - sensibility), that is,</p> <p>—— Albinati, Julio; Meira, Wagner; Pappa, Gisele L.; Wilson, Andrew G.-《[IEEE 2017 Brazilian Conference on Intelligent Systems (BRACIS) - Uberlandia, Brazil (2017.10.2-2017.10.5)] 2017 Brazilian Conference on Intelligent Systems (BRACIS) - Efficient Gaussian Process-Based Inference for Modelling Spatio-Temporal Dengue Fever》-2017 (是否引证: 否)</p> <p>2. and can measure the hit-false alarm tradeoffs using well known measures of sensitivity or recall and false positive rate or fall-out.</p> <p>—— Young, William T.; Memory, Alex; Goldberg, Henry G.; Senator, Ted E.-《[IEEE 2014 IEEE Security and Privacy Workshops (SPW) - San Jose, CA (2014.5.17-2014.5.18)] 2014 IEEE Security and Privacy Workshops - Detecting Unknown Insider Threat Scenarios》-2014 (是否引证: 否)</p> <p>3. For a binary outcome, the standard description of discrimination is the receiver operating characteristic (ROC) curve, which displays the trade-off between specificity (the probability that a control marker value is below the cut-off)</p> <p>——Biometrical journal. Biometrische Zeitschrift Ian R. White; Eleni Rapsomaniki-《Covariate-adjusted measures of discrimination for survival data》-2015 (是否引证: 否)</p>
4.In summary, in order to evaluate the model performance on the binary classification of the level of breast cancer, this project will conduct a comprehensive evaluation,	<p>1. Next, the optimal threshold of RBFNN and the neuron number of hidden layer have to be determined. In order to evaluate the classification performance, several parameters for binary classification test have to be defined. True-Positive (TP:</p> <p>——IEEE Journal of Biomedical and Health Informatics Huang, Yao-Kuang; Chang, Chang-Cheng; Lin, Pin-Xing; Lin, Bor-Shyh-《Quantitative Evaluation of Rehabilitation Effect on Peripheral Circulation of Diabetic Foot》-2017 (是否引证: 否)</p> <p>2. So for comprehensive comparison, DELM is the best of all.4.3. Testing results of the algorithms on binary classification data sets:In order to further evaluate the performance of the algorithms, we choose 12 binary classification data sets as testing data sets.</p> <p>——Neurocomputing Xu, Shuliang; Wang, Junhong-《Dynamic extreme learning machine for data stream classification》-2017 (是否引证: 否)</p> <p>3. After that, the parameters of the xdecay_rate (1);fully-connected layer are trained on the histopathological images of breast cancer. The modified network structure Evaluation Criteria for Classification Results;of the Inception_ResNet_V2 network is shown in Figure 3. To evaluate the performance of the classification model more:The modified Inception_V3 network structure is similar, so accurately and comprehensively,</p> <p>——Frontiers in Genetics Xie, Juanying; Liu, Ran; Luttrell, Joseph; Zhang, Chaoyang-《Deep Learning Based Analysis of Histopathological Images of Breast Cancer》-2019 (是否引证: 否)</p>

202018010212\_Final\_Report\_第8部分

相似文献列表

文献名	复制比	是否引证
1.Natural killer cells in the innate immunity network of atherosclerosis	1.2%(84字)	否

Bonaccorsi, Irene; Pasquale, Claudia De; Campana, Stefania; Barberi, Chiara; Cavaliere, Riccardo; Benedetto, Filippo; Ferlazzo, Guido - 《Immunology Letters》 - 2015		
2.Anomaly Detection for HTTP Using Convolutional Autoencoders Park, Seungyoung;Kim, Myungjin;Lee, Seokwoo - 《IEEE Access》 - 2018	1.1%(76字)	否
3.[IEEE 2007 IEEE Wireless Communications and Networking Conference - Kowloon, China (2007.03.11 - 2007.03.15)] 2007 IEEE Wireless Communications and Networking Conference - Distributed Coordination of Sensors for End-to-End Reliable Event and Query Delivery Tezcan, Nurcan; Wang, Wenye - 《》 - 2007	1.1%(73字)	否
4.Discriminant Deep Feature Learning based on joint supervision Loss and Multi-layer Feature Fusion for heterogeneous face recognition Hu, Weipeng;Hu, Haifeng - 《Computer Vision and Image Understanding》 - 2019	0.9%(64字)	否

全文对照

202018010212\_Final\_Report\_第9部分

相似文献列表

文献名	复制比	是否引证
1.New Design Technique of Dual-Output Second Generation Current Conveyor S.N. Ahmad;Hassan Jassim Motlak - 《Emerging Trends in Engineering and Technology, 2008. ICETET '08. First International Conference on》 -	1.2%(79字)	否
2.Role of infochemical mediated zooplankton grazing in a phytoplankton competition model Lewis, Nicola D.; Breckels, Mark N.; Steinke, Michael; Codling, Edward A. - 《Ecological Complexity》 - 2013	1.1%(77字)	否
3.Oxidation of radioactive palmitate and glucose infused into the cortical subarachnoid space Little;Hori, S;Spitzer, JJ - 《American Journal of Physiology -- Legacy Content》 - 1969	1%(70字)	否
4.Study regarding the development of agility skills of students aged between 10 and 12 years old Sopa, Ioan Sabin; Pomohaci, Marcel - 《Timisoara Physical Education and Rehabilitation Journal》 - 2016	0.9%(62字)	否

全文对照

202018010212\_Final\_Report\_第10部分

相似文献列表

文献名	复制比	是否引证
1.一台概念向量机器分类网文件的能力上的本体论层次的效果。 Graham, Jeffrey A. - 《Ph.D.硕士论文》 -	1%(66字)	否
2.Breast Cancer Multi-classification through Deep Neural Network and Hierarchical Classification Approach Murtaza, Ghulam;Shuib, Liyana;Mujtaba, Ghulam;Raza, Ghulam - 《Multimedia Tools and Applications》 - 2019	1%(65字)	否
3.FlyTED: the Drosophila Testis Gene Expression Database Zhao, J.; Klyne, G.; Benson, E.; Gudmannsdottir, E.; White-Cooper, H.; Shotton, D. - 《Nucleic Acids Research》 - 2010	0.9%(62字)	否

全文对照

202018010212\_Final\_Report\_第11部分

相似文献列表

文献名	复制比	是否引证
1.Research Pradigms in Computer Science Peter Wegner - 《》 -	2.5%(136字)	否
2.Gender and Professional Ethics in the IT Industry Androniki Panteli; Janet Stack; Harvie Ramsay - 《Journal of Business Ethics》 - 1999	2%(107字)	否
3.Fuzzy grey relational analysis for software effort estimation Mohammad Azzeh; Daniel Neagu; Peter I. Cowling - 《Empirical Software Engineering》 - 2010	1.7%(93字)	否
4. “SSCP Review Seminar + Mock Exam ” by Mike Myint - 《百科》 - 2020	1.7%(92字)	否
5.Reduction of the dimension of a document space using the fuzzified output of a Kohonen network Vicente P. Guerrero; Félix de Moya Anegón - 《Journal of the American Society for Information Science and Technology》 - 2001	1.7%(92字)	否

[查看更多相似文献](#)

全文对照

原文内容	相似内容来源
<p>1. it is critical to address a wide spectrum of legal, social, ethical, and environmental concerns. This involves obeying the professional standards set forth by institutions like ACM(Association for Computing Machinery) and the BCS (The British Computer Society).</p>	<p>1.IET), the Institute of Electrical and Electronics Engineers (IEEE), the British Computer Society (BCS) and the Association for Computing Machinery (ACM).;An Analysis of Phishing Blacklists: Google Safe Browsing, OpenPhish, and PhishTank;Research output:</p> <p>——百科 - 《Professor Peter Komisarczuk - Research - Royal Holloway, University of London》-2020 (是否引证: 否)</p> <p>2. Through its grounding in real social relations and human activities, it seeks to understand and address the whole spectrum of social, ethical, environmental and political issues of today. Through philosophy, we are able not only to understand life,</p> <p>——百科 - 《Philosophy (BA)   University of Wales Trinity Saint David》-2020 (是否引证: 否)</p>

202018010212\_Final\_Report\_第12部分

相似文献列表

全文对照

说明：1.指标是由系统根据《学术论文不端行为的界定标准》自动生成的  
2.本报告单仅对您所选择比对资源范围内检测结果负责

写作辅助工具

<p><a href="#">选题分析</a> 帮您选择合适的论文题目</p>	<p><a href="#">资料搜集</a> 提供最全最好的参考文章</p>	<p><a href="#">提纲推荐</a> 辅助生成文章大纲</p>	<p><a href="#">在线写作</a> 规范写作，提供灵感</p>	<p><a href="#">参考文献</a> 规范参考文献，查漏补缺</p>
---	---	--	---	---