Ansible Tasks -01

- Setup one master and two worker nodes in ansible.

☐	Ansible	i-0872326a6e99ccf0f	Running
☐	Slave-01	i-092bcda893200b826	Running
☑	Slave-02	i-04fb256d4a701b4ac	Running

```
[ec2-user@ip-172-31-24-112 ansible]$ cat hosts
[webservers]
web1 ansible_host=13.220.115.189
web2 ansible_host=54.91.3.135
[ec2-user@ip-172-31-24-112 ansible]$
```

- Execute the adhoc command shared in #dvps-cloud-documents-17 Channel.
- ansible all -m ping

```
[ec2-user@ip-172-31-24-112 ansible]$ ansible webservers -m ping
[WARNING]: Platform linux on host web1 is using the discovered Python interpreter at /usr/bi
core/2.15/reference_appendices/interpreter_discovery.html for more information.
web1 | SUCCESS => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": false,
    "ping": "pong"
}
[WARNING]: Platform linux on host web2 is using the discovered Python interpreter at /usr/bi
core/2.15/reference_appendices/interpreter_discovery.html for more information.
web2 | SUCCESS => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": false,
    "ping": "pong"
}
```

- ansible all -m ping -i ansible_hosts

```
[ec2-user@ip-172-31-24-112 ~]$ cat ansible_hosts
[slave01]
13.220.115.189
[slave02]
54.91.3.135
```

Ansible Tasks -01

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m ping -i ansible_hosts
13.220.115.189 | SUCCESS => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": false,
    "ping": "pong"
}
54.91.3.135 | SUCCESS => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": false,
    "ping": "pong"
}
```

- ansible all -m setup

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m setup
web1 | SUCCESS => {
    "ansible_facts": {
        "ansible_all_ipv4_addresses": [
            "172.31.29.27"
        ],
        "ansible_all_ipv6_addresses": [
            "fe80::8ff:f1ff:fec0:dc4d"
        ],
        "ansible_apparmor": {
            "status": "disabled"
```

```
}
web2 | SUCCESS => {
    "ansible_facts": {
        "ansible_all_ipv4_addresses": [
            "172.31.31.155"
        ],
        "ansible_all_ipv6_addresses": [
            "fe80::8ff:f4ff:fe3c:d703"
        ],
        "ansible_apparmor": {
            "status": "disabled"
        },
```

- ansible all -m ping --user=ec2-user --ask-pass

Ansible Tasks -01

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m ping --user=ec2-user --ask-pass
SSH password:
web1 | SUCCESS => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": false,
    "ping": "pong"
}
web2 | SUCCESS => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": false,
    "ping": "pong"
}
```

- ansible all -a uptime

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -a uptime
web1 | CHANGED | rc=0 >>
 14:10:15 up 39 min,  2 users,  load average: 0.00, 0.00, 0.00
web2 | CHANGED | rc=0 >>
 14:10:15 up 39 min,  2 users,  load average: 0.00, 0.00, 0.00
```

- ansible all -a "free -m"

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -a "free -m"
web1 | CHANGED | rc=0 >>
              total        used        free      shared  buff/cache   available
Mem:            916         185         499           0         231         600
Swap:             0           0           0
web2 | CHANGED | rc=0 >>
              total        used        free      shared  buff/cache   available
Mem:            916         182         502           0         231         602
Swap:             0           0           0
[ec2-user@ip-172-31-24-112 ~]$
```

- ansible all -m shell -a "cat /etc/passwd | grep -i ec2-user" --become --ask-become-pass

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m shell -a "cat /etc/passwd | grep -i ec2-user" --become --ask-become-pass
BECOME password:
web1 | CHANGED | rc=0 >>
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
web2 | CHANGED | rc=0 >>
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
```

- ansible all -m shell -a "cat /etc/passwd|grep -i ec2-user" -b –K

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m shell -a "cat /etc/passwd|grep -i ec2-user" -b -K
BECOME password:
web1 | CHANGED | rc=0 >>
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
web2 | CHANGED | rc=0 >>
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
```

- ansible all -m file -a "path=/home/ansadm/test state=directory mode=0755" -b --become-user=ansadm

Ansible Tasks -01

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m file -a "path=/home/ec2-user/test state=directory mode=0755" -b --become-user=ec2-user
web1 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "gid": 1000,
    "group": "ec2-user",
    "mode": "0755",
    "owner": "ec2-user",
    "path": "/home/ec2-user/test",
    "secontext": "unconfined_u:object_r:user_home_t:s0",
    "size": 6,
    "state": "directory",
    "uid": 1000
}
web2 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "gid": 1000,
    "group": "ec2-user",
    "mode": "0755",
    "owner": "ec2-user",
    "path": "/home/ec2-user/test",
    "secontext": "unconfined_u:object_r:user_home_t:s0",
    "size": 6,
    "state": "directory",
    "uid": 1000
}
```

```
Last login: Thu Mar 12 05:28:31 2026 from 172.31.24.112
[ec2-user@ip-172-31-29-27 ~]$ ls
test
```

```
Last login: Thu Mar 12 05:28:31 2026 from 172.31.24.112
[ec2-user@ip-172-31-31-155 ~]$ ls
test
```

- ansible all -s -m group -a "name=test state=present" -b –K

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m group -a "name=test state=present" -b -K
BECOME password:
web2 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "gid": 1001,
    "name": "test",
    "state": "present",
    "system": false
}
web1 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "gid": 1001,
    "name": "test",
    "state": "present",
    "system": false
}
```

```
ec2-user:x:1000:
test:x:1001:
[ec2-user@ip-172-31-29-27 ~]$
```

```
ec2-user:x:1000:
test:x:1001:
[ec2-user@ip-172-31-31-155 ~]$
```

Ansible Tasks -01

- ansible all -m file -a "path=/home/ec2-user/testfile state=touch mode=0755"

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m file -a "path=/home/ec2-user/testfile state=touch mode=0755"
web1 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "dest": "/home/ec2-user/testfile",
    "gid": 1000,
    "group": "ec2-user",
    "mode": "0755",
    "owner": "ec2-user",
    "secontext": "unconfined_u:object_r:user_home_t:s0",
    "size": 0,
    "state": "file",
    "uid": 1000
}
web2 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "dest": "/home/ec2-user/testfile",
    "gid": 1000,
    "group": "ec2-user",
    "mode": "0755",
    "owner": "ec2-user",
    "secontext": "unconfined_u:object_r:user_home_t:s0",
    "size": 0,
    "state": "file",
    "uid": 1000
}
```

-

```
[ec2-user@ip-172-31-29-27 ~]$ ls -l
total 0
drwxr-xr-x. 2 ec2-user ec2-user 6 Mar 12 05:28 test
-rwxr-xr-x. 1 ec2-user ec2-user 0 Mar 12 05:42 testfile
```

-

```
drwxr-xr-x. 2 ec2-user ec2-user 6 Mar 12 05:28 test
-rwxr-xr-x. 1 ec2-user ec2-user 0 Mar 12 05:42 testfile
[ec2-user@ip-172-31-31-155 ~]$
```

- ansible all -m file -a "path=/home/ansadm group=weblogic owner=weblogic" -b

Ansible Tasks -01

- ```
  [ec2-user@ip-172-31-24-112 ~]$ ansible all -m file -a "path=/home/wolf group=test owner=wolf" -b
  web1 | CHANGED => {
      "ansible_facts": {
          "discovered_interpreter_python": "/usr/bin/python3.9"
      },
      "changed": true,
      "gid": 1001,
      "group": "test",
      "mode": "0700",
      "owner": "wolf",
      "path": "/home/wolf",
      "secontext": "unconfined_u:object_r:user_home_dir_t:s0",
      "size": 62,
      "state": "directory",
      "uid": 1001
  }
  web2 | CHANGED => {
      "ansible_facts": {
          "discovered_interpreter_python": "/usr/bin/python3.9"
      },
      "changed": true,
      "gid": 1001,
      "group": "test",
      "mode": "0700",
      "owner": "wolf",
      "path": "/home/wolf",
      "secontext": "unconfined_u:object_r:user_home_dir_t:s0",
      "size": 62,
      "state": "directory",
      "uid": 1001
  }
  ```
- ```
  [wolf@ip-172-31-29-27 ~]$ ls -ld /home/wolf
  drwx------. 2 wolf test 83 Mar 12 05:48 /home/wolf
  [wolf@ip-172-31-29-27 ~]$
  ```
- ```
  [ec2-user@ip-172-31-31-155 ~]$ ls -ld /home/wolf
  drwx------. 2 wolf test 62 Mar 12 05:46 /home/wolf
  [ec2-user@ip-172-31-31-155 ~]$
  ```
- ansible all -m yum -a "name=httpd state=installed"
  ```

Ansible Tasks -01

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m dnf -a "name=httpd state=installed" -b
web1 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "msg": "",
    "rc": 0,
    "results": [
        "Installed: libbrotli-1.0.9-4.amzn2023.0.2.x86_64",
        "Installed: httpd-2.4.66-1.amzn2023.0.1.x86_64",
        "Installed: httpd-filesystem-2.4.66-1.amzn2023.0.1.noarch",
        "Installed: apr-util-lmdb-1.6.3-1.amzn2023.0.2.x86_64",
        "Installed: mod_lua-2.4.66-1.amzn2023.0.1.x86_64",
        "Installed: mailcap-2.1.49-3.amzn2023.0.3.noarch",
        "Installed: apr-util-openssl-1.6.3-1.amzn2023.0.2.x86_64",
        "Installed: httpd-core-2.4.66-1.amzn2023.0.1.x86_64",
        "Installed: mod_http2-2.0.27-1.amzn2023.0.3.x86_64",
        "Installed: generic-logos-httpd-18.0.0-12.amzn2023.0.3.noarch",
        "Installed: apr-1.7.5-1.amzn2023.0.4.x86_64",
        "Installed: httpd-tools-2.4.66-1.amzn2023.0.1.x86_64",
        "Installed: apr-util-1.6.3-1.amzn2023.0.2.x86_64"
    ]
}
web2 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "msg": "",
    "rc": 0,
    "results": [
        "Installed: libbrotli-1.0.9-4.amzn2023.0.2.x86_64",
        "Installed: httpd-2.4.66-1.amzn2023.0.1.x86_64",
        "Installed: httpd-filesystem-2.4.66-1.amzn2023.0.1.noarch",
        "Installed: apr-util-lmdb-1.6.3-1.amzn2023.0.2.x86_64",
        "Installed: mod_lua-2.4.66-1.amzn2023.0.1.x86_64",
        "Installed: mailcap-2.1.49-3.amzn2023.0.3.noarch",
        "Installed: apr-util-openssl-1.6.3-1.amzn2023.0.2.x86_64",
        "Installed: httpd-core-2.4.66-1.amzn2023.0.1.x86_64",
        "Installed: mod_http2-2.0.27-1.amzn2023.0.3.x86_64",
        "Installed: generic-logos-httpd-18.0.0-12.amzn2023.0.3.noarch",
        "Installed: apr-1.7.5-1.amzn2023.0.4.x86_64",
        "Installed: httpd-tools-2.4.66-1.amzn2023.0.1.x86_64",
        "Installed: apr-util-1.6.3-1.amzn2023.0.2.x86_64"
    ]
}
```

-

```
[ec2-user@ip-172-31-29-27 ~]$ sudo systemctl status httpd
o httpd.service - The Apache HTTP Server
     Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; preset: disabled)
     Active: inactive (dead)
       Docs: man:httpd.service(8)
[ec2-user@ip-172-31-29-27 ~]$
```

```
[ec2-user@ip-172-31-31-155 ~]$ sudo systemctl status httpd
o httpd.service - The Apache HTTP Server
     Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; preset: disabled)
     Active: inactive (dead)
       Docs: man:httpd.service(8)
[ec2-user@ip-172-31-31-155 ~]$
```

- ansible all -m service -a "name=httpd state=started enabled=yes"

Ansible Tasks -01

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m service -a "name=httpd state=started enabled=yes" -b
web1 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "enabled": true,
    "name": "httpd",
    "state": "started",
    "status": {
        "AccessSELinuxContext": "system_u:object_r:httpd_unit_file_t:s0",
```

```
web2 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "enabled": true,
    "name": "httpd",
    "state": "started",
    "status": {
        "AccessSELinuxContext": "system_u:object_r:httpd_unit_file_t:s0",
        "ActiveEnterTimestampMonotonic": "0",
```

```
[ec2-user@ip-172-31-29-27 ~]$ sudo systemctl status httpd
● httpd.service - The Apache HTTP Server
     Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset: disabled)
     Active: active (running) since Thu 2026-03-12 05:56:02 UTC; 48s ago
       Docs: man:httpd.service(8)
   Main PID: 28837 (httpd)
     Status: "Total requests: 0; Idle/Busy workers 100/0;Requests/sec: 0; Bytes servec
      Tasks: 177 (limit: 1067)
     Memory: 13.3M
        CPU: 110ms
     CGroup: /system.slice/httpd.service
```

```
[ec2-user@ip-172-31-31-155 ~]$ sudo systemctl status httpd
● httpd.service - The Apache HTTP Server
     Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset: disabled)
     Active: active (running) since Thu 2026-03-12 05:56:03 UTC; 1min 14s ago
       Docs: man:httpd.service(8)
   Main PID: 28539 (httpd)
     Status: "Total requests: 0; Idle/Busy workers 100/0;Requests/sec: 0; Bytes served/sec:
      Tasks: 177 (limit: 1067)
     Memory: 13.3M
        CPU: 131ms
     CGroup: /system.slice/httpd.service
             ├─28539 /usr/sbin/httpd -DFOREGROUND
```

- ansible all -m service -a "name=httpd state=stopped enabled=yes"

```
[ec2-user@ip-172-31-24-112 ~]$ ansible all -m service -a "name=httpd state=stopped enabled=yes" -b
web1 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "enabled": true,
    "name": "httpd",
    "state": "stopped",
    "status": {
```

Ansible Tasks -01

```
web2 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3.9"
    },
    "changed": true,
    "enabled": true,
    "name": "httpd",
    "state": "stopped",
    "status": {
```

```
[ec2-user@ip-172-31-29-27 ~]$ sudo systemctl status httpd
○ httpd.service - The Apache HTTP Server
     Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset: disabled)
     Active: inactive (dead) since Thu 2026-03-12 05:58:14 UTC; 13s ago
   Duration: 2min 11.220s
       Docs: man:httpd.service(8)
    Process: 28837 ExecStart=/usr/sbin/httpd $OPTIONS -DFOREGROUND (code=exited, statu
   Main PID: 28837 (code=exited, status=0/SUCCESS)
```

```
[ec2-user@ip-172-31-31-155 ~]$ sudo systemctl status httpd
○ httpd.service - The Apache HTTP Server
     Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset: disabled)
     Active: inactive (dead) since Thu 2026-03-12 05:58:14 UTC; 17s ago
   Duration: 2min 10.117s
       Docs: man:httpd.service(8)
```