

# Copyright Notice

These slides are distributed under the Creative Commons License.

[DeepLearning.AI](#) makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite [DeepLearning.AI](#) as the source of the slides.

For the rest of the details of the license, see <https://creativecommons.org/licenses/by-sa/2.0/legalcode>



deeplearning.ai

# Probability and Bayes' Rule

# Outline

- Probabilities
- Bayes' rule (Applied in different fields, including NLP)
- Build your own Naive-Bayes tweet classifier!

# Introduction

Corpus of tweets

		Positive		

Tweets containing the word  
“happy”

		Positive		

# Probabilities

Corpus of tweets

		Positive		
		Negative		

$A \rightarrow \text{Positive tweet}$

$$P(A) = P(\text{Positive}) = N_{\text{pos}} / N$$

# Probabilities

Corpus of tweets

		Positive		
		Negative		

$A \rightarrow \text{Positive tweet}$

$$P(A) = N_{\text{pos}} / N = 13 / 20 = 0.65$$

$$P(\text{Negative}) = 1 - P(\text{Positive}) = 0.35$$

# Probabilities


Tweets containing the word  
"happy"


$B \rightarrow$  tweet contains "happy".


$$P(B) = P(\text{happy}) = N_{\text{happy}} / N$$

$$P(B) = 4 / 20 = 0.2$$

# Probability of the intersection



$$P(A \cap B) = P(A, B) = \frac{3}{20} = 0.15$$








deeplearning.ai


# Bayes' Rule

# Conditional Probabilities




$$P(A \mid B) = P(\text{Positive} \mid \text{"happy"})$$

$$P(A \mid B) = 3 / 4 = 0.75$$




# Conditional Probabilities



$$P(B | A) = P(\text{"happy"} | \text{Positive})$$

$$P(B | A) = 3 / 13 = 0.231$$



# Conditional probabilities




```
graph TD; A[Conditional probabilities] --> B[Probability of B, given A happened]; A --> C[Looking at the elements of set A, the chance that one also belongs to set B];
```

Probability of B, given A happened

Looking at the elements of set A,  
the chance that one also belongs to  
set B

# Conditional probabilities



$$P(\text{Positive} | \text{"happy"}) = \frac{P(\text{Positive} \cap \text{"happy"})}{P(\text{"happy"})}$$

## Bayes' rule

$$P(\text{Positive} | \text{"happy"}) = \frac{P(\text{Positive} \cap \text{"happy"})}{P(\text{"happy"})}$$

$$P(\text{"happy"} | \text{Positive}) = \frac{P(\text{"happy"} \cap \text{Positive})}{P(\text{Positive})}$$

## Quiz

**Objective:** Derive Bayes' rule from the equations given on the last slide.

**Question:**

From the equations presented below, express the probability of a tweet being positive given that it contains the word happy in terms of the probability of a tweet containing the word happy given that it is positive

$$P(\text{Positive} | \text{"happy"}) = \frac{P(\text{Positive} \cap \text{"happy"})}{P(\text{"happy"})} \qquad P(\text{"happy"} | \text{Positive}) = \frac{P(\text{"happy"} \cap \text{Positive})}{P(\text{Positive})}$$

**Type:** Multiple Choice, single answer

**Options and solution:**

$$P(\text{Positive} | \text{"happy"}) = P(\text{"happy"} | \text{Positive}) \times \frac{P(\text{Positive})}{P(\text{"happy"})}$$

That's right. You just derived Bayes' rule.

$$P(\text{Positive} | \text{"happy"}) = P(\text{"happy"} | \text{Positive}) \times \frac{P(\text{"happy"})}{P(\text{Positive})}$$

The ratio is upside-down in this equation.

$$P(\text{Positive} | \text{"happy"}) = P(\text{"happy"} \cap \text{Positive}) \times \frac{P(\text{Positive})}{P(\text{"happy"})}$$


Your result should not include any intersection probabilities.

$$P(\text{Positive} | \text{"happy"}) = P(\text{"happy"} \cap \text{Positive}) \times \frac{P(\text{"happy"})}{P(\text{Positive})}$$

Your result should not include any intersection probabilities.

# Bayes' rule

$$P(\text{Positive} | \text{"happy"}) = P(\text{"happy"} | \text{Positive}) \times \frac{P(\text{Positive})}{P(\text{"happy"})}$$





## Quiz: Bayes' Rule Applied

**Objective:** Compute conditional probability using Bayes Rule

**Question:**

$$P(X|Y) = P(Y|X) \times \frac{P(X)}{P(Y)}$$

Here, again, is Bayes' rule:

Suppose that in your dataset, 25% of the positive tweets contain the word 'happy'. You also know that a total of 13% of the tweets in your dataset contain the word 'happy', and that 40% of the total number of tweets are positive. You observe the tweet: "happy to learn NLP". What is the probability that this tweet is positive?

**Type:** Multiple Choice, single answer

**Options and solution:**

**A:  $P(\text{Positive} | \text{"happy"}) = 0.77$**  That's right. You just applied Bayes' rule.

**B:  $P(\text{Positive} | \text{"happy"}) = 0.08$**  Oops, looks like you might have the ratio of  $P(X)$  and  $P(Y)$  upside-down.

**C:  $P(\text{Positive} | \text{"happy"}) = 0.10$**  Remember to calculate the ratio in the formula for Bayes' rule.

**D:  $P(\text{Positive} | \text{"happy"}) = 1.92$**  Did you use the probability of a tweet being positive? Remember that a fractional probability must be between 0 and 1.

# Summary

- Conditional probabilities  $\longrightarrow$  Bayes' Rule
- $P(X|Y) = P(Y|X) \times \frac{P(X)}{P(Y)}$



deeplearning.ai

# Naïve Bayes Introduction

---

# Naïve Bayes for Sentiment Analysis

## Positive tweets

I am happy because I am learning NLP  
I am happy, not sad.

## Negative tweets

I am sad, I am not learning NLP  
I am sad, not happy

word	Pos	Neg
I	3	3
am	3	3
happy	2	1
because	1	0
learning	1	1
NLP	1	1
sad	1	2
not	1	2
$N_{\text{class}}$	13	12



$P(w_i \mid \text{class})$

word	Pos	Neg
I	0.24	0.25
am	0.24	0.25
happy	0.15	0.08
because	0.08	0
learning	0.08	0.08
NLP	0.08	0.08
sad	0.08	0.08
not	0.08	0.17

# Naïve Bayes

Tweet: I am happy today; I am learning.

$$\prod_{i=1}^m \frac{P(w_i|pos)}{P(w_i|neg)} = \frac{0.14}{0.10} = 1.4 > 1$$

$$\frac{\cancel{0.20}}{\cancel{0.20}} * \frac{\cancel{0.20}}{\cancel{0.20}} * \frac{0.14}{0.10} * \frac{\cancel{0.20}}{\cancel{0.20}} * \frac{\cancel{0.20}}{\cancel{0.20}} * \frac{\cancel{0.10}}{\cancel{0.10}}$$

word	Pos	Neg
I	0.20	0.20
am	0.20	0.20
happy	0.14	0.10
because	0.10	0.05
learning	0.10	0.10
NLP	0.10	0.10
sad	0.10	0.10
not	0.10	0.15

# Summary

- Naive Bayes inference condition rule for binary classification
- Table of probabilities

$$\prod_{i=1}^m \frac{P(w_i|pos)}{P(w_i|neg)}$$





deeplearning.ai

# Laplacian Smoothing

# Laplacian Smoothing

$$P(w_i | \text{class}) = \frac{\text{freq}(w_i, \text{class})}{N_{\text{class}}} \quad \text{class} \in \{\text{Positive}, \text{Negative}\}$$

$$P(w_i | \text{class}) = \frac{\text{freq}(w_i, \text{class}) + 1}{N_{\text{class}} + V_{\text{class}}}$$

$N_{\text{class}}$  = frequency of all words in class

$V_{\text{class}}$  = number of unique words in class



# Introducing $P(w_i | \text{class})$ with smoothing

word	Pos	Neg		word	Pos	Neg
I	3	3	<div> <del>Laplace</del>  <b>additive</b> Smoothing         </div>			
am	3	3				
happy	2	1				
because	1	0				
learning	1	1				
NLP	1	1				
sad	1	2				
not	1	2				
Nclass	13		$V = 8$	Sum	1	1
12						

# Summary

- Laplacian smoothing to avoid  $P(w_i|class) = 0$
- Naïve Bayes formula

$$\prod_{i=1}^m \frac{P(w_i|pos)}{P(w_i|neg)}$$




deeplearning.ai

# Log Likelihood, Part 1

---

# Ratio of probabilities



word	Pos	Neg	ratio
I	0.19	0.20	
am	0.19	0.20	
happy	0.14	0.10	
because	0.10	0.05	
learning	0.10	0.10	
NLP	0.10	0.10	1
sad	0.10	0.15	
not	0.10	0.15	0.6

$$\text{ratio}(w_i) = \frac{P(w_i \mid \text{Pos})}{P(w_i \mid \text{Neg})}$$

$$\approx \frac{\text{freq}(w_i, 1) + 1}{\text{freq}(w_i, 0) + 1}$$

# Naïve Bayes' inference

$class \in \{pos, neg\}$

$w \rightarrow$  Set of  $m$  words in a tweet

$$\frac{P(pos)}{P(neg)} \prod_{i=1}^m \frac{P(w_i|pos)}{P(w_i|neg)} > 1$$

- A simple, fast, and powerful baseline
- A probabilistic model used for classification



# Log Likelihood

$$\frac{P(pos)}{P(neg)} \prod_{i=1}^m \frac{P(w_i|pos)}{P(w_i|neg)}$$

- Products bring risk of underflow

- $\log(a * b) = \log(a) + \log(b)$

- $\log\left(\frac{P(pos)}{P(neg)} \prod_{i=1}^n \frac{P(w_i|pos)}{P(w_i|neg)}\right) \Rightarrow \log \frac{P(pos)}{P(neg)} + \sum_{i=1}^n \log \frac{P(w_i|pos)}{P(w_i|neg)}$

**log prior + log likelihood**

# Calculating Lambda

tweet: I am happy because I am learning.

$$\lambda(w) = \log \frac{P(w|pos)}{P(w|neg)}$$

$$\lambda(am) = \log \frac{0.04}{0.04} = \log(1) = 0$$

word	Pos	Neg	$\lambda$
I	0.05	0.05	
am	0.04	0.04	
happy	0.09	0.01	
because	0.01	0.01	
learning	0.03	0.01	
NLP	0.02	0.02	
sad	0.01	0.09	
not	0.02	0.03	-0.4

# Summing the Lambdas

doc: I am happy because I am learning.

$$\lambda(w) = \log \frac{P(w|pos)}{P(w|neg)}$$

$$\lambda(\text{happy}) = \log \frac{0.09}{0.01} \approx 2.2$$

word	Pos	Neg	$\lambda$
I	0.05	0.05	0
am	0.04	0.04	0
happy	0.09	0.01	
because	0.01	0.01	
learning	0.03	0.01	
NLP	0.02	0.02	
sad	0.01	0.09	
not	0.02	0.03	-0.4

# Summary

- Word sentiment

$$ratio(w) = \frac{P(w|pos)}{P(w|neg)}$$

$$\lambda(w) = \log \frac{P(w|pos)}{P(w|neg)}$$



deeplearning.ai

# Log Likelihood, Part 2

# Log Likelihood

doc: I am happy because I am learning.


$$\sum_{i=1}^m \log \frac{P(w_i|pos)}{P(w_i|neg)} = \sum_{i=1}^m \lambda(w_i)$$

$$\text{log likelihood} = 0 \begin{matrix} + \\ 0 \end{matrix} \begin{matrix} + \\ 2.2 \end{matrix} \begin{matrix} + \\ 0 \end{matrix} \begin{matrix} + \\ 0 \end{matrix} \begin{matrix} + \\ 0 \end{matrix} \begin{matrix} + \\ 1.1 \end{matrix} = 3.3$$

word	Pos	Neg	$\lambda$
I	0.05	0.05	0
am	0.04	0.04	0
happy	0.09	0.01	2.2
because	0.01	0.01	0
learning	0.03	0.01	1.1
NLP	0.02	0.02	0
sad	0.01	0.09	-2.2
not	0.02	0.03	-0.4

# Log Likelihood


$$\prod_{i=1}^m \frac{P(w_i|pos)}{P(w_i|neg)} > 1$$



$$3.3 > 0$$




$$\sum_{i=1}^m \log \frac{P(w_i|pos)}{P(w_i|neg)} > 0$$



# Summary

Tweet sentiment:

$$\log \prod_{i=1}^m \text{ratio}(w_i) = \sum_{i=1}^m \lambda(w_i) > 0$$







deeplearning.ai

# Training Naïve Bayes

# Outline

- Five steps for training a Naïve Bayes model

# Training Naïve Bayes

Step 0: Collect and annotate corpus

Positive tweets

I am happy because I am learning

NLP  
I am happy, not sad. @NLP

Negative tweets

I am sad, I am not learning NLP

I am sad, not happy!!

Step 1:  
Preprocess

- Lowercase
- Remove punctuation, urls, names
- Remove stop words
- Stemming
- Tokenize sentences

Positive tweets

[happi, because, learn, NLP]

[happi, not, sad]

Negative tweets

[sad, not, learn, NLP]

[sad, not, happi]

# Training Naïve Bayes

## Positive tweets

[happi, because, learn, NLP]

[happi, not, sad]

## Negative tweets

[sad, not, learn, NLP]

[sad, not, happi]

Step 2:  
Word  
count

freq(w, class)

word	Pos	Neg
happi	2	1
because	1	0
learn	1	1
NLP	1	1
sad	1	2
not	1	2
$N_{\text{class}}$	7	7

# Training Naïve Bayes

freq(w, class)		
word	Pos	Neg
happi	2	1
because	1	0
learn	1	1
NLP	1	1
sad	1	2
not	1	2
$N_{\text{class}}$	7	7

Step 3:  
 $P(w|\text{class})$

$$V_{\text{class}} = 6$$

$$\frac{\text{freq}(w, \text{class}) + 1}{N_{\text{class}} + V_{\text{class}}}$$

$$\lambda(w) = \log \frac{P(w|\text{pos})}{P(w|\text{neg})}$$

Step 4:  
Get  
lambda

word	Pos	Neg	$\lambda$
happy	0.23	0.15	0.43
because	0.15	0.07	0.6
learning	0.08	0.08	0
NLP	0.08	0.08	0
sad	0.08	0.17	-0.75
not	0.08	0.17	-0.75

# Training Naïve Bayes

Step 5:  
Get the  
log prior

$D_{\text{pos}}$  = Number of positive tweets  
 $D_{\text{neg}}$  = Number of negative tweets

$$\text{logprior} = \log \frac{D_{\text{pos}}}{D_{\text{neg}}}$$

If dataset is balanced,  $D_{\text{pos}} = D_{\text{neg}}$  and  $\text{logprior} = 0$ .

# Summary

1. Get or annotate a dataset with positive and negative tweets
2. Preprocess the tweets:  $\text{process\_tweet}(\text{tweet}) \rightarrow [w_1, w_2, w_3, \dots]$
3. Compute  $\text{freq}(w, \text{class})$
4. Get  $P(w \mid \text{pos})$ ,  $P(w \mid \text{neg})$
5. Get  $\lambda(w)$
6. Compute  $\text{logprior} = \log(P(\text{pos}) / P(\text{neg}))$



deeplearning.ai

# Testing Naïve Bayes



# Outline

- Predict using a Näive Bayes Model
- Using your validation set to compute model accuracy

# Predict using Naïve Bayes

- log-likelihood dictionary  $\lambda(w) = \log \frac{P(w|pos)}{P(w|neg)}$

$$\logprior = \log \frac{D_{pos}}{D_{neg}} = 0$$

- Tweet: [I, pass, the, NLP, interview] 🍀

$$score = -0.01 + 0.5 - 0.01 + 0 + \logprior = 0.48$$

$$pred = score > 0$$

word	$\lambda$
I	-0.01
the	-0.01
happi	0.63
because	0.01
pass	0.5
NLP	0
sad	-0.75
not	-0.75

# Testing Naïve Bayes

- $X_{val}$   $Y_{val}$   $\lambda$   $logprior$

$$score = predict(X_{val}, \lambda, logprior)$$

$$pred = score > 0 \quad \begin{bmatrix} 0.5 \\ -1 \\ 1.3 \\ \vdots \\ score_m \end{bmatrix} > 0 = \begin{bmatrix} 0.5 > 0 \\ -1 > 0 \\ 1.3 > 0 \\ \vdots \\ score_m > 0 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \\ 1 \\ \vdots \\ pred_m \end{bmatrix}$$

# Testing Naïve Bayes

- $X_{val}$   $Y_{val}$   $\lambda$   $logprior$

$score = predict(X_{val}, \lambda, logprior)$

$pred = score > 0$

$$\frac{1}{m} \sum_{i=1}^m (pred_i == Y_{val_i})$$

$$\begin{bmatrix} \frac{0}{1} \\ 1 \\ \vdots \\ pred_m \end{bmatrix} == \begin{bmatrix} \frac{0}{0} \\ 1 \\ \vdots \\ Y_{val_m} \end{bmatrix}$$
$$\begin{bmatrix} \frac{1}{0} \\ 1 \\ \vdots \\ pred_m == Y_{val_m} \end{bmatrix}$$

# Summary

- $X_{val} \ Y_{val} \longrightarrow$  Performance on unseen data
- Predict using  $\lambda$  and *logprior* for each new tweet
- Accuracy  $\longrightarrow \frac{1}{m} \sum_{i=1}^m (pred_i == Y_{val_i})$
- What about words that do not appear in  $\lambda(w)$ ?



deeplearning.ai

# Applications of Naïve Bayes

# Applications of Naïve Bayes

$$P(pos|tweet) \approx P(pos)P(tweet|pos)$$

$$P(neg|tweet) \approx P(neg)P(tweet|neg)$$

$$\frac{P(pos|tweet)}{P(neg|tweet)} = \frac{P(pos)}{P(neg)} \prod_{i=1}^m \frac{P(w_i|pos)}{P(w_i|neg)}$$

# Applications of Naïve Bayes

Author identification:

$$\frac{P(\text{Shakespeare}|\text{book})}{P(\text{Shakespeare}|\text{book})}$$

Spam filtering:

$$\frac{P(\text{spam}|\text{email})}{P(\text{nospam}|\text{email})}$$



# Applications of Naïve Bayes

Information retrieval:

$$P(\text{document}_k | \text{query}) \propto \prod_{i=0}^{|\text{query}|} P(\text{query}_i | \text{document}_k)$$

Retrieve document if  $P(\text{document}_k | \text{query}) > \text{threshold}$

"Icon made by [Vector Market](https://www.vectormarket.com) from [www.flaticon.com](https://www.flaticon.com)"

# Applications of Naïve Bayes

Word disambiguation:

$$\frac{P(\text{river}|\text{text})}{P(\text{money}|\text{text})}$$

Bank:



["Pictures with CC"](#)

# Naïve Bayes Applications

- Sentiment analysis
- Author identification
- Information retrieval
- Word disambiguation
- Simple, fast and robust!



deeplearning.ai

# Naïve Bayes Assumptions

# Outline

- Independence
- Relative frequency in corpus

# Naïve Bayes Assumptions

- Independence

“It is sunny and hot in the Sahara desert.”



# Naïve Bayes Assumptions

“It’s always cold and snowy in \_\_\_.”



spring?? summer? fall?? winter??

# Naïve Bayes Assumptions

- Relative frequencies in corpus





# Summary

- Independence: Not true in NLP
- Relative frequency of classes affect the model



deeplearning.ai

# Error Analysis

# Outline

- Removing punctuation and stop words
- Word order
- Adversarial attacks

# Processing as a Source of Errors: Punctuation

**Tweet:** My beloved grandmotherX(

**processed\_tweet:** [belov, grandmoth]

# Processing as a Source of Errors: Removing Words

**Tweet:** This is not good, because your attitude is not even close to being nice.

**processed\_tweet:** [good, attitude, close, nice]

# Processing as a Source of Errors: Word Order

**Tweet:** I am happy because I do not go.



**Tweet:** I am not happy because I did go.



# Adversarial attacks

## Sarcasm, Irony and Euphemisms

**Tweet:** This is a ridiculously powerful movie. The plot was gripping and I cried right through until the ending!

**processed\_tweet:** [ridicul, power, movi, plot, grip, cry, end]

# Summary

- Removing punctuation
- Removing words
- Word order
- Adversarial attacks