



## 80 Years of Innovation



### CUTEX-180 Y-axis Series

Compact Horizontal Turning Center with  
6"-8" Chuck Loaded with Options



### Hi-TECH-230 Y-axis Series

Box Way Type Horizontal Turning Center  
with 8"-10" Chuck Loaded with Options

Contact us for Special Promotional Offer

**Chuck Size:** A: 6"(A2-5) | B: 8"(A2-6)

**NC Control:** Fanuc 0i-TF Plus

**Max. Spindle Speed A | B:**

6,000rpm | 4,500rpm

**Max. Bar Size: A:** Ø51mm | **B:** Ø65mm

**Chuck Size:** A: 8"(A2-6) | B/C: 10"(A2-8)

**NC Control:** Fanuc 0i-TF Plus

**Max. Spindle Speed A | B | C:**

4,500rpm | 3,500rpm | 3,500rpm

**Max. Bar Size:** A: Ø65mm | B/C: Ø81mm

Specifications above reflect machine models with YMC & YSMC configurations

S: Sub Spindle | MC: Live Tool | L: Long version | XL: Extra Long version

**Promotion Disclaimer:** The HwaCheon 80<sup>th</sup> Anniversary Promotion applies to Hi-TECH-230 A/B/C models with YMC/YSMC configuration, as well as the CUTEX-180 A/B models with YMC/YSMC configurations.

**Promotional Period Ends:** 31<sup>st</sup> Dec-2025

# QuantusTechnik

Locations: • Pune    • Kolhapur    • Bangalore



rajesh.gaikwaad@quantus-technik.com



+91-922 551 3636

## Standard Accessories: (CUTEX-180 series)

- Main chuck 6" (B-series: chuck 8")
- Soft Jaws
- BMT55 Turnmill (12 Station turret with Turnmill)
- 24 Positions (12 Station turret with Turnmill)
- U-Drill Holder Cap
- Digital Tailstock (use Hydraulic Cylinder) (Not available on Sub-spindle models (SMC))
- 0.05MPa Coolant Pump
- Coolant Level Sensor
- Tool Load Detect (L-HTLD)
- Tool Life Management
- Automatic Tool Offset (Tool Presetter option is required)
- Lathe Calculator Function (L-CAL)
- Work / Tool Management (L-COUNT)
- Hwacheon Lathe Vibration Control System (HLVC)
- M-Code & G-Code List Help
- Signal Lamp with 3 Color (R / G / Y)
- Manual Guide I
- 15" Non touch display



## Standard Accessories: (Hi-TECH 230 series)

- Soft Jaw
- BMT65 Turnmill (12 Station turret with Turnmill)
- 24 Positions (12 Station turret with Turnmill)
- Axial Driven Holder (BMT65)
- Radial Driven Holder (BMT65)
- U-Drill Holder Cap
- Coolant Pump 0.05 MPa
- Coolant Level Sensor
- Tool Load Detect (L-HTLD)
- Tool Life Management
- Automatic Tool Offset (Tool presetter option is required)
- Lathe Calculator Function (L-CAL)
- Work / ToolManagement (L-COUNT)
- Hwacheon Lathe Vibration Control System (HLVC)
- M-Code & G-Code List Help
- Signal Lamp with 3 Color (R / G / Y)
- Manual Guide I
- 15" Non touch display



**QuantusTechnik**

Locations: • Pune • Kolhapur • Bangalore



rajesh.gaikwaad@quantus-technik.com



+91-922 551 3636