



## Recommendation Systems

Recommendation systems are a collection of algorithms used to recommend items to users based on information taken from the user. These systems have become ubiquitous, and can be commonly seen in online stores, movies databases and job finders. In this tutorial, we will explore Content-based recommendation systems and implement a simple version of one using Python and the Pandas library.

## Acquiring the Data

Dataset acquired from [GroupLens](#)

Let's download and import the data on movie recommendation using `pandas.read_csv()` method.

[Download Dataset](#)

Unzip the downloaded file and place it to your project directory

## Importing required packages

```
In [4]: import pandas as pd
from math import sqrt
import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
```

## Reading the data

Now let's read each file into their Dataframes:

```
In [5]: #Storing the movie information into a pandas dataframe
movies_df = pd.read_csv('movies.csv')
#Storing the user information into a pandas dataframe
ratings_df = pd.read_csv('ratings.csv')
#Head is a function that gets the first N rows of a dataframe. N's default is 5.
movies_df.head()
```

```
Out[5]:
```

	movieId	title	genres
0	1	Toy Story (1995)	Adventure Animation Children Comedy Fantasy
1	2	Jumanji (1995)	Adventure Children Fantasy
2	3	Grumpier Old Men (1995)	Comedy Romance
3	4	Waiting to Exhale (1995)	Comedy Drama Romance
4	5	Father of the Bride Part II (1995)	Comedy

Let's also remove the year from the **title** column by using pandas' replace function and store in a new **year** column.

```
In [6]: #Using regular expressions to find a year stored between parentheses
#We specify the parantheses so we don't conflict with movies that have years in their titles
movies_df['year'] = movies_df.title.str.extract('(\d\d\d\d)', expand=False)
#Removing the parentheses
movies_df['year'] = movies_df.year.str.extract('(\d\d\d\d)', expand=False)
#Removing the years from the 'title' column
movies_df['title'] = movies_df.title.str.replace('(\d\d\d\d)', '')
#Applying the strip function to get rid of any ending whitespace characters that may have appeared
movies_df['title'] = movies_df['title'].apply(lambda x: x.strip())
movies_df.head()
```

```
C:\Users\Meer Moazzam\AppData\Local\Temp\ipykernel_13160\1143695627.py:7: FutureWarning: The default value of r
egex will change from True to False in a future version.
  movies_df['title'] = movies_df.title.str.replace('(\d\d\d\d\d\d\d\d\d\d)', '')
```

```
Out[6]:
```

	movieid	title	genres	year
0	1	Toy Story	Adventure Animation Children Comedy Fantasy	1995
1	2	Jumanji	Adventure Children Fantasy	1995
2	3	Grumpier Old Men	Comedy Romance	1995
3	4	Waiting to Exhale	Comedy Drama Romance	1995
4	5	Father of the Bride Part II	Comedy	1995

With that, let's also split the values in the **Genres** column into a **list of Genres** to simplify for future use. This can be achieved by applying Python's split string function on the correct column.

```
In [7]: #Every genre is separated by a | so we simply have to call the split function on |
movies_df['genres'] = movies_df.genres.str.split('|')
movies_df.head()
```

```
Out[7]:
```

	movieid	title	genres	year
0	1	Toy Story	[Adventure, Animation, Children, Comedy, Fantasy]	1995
1	2	Jumanji	[Adventure, Children, Fantasy]	1995
2	3	Grumpier Old Men	[Comedy, Romance]	1995
3	4	Waiting to Exhale	[Comedy, Drama, Romance]	1995
4	5	Father of the Bride Part II	[Comedy]	1995

Since keeping genres in a list format isn't optimal for the content-based recommendation system technique, we will use the One Hot Encoding technique to convert the list of genres to a vector where each column corresponds to one possible value of the feature. This encoding is needed for feeding categorical data. In this case, we store every different genre in columns that contain either 1 or 0. 1 shows that a movie has that genre and 0 shows that it doesn't. Let's also store this dataframe in another variable since genres won't be important for our first recommendation system.

```
In [8]: #Copying the movie dataframe into a new one since we won't need to use the genre information in our first case.
moviesWithGenres_df = movies_df.copy()

#For every row in the dataframe, iterate through the list of genres and place a 1 into the corresponding column
for index, row in movies_df.iterrows():
    for genre in row['genres']:
        moviesWithGenres_df.at[index, genre] = 1
#Filling in the NaN values with 0 to show that a movie doesn't have that column's genre
moviesWithGenres_df = moviesWithGenres_df.fillna(0)
moviesWithGenres_df.head()
```

```
Out[8]:
```

	movieid	title	genres	year	Adventure	Animation	Children	Comedy	Fantasy	Romance	...	Horror	Mystery	Sci-Fi	IMAX	Docu
0	1	Toy Story	[Adventure, Animation, Children, Comedy, Fantasy]	1995	1.0	1.0	1.0	1.0	1.0	0.0	...	0.0	0.0	0.0	0.0	
1	2	Jumanji	[Adventure, Children, Fantasy]	1995	1.0	0.0	1.0	0.0	1.0	0.0	...	0.0	0.0	0.0	0.0	
2	3	Grumpier Old Men	[Comedy, Romance]	1995	0.0	0.0	0.0	1.0	0.0	1.0	...	0.0	0.0	0.0	0.0	
3	4	Waiting to Exhale	[Comedy, Drama, Romance]	1995	0.0	0.0	0.0	1.0	0.0	1.0	...	0.0	0.0	0.0	0.0	
4	5	Father of the Bride Part II	[Comedy]	1995	0.0	0.0	0.0	1.0	0.0	0.0	...	0.0	0.0	0.0	0.0	

5 rows × 24 columns

Now, let's move towards at the ratings dataframe.

```
In [9]: ratings_df.head()
```

```
Out[9]:
```

	userId	movieId	rating	timestamp
0	1	169	2.5	1204927694
1	1	2471	3.0	1204927438
2	1	48516	5.0	1204927435
3	2	2571	3.5	1436165433
4	2	109487	4.0	1436165496

Every row in the ratings dataframe has a user id associated with at least one movie, a rating and a timestamp showing when they reviewed it. We won't be needing the timestamp column, so let's drop it to save memory.

```
In [10]: #Drop removes a specified row or column from a dataframe
ratings_df = ratings_df.drop('timestamp', 1)
ratings_df.head()
```

C:\Users\Meer Moazzam\AppData\Local\Temp\ipykernel\_13160\3391429438.py:2: FutureWarning: In a future version of pandas all arguments of DataFrame.drop except for the argument 'labels' will be keyword-only.  
 ratings\_df = ratings\_df.drop('timestamp', 1)

```
Out[10]:
```

	userId	movieId	rating
0	1	169	2.5
1	1	2471	3.0
2	1	48516	5.0
3	2	2571	3.5
4	2	109487	4.0

Now, let's take a look at how to implement **Content-Based** or **Item-Item recommendation systems**. This technique attempts to figure out what a user's favourite aspects of an item is, and then recommends items that present those aspects. In our case, we're going to try to figure out the input's favorite genres from the movies and ratings given.

Let's begin by creating an input user to recommend movies to:

Notice: To add more movies, simply increase the amount of elements in the **userInput**. Feel free to add more in! Just be sure to write it in with capital letters and if a movie starts with a "The", like "The Matrix" then write it in like this: 'Matrix, The'.

```
In [11]: userInput = [
            {'title': 'Breakfast Club, The', 'rating': 5},
            {'title': 'Toy Story', 'rating': 3.5},
            {'title': 'Jumanji', 'rating': 2},
            {'title': 'Pulp Fiction', 'rating': 5},
            {'title': 'Akira', 'rating': 4.5}
        ]
inputMovies = pd.DataFrame(userInput)
inputMovies
```

```
Out[11]:
```

	title	rating
0	Breakfast Club, The	5.0
1	Toy Story	3.5
2	Jumanji	2.0
3	Pulp Fiction	5.0
4	Akira	4.5

## Add movieId to input user

With the input complete, let's extract the input movie's ID's from the movies dataframe and add them into it.

We can achieve this by first filtering out the rows that contain the input movie's title and then merging this subset with the input dataframe. We also drop unnecessary columns for the input to save memory space.

```
In [12]: #Filtering out the movies by title
inputId = movies_df[movies_df['title'].isin(inputMovies['title'].tolist())]
#Then merging it so we can get the movieId. It's implicitly merging it by title.
inputMovies = pd.merge(inputId, inputMovies)
#Dropping information we won't use from the input dataframe
inputMovies = inputMovies.drop('genres', 1).drop('year', 1)
#Final input dataframe
#If a movie you added in above isn't here, then it might not be in the original
#dataframe or it might spelled differently, please check capitalisation.
inputMovies
```



Now we're ready to start learning the input's preferences!

To do this, we're going to turn each genre into weights. We can do this by using the input's reviews and multiplying them into the input's genre table and then summing up the resulting table by column. This operation is actually a dot product between a matrix and a vector, so we can simply accomplish by calling the Pandas "dot" function.

```
In [15]: inputMovies['rating']
```

```
Out[15]:
0    3.5
1    2.0
2    5.0
3    4.5
4    5.0
Name: rating, dtype: float64
```

```
In [16]: #Dot produt to get weights
userProfile = userGenreTable.transpose().dot(inputMovies['rating'])
#The user profile
userProfile
```

```
Out[16]:
Adventure      10.0
Animation       8.0
Children        5.5
Comedy         13.5
Fantasy         5.5
Romance         0.0
Drama          10.0
Action          4.5
Crime           5.0
Thriller        5.0
Horror          0.0
Mystery         0.0
Sci-Fi          4.5
IMAX            0.0
Documentary     0.0
War             0.0
Musical         0.0
Western         0.0
Film-Noir       0.0
(no genres listed) 0.0
dtype: float64
```

Now, we have the weights for every of the user's preferences. This is known as the User Profile. Using this, we can recommend movies that satisfy the user's preferences.

Let's start by extracting the genre table from the original dataframe:

```
In [19]: #Now let's get the genres of every movie in our original dataframe
genreTable = moviesWithGenres_df.set_index(moviesWithGenres_df['movieId'])
#And drop the unnecessary information
genreTable = genreTable.drop('movieId', 1).drop('title', 1).drop('genres', 1).drop('year', 1)
genreTable.head()
```

```
C:\Users\Meer Moazzam\AppData\Local\Temp\ipykernel_13160\789887408.py:4: FutureWarning: In a future version of pandas all arguments of DataFrame.drop except for the argument 'labels' will be keyword-only.
  genreTable = genreTable.drop('movieId', 1).drop('title', 1).drop('genres', 1).drop('year', 1)
C:\Users\Meer Moazzam\AppData\Local\Temp\ipykernel_13160\789887408.py:4: FutureWarning: In a future version of pandas all arguments of DataFrame.drop except for the argument 'labels' will be keyword-only.
  genreTable = genreTable.drop('movieId', 1).drop('title', 1).drop('genres', 1).drop('year', 1)
C:\Users\Meer Moazzam\AppData\Local\Temp\ipykernel_13160\789887408.py:4: FutureWarning: In a future version of pandas all arguments of DataFrame.drop except for the argument 'labels' will be keyword-only.
  genreTable = genreTable.drop('movieId', 1).drop('title', 1).drop('genres', 1).drop('year', 1)
C:\Users\Meer Moazzam\AppData\Local\Temp\ipykernel_13160\789887408.py:4: FutureWarning: In a future version of pandas all arguments of DataFrame.drop except for the argument 'labels' will be keyword-only.
  genreTable = genreTable.drop('movieId', 1).drop('title', 1).drop('genres', 1).drop('year', 1)
```

```
Out[19]:
```

	Adventure	Animation	Children	Comedy	Fantasy	Romance	Drama	Action	Crime	Thriller	Horror	Mystery	Sci-Fi	IMAX	Docume
movieId															
1	1.0	1.0	1.0	1.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
2	1.0	0.0	1.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
3	0.0	0.0	0.0	1.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
4	0.0	0.0	0.0	1.0	0.0	1.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
5	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

```
In [20]: genreTable.shape
```

```
Out[20]: (34208, 20)
```

With the input's profile and the complete list of movies and their genres in hand, we're going to take the weighted average of every movie

that the input profile and the complete list of movies and their genres in hand, we're going to take the weighted average of every movie based on the input profile and recommend the top twenty movies that most satisfy it.

```
In [21]: #Multiply the genres by the weights and then take the weighted average
recommendationTable_df = ((genreTable*userProfile).sum(axis=1))/(userProfile.sum())
recommendationTable_df.head()
```

```
Out[21]: movieId
1      0.594406
2      0.293706
3      0.188811
4      0.328671
5      0.188811
dtype: float64
```

```
In [22]: #Sort our recommendations in descending order
recommendationTable_df = recommendationTable_df.sort_values(ascending=False)
#Just a peek at the values
recommendationTable_df.head()
```

```
Out[22]: movieId
5018      0.748252
26093     0.734266
27344     0.720280
148775    0.685315
6902      0.678322
dtype: float64
```

Now here's the recommendation table!

```
In [23]: #The final recommendation table
movies_df.loc[movies_df['movieId'].isin(recommendationTable_df.head(20).keys())]
```

```
Out[23]:
```

	movieId		title	genres	year
664	673		Space Jam	[Adventure, Animation, Children, Comedy, Fanta...	1996
1824	1907		Mulan	[Adventure, Animation, Children, Comedy, Drama...	1998
2902	2987		Who Framed Roger Rabbit?	[Adventure, Animation, Children, Comedy, Crime...	1988
4923	5018		Motorama	[Adventure, Comedy, Crime, Drama, Fantasy, Mys...	1991
6793	6902		Interstate 60	[Adventure, Comedy, Drama, Fantasy, Mystery, S...	2002
8605	26093	Wonderful World of the Brothers Grimm, The		[Adventure, Animation, Children, Comedy, Drama...	1962
8783	26340	Twelve Tasks of Asterix, The (Les douze travau...		[Action, Adventure, Animation, Children, Comed...	1976
9296	27344	Revolutionary Girl Utena: Adolescence of Utena...		[Action, Adventure, Animation, Comedy, Drama, ...	1999
9825	32031		Robots	[Adventure, Animation, Children, Comedy, Fanta...	2005
11716	51632		Atlantis: Milo's Return	[Action, Adventure, Animation, Children, Comed...	2003
11751	51939	TMNT (Teenage Mutant Ninja Turtles)		[Action, Adventure, Animation, Children, Comed...	2007
13250	64645		The Wrecking Crew	[Action, Adventure, Comedy, Crime, Drama, Thri...	1968
16055	81132		Rubber	[Action, Adventure, Comedy, Crime, Drama, Film...	2010
18312	91335		Gruffalo, The	[Adventure, Animation, Children, Comedy, Drama]	2009
22778	108540	Ernest & Célestine (Ernest et Célestine)		[Adventure, Animation, Children, Comedy, Drama...	2012
22881	108932		The Lego Movie	[Action, Adventure, Animation, Children, Comed...	2014
25218	117646		Dragonheart 2: A New Beginning	[Action, Adventure, Comedy, Drama, Fantasy, Th...	2000
26442	122787		The 39 Steps	[Action, Adventure, Comedy, Crime, Drama, Thri...	1959
32854	146305		Princes and Princesses	[Animation, Children, Comedy, Drama, Fantasy, ...	2000
33509	148775		Wizards of Waverly Place: The Movie	[Adventure, Children, Comedy, Drama, Fantasy, ...	2009

## Pros and Cons of Content-Based Filtering

### Pros

- Learns user's preferences
- Highly personalized for the user

### Cons

- Doesn't take into account what others think of the item, so low quality item recommendations might happen
- Extracting data is not always intuitive
- Determining what characteristics of the item the user dislikes or likes is not always obvious

Thank you

# Author

Moazzam Ali

---

© [MT Learners](#) 2022. All rights reserved.

Loading [MathJax]/jax/output/CommonHTML/fonts/TeX/fontdata.js