

Cryptographic primitives

Blockchain Course
Dimitris Grigoriou, Christos Nasikas, Dionysis Zindros

Hash functions


Hash functions

- Map data of arbitrary size to a string of a fixed length
- $h(x) = y$, where $h: \{0, 1\}^* \rightarrow \{0, 1\}^n$
- Various applications: hash tables, file integrity, cache mechanisms, identifiers, time-stamping

Cryptographic Hash Functions

- $h(x) = y$
- Easy to calculate y , given x
- Properties:
 - Collision resistance: Nobody can find different x, x' that produce the same y
 - Hiding: Practically infeasible to find x from y
 - Puzzle-friendly: Even a small change to x affects significantly y

Cryptographic Hash Functions



sha2

- Descendant of sha1
- It is considered safe for cryptographic applications
- SHA224: $\{0,1\}^* \rightarrow \{0,1\}^{224}$
- SHA256: $\{0,1\}^* \rightarrow \{0,1\}^{256}$
- SHA384: $\{0,1\}^* \rightarrow \{0,1\}^{384}$
- SHA512: $\{0,1\}^* \rightarrow \{0,1\}^{512}$

Example of sha256

sha256('NBG')

=

79DE06AB4736A8430605FBE1CA7F69E5E9DBB792E977

4C583FFD06F3DFD1273

'Reversing' a hash

- Hashes are designed to be one-way, irreversible
- So, the reversing can be done only by **brute-force**
 - Try all possible strings of length 0, 1, 2, 3 etc...
 - Try words from a dictionary

Hash dictionary attack

```
for (word in dictionary):  
    if(SHA256(word) == c):  
        return word
```

Commitment schemes

Commitment schemes

- Alice wants to commit to a value “b”
- Alice and Bob do not trust each other
- **Binding:** Bob wants to know that Alice will not change her mind about b
- **Hiding:** Alice does not want to reveal her value beforehand


Commitment schemes: phases

- Commitment phase:
 - Alice chooses and commits to a value
 - Sends a secret to Bob
 - **Hiding:** Bob cannot use the secret to find the value of Alice
- Reveal phase:
 - Bob learns the initial value Alice chose
 - **Binding:** Bob confirms that Alice didn't change her value using the secret

Commitment schemes: using a hash

- Commitment phase:
 - Alice computes $\mathbf{c} = \mathbf{H}(\mathbf{b})$
 - Send \mathbf{c} to Bob
 - Bob cannot reverse \mathbf{c} to get \mathbf{b}

Commitment schemes: commitment phase



Computes $c = h(b)$

c




c

Commitment schemes: using a hash

- Reveal phase:
 - Alice sent **b** to Bob
 - Bob checks that $H(b) = c$

Reveal phase: reveal phase



b

b



Checks that
 $c = h(b)$

Proof of work

- Cryptographic primitive that describes the proof of executed CPU cycles
- Alice wants to prove that Bob will dedicate his CPU power only for her
- How can she do that ?


Proof of work

- Alice chooses a random *salt* K , big enough (i.e. 128 bits)
- Alice sends to Bob the salt K , and a target parameter T .
- The target parameter defines the amount of work to be done

Proof of work

- Bob calculates x such that
 - $H(K \parallel x) < T$
- x is the *nonce*
- Bob sends x to Alice
- Alice validates that $H(K \parallel x) < T$


Proof of work: Request



K, T




Proof of work: Work



$H(K \parallel x) < T ?$

Proof of work: Proof



$H(K \parallel x) < T ?$

x



Proof of work: Algorithm

```
while (H(K || x) >= T):
```

```
    x = rand()
```

```
return x
```

Proof of work

- Very important to blockchain consensus mechanisms
- More details in the following lectures...

Merkle trees

Merkle Trees

- A data structure: usually a binary tree
- Used for efficiently summarizing and verifying the integrity and validity of large sets of data
- Useful in peer-to-peer networks
 - Damaged / Altered blocks can be received and identified as such
 - Prevent malicious actors to send fake blocks
- Used in ipfs, git, BitTorrent, nosql databases, bitcoin, ethereum


Merkle Trees

- Proofs for data integrity and validity
- Proofs require little memory and space
- Proofs require tiny amounts of information to be transmitted across networks

Merkle Trees

- Used for keeping a summary of all the information in a block
- Digital fingerprint of the entire set of information
- Information hasn't been altered or tampered within a block
- Fast proof of inclusion

Binary tree



Merkle tree: construction

Transactions


T1

T2


T3

T4


Merkle tree: construction




Merkle tree: construction




Merkle tree: construction



Merkle tree: construction




Merkle tree: bitcoin block




Merkle tree: proof of inclusion

- How do I prove that a transaction belongs to a certain tree?
- No need to download the entire tree


Merkle tree: proof of inclusion




Merkle tree: proof of inclusion



Merkle tree: proof of inclusion



Merkle tree: proof of inclusion



Merkle tree: proof of inclusion

- As a client that needs to store space there is no need to store the entire tree, but only the header


Tries

- Called also radix tree or prefix tree
- Search tree: ordered tree data structure
- Used to store a set or an associative array
- Keys usually are strings

Tries: example

{ do: 0, dog: 1, dax: 2, dogu: 3, dodo: 4, house: 5, houses: 6 }


Tries



Patricia (or radix) trie


- Space-optimized trie
- Each node that is the only child is merged with its parent

Patricia trie




Digital signatures

Digital signatures



“See you at 9pm”



“See you at 10pm”



Did Alice send the message ?
Is this the message Alice wrote ?

Digital signatures

- **Integrity:** The signed message was not *altered* in transit
- **Authentication:** The signature was created by a known sender
- **Non-repudiation:** The sender cannot deny having signed the message

Digital signatures

- The sender produce a key pair (vk , sk)
- sk : signing key
- vk : verification key

Digital signatures

- Verification key is **public**
 - publicly verifiable
 - transferable signatures
- Signing key is private

Digital signatures


- $\sigma = \text{sign}(\text{sk}, m)$
- $\text{verify}(\text{vk}, \sigma, m) = \{0, 1\}$

Digital signatures



$\sigma = \text{sign}(\text{sk}, \text{'See you at 9pm'})$

See you at 9pm



σ

See you at 10pm



$\text{verify}(\text{vk}, \sigma, \text{'See you at 10pm'})$
= false

Not Alice!!

Digital signatures

- Digital signatures are very important to blockchain systems
- A valid signature implies ownership
- More details in the following lectures...