

Module Interface Specification for Software Engineering

Team 4, EvENGage
Virochaan Ravichandran Gowri
Omar Al-Asfar
Rayyan Suhail
Ibrahim Quraishi
Mohammad Mahdi Mahboob

January 21, 2026

1 Revision History

Date		Version	Notes
November 2025	13,	1.0	Revision -1

2 Symbols, Abbreviations and Acronyms

Glossary

admin A privileged system user affiliated with [McMaster Engineering Society \(MES\)](#) who can access survey, event, and attendee records; track finances; and update event statuses. plural.

attendee An individual who attends an [MES](#) event, and uses the system to register, receive event updates, provide feedback, or fill out survey responses. plural.

Acronyms

CFES Canadian Federation of Engineering Students.

MES McMaster Engineering Society.

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Introduction	1
4	Notation	1
5	Module Decomposition	2
6	MIS of M1: Main System Module	3
6.1	Module	3
6.2	Uses	3
6.3	Syntax	3
6.3.1	Exported Constants	3
6.3.2	Exported Access Programs	3
6.4	Semantics	3
6.4.1	State Variables	3
6.4.2	Environment Variables	3
6.4.3	Assumptions	3
6.4.4	Access Routine Semantics	3
6.4.5	Local Functions	3
7	MIS of M2: User Authentication Module	4
7.1	Module	4
7.2	Uses	4
7.3	Syntax	4
7.3.1	Exported Constants	4
7.3.2	Exported Access Programs	4
7.4	Semantics	4
7.4.1	State Variables	4
7.4.2	Environment Variables	4
7.4.3	Assumptions	4
7.4.4	Access Routine Semantics	5
7.4.5	Local Functions	5
8	MIS of M3: User Authorization Module	7
8.1	Module	7
8.2	Uses	7
8.3	Syntax	7
8.3.1	Exported Constants	7
8.3.2	Exported Access Programs	7

8.4	Semantics	7
8.4.1	State Variables	7
8.4.2	Environment Variables	7
8.4.3	Assumptions	7
8.4.4	Access Routine Semantics	7
8.4.5	Local Functions	8
9	MIS of M4: Form Template Module	9
9.1	Module	9
9.2	Uses	9
9.3	Syntax	10
9.3.1	Exported Constants	10
9.3.2	Exported Access Programs	10
9.4	Semantics	10
9.4.1	State Variables	10
9.4.2	Environment Variables	11
9.4.3	Assumptions	11
9.4.4	Access Routine Semantics	11
9.4.5	Local Functions	13
10	MIS of M5: Form Submission Module	14
10.1	Module	14
10.2	Uses	14
10.3	Syntax	14
10.3.1	Exported Constants	14
10.3.2	Exported Access Programs	14
10.4	Semantics	14
10.4.1	State Variables	14
10.4.2	Environment Variables	14
10.4.3	Assumptions	15
10.4.4	Access Routine Semantics	15
10.4.5	Local Functions	16
11	MIS of M6: Event Management Module	17
11.1	Module	17
11.2	Uses	17
11.3	Syntax	17
11.3.1	Exported Constants	17
11.3.2	Exported Access Programs	17
11.4	Semantics	17
11.4.1	State Variables	17
11.4.2	Environment Variables	17
11.4.3	Assumptions	17

11.4.4	Access Routine Semantics	17
11.4.5	Local Functions	18
12	MIS of M7: Event Notification Module	19
12.1	Module	19
12.2	Uses	19
12.3	Syntax	19
12.3.1	Exported Constants	19
12.3.2	Exported Access Programs	19
12.4	Semantics	19
12.4.1	State Variables	19
12.4.2	Environment Variables	19
12.4.3	Assumptions	19
12.4.4	Access Routine Semantics	19
12.4.5	Local Functions	20
13	MIS of M8: Registration Module	21
13.1	Module	21
13.2	Uses	21
13.3	Syntax	21
13.3.1	Exported Constants	21
13.3.2	Exported Access Programs	21
13.4	Semantics	21
13.4.1	State Variables	21
13.4.2	Environment Variables	21
13.4.3	Assumptions	22
13.4.4	Access Routine Semantics	22
13.4.5	Local Functions	23
14	MIS of M9: Attendance Tracking Module	24
14.1	Module	24
14.2	Uses	24
14.3	Syntax	24
14.3.1	Exported Constants	24
14.3.2	Exported Access Programs	24
14.4	Semantics	24
14.4.1	State Variables	24
14.4.2	Environment Variables	24
14.4.3	Assumptions	24
14.4.4	Access Routine Semantics	24
14.4.5	Local Functions	25

15 MIS of M10: Report Generation Module	26
15.1 Module	26
15.2 Uses	26
15.3 Syntax	26
15.3.1 Exported Constants	26
15.3.2 Exported Access Programs	26
15.4 Semantics	26
15.4.1 State Variables	26
15.4.2 Environment Variables	26
15.4.3 Assumptions	26
15.4.4 Access Routine Semantics	27
15.4.5 Local Functions	27
16 MIS of M11: Analytics Module	28
16.1 Module	28
16.2 Uses	28
16.3 Syntax	28
16.3.1 Exported Constants	28
16.3.2 Exported Access Programs	28
16.4 Semantics	28
16.4.1 State Variables	28
16.4.2 Environment Variables	28
16.4.3 Assumptions	28
16.4.4 Access Routine Semantics	29
16.4.5 Local Functions	29
17 MIS of M12: Database Access Module	30
17.1 Module	30
17.2 Uses	30
17.3 Syntax	30
17.3.1 Exported Constants	30
17.3.2 Exported Access Programs	30
17.4 Semantics	30
17.4.1 State Variables	30
17.4.2 Environment Variables	31
17.4.3 Assumptions	31
17.4.4 Access Routine Semantics	31
17.4.5 Local Functions	32
18 MIS of M13: Audit Module	33
18.1 Module	33
18.2 Uses	33
18.3 Syntax	33

18.3.1	Exported Constants	33
18.3.2	Exported Access Programs	33
18.4	Semantics	33
18.4.1	State Variables	33
18.4.2	Environment Variables	33
18.4.3	Assumptions	33
18.4.4	Access Routine Semantics	34
18.4.5	Local Functions	34
19	Appendix	35

3 Introduction

The following document details the Module Interface Specifications for EvENGage. EvENGage is a custom event and survey management system being designed for the MES to simplify and centralize the process of hosting events, conferences, and surveys.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at <https://github.com/VirochaanRG/MES-Event-Management-System/>.

4 Notation

The structure of the MIS for modules comes from ?, with the addition that template modules have been adapted from ?. The mathematical notation comes from Chapter 3 of ?. For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by Software Engineering.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	\mathbb{N}	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$
string	string	An ordered list of characters of any length
Cookie	Cookie	A file stored on the client device storing user data
List of type T	list(T)	A dynamically sized list of elements of type T
Set of type T	set(T)	A dynamically sized set of elements of type T
Map of type K to V	map(K, V)	A collection mapping keys of type K to values of type V. Shorthand notation for set(tuple(K, V)).
Tuple of types T1, T2, ...	tuple(T1, T2, ...)	A finite ordered collection of elements of the specified types
Date and time	DateTime	A specific date and time using the Gregorian calendar and 24-hour clock

The specification of Software Engineering uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, Software Engineering uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding Module	No Modules
Behaviour-Hiding Modules	M1: Main System Module
	M2: User Authentication Module
	M3: User Authorization Module
	M4: Form Template Module
	M5: Form Submission Module
	M6: Event Management Module
	M7: Event Notification Module
	M8: Registration Module
	M9: Attendance Tracking Module
	M10: Report Generation Module
Software-Decision Modules	M11: Analytics Module
	M12: Database Access Module
	M13: Audit Module

Table 1: Module Hierarchy

6 MIS of M1: Main System Module

6.1 Module

Acts as the entry point for all other modules

6.2 Uses

Acts as the entry point for M2, M4, M6, M10.

6.3 Syntax

6.3.1 Exported Constants

None

6.3.2 Exported Access Programs

None

6.4 Semantics

6.4.1 State Variables

None

6.4.2 Environment Variables

None

6.4.3 Assumptions

This module can be invoked externally by a user who has access to the backend server.

6.4.4 Access Routine Semantics

N/A

6.4.5 Local Functions

None

7 MIS of M2: User Authentication Module

7.1 Module

Contains functionality for authenticating users and registering new users.

7.2 Uses

None

7.3 Syntax

7.3.1 Exported Constants

None

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
attemptLogin	username : string password : string	sessionCookie : Cookie	None
logout	sessionCookie : Cookie	None	InvalidSession
validateSession	sessionCookie : Cookie	sessionIsValid : bool	None
registerUser	username : string password : string	registrationSuccessful : bool	None

7.4 Semantics

7.4.1 State Variables

sessions : set(Cookie): Set of all active sessions

credentials : map(string, string): Mapping of all registered usernames to their passwords

7.4.2 Environment Variables

currentTime : DateTime: Stores the current date and time

7.4.3 Assumptions

Passwords are encrypted before storage.

7.4.4 Access Routine Semantics

`attemptLogin(username : string, password : string):`

Attempts a login given a username and password.

- transition: If `tuple(username, password) ∈ credentials`, then `sessions := sessions ∪ set(generateCookie(username))`
- output: Cookie containing session data to be sent back to the client
- exception: None

`logout(sessionCookie: Cookie):`

Logs the specified user out.

- transition: `sessions := sessions - set(sessionCookie)`
- output: None
- exception: `InvalidSession` if session is not found in `sessions`

`validateSession(sessionCookie: Cookie):`

Validates and refreshes a users session.

- transition: If `sessionCookie ∈ sessions`, then `sessionCookie.lastRefresh := currentTime`
- output: Boolean indicating if `sessionCookie` exists in `sessions`
- exception: None

`registerUser(username : string, password : string):`

Registers a new user to the database of users.

- transition: `credentials := credentials ∪ set(tuple(username, password))`
- output: Boolean stating whether registration was successful
- exception: None

7.4.5 Local Functions

`generateCookie(username : string):`

Generates a cookie for a user.

- transition: None
- output: Cookie containing `username` and `lastRefresh := currentTime`
- exception: None

`refreshSessions()`:

Checks all sessions and invalidates old sessions. Scheduled to run periodically.

- transition: $\forall s \in \text{sessions} \mid s.\text{lastRefresh} - \text{currentTime} > 3\text{hrs}, \text{sessions} := \text{sessions} - s$
- output: None
- exception: None

8 MIS of M3: User Authorization Module

8.1 Module

Contains functionality for role based access management

8.2 Uses

Uses M2 for authentication before checking authorizations.

8.3 Syntax

8.3.1 Exported Constants

`validRoles : set(Role)`: The set of all valid roles that can be assigned to users.

8.3.2 Exported Access Programs

Name	In	Out	Exceptions
addRole	<code>userId : N</code>	None	InvalidRole
	<code>role : Role</code>		InvalidUser
removeRole	<code>userId : N</code>	None	InvalidRole
	<code>role : Role</code>		InvalidUser
hasPermission	<code>userId : N</code>	<code>hasPermission : bool</code>	InvalidRole
	<code>role : Role</code>		InvalidUser
getUserRoles	<code>userId : N</code>	<code>roles : set(Role)</code>	InvalidUser

8.4 Semantics

8.4.1 State Variables

`roles : map(N, set(T))`: Mapping of user ID to the set of roles the user is assigned.

8.4.2 Environment Variables

None

8.4.3 Assumptions

At least one user who has permission to assign and revoke roles already exists in the system.

8.4.4 Access Routine Semantics

`addRole(userId : N, role : Role)`:

Assigns a role to a user.

- transition: Inserts the specified role into the set attached to the user ID in **roles**
- output: None
- exception: InvalidRole if the role does not exist, InvalidUser if the user does not exist

removeRole(userId : N, role : Role):

Revokes a role from a user.

- transition: Removes the specified role from the set attached to the user ID in **roles**
- output: None
- exception: InvalidRole if the role does not exist, InvalidUser if the user does not exist

hasPermission(userId : N, role : Role):

Checks if a user has a certain permission.

- transition: None
- output: A boolean value which is true if the set attached to the user ID in **roles** contains the specified role
- exception: InvalidRole if the role does not exist, InvalidUser if the user does not exist

getUserRoles(userId : N):

Gets all roles assigned to a given user.

- transition: None
- output: The set of roles attached to the user ID in **roles**
- exception: InvalidUser if the user does not exist

8.4.5 Local Functions

None

9 MIS of M4: Form Template Module

9.1 Module

Contains functionality for creating and linking form modules.

9.2 Uses

Uses M3 to check for form managment permissions.

9.3 Syntax

9.3.1 Exported Constants

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
createModule	moduleTitle : string questions : list(Question)	module : FormModule	None
deleteModule	moduleId : N	None	InvalidModule
editModule	moduleId : N newModuleName : string newQuestions : list(Question)	None	InvalidModule
copyModule	moduleId : N	copiedModule : FormModule	InvalidModule
getModules	None	modules : set(FormModule)	None
linkQuestion	question : Question linkedModule: list(string)	None	InvalidModule IllegalArgument
createForm	formName : string startingModuleId : N formSettings : map(string, string)	Form	None
deleteForm	formId : N	None	InvalidForm
editForm	newFormName : string startingModuleId : N newFormSettings : map(string, string)	None	InvalidForm
releaseForm	formId : N, deadline : DateTime	None	InvalidForm
hideForm	formName : string, startingModuleId : N	None	InvalidForm

9.4 Semantics

9.4.1 State Variables

modules : set(FormModule): Set of all created form modules.

createdForms : set(Form): Set of all created forms.

9.4.2 Environment Variables

`currentTime` : `DateTime`: The current date and time

9.4.3 Assumptions

The calculated current date and time is within 5 seconds of the real date and time

9.4.4 Access Routine Semantics

`createModule(moduleTitle : string, questions : list(Question)):`

Creates a new module given a title and a list of questions.

- transition: Inserts the created module into `modules`
- output: The created `FormModule`
- exception: None

`deleteModule(moduleId : N):`

Deletes a module.

- transition: Removes the created module from `modules`
- output: None
- exception: `InvalidModule` if module does not exist

`editModule(moduleId : N, newModuleName : string, newQuestions : list(Question)):`

Edits the module, assigning a new name and question list.

- transition: Removes the specified module, then inserts the modified one into `modules`
- output: None
- exception: `InvalidModule` if module does not exist

`copyModule(moduleId : N):`

Copies an existing module.

- transition: Creates a copy of the given module with a different module ID, then inserts it into `modules`
- output: The copied `FormModule`
- exception: `InvalidModule` if module does not exist

`getModules():`

Retrieves the set of all modules.

- transition: None
- output: A copy of `modules`
- exception: None

`linkQuestion(question : Question, linkedModuleIds: list(N)):`

Links the answers of a question to another module for branching forms.

- transition: Modifies the module in `modules` containing the specified Question
- output: None
- exception: `InvalidModule` if module does not exist, `IllegalArgument` if the size of `linkedModuleIds` does not match the number of possible answers in the question.

`createForm(formTitle : string, startingModuleId: string, formSettings : map(string, string)):`

Creates a form starting from a specified module with certain settings (e.g. multiple submissions, editable submissions)

- transition: Inserts the created form into `createdForms`
- output: The created Form
- exception: None

`deleteForm(formId : N):`

Deletes the specified form.

- transition: Removes the specified form from `createdForms`
- output: None
- exception: `InvalidForm` if form does not exist

`editForm(formTitle : string, startingModuleId: string, formSettings : map(string, string)):`

Edits the specified form.

- transition: Removes the specified form from `createdForms` and inserts the modified form
- output: None
- exception: `InvalidForm` if form does not exist

`releaseForm(formId: string, deadline : DateTime):`

Releases a form for submissions with the specified deadline.

- transition: Modifies the visibility of the specified form in `createdForms`
- output: None
- exception: `InvalidForm` if form does not exist

`hideForm(formId: string):`

Closes submissions for a form.

- transition: Modifies the visibility of the specified form in `createdForms`
- output: None
- exception: `InvalidForm` if form does not exist

9.4.5 Local Functions

`expireForms():`

Periodically checks `createdForms` for expired deadlines and closes them.

- transition: Modifies the visibility of the forms in `createdForms`
- output: None
- exception: None

10 MIS of M5: Form Submission Module

10.1 Module

Contains functionality for submitting reponses to forms.

10.2 Uses

Uses M4 to retrieve fillable forms.

10.3 Syntax

10.3.1 Exported Constants

None

10.3.2 Exported Access Programs

Name	In	Out	Exceptions
getFillableForms	userId : \mathbb{N}	fillableForms : set(Form)	InvalidUser
respondToForm	userId : \mathbb{N} formId : \mathbb{N} formResponse : map(Question, string)	responseId : \mathbb{N}	InvalidUser InvalidForm IllegalArgument
getResponses	userId : \mathbb{N} formId : \mathbb{N}	responseIds : set(\mathbb{N})	InvalidUser InvalidForm
editResponse	userId : \mathbb{N} responseId : \mathbb{N} formResponse : map(Question, string)	None	InvalidUser InvalidForm IllegalArgument UnsupportedOperation

10.4 Semantics

10.4.1 State Variables

formResponses : map(form : Form, responseIds : list(\mathbb{N})): A list of responses for each form

userResponses : map(userId : \mathbb{N} , responseIds : list(\mathbb{N})): A list of responses for each user

10.4.2 Environment Variables

None

10.4.3 Assumptions

None

10.4.4 Access Routine Semantics

`getFillableForms(userId : N):`

Retrieves all forms fillable by the user.

- transition: None
- output: The set of all forms available for the user to fill
- exception: InvalidUser if user does not exist

`respondToForm(userId : N, formId: string,
formResponse: map(Question, string)):`

Records a user's response to a form.

- transition: Inserts the created response ID into `userResponses` and `formResponses`
- output: None
- exception: InvalidUser if user does not exist, InvalidForm if the form does not exist, IllegalArgument if the responses do not match the expected format given by the form (e.g. unidentified question)

`getResponses(userId : N, formId: string):`

Retrieves all of a user's responses for a given forms.

- transition: None
- output: The set of all responses for the user in `userResponses` for a particular form in `formResponses`
- exception: InvalidUser if user does not exist, InvalidForm if the form does not exist

`editResponse(userId : N, formId: string,
formResponse: map(Question, string)):`

Modifies a user's response to a form.

- transition: Edits the response for the given form (if it allows editing) in `userResponses` and `formResponses`
- output: None
- exception: InvalidUser if user does not exist, InvalidForm if the form does not exist, IllegalArgument if the responses do not match the expected format given by the form, UnsupportedOperationException if the form does not allow editing responses

10.4.5 Local Functions

None

11 MIS of M6: Event Management Module

11.1 Module

Contains functionality for creating and managing events.

11.2 Uses

Uses M3 to check permissions for managing events, and M7 for sending event related notifications.

11.3 Syntax

11.3.1 Exported Constants

11.3.2 Exported Access Programs

Name	In	Out	Exceptions
createEvent	eventDetails : EventData	eventId : \mathbb{N}	IllegalArgument
editEvent	eventId : \mathbb{N} eventDetails : \mathbb{N}	None	InvalidEvent IllegalArgument
deleteEvent	eventId : \mathbb{N}	None	InvalidEvent
getAllEvents	None	eventIds: $\text{set}(\mathbb{N})$	None
getEventDetails	eventId : \mathbb{N}	eventData : EventData	InvalidEvent

11.4 Semantics

11.4.1 State Variables

events : $\text{map}(\mathbb{N}, \text{EventData})$: Mapping of all event IDs to their details

11.4.2 Environment Variables

currentTime : DateTime : Current date and time

11.4.3 Assumptions

The calculated current date and time is within 5 seconds of the actual date and time

11.4.4 Access Routine Semantics

createEvent(eventDetails : EventData):
Creates a new event.

- transition: Inserts an event into events.

- output: ID of the created event
- exception: None

`editEvent(eventId : string, eventDetails : EventData):`

Edits an existing event.

- transition: Removes the event details in `events` with the new details for the event ID
- output: None
- exception: `InvalidEvent` if event does not exist

`deleteEvent(eventId : string):`

Deletes/cancels an event.

- transition: Removes the event from `events`
- output: None
- exception: `InvalidEvent` if event does not exist

`getAllEvents():`

Retrieves all events.

- transition: None
- output: A copy of all keys in `events`
- exception: None

`getEventDetails(eventId : string):`

Retrieves the details of an event.

- transition: None
- output: The event details for the given event ID in `events`
- exception: `InvalidEvent` if event does not exist

11.4.5 Local Functions

None

12 MIS of M7: Event Notification Module

12.1 Module

Contains functionality for notifying users abouts upcoming events.

12.2 Uses

None

12.3 Syntax

12.3.1 Exported Constants

None

12.3.2 Exported Access Programs

Name	In	Out	Exceptions
sendNotification	userIds : list(N) message : string	None	InvalidUser
scheduleNotification	userIds : list(N) message : string datetime: DateTime	None	InvalidEvent

12.4 Semantics

12.4.1 State Variables

None

12.4.2 Environment Variables

None

12.4.3 Assumptions

None

12.4.4 Access Routine Semantics

`sendNotification(userIds : list(N), message : string,
datetime: DateTime):`

Sends a notification to the list of users specified.

- transition: None

- output: None
- exception: None

`scheduleNotification(userIds : list(N), message : string,
datetime : DateTime):`

Schedules a notification to send to the list of users specified.

- transition: None
- output: None
- exception: None

12.4.5 Local Functions

`checkScheduleNotifications():`

Periodically checks and sends out scheduled notifications at their deadline.

- transition: None
- output: None
- exception: None

13 MIS of M8: Registration Module

13.1 Module

Contains functionality for registering users for events.

13.2 Uses

- Event Management Module (M7)

13.3 Syntax

13.3.1 Exported Constants

13.3.2 Exported Access Programs

Name	In	Out	Exceptions
registerUser	eventId : \mathbb{N} userId : \mathbb{N}	confirmation : string	InvalidUser InvalidEvent
delistUser	eventId : \mathbb{N} userId : \mathbb{N}	removed : bool	InvalidUser InvalidEvent
getRegistrationCode	confirmation : string	code : QRCode	InvalidConfirmation
getRegistrationCode	userId : \mathbb{N} eventId : \mathbb{N}	code : QRCode	InvalidUser InvalidEvent InvalidRegistration
getConfirmationInfo	confirmation : string	userId : \mathbb{N} eventId : \mathbb{N}	InvalidConfirmation

13.4 Semantics

13.4.1 State Variables

- `eventAttendees` : `map(eventId : \mathbb{N} , users : set(\mathbb{N}))`: A set of users who have registered for each event.
- `confirmations` : `map(confirmation : string, registration : tuple(userId : \mathbb{N} , eventId : \mathbb{N}))`: A mapping of all confirmation strings into (userId, eventId) tuples.

13.4.2 Environment Variables

None.

13.4.3 Assumptions

There is no payment handling done by this module. Any events requiring payments will have that processed separately before a user can register.

13.4.4 Access Routine Semantics

`registerUser(eventId, userId):`

- transition: Update the `eventAttendees` sets with the new registered user. Update the `confirmations` with the generated confirmation code.
- output: Provide the generated registration code.
- exception: Returns `InvalidUser` if the given `userId` does not exist; returns `InvalidEvent` if the given `eventId` does not exist.

`delistUser(eventId, userId):`

- transition: Update the `eventAttendees` sets with removal of the specified user. Update the `confirmations` with the removed confirmation code.
- output: Boolean confirming that there was a change in the `eventAttendees` after the user was removed from the registration of the specified event. If the user was not registered to begin with, there is no harm to the system, but `false` is returned.
- exception: Returns `InvalidUser` if the given `userId` does not exist; returns `InvalidEvent` if the given `eventId` does not exist.

`getRegistrationCode(confirmation) (1):`

- transition: None.
- output: A generated `QRCode` based on the given confirmation code.
- exception: Returns `InvalidConformation` if a non-existent confirmation is provided.

`getRegistrationCode(userId, eventId) (2):`

- exception: Returns `InvalidUser` if the given `userId` does not exist; returns `InvalidEvent` if the given `eventId` does not exist; returns `InvalidRegistration` if the given user did not register for the event.

`getConfirmationInfo(confirmation):`

- transition: None.
- output: A `(userId, eventId)` tuple to specify a registration instance.
- exception: Returns `InvalidConformation` if a non-existent confirmation is provided.

13.4.5 Local Functions

Internal functions may handle confirmation string and QR Code generation. The only specification is that the same confirmation string is generated for a given (`userId`, `eventId`) tuple, and the same QR Code is generated for a single registration instance (i.e. from a given confirmation string).

14 MIS of M9: Attendance Tracking Module

14.1 Module

Contains functionality for tracking live event attendance.

14.2 Uses

- Event Management Module (M7)
- Registration Module (M8)

14.3 Syntax

14.3.1 Exported Constants

14.3.2 Exported Access Programs

Name	In	Out	Exceptions
markAttendance	code : QRCode	confirm : bool	InvalidQRCode
markAttendance	eventId : \mathbb{N}	confirm : bool	InvalidUser
getAttendance	userId : \mathbb{N} eventId : \mathbb{N}	attendance : set(\mathbb{N})	InvalidEvent InvalidEvent

14.4 Semantics

14.4.1 State Variables

- attendance : map(eventId : \mathbb{N} , users : set(\mathbb{N})): A set of users who have attended each event.

14.4.2 Environment Variables

None.

14.4.3 Assumptions

Attendance only counts the first time a user enters the event. During the event, once a user is registered, physical admins can monitor re-entry of attendees.

14.4.4 Access Routine Semantics

getRegistrationCode(code) (1):

- transition: Update the attendance set for the event with the attending user if the user can attend the event.

- output: Boolean confirming the user has been tracked if they are allowed to attend the event.
- exception: Returns `InvalidQRCode` if the QR Code provided does not work, potentially implying the user cannot register the even.

`getRegistrationCode(userId, eventId)` (2):

- exception: Returns `InvalidUser` if the given `userId` does not exist; returns `InvalidEvent` if the given `eventId` does not exist.

14.4.5 Local Functions

Internal functions may handle validating QR codes for a given event registration. There must be a way for the module to derive the corresponding registration information from the code.

15 MIS of M10: Report Generation Module

15.1 Module

Contains functionality for generating data visualizations and exporting data to specified formats.

15.2 Uses

- Main System Module (M1)
- Form Submission Module (M5)

15.3 Syntax

15.3.1 Exported Constants

- **Graphs** : `set(GraphType)`: The set of all valid graphs which can be rendered.
- **Formats** : `set(FileType)`: The set of all valid file formats which can be generated.

15.3.2 Exported Access Programs

Name	In	Out	Exceptions
plotData	data : <code>list(\mathbb{R})</code>	plot : <code>Graph</code>	InvalidData
	graph : <code>GraphType</code>		InvalidGraphType
exportData	data : <code>list(\mathbb{R})</code>	file : <code>File</code>	IncompatibleData
	format : <code>FileType</code>		InvalidData InvalidFileType

15.4 Semantics

15.4.1 State Variables

None.

15.4.2 Environment Variables

None.

15.4.3 Assumptions

When \mathbb{R} is specified for data input, it means that the data can be mapped in one way or another onto \mathbb{R} .

15.4.4 Access Routine Semantics

`plotData(data, graph):`

- transition: None.
- output: Plot of the data in the specified graph type.
- exception: Returns `InvalidData` if the data is corrupt; returns `InvalidGraphType` if the given `GraphType` does not exist; returns `IncompatibleData` if the given data cannot be represented with the given graph type.

`exportData(data, format):`

- transition: None.
- output: File of the data in the specified file format.
- exception: Returns `InvalidData` if the data is corrupt; returns `InvalidFileType` if the given `FileType` does not exist.

15.4.5 Local Functions

None.

16 MIS of M11: Analytics Module

16.1 Module

Contains functionality for computing summary statistics and trends for events, registrations, attendance, and surveys.

16.2 Uses

Database Access Module (M12)

Registration Module (M8)

Attendance Tracking Module (M9)

Form Submission Module (M5)

16.3 Syntax

16.3.1 Exported Constants

None

16.3.2 Exported Access Programs

Name	In	Out	Exceptions
getEventStats	eventId : \mathbb{N}	stats : EventStats	EventNotFound
getSurveyStats	surveyId : \mathbb{N}	summary : SurveySummary	SurveyNotFound
getRegistrationTrends	eventId : \mathbb{N}	trend : list(RegistrationPoint)	EventNotFound

16.4 Semantics

16.4.1 State Variables

None

16.4.2 Environment Variables

None

16.4.3 Assumptions

- The Database Access Module (M11) correctly stores registrations, attendance records, and survey responses.
- The given `eventId` and `surveyId` refer to events and surveys that were, if they exist, created by other modules.

16.4.4 Access Routine Semantics

`getEventStats(eventId : N):`

- transition: None (read-only). Queries the database for all registrations and attendance records associated with `eventId` and computes totals such as number of registrations, check-ins, and attendance rate.
- output: `stats` containing the computed summary values.
- exception:
 - `EventNotFound` if `eventId` does not correspond to any event.

`getSurveyStats(surveyId : N):`

- transition: None (read-only). Queries survey responses associated with `surveyId` and aggregates them per question (for example, counts per option for multiple-choice questions).
- output: `summary` containing aggregated statistics for each question.
- exception:
 - `SurveyNotFound` if `surveyId` does not correspond to any survey.

`getRegistrationTrends(eventId : N):`

- transition: None (read-only). Retrieves timestamps of registrations for `eventId` and computes cumulative registration counts over time.
- output: `trend` as a list of `RegistrationPoint` records, each containing a timestamp and cumulative registration count.
- exception:
 - `EventNotFound` if `eventId` does not correspond to any event.

16.4.5 Local Functions

None

17 MIS of M12: Database Access Module

17.1 Module

Provides a generic interface for reading from and writing to the application's PostgreSQL database. Responsible for connection management, transactions, and basic CRUD operations used by higher-level modules (e.g., event management, registration, analytics).

17.2 Uses

None

17.3 Syntax

17.3.1 Exported Constants

None

17.3.2 Exported Access Programs

Name	In	Out	Exceptions
fetchRow	table : string, id : \mathbb{N}	row : Record	RecordNotFound, DatabaseError
fetchRows	table : string, filter : FilterExpr	rows : list(Record)	DatabaseError
insertRow	table : string, data : Record	id : \mathbb{N}	DatabaseError
updateRow	table : string, id : \mathbb{N} , data : Record	-	RecordNotFound, DatabaseError
deleteRow	table : string, id : \mathbb{N}	-	RecordNotFound, DatabaseError

17.4 Semantics

17.4.1 State Variables

- connectionPool : ConnectionPool
Pool of reusable connections to the PostgreSQL database.
- activeTx : set(TransactionId)
Set of identifiers for currently active transactions.

17.4.2 Environment Variables

- `dbServer` : `PostgreSQLInstance`
Running PostgreSQL database server hosting the application schema.

17.4.3 Assumptions

- The database schema has been created and migrated before any access program is invoked.
- `connectionPool` is initialized during system startup.
- `Record` and `FilterExpr` are abstract data structures whose concrete representation is handled by the ORM / query layer.

17.4.4 Access Routine Semantics

`fetchRow(table : string, id : N):`

- `transition`: `None`.
- `output`: Returns the row in `table` whose primary key equals `id`.
- `exception`:
 - `RecordNotFound` if no matching row exists.
 - `DatabaseError` if a low-level database error occurs.

`fetchRows(table : string, filter : FilterExpr):`

- `transition`: `None`.
- `output`: Returns all rows in `table` that satisfy `filter`.
- `exception`: `DatabaseError` if a low-level database error occurs.

`insertRow(table : string, data : Record):`

- `transition`: Inserts a new row into `table` populated with the fields in `data`.
- `output`: Returns the primary key `id` assigned to the new row.
- `exception`: `DatabaseError` if the insert fails (e.g., constraint violation, connectivity issues).

`updateRow(table : string, id : N, data : Record):`

- `transition`: Updates the existing row in `table` with primary key `id` using the fields in `data`.

- output: None.
- exception:
 - RecordNotFound if no matching row exists.
 - DatabaseError if the update fails.

deleteRow(table : string, id : N):

- transition: Removes the row in `table` whose primary key equals `id`.
- output: None.
- exception:
 - RecordNotFound if no matching row exists.
 - DatabaseError if the delete fails.

17.4.5 Local Functions

- acquireConnection() : Connection
Obtains a connection from `connectionPool`, opening a new one if required.
- releaseConnection(c : Connection)
Returns `c` to `connectionPool` or closes it on error.
- mapRowToRecord(raw : Row) : Record
Maps a raw database row to the abstract `Record` structure.

18 MIS of M13: Audit Module

18.1 Module

Contains functionality for recording administrative and sensitive system actions in an append-only audit log for traceability and accountability.

18.2 Uses

Database Access Module (M12)

18.3 Syntax

18.3.1 Exported Constants

None

18.3.2 Exported Access Programs

Name	In	Out	Exceptions
recordEvent	entry : AuditEntry	-	DatabaseError
getAuditLog	filter : AuditFilter	entries : list(AuditEntry)	DatabaseError

18.4 Semantics

18.4.1 State Variables

- auditLog : set(AuditEntry)
Abstract representation of all recorded audit entries.

18.4.2 Environment Variables

None

18.4.3 Assumptions

- Audit entries produced by other modules accurately describe the action taken.
- The underlying database schema includes an audit log table.

18.4.4 Access Routine Semantics

`recordEvent(entry : AuditEntry):`

- `transition`: Adds `entry` to `auditLog` and persists it through the Database Access Module.
- `output`: None
- `exception`:
 - `DatabaseError` if the entry could not be written.

`getAuditLog(filter : AuditFilter):`

- `transition`: None (read-only)
- `output`: Returns all `AuditEntry` values matching the given filter, such as by user, action type, or date range.
- `exception`:
 - `DatabaseError` if retrieval fails.

18.4.5 Local Functions

None

19 Appendix

[Extra information if required —SS]

Appendix — Reflection

The information in this section will be used to evaluate the team members on the graduate attribute of Problem Analysis and Design.

The purpose of reflection questions is to give you a chance to assess your own learning and that of your group as a whole, and to find ways to improve in the future. Reflection is an important part of the learning process. Reflection is also an essential component of a successful software development process.

Reflections are most interesting and useful when they're honest, even if the stories they tell are imperfect. You will be marked based on your depth of thought and analysis, and not based on the content of the reflections themselves. Thus, for full marks we encourage you to answer openly and honestly and to avoid simply writing "what you think the evaluator wants to hear."

Please answer the following questions. Some questions can be answered on the team level, but where appropriate, each team member should write their own response:

Group Reflection

1. Which of your design decisions stemmed from speaking to your client(s) or a proxy (e.g. your peers, stakeholders, potential users)? For those that were not, why, and where did they come from? Some of our design decision in relation to the separation of the modules into the event related modules and form related modules was decided through consultation with our clients. This was an important distinction for us to make because there were some design solutions where we could have had these components together. We found through discussion that separating these two functions into separate module (or group of modules) would probably be the best for future maintainability, testing these modules and actually implementing them. We also had discussions relating to the report generation and data analytics module. We found that separating these modules would be good for expandability in the future if we wanted to perform further analysis or in a different form.

Our other design sources primarily came from our past experiences working with these types of web applications and how we wanted to develop it to make it a seamless development experience. For instance, creating a separate data access layer module was decision we made since some team members learned from past projects that it would be redundant to try and access the database directly from the other modules and a unified interface would be better. For some other decisions we decided to look into best practices when designing web applications to ensure that our structure and implementation was good.

2. While creating the design doc, what parts of your other documents (e.g. requirements, hazard analysis, etc), if any, needed to be changed, and why? We found that in general

that our other documents didn't really need to be modified when creating this documentation. This was because we had to essentially utilize the requirements to inform our design decisions and the separation of modules to implement our requirements. This meant that we built off our design from these documents so we didn't feel had any changes that needed to be made currently for the past documents in relation to our design.

3. What are the limitations of your solution? Put another way, given unlimited resources, what could you do to make the project better? (LO_ProbSolutions)
4. Give a brief overview of other design solutions you considered. What are the benefits and tradeoffs of those other designs compared with the chosen design? From all the potential options, why did you select the documented design? (LO_Explores)

Virochaan Ravichandran Gowri Reflection

1. What went well while writing this deliverable?

Overall we had a good understanding of what we wanted to do when designing and creating our platform. We had a general idea of what the structure of the system was going to be and we also knew what kind of modules that we wanted to actually deliver. We had some more discussions to finetune our modules to ensure that they weren't too large or encompassing too much functionality but since we had a good understanding of it in the first place it was quite easy for us to develop a effective architecture. We also managed to have a good timeline as we had a plan for what we wanted develop and in what order already in place and we discussed before hand what sections each person would try and do.

2. What pain points did you experience during this deliverable, and how did you resolve them?

The main painpoint was understanding the different terms in the MIS and how to properly fill them for each module. We had the added difficulty of having multiple UI related components so it added an added difficulty to properly ensure we completed the sections. We had a small challenge in the Module Guide in ensuring that the structure and hierarchy of the modules made sense. This was because we had the possibility of cyclic dependencies so we resolved this by decomposing some of the modules further.