

Memory-Based One-Class Collaborative Filtering

Weike Pan


College of Computer Science and Software Engineering
Shenzhen University

Outline

- 1 Introduction
- 2 Similarity Measurement
- 3 Neighborhood Selection
- 4 Prediction Rule
- 5 Experiments
- 6 Conclusion
- 7 References

Recommendation with Implicit Feedback

- We may represent users' implicit feedback in a **matrix** form:

?	1	?	?	?	?
?	?	1	1	1	?
?					1
?					1
?	1	?	1	?	1
1	?	?	1	?	?

- If we can **estimate the missing values** (denoted as “?”) in the matrix or **rank the items directly**, we can make recommendations for each user.

Notations

Table: Some notations.

n	user number
m	item number
$u \in \{1, 2, \dots, n\}$	user ID
$i, j \in \{1, 2, \dots, m\}$	item ID
\hat{r}_{ui}	predicted rating of user u on item i
\mathcal{I}	the whole item set
\mathcal{U}	the whole user set
\mathcal{I}_u	a set of items preferred by user u
\mathcal{U}_k	a set of users that prefers item k
\mathcal{U}_j	a set of users that prefers item j
\mathcal{N}_j	a set of top- K nearest neighbors of item j
\mathcal{N}_u	a set of top- K nearest neighbors of user u

Jaccard Index

- The similarity between item k and item j is as follows,

$$s_{kj} = \frac{|\mathcal{U}_k \cap \mathcal{U}_j|}{|\mathcal{U}_k \cup \mathcal{U}_j|} \quad (1)$$

- The default value is $s_{kj} = 0$

Cosine Similarity

- The similarity between item k and item j is as follows,

$$s_{kj} = \frac{|\mathcal{U}_k \cap \mathcal{U}_j|}{\sqrt{|\mathcal{U}_k|} \sqrt{|\mathcal{U}_j|}} \quad (2)$$

- The default value is $s_{kj} = 0$

Cosine Similarity - Penalty on Popular Item

- The similarity between item k and item j is as follows,

$$s_{kj} = \frac{|\mathcal{U}_k \cap \mathcal{U}_j|}{|\mathcal{U}_k|^\alpha |\mathcal{U}_j|^{1-\alpha}} \quad (3)$$

where $0.5 \leq \alpha \leq 1$.

- Notes

- When $\alpha = 0.5$, it reduces to the **cosine similarity**
- A large value of α (i.e., $\alpha > 0.5$) will **give a penalty on a popular item k**
- When $\alpha = 1$, it reduces to the **confidence in association rule mining** (will be discussed soon)

Cosine Similarity - Inverse User Frequency

- The similarity between item k and item j is as follows [Breese et al., 1998],

$$s_{kj} = \frac{\sum_{w \in \mathcal{U}_k \cap \mathcal{U}_j} \frac{1}{\log(1 + |\mathcal{I}_w|)}}{\sqrt{|\mathcal{U}_k|} \sqrt{|\mathcal{U}_j|}} \quad (4)$$

- Notes
 - It is a well-known trick in information retrieval

Confidence in Association Rule Mining

- The confidence (or **probability**) that a user who preferred item k will prefer item j is as follows [Kim and Kim, 2003],

$$s_{kj} = \frac{|\mathcal{U}_k \cap \mathcal{U}_j|}{|\mathcal{U}_k|} \quad (5)$$

- Notes

- Association rule mining can be considered as a special case of item-based OCCF
- The support is defined as $s_{kj} = \frac{|\mathcal{U}_k \cap \mathcal{U}_j|}{|\mathcal{U}|}$

Normalization

- Once we have obtained the similarity matrix $[s_{kj}]_{m \times m}$, $k, j = 1, \dots, m$, we can normalize the similarity as follows [Karypis, 2001],

$$\bar{s}_{kj} = \frac{s_{kj}}{\max_{j', j' \neq k} s_{kj'}} \quad (6)$$

- Notes

- It is **NOT** a global normalization, i.e., $\frac{s_{kj}}{\max_{k', j'} s_{k'j'}}$
- It makes the similarity “between item k and item j ” and the similarity “between item k' and item j' ” **more comparable**

Neighborhood Selection

- Select the top- K most nearest items of item j w.r.t. the similarity measurement, e.g., \mathcal{N}_j .

Item-Based OCCF

- The prediction rule is as follows,

$$\hat{r}_{uj} = \sum_{k \in \mathcal{I}_u \cap \mathcal{N}_j} s_{kj} \quad (7)$$

where s_{kj} is the similarity (or confidence in association rule mining) between item k and item j .

- Note that we may have $|\mathcal{I}_u \cap \mathcal{N}_j| < K$, but that is usually acceptable for OCCF

User-Based OCCF

- The prediction rule is as follows,

$$\hat{r}_{uj} = \sum_{w \in \mathcal{U}_j \cap \mathcal{N}_u} s_{wu} \quad (8)$$

where s_{wu} is the similarity (or confidence in association rule mining) between user w and user u .

- Note that we may have $|\mathcal{U}_j \cap \mathcal{N}_u| < K$, but that is usually acceptable for OCCF

Data Set

- We use the files `u1.base` and `u1.test` of MovieLens100K¹ as our training data and test data, respectively.
- user number: $n = 943$; item number: $m = 1682$.
- `u1.base` (training data): 80000 rating records, and the density (or sparsity) is $80000/943/1682 = 5.04\%$.
- `u1.test` (test data): 20000 rating records.
- **Pre-processing (for simulation)**: we only keep the (user, item) pairs with ratings 4 or 5 in `u1.base` and `u1.test` as preferred (user, item) pairs, and remove all other records. Finally, we obtain **`u1.base.OCCF`** and **`u1.test.OCCF`**.

¹<http://grouplens.org/datasets/>

Implementation Details

- How to store the implicit feedback if we use item-based method?
 - For similarity measurement s_{kj} : $\mathcal{U}_k, \mathcal{U}_j$
 - In prediction rule \hat{r}_{uj} : $\mathcal{I}_u, \mathcal{N}_j$
- How to store the implicit feedback if we use user-based method?
 - For similarity measurement s_{wu} : $\mathcal{I}_w, \mathcal{I}_u$
 - In prediction rule \hat{r}_{uj} : $\mathcal{U}_j, \mathcal{N}_u$

Evaluation Metrics

- *Pre@5*: The precision of user u is defined as,

$$Pre_u@k = \frac{1}{k} \sum_{\ell=1}^k \delta(i(\ell) \in \mathcal{I}_u^{te}),$$

where $\delta(x) = 1$ if x is true and $\delta(x) = 0$ otherwise. Then, we have $Pre@k = \sum_{u \in \mathcal{U}^{te}} Pre_u@k / |\mathcal{U}^{te}|$.

- *Rec@5*: The recall of user u is defined as,

$$Rec_u@k = \frac{1}{|\mathcal{I}_u^{te}|} \sum_{\ell=1}^k \delta(i(\ell) \in \mathcal{I}_u^{te}),$$

which means how many preferred items are recommended in the top- k list. Then, we have $Rec@k = \sum_{u \in \mathcal{U}^{te}} Rec_u@k / |\mathcal{U}^{te}|$.

Results

Table: Prediction performance of PopRank and memory-based OCCF (Jaccard Index, $K = 50$) on MovieLens100K (u1.base.OCCF, u1.test.OCCF).

	PopRank	Item-based	User-based	Hybrid
<i>Pre@5</i>	0.2338	0.3632	0.3768	0.3978
<i>Rec@5</i>	0.0571	0.1102	0.1207	0.1314

Observation: the hybrid method performs best, which is expected.

Conclusion

Three major components

- Similarity measurement and related techniques
- Neighborhood selection
- Prediction rule

Homework

- Reading: chapter 2 of the Chinese reference book by Liang Xiang (i.e., *Action in Recommender Systems*).
- More references:
 - user-based + item-based: [Wang et al., 2006], [Symeonidis et al., 2008]
 - item-based: [Deshpande and Karypis, 2004]
 - user-based: [Sarwar et al., 2000]
 - recent papers: [Sigurbjörnsson and van Zwol, 2008], [Aiolli, 2013]



Aioli, F. (2013).

Efficient top-n recommendation for very large scale binary rated datasets.

In *Proceedings of the 7th ACM Conference on Recommender Systems, RecSys '13*, pages 273–280, New York, NY, USA. ACM.



Breese, J. S., Heckerman, D., and Kadie, C. (1998).

Empirical analysis of predictive algorithms for collaborative filtering.

In *Proceedings of the Fourteenth Conference on Uncertainty in Artificial Intelligence, UAI'98*, pages 43–52, San Francisco, CA, USA. Morgan Kaufmann Publishers Inc.



Deshpande, M. and Karypis, G. (2004).

Item-based top-n recommendation algorithms.

ACM Trans. Inf. Syst., 22(1):143–177.



Karypis, G. (2001).

Evaluation of item-based top-n recommendation algorithms.

In *Proceedings of the Tenth International Conference on Information and Knowledge Management, CIKM '01*, pages 247–254, New York, NY, USA. ACM.



Kim, C. and Kim, J. (2003).

A recommendation algorithm using multi-level association rules.

In *Proceedings of the 2003 IEEE/WIC International Conference on Web Intelligence, WI '03*, pages 524–, Washington, DC, USA. IEEE Computer Society.



Sarwar, B., Karypis, G., Konstan, J., and Riedl, J. (2000).

Analysis of recommendation algorithms for e-commerce.

In *Proceedings of the 2Nd ACM Conference on Electronic Commerce, EC '00*, pages 158–167, New York, NY, USA. ACM.



Sigurbjörnsson, B. and van Zwol, R. (2008).

Flickr tag recommendation based on collective knowledge.

In *Proceedings of the 17th International Conference on World Wide Web, WWW '08*, pages 327–336, New York, NY, USA. ACM.



Symeonidis, P., Nanopoulos, A., Papadopoulos, A. N., and Manolopoulos, Y. (2008).

Nearest-biclusters collaborative filtering based on constant and coherent values.

Inf. Retr., 11(1):51–75.



Wang, J., de Vries, A. P., and Reinders, M. J. T. (2006).

Unifying user-based and item-based collaborative filtering approaches by similarity fusion.

In *Proceedings of the 29th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR '06, pages 501–508, New York, NY, USA. ACM.