

Virto Industrial Supply

Safety Data Sheet

VIS Multi-Purpose Industrial Lubricant, ISO VG 46

Issued: 1 January 2026 Revision 4 Supersedes: revision 3

Prepared in accordance with the OSHA Hazard Communication Standard, 29 CFR 1910.1200, and the UN Globally Harmonised System (GHS), revision 9.

This safety data sheet covers the industrial lubricant range supplied in 1 L, 5 L, 20 L and 205 L containers.

1. Identification

Product name: VIS Multi-Purpose Industrial Lubricant, ISO VG 46.

Recommended use: general machine lubrication, bearings, chain drives.

Supplier: Virto Industrial Supply, 400 Industrial Parkway, Memphis TN 38118.

Emergency telephone: +1 901 555 0199 (24 hour).

2. Hazard identification

GHS classification: not classified as hazardous under GHS criteria.

Precautionary statements: P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves. P501 Dispose of contents in accordance with local regulation.

3. Composition / information on ingredients

Severely hydrotreated base oil (CAS 64742-54-7): 85 - 95%.

Zinc dialkyldithiophosphate (CAS 68649-42-3): 1 - 3%.

Performance additives: balance.

4. First-aid measures

Eye contact: flush with water for 15 minutes. Seek medical advice if irritation persists.

Skin contact: wash with soap and water. Remove contaminated clothing.

Ingestion: do not induce vomiting. Seek immediate medical attention.

5. Fire-fighting measures

Suitable extinguishing media: foam, dry chemical, carbon dioxide.

Unsuitable media: direct water jet. Flash point: 232 °C (COC).

6. Accidental release measures

Contain the spill. Absorb with inert material. Prevent entry to drains and watercourses.

7. Handling and storage

Store between 5 °C and 40 °C in a well-ventilated area away from oxidising agents.

Keep containers closed when not in use. Shelf life 60 months from date of manufacture.

8. Exposure controls / personal protection

Oil mist, mineral: TWA 5 mg/m³ (ACGIH).

Wear nitrile gloves and safety glasses. Use local exhaust ventilation where mist may form.

9. Physical and chemical properties

Appearance: clear amber liquid. Odour: characteristic mild.

Density at 15 °C: 0.872 g/cm³. Kinematic viscosity at 40 °C: 46 mm²/s. Pour point: -27 °C.

10. Stability and reactivity

Stable under normal conditions of storage and use.

Incompatible materials: strong oxidising agents. Hazardous decomposition products: none in normal use.

11. Toxicological information

Acute oral LD50 (rat): > 5000 mg/kg. Acute dermal LD50 (rabbit): > 2000 mg/kg.

Skin irritation: prolonged or repeated contact may cause defatting and dermatitis.

12. Ecological information

Not readily biodegradable. Do not allow to enter drains, soil or watercourses.

13. Disposal considerations

Dispose of used product through a licensed waste oil contractor in accordance with local regulation.

14. Transport information

Not classified as dangerous for transport under DOT, IMDG or IATA.

15. Regulatory information

All components are listed on the TSCA inventory. SARA 313: no listed components above threshold.

16. Other information

Revision 4 updates sections 8 and 11 following the 2025 exposure review.

This data sheet is provided without warranty as to its completeness or accuracy.

Appendix — exposure and handling notes

Continuation sheet. Workplace exposure assessments, glove breakthrough data and disposal contacts for each supplying region are tabulated on this and the following pages. The controlled master copy is held by the HSE manager at the Memphis distribution centre.

Appendix — exposure and handling notes

Continuation sheet. Workplace exposure assessments, glove breakthrough data and disposal contacts for each supplying region are tabulated on this and the following pages. The controlled master copy is held by the HSE manager at the Memphis distribution centre.

Appendix — exposure and handling notes

Continuation sheet. Workplace exposure assessments, glove breakthrough data and disposal contacts for each supplying region are tabulated on this and the following pages. The controlled master copy is held by the HSE manager at the Memphis distribution centre.

Appendix — exposure and handling notes

Continuation sheet. Workplace exposure assessments, glove breakthrough data and disposal contacts for each supplying region are tabulated on this and the following pages. The controlled master copy is held by the HSE manager at the Memphis distribution centre.

Appendix — exposure and handling notes

Continuation sheet. Workplace exposure assessments, glove breakthrough data and disposal contacts for each supplying region are tabulated on this and the following pages. The controlled master copy is held by the HSE manager at the Memphis distribution centre.