

Haskell and Scala

comparison

Adam Szlachta

March 20, 2013

ver. 1.0
adam.szlachta@gmail.com

Introduction

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- Haskell and Scala introduction
- History
- Functional programming essence
- Syntax and features comparison
- Scala libraries influenced by Haskell
- Summary

Features incorporated in Scala

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary


Laziness

Algebraic data
types


Classes

Monadic features

Summary



Languages which influenced Scala



Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Haskell logo and name

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary



From Wikipedia

Lambda calculus (also written as λ -calculus or called “the lambda calculus”) is a formal system in mathematical logic and computer science for expressing computation by way of variable binding and substitution.

From Wikipedia

Haskell Brooks Curry (1900-1982) was an American mathematician and logician. Curry is best known for his work in combinatory logic.



Haskell logo and name

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary



From Wikipedia

Lambda calculus (also written as λ -calculus or called “the lambda calculus”) is a formal system in mathematical logic and computer science for expressing computation by way of variable binding and substitution.

From Wikipedia

Haskell Brooks Curry (1900-1982) was an American mathematician and logician. Curry is best known for his work in combinatory logic.



Functional programming languages history

Haskell and Scala

Adam Szlachta

Introduction

History

Functional programming

Basic syntax comparison

Functions

Syntax summary


Laziness

Algebraic data types

Classes

Monadic features

Summary



Functional programming

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- **avoiding side effects**
- avoiding state (mutable data)
- referential transparency and lazy evaluation
- first-class functions
- based on theories
 - λ -calculus (α -conversion, β -reduction, η -conversion)
 - category theory

Functional programming

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- avoiding side effects
- avoiding state (mutable data)
- referential transparency and lazy evaluation
- first-class functions
- based on theories
 - λ -calculus (α -conversion, β -reduction, η -conversion)
 - category theory

Functional programming

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- avoiding side effects
- avoiding state (mutable data)
- referential transparency and lazy evaluation
- first-class functions
- based on theories
 - λ -calculus (α -conversion, β -reduction, η -conversion)
 - category theory

Functional programming

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- avoiding side effects
- avoiding state (mutable data)
- referential transparency and lazy evaluation
- first-class functions
- based on theories
 - λ -calculus (α -conversion, β -reduction, η -conversion)
 - category theory

Functional programming

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- avoiding side effects
- avoiding state (mutable data)
- referential transparency and lazy evaluation
- first-class functions
- based on theories
 - λ -calculus (α -conversion, β -reduction, η -conversion)
 - category theory

Functional programming

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- avoiding side effects
- avoiding state (mutable data)
- referential transparency and lazy evaluation
- first-class functions
- based on theories
 - λ -calculus (α -conversion, β -reduction, η -conversion)
 - category theory

Functional programming

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- avoiding side effects
- avoiding state (mutable data)
- referential transparency and lazy evaluation
- first-class functions
- based on theories
 - λ -calculus (α -conversion, β -reduction, η -conversion)
 - category theory

Hello, World!

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
module Main where

main :: IO ()
main = putStrLn "Hello, World!"
```

```
object HelloWorld {
  def main(args: Array[String]) {
    println("Hello, World!")
  }
}
```

Haskell

Scala

Hello, World!

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
module Main where

main :: IO ()
main = putStrLn "Hello, World!"
```

```
object HelloWorld {
  def main(args: Array[String]) {
    println("Hello, World!")
  }
}
```

Haskell

Scala

Who is this?

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary



Referential transparency

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

The Polish Parliament meets in **the capital of Poland**.

The Polish Parliament meets in **Warsaw**.

Warsaw has been **the capital of Poland** since 1815.

Referential transparency

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

The Polish Parliament meets in **the capital of Poland**.

The Polish Parliament meets in **Warsaw**.

Warsaw has been **the capital of Poland** since 1815.

Referential transparency

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

The Polish Parliament meets in **the capital of Poland**.

The Polish Parliament meets in **Warsaw**.

Warsaw has been **the capital of Poland** since 1815.

Referential transparency

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

From Wikipedia

Referential transparency is a property whereby an expression can be replaced by its value without affecting the program.

Example:

```
text = reverse "redrum"
```

can be replaced with:

```
text = "murder"
```

Referential transparency

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

From Wikipedia

Referential transparency is a property whereby an expression can be replaced by its value without affecting the program.

Example:

```
text = reverse "redrum"
```

can be replaced with:

```
text = "murder"
```

Referential transparency

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

From Wikipedia

Referential transparency is a property whereby an expression can be replaced by its value without affecting the program.

Example:

```
text = reverse "redrum"
```

can be replaced with:

```
text = "murder"
```

Who is this?

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary



Heron's formula

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness


Algebraic data
types

Classes

Monadic features

Summary

$$T = \sqrt{s(s-a)(s-b)(s-c)}, \text{ where } s = \frac{a+b+c}{2}$$



Function definition

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
triangleArea :: Double -> Double -> Double -> Double
triangleArea a b c =
    let s = (a + b + c) / 2 in
    sqrt (s * (s - a) * (s - b) * (s - c))
```

Haskell

```
def triangleArea(a: Double, b: Double, c: Double): Double = {
    val s = (a + b + c) / 2
    return Math.sqrt (s * (s - a) * (s - b) * (s - c))
}
```

Scala

Function definition

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
triangleArea :: Double -> Double -> Double -> Double
triangleArea a b c =
    let s = (a + b + c) / 2 in
    sqrt (s * (s - a) * (s - b) * (s - c))
```

Haskell

```
def triangleArea(a: Double, b: Double, c: Double): Double = {
    val s = (a + b + c) / 2
    return Math.sqrt (s * (s - a) * (s - b) * (s - c))
}
```

Scala

Function definition

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
triangleArea a b c =  
    let s = (a + b + c) / 2 in  
    sqrt (s * (s - a) * (s - b) * (s - c))
```

```
triangleArea a b c =  
    sqrt (s * (s - a) * (s - b) * (s - c))  
    where  
        s = (a + b + c) / 2
```

Haskell

Currying

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
add x y = x + y
```

```
add5 = add 5
```

```
print $ add5 10
```

Haskell

```
def add(x: Int)(y: Int) = x + y
```

```
def add5 = add(5)_
```

```
println (add5(10))
```

Scala

Map, fold and lambda expressions

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
add1 :: [Int] -> [Int]
add1 xs = map (\x -> x + 1) xs
```

```
sum :: [Int] -> Int
sum xs = foldr (\x y -> x + y) 0 xs
```

```
add1 :: [Int] -> [Int]
add1 xs = map (+ 1) xs
```

```
sum :: [Int] -> Int
sum xs = foldr (+) 0 xs
```

```
def add1(xs: List[Int]): List[Int] = xs.map(x => x + 1)
```

```
def sum(xs: List[Int]): Int = xs.foldRight(0)((x, y) => x + y)
```

```
def add1(xs: List[Int]): List[Int] = xs.map(_ + 1)
```

```
def sum(xs: List[Int]): Int = xs.foldRight(0)(_ + _)
```

Haskell

Scala

Map, fold and lambda expressions

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
add1 :: [Int] -> [Int]
add1 xs = map (\x -> x + 1) xs
```

```
sum :: [Int] -> Int
sum xs = foldr (\x y -> x + y) 0 xs
```

```
add1 :: [Int] -> [Int]
add1 xs = map (+ 1) xs
```

```
sum :: [Int] -> Int
sum xs = foldr (+) 0 xs
```

```
def add1(xs: List[Int]): List[Int] = xs.map(x => x + 1)

def sum(xs: List[Int]): Int = xs.foldRight(0)((x, y) => x + y)
```

```
def add1(xs: List[Int]): List[Int] = xs.map(_ + 1)

def sum(xs: List[Int]): Int = xs.foldRight(0)(_ + _)
```

Haskell

Scala

Map, fold and lambda expressions

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
add1 :: [Int] -> [Int]
add1 xs = map (\x -> x + 1) xs
```

```
sum :: [Int] -> Int
sum xs = foldr (\x y -> x + y) 0 xs
```

```
add1 :: [Int] -> [Int]
add1 xs = map (+ 1) xs
```

```
sum :: [Int] -> Int
sum xs = foldr (+) 0 xs
```

```
def add1(xs: List[Int]): List[Int] = xs.map(x => x + 1)

def sum(xs: List[Int]): Int = xs.foldRight(0)((x, y) => x + y)

def add1(xs: List[Int]): List[Int] = xs.map(_ + 1)

def sum(xs: List[Int]): Int = xs.foldRight(0)(_ + _)
```

Haskell

Scala

Map, fold and lambda expressions

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
add1 :: [Int] -> [Int]
add1 xs = map (\x -> x + 1) xs
```

```
sum :: [Int] -> Int
sum xs = foldr (\x y -> x + y) 0 xs
```

```
add1 :: [Int] -> [Int]
add1 xs = map (+ 1) xs
```

```
sum :: [Int] -> Int
sum xs = foldr (+) 0 xs
```

```
def add1(xs: List[Int]): List[Int] = xs.map(x => x + 1)

def sum(xs: List[Int]): Int = xs.foldRight(0)((x, y) => x + y)

def add1(xs: List[Int]): List[Int] = xs.map(_ + 1)

def sum(xs: List[Int]): Int = xs.foldRight(0)(_ + _)
```

Haskell

Scala

Point-free notation

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Standard notation:

```
double x = 2*x
```

```
sum xs = foldr (+) 0 xs
```

Point-free notation:

```
double = (2*)
```

```
sum = foldr (+) 0
```

Haskell

Point-free notation

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Standard notation:

```
double x = 2*x
```

```
sum xs = foldr (+) 0 xs
```

Point-free notation:

```
double = (2*)
```

```
sum = foldr (+) 0
```

Haskell

Syntax

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

	Haskell	Scala	Python	Java
semicolons	optional	optional	optional	obligatory
curly brackets	optional	yes***	no	yes
significant indentation	yes	no	yes	no
type inference	yes	yes	dynamic	no
functions definitions	whitespace	()*	()	()
functions call	whitespace	()**	()	()
point-free notation	yes	no	no	no

* optional for arity-0

** optional for arity-0 and arity-1

*** optional for purely functional bodies (but without val definitions)

Strict and non-strict semantics

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Meaning

Lazy evaluation means evaluating expression only when it is needed.

Meaning

Non-strictness means that the evaluation of expressions proceed from the outside (e.g. from '+' in $(a + (b * c))$). Usually identified with lazy evaluation.

Note

Useless for not purely functional computations!

Strict and non-strict semantics

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Meaning

Lazy evaluation means evaluating expression only when it is needed.

Meaning

Non-strictness means that the evaluation of expressions proceed from the outside (e.g. from '+' in $(a + (b * c))$). Usually identified with lazy evaluation.

Note

Useless for not purely functional computations!

Strict and non-strict semantics

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Meaning

Lazy evaluation means evaluating expression only when it is needed.

Meaning

Non-strictness means that the evaluation of expressions proceed from the outside (e.g. from '+' in $(a + (b * c))$). Usually identified with lazy evaluation.

Note

Useless for not purely functional computations!

Lazy values

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
lazyArgument = g (f x)
```

```
lazyArgument = g $ f x
```

```
strictArgument = g $! f x
```

Haskell

```
lazy val lazyValue = g(f(x))
```

```
val strictValue = g(f(x))
```

Scala

Lazy values

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
lazyArgument = g (f x)
```

```
lazyArgument = g $ f x
```

```
strictArgument = g $! f x
```

```
lazy val lazyValue = g(f(x))
```

```
val strictValue = g(f(x))
```

Haskell

Scala

Lazy values

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
lazyArgument = g (f x)
```

```
lazyArgument = g $ f x
```

```
strictArgument = g $! f x
```

```
lazy val lazyValue = g(f(x))
```

```
val strictValue = g(f(x))
```

Haskell

Scala

Infinite streams

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
take 10 [1..]
```

```
[1,2,3,4,5,6,7,8,9,10]
```

Haskell

```
Stream.from(1).take(10).toList
```

```
List(1, 2, 3, 4, 5, 6, 7, 8, 9, 10)
```

Scala

Algebraic data types

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types


Classes

Monadic features

Summary

From Wikipedia

Algebraic data type is a kind of composite type, i.e. a type formed by combining other types. Two common classes of algebraic type are product types, i.e. tuples and records, and sum types, also called tagged unions or variant types.



Algebraic data types

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
data Boolean = True | False
```

```
data List a = Nil | Cons a (List a)
```

```
data Tree a = Empty
            | Leaf a
            | Node (Tree a) (Tree a)
```

```
trait Boolean
case class True extends Boolean
case class False extends Boolean
```

```
trait List[A]
case class Nil[A]() extends List[A]
case class Cons[A](v: A, l: List[A]) extends List[A]
```

```
trait Tree[A]
case class Empty[A]() extends Tree[A]
case class Leaf[A](v: A) extends Tree[A]
case class Branch[A](l: Tree[A], r: Tree[A]) extends Tree[A]
```

Haskell

Scala

Algebraic data types

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
data Boolean = True | False
```

```
data List a = Nil | Cons a (List a)
```

```
data Tree a = Empty
            | Leaf a
            | Node (Tree a) (Tree a)
```

```
trait Boolean
case class True extends Boolean
case class False extends Boolean
```

```
trait List[A]
case class Nil[A]() extends List[A]
case class Cons[A](v: A, l: List[A]) extends List[A]
```

```
trait Tree[A]
case class Empty[A]() extends Tree[A]
case class Leaf[A](v: A) extends Tree[A]
case class Branch[A](l: Tree[A], r: Tree[A]) extends Tree[A]
```

Haskell

Scala

Algebraic data types

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
data Boolean = True | False
```

```
data List a = Nil | Cons a (List a)
```

```
data Tree a = Empty
            | Leaf a
            | Node (Tree a) (Tree a)
```

```
trait Boolean
case class True extends Boolean
case class False extends Boolean
```

```
trait List[A]
case class Nil[A]() extends List[A]
case class Cons[A](v: A, l: List[A]) extends List[A]
```

```
trait Tree[A]
case class Empty[A]() extends Tree[A]
case class Leaf[A](v: A) extends Tree[A]
case class Branch[A](l: Tree[A], r: Tree[A]) extends Tree[A]
```

Haskell

Scala

Algebraic data types

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
data Boolean = True | False
```

```
data List a = Nil | Cons a (List a)
```

```
data Tree a = Empty
            | Leaf a
            | Node (Tree a) (Tree a)
```

```
trait Boolean
case class True extends Boolean
case class False extends Boolean
```

```
trait List[A]
case class Nil[A]() extends List[A]
case class Cons[A](v: A, l: List[A]) extends List[A]
```

```
trait Tree[A]
case class Empty[A]() extends Tree[A]
case class Leaf[A](v: A) extends Tree[A]
case class Branch[A](l: Tree[A], r: Tree[A]) extends Tree[A]
```

Haskell

Scala

Algebraic data types

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Note

Algebraic data type can be recursive and act as unions, structs and enums.

```
data DaysOfWeek = Monday | Tuesday | Wednesday | Thursday  
                | Friday | Saturday | Sunday
```

```
data Account = Account  
  { number      :: Int  
  , firstName   :: String  
  , lastName    :: String  
  , balance     :: Float }
```

```
data Account = Account Int String String Float
```

```
data Tree = Branch { left  :: Tree  
                    , value :: Int  
                    , right :: Tree }  
          | Leaf { value :: Int }
```

```
data Tree = Branch Tree Int Tree | Leaf Int
```

Haskell

Algebraic data types

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Note

Algebraic data type can be recursive and act as unions, structs and enums.

```
data DaysOfWeek = Monday | Tuesday | Wednesday | Thursday  
                | Friday | Saturday | Sunday
```

```
data Account = Account  
  { number      :: Int  
  , firstName   :: String  
  , lastName    :: String  
  , balance     :: Float }
```

```
data Account = Account Int String String Float
```

```
data Tree = Branch { left  :: Tree  
                    , value :: Int  
                    , right :: Tree }  
          | Leaf { value :: Int }
```

```
data Tree = Branch Tree Int Tree | Leaf Int
```

Haskell

Algebraic data types

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Note

Algebraic data type can be recursive and act as unions, structs and enums.

```
data DaysOfWeek = Monday | Tuesday | Wednesday | Thursday  
                | Friday | Saturday | Sunday
```

```
data Account = Account  
  { number      :: Int  
  , firstName   :: String  
  , lastName    :: String  
  , balance     :: Float }
```

```
data Account = Account Int String String Float
```

```
data Tree = Branch { left  :: Tree  
                    , value :: Int  
                    , right :: Tree }  
          | Leaf { value :: Int }
```

```
data Tree = Branch Tree Int Tree | Leaf Int
```

Haskell

Algebraic data types

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Note

Algebraic data type can be recursive and act as unions, structs and enums.

```
data DaysOfWeek = Monday | Tuesday | Wednesday | Thursday  
                | Friday | Saturday | Sunday
```

```
data Account = Account  
  { number      :: Int  
  , firstName   :: String  
  , lastName    :: String  
  , balance     :: Float }
```

```
data Account = Account Int String String Float
```

```
data Tree = Branch { left  :: Tree  
                    , value :: Int  
                    , right :: Tree }  
          | Leaf { value :: Int }
```

```
data Tree = Branch Tree Int Tree | Leaf Int
```

Haskell

Pattern matching

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
data Tree a = Empty | Leaf a | Branch (Tree a) (Tree a)
```

```
treeToString :: Show a => Tree a -> String
treeToString t = case t of
    Empty -> "empty"
    Leaf a -> "leaf " ++ show a
    Branch l r -> "branch[" ++ treeToString l ++
                  " " ++ treeToString r ++ "]"
```

```
print $ treeToString $ Branch (Branch (Leaf 2) (Leaf 3)) (Leaf 4)
```

```
trait Tree[A]
case class Empty[A]() extends Tree[A]
case class Leaf[A](v: A) extends Tree[A]
case class Branch[A](l: Tree[A], r: Tree[A]) extends Tree[A]
```

```
def treeToString[A](t: Tree[A]): String = t match {
    case Empty() => "empty"
    case Leaf(a) => "leaf " + a
    case Branch(l, r) => "branch[" + treeToString(l) +
                        " " + treeToString(r) + "]"
}
```

```
println(treeToString(Branch(Branch(Leaf(2), Leaf(3)), Leaf(4))))
```

Haskell

Scala

Pattern matching

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
data Tree a = Empty | Leaf a | Branch (Tree a) (Tree a)
```

```
treeToString :: Show a => Tree a -> String
```

```
treeToString t = case t of
```

```
    Empty -> "empty"
```

```
    Leaf a -> "leaf " ++ show a
```

```
    Branch l r -> "branch[" ++ treeToString l ++  
                  " " ++ treeToString r ++ "]"
```

```
print $ treeToString $ Branch (Branch (Leaf 2) (Leaf 3)) (Leaf 4)
```

```
trait Tree[A]
```

```
case class Empty[A]() extends Tree[A]
```

```
case class Leaf[A](v: A) extends Tree[A]
```

```
case class Branch[A](l: Tree[A], r: Tree[A]) extends Tree[A]
```

```
def treeToString[A](t: Tree[A]): String = t match {
```

```
    case Empty() => "empty"
```

```
    case Leaf(a) => "leaf " + a
```

```
    case Branch(l, r) => "branch[" + treeToString(l) +  
                        " " + treeToString(r) + "]"
```

```
}
```

```
println(treeToString(Branch(Branch(Leaf(2), Leaf(3)), Leaf(4))))
```

Haskell

Scala

Pattern matching

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
data Tree a = Empty | Leaf a | Branch (Tree a) (Tree a)
```

```
treeToString :: Show a => Tree a -> String
```

```
treeToString t = case t of
```

```
    Empty -> "empty"
```

```
    Leaf a -> "leaf " ++ show a
```

```
    Branch l r -> "branch[" ++ treeToString l ++  
                  " " ++ treeToString r ++ "]"
```

```
print $ treeToString $ Branch (Branch (Leaf 2) (Leaf 3)) (Leaf 4)
```

```
trait Tree[A]
```

```
case class Empty[A]() extends Tree[A]
```

```
case class Leaf[A](v: A) extends Tree[A]
```

```
case class Branch[A](l: Tree[A], r: Tree[A]) extends Tree[A]
```

```
def treeToString[A](t: Tree[A]): String = t match {
```

```
    case Empty() => "empty"
```

```
    case Leaf(a) => "leaf " + a
```

```
    case Branch(l, r) => "branch[" + treeToString(l) +  
                        " " + treeToString(r) + "]"
```

```
}
```

```
println(treeToString(Branch(Branch(Leaf(2), Leaf(3)), Leaf(4))))
```

Haskell

Scala

Pattern matching

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
data Tree a = Empty | Leaf a | Branch (Tree a) (Tree a)
```

```
treeToString t = case t of
    Empty -> "empty"
    Leaf a -> "leaf " ++ show a
    Branch l r -> "branch[" ++ treeToString l ++
                  " " ++ treeToString r ++ "]"
```

```
treeToString Empty = "empty"
treeToString (Leaf a) = "leaf " ++ show a
treeToString (Branch l r) =
    "branch[" ++ treeToString l ++ " " ++ treeToString r ++ "]"
```

```
print $ treeToString $ Branch (Branch (Leaf 2) (Leaf 3)) (Leaf 4)
```

```
"branch[branch[leaf 2 leaf 3] leaf 4]"
```


Default implementations

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
class Equal a where
    (==), (/==) :: a -> a -> Bool
    x /== y = not $ x == y
```

```
trait Equal[_] {
    def ==(x: Equal[_]): Boolean
    def /==(x: Equal[_]): Boolean = !(this == x)
}
```

Haskell

Scala

Default implementations

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
instance Eq a => Equal (Tree a) where
    Empty == Empty = True
    Leaf x == Leaf y = x == y
    Branch l1 r1 == Branch l2 r2 = l1 == l2 && r1 == r2
    _ == _ = False
```

```
trait Tree[A] extends Equal[A]
case class Empty[A]() extends Tree[A] {
    def ==(x: Equal[_]): Boolean = x match {
        case Empty() => true
        case _ => false
    }
}

case class Leaf[A](v: A) extends Tree[A] {
    def ==(x: Equal[_]): Boolean = x match {
        case Leaf(v1) => v == v1
        case _ => false
    }
}

case class Branch[A](l: Tree[A], r: Tree[A]) extends Tree[A] {
    def ==(x: Equal[_]): Boolean = x match {
        case Branch(l1, r1) => l == l1 && r == r1
        case _ => false
    }
}
```

Haskell

Scala

Default implementations

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
instance Eq a => Equal (Tree a) where
    Empty === Empty = True
    Leaf x === Leaf y = x == y
    Branch l1 r1 === Branch l2 r2 = l1 === l2 && r1 === r2
    _ === _ = False
```

```
trait Tree[A] extends Equal[A]
case class Empty[A]() extends Tree[A] {
    def ===(x: Equal[_]): Boolean = x match {
        case Empty() => true
        case _ => false
    }
}

case class Leaf[A](v: A) extends Tree[A] {
    def ===(x: Equal[_]): Boolean = x match {
        case Leaf(v1) => v == v1
        case _ => false
    }
}

case class Branch[A](l: Tree[A], r: Tree[A]) extends Tree[A] {
    def ===(x: Equal[_]): Boolean = x match {
        case Branch(l1, r1) => l === l1 && r === r1
        case _ => false
    }
}
```

Haskell

Scala

Who is this?

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary



List comprehensions

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
[x | i <- [0..10], let x = i*i, x > 20]
```

```
genSquares :: [Int]
genSquares = do
  i <- [0..10]
  let x = i*i
  guard (x > 20)
  return x
```

Works in any monadic context.

```
for { i <- List.range(0, 11); x = i*i; if x > 20 } yield x
```

```
def genSquares(): List[Int] = for {
  i <- List.range(0, 11)
  x = i*i
  if x > 20
} yield x
```

Works for any type implementing map/flatMap/filter.

Haskell

Scala

List comprehensions

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
[x | i <- [0..10], let x = i*i, x > 20]
```

```
genSquares :: [Int]
genSquares = do
  i <- [0..10]
  let x = i*i
  guard (x > 20)
  return x
```

Works in any monadic context.

```
for { i <- List.range(0, 11); x = i*i; if x > 20 } yield x
```

```
def genSquares(): List[Int] = for {
  i <- List.range(0, 11)
  x = i*i
  if x > 20
} yield x
```

Works for any type implementing map/flatMap/filter.

Haskell

Scala

List comprehensions

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
[x | i <- [0..10], let x = i*i, x > 20]
```

```
genSquares :: [Int]
genSquares = do
  i <- [0..10]
  let x = i*i
  guard (x > 20)
  return x
```

Works in any monadic context.

```
for { i <- List.range(0, 11); x = i*i; if x > 20 } yield x
```

```
def genSquares(): List[Int] = for {
  i <- List.range(0, 11)
  x = i*i
  if x > 20
} yield x
```

Works for any type implementing map/flatMap/filter.

Haskell

Scala

List comprehensions

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
[x | i <- [0..10], let x = i*i, x > 20]
```

```
genSquares :: [Int]
genSquares = do
  i <- [0..10]
  let x = i*i
  guard (x > 20)
  return x
```

Works in any monadic context.

```
for { i <- List.range(0, 11); x = i*i; if x > 20 } yield x
```

```
def genSquares(): List[Int] = for {
  i <- List.range(0, 11)
  x = i*i
  if x > 20
} yield x
```

Works for any type implementing map/flatMap/filter.

Haskell

Scala

Monadic notation

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

do

```
x <- Just 8
y <- fun1 x
z <- fun2 y
return z
```

```
Just 8 >=> \x ->
fun1 x >=> \y ->
fun2 y >=> return
```

do

```
x <- Just 8
y <- fun1 x
fun2 y
```

```
Just 8 >=> \x ->
fun1 x >=> \y ->
fun2 y
```

Haskell

for {

```
x <- Some(8)
y <- fun1(x)
z <- fun2(y)
} yield z
```

```
Some(8).flatMap (x =>
fun1(x).flatMap (y =>
fun2(y).map      (z =>
                    z)))
```

Scala

Monadic notation

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

do

```
x <- Just 8
y <- fun1 x
z <- fun2 y
return z
```

```
Just 8 >=> \x ->
fun1 x >=> \y ->
fun2 y >=> return
```

do

```
x <- Just 8
y <- fun1 x
fun2 y
```

```
Just 8 >=> \x ->
fun1 x >=> \y ->
fun2 y
```

Haskell

for {

```
x <- Some(8)
y <- fun1(x)
z <- fun2(y)
```

} yield z

```
Some(8).flatMap (x =>
fun1(x).flatMap (y =>
fun2(y).map      (z =>
                    z)))
```

Scala

I/O isolation

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
getLine :: IO String
getLine = ...
putStr :: String -> IO ()
putStr = ...
```

```
getLineWithPrompt :: String -> IO String
getLineWithPrompt prompt = do
    putStr prompt
    getLine
```

```
line :: IO String
line = getLineWithPrompt "> "
```

```
object Console {
    def readLine(): String = { ... }
    def print(obj: Any) { ... }
}
```

```
def getLineWithPrompt(prompt: String): String = {
    Console.print(prompt)
    Console.readLine()
}
```

```
val line: String = getLineWithPrompt("> ")
```

Haskell

Scala

I/O isolation

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
getLine :: IO String
getLine = ...
putStr :: String -> IO ()
putStr = ...
```

```
getLineWithPrompt :: String -> IO String
getLineWithPrompt prompt = do
    putStr prompt
    getLine
```

```
line :: IO String
line = getLineWithPrompt "> "
```

```
object Console {
    def readLine(): String = { ... }
    def print(obj: Any) { ... }
}
```

```
def getLineWithPrompt(prompt: String): String = {
    Console.print(prompt)
    Console.readLine()
}
```

```
val line: String = getLineWithPrompt("> ")
```

Haskell

Scala

I/O isolation

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

```
getLine :: IO String
getLine = ...
putStr :: String -> IO ()
putStr = ...
```

```
getLineWithPrompt :: String -> IO String
getLineWithPrompt prompt = do
    putStr prompt
    getLine
```

```
line :: IO String
line = getLineWithPrompt "> "
```

```
object Console {
    def readLine(): String = { ... }
    def print(obj: Any) { ... }
}
```

```
def getLineWithPrompt(prompt: String): String = {
    Console.print(prompt)
    Console.readLine()
}
```

```
val line: String = getLineWithPrompt("> ")
```

Haskell

Scala

Features comparison

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

	Haskell	Scala	Java
strong static typing	yes	yes	yes
type inference	yes	yes	no
higher order types	yes	yes	yes**
algebraic data types	yes	yes (verbose)	no
infinite streams	yes	yes	no*
strict semantics	optional	default	yes
lazy evaluation	default	optional	no
currying	default	optional	no
lambda expressions	yes	yes	no*
immutability	enforced	not enforced	not enforced
side effects isolation	yes	no	no
default implementations	yes	yes	no*

* will be in Java 8

** not as good as in Haskell/Scala

Who is this?

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary



Haskell is useless

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness


Algebraic data
types

Classes

Monadic features

Summary

Simon Peyton Jones



Haskell is useless

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness


Algebraic data
types

Classes

Monadic features

Summary

Simon Peyton Jones



Haskell is useless

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness


Algebraic data
types

Classes

Monadic features

Summary

Simon Peyton Jones



Haskell is useless

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness


Algebraic data
types

Classes

Monadic features

Summary

Simon Peyton Jones



Libraries and tools inspired by Haskell

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- Type classes library Scalaz
(Haskell standard library)
- Combinator parser
(Haskell: Parsec, attoparsec, polyparse)
- Automated specification-based testing ScalaCheck
(Haskell: QuickCheck)

Libraries and tools inspired by Haskell

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- Type classes library Scalaz
(Haskell standard library)
- Combinator parser
(Haskell: Parsec, attoparsec, polyparse)
- Automated specification-based testing ScalaCheck
(Haskell: QuickCheck)

Libraries and tools inspired by Haskell

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

- Type classes library Scalaz
(Haskell standard library)
- Combinator parser
(Haskell: Parsec, attoparsec, polyparse)
- Automated specification-based testing ScalaCheck
(Haskell: QuickCheck)

Resources

Haskell and Scala

Adam Szlachta

Introduction

History

Functional
programming

Basic syntax
comparison

Functions

Syntax summary

Laziness

Algebraic data
types

Classes

Monadic features

Summary

Links

- <http://808Fabrik.com/scala>
- <http://hyperpolyglot.org/ml>
- <http://downgra.de>
- <http://hseeberger.wordpress.com>
- <http://code.google.com/p/scalaz/>
- <http://code.google.com/p/scalacheck/>
- <http://www.artima.com/pins1ed/combinator-parsing.html>
- <http://www.haskell.org/haskellwiki/Typeclassopedia>
- <http://typeclassopedia.bitbucket.org>

Books and papers

- Eugenio Moggi, “Notions of computation and monads”
- Philip Wadler, “Comprehending Monads”
- Philip Wadler, “Monads for functional programming”
- Conor McBride, Ross Paterson, “Applicative programming with effects”
- Ross Paterson, “Arrows and computation”
- Jeff Newbern, “All About Monads”
- Brent Yorgey, “The Typeclassopedia” in “The Monad.Reader Issue 13”