

---

## Web Technology Lab

### Program – 9

Develop jQuery script (with HTML/CSS) for:

- a) Appends the content at the end of the existing paragraph and list.
- b) Change the state of the element with CSS style using animate() method.
- c) Change the color of any div that is animated.

#### Program :

```
<!DOCTYPE html>

<head>
  <script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>
  <title>jQuery Example | vtucode</title>
  <style>
    body {
      font-family: 'Roboto', sans-serif;
      background-color: #f4f7f6;
      margin: 0;
      padding: 0;
      display: flex;
      justify-content: center;
      align-items: center;
      height: 100vh;
    }

    .container {
      text-align: center;
      background: #fff;
      padding: 30px;
      border-radius: 12px;
```

```
    box-shadow: 0 4px 20px rgba(0, 0, 0, 0.1);
    transition: transform 0.3s ease-in-out;
}
```

```
.container:hover {
    transform: scale(1.02);
}
```

```
#paragraph {
    margin-bottom: 20px;
    color: #333;
    font-size: 18px;
    line-height: 1.5;
}
```

```
#list {
    margin-bottom: 20px;
    list-style: none;
    padding: 0;
}
```

```
#list li {
    background: #e8f0fe;
    margin: 5px 0;
    padding: 10px;
    border-radius: 8px;
    transition: background 0.3s;
}
```

```
#list li:hover {
    background: #d0e2fe;
}
```

```
.box {
    padding: 0 10px;
    width: 100px;
    height: 100px;
    background-color: #007bff;
    margin: 20px auto;
    line-height: 100px;
    color: white;
    text-align: center;
    border-radius: 8px;
    transition: all 0.3s ease;
}
```

```

button {
  padding: 12px 24px;
  margin: 10px;
  cursor: pointer;
  border: none;
  border-radius: 6px;
  font-size: 16px;
  background: #007bff;
  color: white;
  transition: box-shadow 0.3s, transform 0.2s;
  box-shadow: 0 4px 10px rgba(0, 0, 0, 0.1);
}

button:hover {
  box-shadow: 0 0 0 2px #fff, 0 0 0 4px #007bff;
}

button:focus {
  box-shadow: 0 0 0 2px #fff, 0 0 0 4px #007bff;
}

button:active {
  background: #004494;
  transform: translateY(0);
}
</style>
</head>

<body>
  <div class="container">
    <p id="paragraph">This is an existing paragraph.</p>
    <ul id="list">
      <li>List item 1</li>
      <li>List item 2</li>
    </ul>
    <div class="box" id="box">Animate me!</div>
    <button id="appendButton">Append Content</button>
    <button id="animateButton">Animate Box</button>
  </div>

  <script>
    $(document).ready(function () {

      $("#appendButton").click(function () {
        $("#paragraph").append(" Appended text.");
        $("#list").append("<li>New appended list item</li>");
      });
    });
  </script>

```

```

});

$("#animateButton").click(function () {

    $("#box").stop(true, true).css({
        width: "100px",
        height: "100px",
        opacity: 1,
        backgroundColor: "blue"
    }).animate({
        width: "200px",
        height: "200px",
        opacity: 0.5
    }, 1000, function () {

        $(this).css("background-color", "green");
    });
});
});
</script>
</body>
</html>

```

Output :

This is an existing paragraph.

List item 1

List item 2

Animate me!

Append Content

Animate Box