



VISAANTH M 2024-IT ▾

V2**Started on** Tuesday, 7 October 2025, 6:32 PM**State** Finished**Completed on** Tuesday, 7 October 2025, 6:33 PM**Time taken** 53 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main(){
3      int n;
4      scanf("%d",&n);
5      int a[n],a1[n];
6      for(int i=0;i<n;i++){
7          scanf("%d",&a[i]);
8      }
9      for(int i=0;i<n;i++){
10         scanf("%d",&a1[i]);
11     }
12     for(int i=0;i<n-1;i++){
13         for(int j=i+1;j<n;j++){
14             if(a[i]>a[j]){
15                 int t=a[i];
16                 a[i]=a[j];
17                 a[j]=t;
18             }
19         }
20     }
21     for(int i=0;i<n-1;i++){
22         for(int j=i+1;j<n;j++){
23             if(a1[i]<a1[j]){
24                 int t=a1[i];
25                 a1[i]=a1[j];
26                 a1[j]=t;
27             }
28         }
29     }
30     int m=0;
31     for(int i=0;i<n;i++){
32         m+=a[i]*a1[i];
33     }
34     printf("%d",m);
35 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)